

Thilawa Special Economic
Zone (Zone A) Development

Environmental Monitoring Report (Operation Phase)



Myanmar Japan Thilawa
Development Limited.

April 2022

CONTENTS

- 1. Executive Summary**
- 2. Summary of Monitoring Activities**
- 3. Monitoring Results**
- 4. Environmental Monitoring Form**

Appendix

- A. Water and Wastewater Monitoring Report for October, 2021**
- B. Water and Wastewater Monitoring Report for December, 2021**
- C. Air Quality Monitoring Report for September, 2021**
- D. Nosie and Vibration Monitoring Report for September, 2021**
- E. Soil Contamination Survey for December, 2021**
- F. Ground subsidence monitoring status
(Location- Admin Complex Compound) October 2021 to March 2022**
- G. General Waste Disposal Record
(Admin Complex Compound) October 2021 to March 2022**
- H. Sewage Treatment Plant Monitoring Record (October 2021 to March 2022)**
- I. Requested Letter Attachments**



1. Executive Summary

The environmental inspection and compliance monitoring program will be implemented under the direction of Ministry of Natural Resources and Environmental Conservation with oversight by Thilawa SEZ Management Committee.

The monitoring record from October 2021 to March 2022 according to the Environment Monitoring Plan is submitted in conformity with the provision of Chapter 9.1, Table 9.1-2 and 9.2, Table 9.2-2 Content of the EIA Report of Thilawa SEZ Development Project (Zone A).

2. Summary of Monitoring Activities

- a) Progress made to date on the implementation of the EMP against the submitted implementation schedule;**

We already submitted EMP for TSEZ Zone-A as following table.

Report No.	Description	Phase	Submission
1	Environmental Monitoring Report	Phase-1 Operation Phase	April, 2016
2	Environmental Monitoring Report	Phase-1 Operation Phase	October, 2016
3	Environmental Monitoring Report	Phase-1 & 2 Operation Phase	April, 2017
4	Environmental Monitoring Report	Phase-1 & 2 Operation Phase	October, 2017
5	Environmental Monitoring Report	Phase-1 & 2 Operation Phase	April, 2018
6	Environmental Monitoring Report	Phase-1 & 2 Operation Phase	October, 2018
7	Environmental Monitoring Report	Phase-1 & 2 Operation Phase	April, 2019
8	Environmental Monitoring Report	Phase-1 & 2 Operation Phase	October, 2019
9	Environmental Monitoring Report	Phase-1 & 2 Operation Phase	April, 2020
10	Environmental Monitoring Report	Phase-1 & 2 Operation Phase	October, 2020
11	Environmental Monitoring Report	Phase-1 & 2 Operation Phase	April, 2021
12	Environmental Monitoring Report	Phase-1 & 2 Operation Phase	October, 2021
13	Environmental Monitoring Report	Phase-1 & 2 Operation Phase	April, 2022

Report (No.13) is submitted this day attached with Operation Phase implementation schedule. Subsequent Operation Phase reports will be submitted on Bi-Annually.

- b) Difficulties encountered in implementing of the EMP and recommendations for remedying those difficulties and steps proposed to prevent or avoid similar future difficulties;**

Required clear guideline for the reference and target standard of water (such as surface water, wastewater, ground water etc.) in order to report TSEZ discharging impact.

- c) Number and type of non-compliance with the EMP and proposed remedial measures and timelines for completion of remediation;**

None

- d) Accidents or incidents relating to the occupational and community health and safety, and the environment:**

Please refer to the attached Environmental Monitoring Form.



- e) Monitoring data on environmental parameters and conditions as committed in the EMP or otherwise required.

Please refer to the attached Environmental Monitoring Form.

3. Monitoring Result

Environmental Monitoring plan report for Operation Phase implemented according to the following table, reference on Table 4.2-3, Chapter 4, EIA Report

Monitoring Plan (Operation Phase)

Category	Item	Location	Frequency	Remark
Air Quality	NO ₂ , SO ₂ , CO, TSP, PM ₁₀	Representative point inside TSEZ Zone-A area	1 week each in dry and wet season (First 3 years after operation stage)	September 2021, Air quality monitoring report (Bi-Annually)
Water Quality	Water temperature, pH, SS, DO, BOD, COD, T-coliform T-N, T-P, Color and odor, HS, HCN, Oil and grease, Formaldehyde, Phenols, Cresols Free Chlorine, Zinc, Chromium, Arsenic, Copper, Mercury, Cadmium, Barium, Selenium, Lead and Nickel	Discharging points and reference points (6 points) which including outflow of retention pond to the river (1 point) Well in the Monastery (1 point)	Bi-monthly for water, temperature, pH, SS, DO, BOD, COD, T-Coliform, T-N, T-P, Color and odor Bi-annually for all parameters	October 2021, Water and waste water quality monitoring report (Bi-Monthly) December 2021, Water and wastewater quality monitoring report (Bi-Annually)
Waste	Status of non-hazardous waste management Status of hazardous waste management	Each tenant	Twice/year (Submission of environmental reports by tenants)	General waste disposal record (Waste generated from common area of TSEZ and Admin complex)
Soil Contamination	Status of control of solid and liquid waste which causes soil contamination	Each tenant	Twice/year (Submission of environmental report by tenants)	December 2021, Soil quality monitoring report (Twice/year)
Noise and Vibration	Noise level at the monastery and residences to check effect of buffer zone for sound proofing to	Each tenant	One time in each dry and wet season (First 3 years after operation stage)	September 2021, Noise and vibration Monitoring Report (Bi-Annually)
Ground Subsidence	Ground elevation Consumption of ground water amount	Representative site (1 point)	Weekly	Refer to Environmental Monitoring form
Offensive Odor	Status offensive odor control by tenants	Each tenant	Twice/ year (Submission of environmental report by tenants)	Refer to Environmental Monitoring form
Bottom Sediment	Combined with water quality monitoring	Same as water quality monitoring	Same as water quality monitoring	Refer to Environmental Monitoring Form
Hydrological situation	Combined with ground subsidence monitoring	Same as ground subsidence monitoring	Same as ground subsidence monitoring	Refer to Environmental Monitoring Form
Risk for infectious disease such as AIDS/HIV	Status of measures of infectious disease	Each tenant	Twice/year (Submission of environmental report by tenants)	Refer to Environmental Monitoring form
Working conditions (including occupational safety)	Prehension of condition of occupational safety and health Prehension of infectious disease	Work site	Twice/year (Submission of environmental report by tenants)	
Accident	Existence of accident	Work site	As occasion arise	

*Remark: Each locator will report their monitoring result directly to Environmental Section, One Stop Service Center, Thilawa SEZ Management Committee.





MYANMAR JAPAN THILAWA DEVELOPMENT LIMITED

Thilawa Special Economic Zone (Zone A)
Development Project (Operation Phase)

Environment Monitoring Form

Environmental Monitoring Plan (Operation Phase)



Environment Monitoring Form

The latest results of the below monitoring items shall be submitted to Authorities on once at Pre-construction phase and on quarterly basis at Construction Phase, and on bi-annually base at Operation Phase. The items, standards to be applied, measurement points, and frequency for each monitoring parameter are established based on the EIA Report for Thilawa Special Economic Zone Development Project (Zone A). Should there be any changes to the original plan, such change shall be reviewed and evaluated by environmental expert.

(1) General

1) Phase of the Project

- Please mark the current phase.

 Pre-Construction Phase Construction Phase Operation Phase

2) Obtainment of Environmental Permits (Not Applicable)

Name of permits	Expected issuance date	Actual issuance date	Concerned authority	Remarks (Conditions, etc.)
Confirming report of Environmental Impact Assessment		3 rd December 2013	Thilawa SEZ Management Committee	
Notification of the comments of Ministry of Natural Resources and Environmental Conservation regarding with the Standard Change of Wastewater Quality of Industrial Zone, Internal Regulations of Thilawa SEZ Zone-A	5 th January 2018	10 th January 2018	Thilawa SEZ Management Committee	



3) Response/Actions to Comments and Guidance from Government Authorities and the Public (Not Applicable)

Monitoring Item	Monitoring Results during Report Period	Duration of Report Period	Frequency
Number and contents of formal comments made by the public		Same timing of submission of Monitoring Report	Upon receipt of comments/complaints
Number and contents of responses from Government agencies			

(2) Monitoring Results
1) Ambient/ Air Quality - September 2021
NO₂, SO₂, CO, TSP, PM10

Location	Item	Unit	Measured Value (Mean)	Measured Value (Min~Max.)	Country's Standard	Target value to be applied	*Referred International Standard	Frequency	Method	Note (Reason of excess of the standard)
Centralized Sewage treatment plant area	NO ₂	mg/m ³	0.064	0.004 - 0.157	Refer to NEQG	0.11	Japan	1 week each in dry and wet season	HAZSCANNER, EPAS	
	SO ₂	mg/m ³	0.038	0.013 - 0.433		0.11	Japan		HAZSCANNER, EPAS	
	CO	mg/m ³	0.043	0.023 - 0.224		11.45	Japan		HAZSCANNER, EPAS	
	TSP	mg/m ³	0.043	0.00 - 0.228		< 0.33	Thailand		HAZSCANNER1R, EPAS	
	PM10	mg/m ³	0.016	0.00 - 0.083		< 0.12	Thailand		HAZSCANNER, EPAS	

***Remark:** Referred to the Japan and Thailand Standard (EIA Report, Table 6.4-1) and Air Quality Monitoring Report (September 2021)



Complains from Residents

- Are there any complaints from residents regarding air quality in this monitoring period? Yes, No

If yes, please describe the contents of complains and its countermeasures to fill in below the table.

Contents of Complaints from Residents	Countermeasures

2)(a) Water Quality - October 2021

Measuring Point: Effluent of Wastewater (Thilawa SEZ discharging point which need to be monitored according to EIA are SW-1, SW-5 and SW-6. SW-2 and SW-4 natural creek water which are combine all the wastewater from the Local industrial water and domestic water from existing living environment are attach as reference points only. GW-1 is also as reference point for monitoring of existing tube well located in the Monastery compound.)

- Are there any effluents to water body in this monitoring period? Yes, No

If yes, please attach "Analysis Record" and fill in the items not to comply with Referred International Standard.

Location	Item	Unit	Measured Value	Country's Standard* ²	Target value to be applied	* ¹ Referred International Standard	Frequency	Method	Note (Reason of excess of the standard)
SW-1	pH	-	8.4	6-9	5.0-9.0	>=4	Once in two months	Instrument Analysis Method	
	DO	ppm	6.22	-	-			Instrument Analysis Method	
	SS	ppm	16	50	Max.50			APHA 2540D Method	
	BOD	ppm	11.41	50	Max.20			APHA-5210B Method	
	COD(Cr)	ppm	15	250	Max.70			APHA 5220D Method	
	Total coliforms	MPN/100ml	350	400	Max.400			APHA 9221B	
	T-N	ppm	0.8	-	Max.80			HACH Method 10072	
	T-P	ppm	-	2	Max 8			APHA 4500-PE	



Location	Item	Unit	Measured Value	Country's Standard ^{*2}	Target value to be applied	*1Referred International Standard	Frequency	Method	Note (Reason of excess of the standard)	
SW-5	Color	Co.Pt	0.48	-	-			APHA 2120C		
	Odor	Co.Pt	1	-	-			APHA 2150B		
	Total Dissolved solids (TDS) ^{*7}	mg/L	148	-	2000			APHA 2540C		
	Iron ^{*7}	mg/L	0.852	3.5	3.5			APHA 3120 B		
	Mercury ^{*7}	mg/L	≤ 0.002	0.01	0.005			APHA 3120 B		
SW-5	pH	-	7.3	6-9	5.0-9.0		Once in two months	Instrument Analysis Method		
	DO	ppm	4.28	-	-			Instrument Analysis Method		
	SS ^{*3}	ppm	78	50	Max.50			APHA 2540D Method		
	BOD	ppm	9.74	50	Max.20			APHA-5210B Method		
	COD(Cr)	ppm	11.2	250	Max.70			APHA 5220D Method		
	Total coliforms ^{*4}	MPN/100ml	9200	400	Max.400			APHA 9221B		
	T-N	ppm	1.6	-	Max.80	>=4		IIAC II Method 10072		
	T-P	ppm	-	2	-			APHA 4500-PE		
	Color	Co.Pt	0.37	-	-	7.5×10 ³		APHA 2120C		
	Odor	Co.Pt	1	-	-			APHA 2150B		
	Total Dissolved solids (TDS) ^{*7}	mg/L	150	-	2000			APHA 2540C		
	Iron ^{*7}	mg/L	2.734	3.5	3.5			APHA 3120 B		
	Mercury ^{*7}	mg/L	≤ 0.002	0.01	0.005			APHA 3120 B		
	pH	-	6.9	6-9	5.0-9.0		Once in two	Instrument Analysis Method		



Location	Item	Unit	Measured Value	Country's Standard ^{*2}	Target value to be applied	* ¹ Referred International Standard	Frequency	Method	Note (Reason of excess of the standard)
SW-6	DO	ppm	4.20	-	-		months	Instrument Analysis Method	
	SS	ppm	18	50	Max.50	>=4		APHA 2540D Method	
	BOD	ppm	19.38	50	Max.20			APHA-5210B Method	
	COD(Cr)	ppm	59	250	Max.70			APHA 5220D Method	
	Total coliforms	MPN/100ml	< 1.8	400	Max.400	7.5×10 ³		APHA 9221B	
	T-N	ppm	8.4	-	Max.80			HACH Method 10072	
	T-P	ppm	-	2	-			APHA 4500-PE	
	Color	Co.Pt	2.25	-	-			APHA 2120C	
	Odor	Co.Pt	1	-	-			APHA 2150B	
	Total Dissolved solids (TDS) ^{*7}	mg/L	382	-	2000			APHA 2540C	
	Iron ^{*7}	mg/L	0.602	3.5	3.5			APHA 3120 B	
	Mercury ^{*7}	mg/L	≤ 0.002	0.01	0.005			APHA 3120 B	





Location	Item	Unit	Measured Value	Country's Standard ^{*2}	Target value to be applied	*1Referred International Standard	Frequency	Method	Note (Reason of excess of the standard)
SW-2 (Reference Point)	pH	-	6.8	6-9	5.0-9.0			Instrument Analysis Method	
	DO	ppm	2.57	-	-			Instrument Analysis Method	
	SS	ppm	50	50	Max.50			APHA 2540D Method	
	BOD	ppm	10.45	50	Max.20			APIIA-5210B Method	
	COD(Cr)	ppm	12.8	250	Max.70			APHA 5220D Method	
	Total coliforms ^{*6}	MPN/100ml	>160000	400	Max.400			APHA 9221B	
	T-N	ppm	1	-	Max.80	>=4	Once in two months	HACH Method 10072	
	T-P	ppm	-	2	-			APHA 4500-PE	
	Color	Co.Pt	10.77	-	-			APHA 2120C	
	Odor	Co.Pt	1	-	-	7.5×10 ³		APHA 2150B	
SW-4 (Reference Point)	Total Dissolved solids (TDS) ^{*7}	mg/L	118	-	2000			APHA 2540C	
	Iron ^{*7}	mg/L	3.84	3.5	3.5			APHA 3120 B	
	Mercury ^{*7}	mg/L	≤ 0.002	0.01	0.005			APHA 3120 B	
	pH	-	7.3	6-9	5.0-9.0			Instrument Analysis Method	
	DO	ppm	4.35	-	-			Instrument Analysis Method	
	SS ^{*5}	ppm	302	50	Max.50	>=4	Once in two months	APHA 2540D Method	
	BOD	ppm	3.58	50	Max.20			APIIA-5210B Method	
	COD(Cr)	ppm	4.1	250	Max.70			APHA 5220D Method	
	Total coliforms ^{*6}	MPN/100ml	160000	400	Max.400	7.5×10 ³		APHA 9221B	
	T-N	ppm	1.6	-	Max.80			HACH Method 10072	



Location	Item	Unit	Measured Value	Country's Standard ^{*2}	Target value to be applied	* ¹ Referred International Standard	Frequency	Method	Note (Reason of excess of the standard)
	T-P	ppm	-	2	-			APHA 4500-PE	
	Color	Co.Pt	3.23	-	-			APHA 2120C	
	Odor	Co.Pt	1	-	-			APHA 2150B	
	Total Dissolved solids (TDS) ^{*7}	mg/L	182	-	2000			APHA 2540C	
	Iron ^{*7,*8}	mg/L	12.628	3.5	3.5			APHA 3120 B	
	Mercury ^{*7}	mg/L	≤ 0.002	0.01	0.005			APHA 3120 B	
GW-1 (Reference Point)	pH	-	7.9					Instrument Analysis Method	
	DO	ppm	5.36					Instrument Analysis Method	
	SS	ppm	8					APHA 2540D Method	
	BOD	ppm	2.81					APHA-5210B Method	
	COD(Cr)	ppm	3.5	None (Available	None	5.5~9.0		APHA 5220D Method	
	Total coliforms*	MPN/100ml	4.5	(Available	(Available	>=4		APHA 9221B	
	T-N	ppm	1.2	Guideline	Guideline	50	Once in two months	HACH Method 10072	
	T-P	ppm	-	value	Value	15		APHA 4500-PE	
	Color	Co.Pt	0	determined by MONREC)	determined by	60		APHA 2120C	
	Odor	Co.Pt	1		(MOI)	7.5×10 ³		APHA 2150B	
	Total Dissolved solids (TDS) ^{*7}	mg/L	1366			0.1		APHA 2540C	
	Iron ^{*7}	mg/L	0.390			0.04		APHA 3120 B	
	Mercury ^{*7}	mg/L	≤ 0.002					APHA 3120 B	

*¹Remark: Referred to the Vietnam Standard (EIA Report), Reference to the Water Quality Monitoring Report, October 2021.

*²Remarks: There is no current country standard but Ministry of Natural Resources and Environmental Conservation submitted the National Emission Quality Guidelines (NEQG) for environmental guidelines. The guidelines filled as the country standards in the environmental monitoring form.

*³Remark: At SW-5, SS higher than the target value due to expected reason i) surface water run-off from bare land in Zone A

*⁴Remark: At SW-5, Total coliform are higher than the target value due to the expected reason-i) the potential expected reason might natural bacteria existed in all area of Zone-A because there are various kind of vegetation and creature such as birds, and small animals in and along the retention canals and retention ponds. Total coliform do not affect human health directly, self-monitoring for E.Coli analysis was carried out to identify health impact by coliform bacteria. As for the result of E.Coli for SW5 was < 1.8 and they were under the reference under target value. It is considered that there is no significant impact to human health.

*⁵ Remark: At SW-4, the results of SS are higher than the target value due to the expected reason i) delivered from upstream area such as natural origin and wastewater from local industrial zone which outside of Thilawa SEZ ii) influence by water from the downstream of monitoring points due to flow back by tidal effect.

*⁶Remark: For reference monitoring points (SW-2 and SW-4), the result of total coliforms is higher than the standard due to two expected reasons: i) runoff of animal waste from the undeveloped area and delivered from local industrial zone and illegal dumping site from outside of Thilawa SEZ in the upstream area ii) delivered from surrounding area by tidal effect.

*⁷ Remark: Recommendation from JICA Environmental expert (TSMC), to be more emphasized on Environmental and analyzing only.

*⁸ Remark: At SW4, the results of iron is higher than standard due to expected reason of i) the influence of natural origin (iron can reach out from soil by run-off). In Yangon, soil is naturally rich in iron.

2)(b) Water Quality – December 2021

Measuring Point: Effluent of Wastewater

- Are there any effluents to water body in this monitoring period? Yes, No

If yes, please attach “Analysis Record” and fill in the items not to comply with Referred International Standard.



Location	Item	Unit	Measured Value (Max)	Country's Standard*2	Target value to be applied*1	Frequ-ency	Method	Note (Reason of excess of the standard)
SW-1	Temperature	°C	23	< 3 (increase)	≤ 35	Once per 6 months	Instrument Analysis Method	
	pH	-	9	6-9	6~9		Instrument Analysis Method	
	SS*3	mg/L	100	50	Max 50		APHA 2540 D Method	
	DO	mg/L	11.92	-	-		Instrument Analysis Method	
	BOD (5)	mg/L	8.05	50	Max 30		APHA 5210 B Method	
	COD (Cr)	mg/L	39.2	250	Max 125		APHA 5220D Method	Refer to water quality report
	Total Coliform	MPN/100 ml	240	400	Max 400		APHA 9221B Method	
	T-N	mg/L	4.6	-	Max 80		HACH Method 10072 Method	
	T-P	mg/L	-	2	Max 2		APHA 4500-P E Method	
	Color	TCU	9.41	-	Max 150		APHA 2120C Method	
	Odor	TON	1	-	-		APHA 2150 B Method	
	Oil and Grease	mg/L	<3.1	10	Max 10		APHA 5520B Method	
	Mercury	mg/L	≤ 0.002	0.01	Max 0.005		APHA 3120 B Method	
	Zinc	mg/L	0.034	2	Max 2		APHA 3120 B Method	
	Arsenic	mg/L	≤ 0.010	0.1	Max 0.1		APHA 3120 B Method	
	Chromium	mg/L	≤ 0.002	0.5	Max 0.5		APHA 3120 B Method	
	Cadmium	mg/L	≤ 0.002	0.1	Max 0.03		APHA 3120 B Method	
	Selenium	mg/L	≤ 0.010	0.1	Max 0.02		APHA 3120 B Method	

Location	Item	Unit	Measured Value (Max)	Country's Standard*2	Target value to be applied*1	Frequ-ency	Method	Note (Reason of excess of the standard)
SW-1	Lead	mg/L	≤ 0.002	0.1	Max 0.1		APHA 3120 B Method	
	Copper	mg/L	≤ 0.002	0.5	Max 0.5		APHA 3120 B Method	
	Barium	mg/L	0.018	-	Max 1		APHA 3120 B Method	
	Nickel	mg/L	≤ 0.002	0.5	Max 0.2		APHA 3120 B Method	
	Cyanide	mg/L	< 0.002	0.1	Max 0.1		HACH 8027 Method	
	Total Cyanide	mg/L	0.009	1	Max 1		APHA 4500-CN-C Method	
	Free Chlorine	mg/L	<0.1	-	Max 1		APHA 4500-CL G Method	
	Sulphide (S ₂ -)	mg/L	0.151	1	Max 1		HACH 8131 Method	
	Formaldehyde	mg/L	0.025	-	Max 1		HACH 8110 Method	
	Phenols	mg/L	0.018	0.5	Max 0.5		USEPA Method 420.1	
	Iron	mg/L	0.246	3.5	Max 3.5		APHA 3120 B Method	
	Total Dissolved Solids	mg/L	390	-	Max 2000		APHA 2540 C Method	
	Total Residual Chlorine	mg/L	0.1	0.2	Max 0.2		APHA 4500-CL G Method	
	Chromium (Hexavalent)	mg/L	< 0.05	0.1	Max 0.1		ISO 11083:1994 Method	
	Ammonia	mg/L	0.7	10	Max 10		HACH Method 10205 Method	
	Fluoride	mg/L	1.772	20	Max 20		APIA 4110 B Method	
	Silver	mg/L	≤ 0.002	0.5	Max 0.5		APHA 3120 B Method	



Location	Item	Unit	Measured Value (Max)	Country's Standard* ²	Target value to be applied* ¹	Frequ-ency	Method	Note (Reason of excess of the standard)
SW-5	Temperature	°C	22	< 3 (increase)	≤ 35	Once per 6 months	Instrument Analysis Method	Refer to water quality report
	pH	-	7.9	6-9	6~9		Instrument Analysis Method	
	SS	mg/L	28	50	Max 50		APHA 2540 D Method	
	DO	mg/L	6.17	-	-		Instrument Analysis Method	
	BOD (5)	mg/L	3.91	50	Max 30		APIHA 5210 B Method	
	COD (Cr)	mg/L	19.2	250	Max 125		APHA 5220D Method	
	Total Coliform* ⁴	MPN/100 ml	1600	400	Max 400		APHA 9221B Method	
	T-N	mg/L	1.7	-	Max 80		HACH Method 10072 Method	
	T-P	mg/L	-	2	Max 2		APHA 4500-P E Method	
	Color	TCU	7.46	-	Max 150		APHA 2120C Method	
	Odor	TON	1	-	-		APIHA 2150 B Method	
	Oil and Grease	mg/L	<3.1	10	Max 10		APHA 5520B Method	
	Mercury	mg/L	≤ 0.002	0.01	Max 0.005		APIHA 3120 B Method	
	Zinc	mg/L	0.016	2	Max 2		APIHA 3120 B Method	
	Arsenic	mg/L	≤ 0.010	0.1	Max 0.1		APIHA 3120 B Method	
	Chromium	mg/L	≤ 0.002	0.5	Max 0.5		APIHA 3120 B Method	
	Cadmium	mg/L	≤ 0.002	0.1	Max 0.03		APIHA 3120 B Method	



Location	Item	Unit	Measured Value (Max)	Country's Standard* ²	Target value to be applied* ¹	Frequency	Method	Note (Reason of excess of the standard)
SW-5	Selenium	mg/L	≤ 0.010	0.1	Max 0.02		APHA 3120 B Method	
	Lead	mg/L	≤ 0.002	0.1	Max 0.1		APHA 3120 B Method	
	Copper	mg/L	≤ 0.002	0.5	Max 0.5		APHA 3120 B Method	
	Barium	mg/L	0.022	-	Max 1		APHA 3120 B Method	
	Nickel	mg/L	≤ 0.002	0.5	Max 0.2		APHA 3120 B Method	
	Cyanide	mg/L	< 0.002	0.1	Max 0.1		HACH 8027 Method	
	Total Cyanide	mg/L	0.003	1	Max 1		APHA 4500-CN-C Method	
	Free Chlorine	mg/L	< 0.1	-	Max 1		APHA 4500-CL G Method	
	Sulphide (S ₂ -)	mg/L	0.044	1	Max 1		HACH 8131 Method	
	Formaldehyde	mg/L	0.027	-	Max 1		HACH 8110 Method	
	Phenols	mg/L	0.007	0.5	Max 0.5		USEPA Method 420.1	
	Iron	mg/L	0.802	3.5	Max 3.5		APHA 3120 B Method	
	Total Dissolved Solids	mg/L	214	-	Max 2000		APIA 2540 C Method	
	Total Residual Chlorine	mg/L	0.1	0.2	Max 0.2		APHA 4500-CL G Method	
	Chromium (Hexavalent)	mg/L	< 0.05	0.1	Max 0.1		ISO 11083:1994 Method	
	Ammonia	mg/L	0.18	10	Max 10		HACH Method 10205 Method	
	Fluoride	mg/L	1.543	20	Max 20		APHA 4110 B Method	



Location	Item	Unit	Measured Value (Max)	Country's Standard*2	Target value to be applied*1	Frequ-ency	Method	Note (Reason of excess of the standard)
SW-5	Silver	mg/L	≤ 0.002	0.5	Max 0.5		APHA 3120 B Method	
SW-6	Temperature	°C	25	< 3 (increase)	≤ 35		Instrument Analysis Method	
	pH	-	6.9	6-9	6~9		Instrument Analysis Method	
	SS	mg/L	14	50	Max 50		APHA 2540 D Method	
	DO	mg/L	5.48	-	-		Instrument Analysis Method	
	BOD (5)	mg/L	3.84	50	Max 30		APHA 5210 B Method	
	COD (Cr)	mg/L	21.2	250	Max 125		APHA 5220D Method	
	Total Coliform	MPN/100 ml	< 1.8	400	Max 400		APHA 9221B Method	
	T-N	mg/L	8.9	-	Max 80	Once per 6 months	HACH Method 10072 Method	
	T-P	mg/L	-	2	Max 2		APHA 4500-P E Method	
	Color	TCU	5.13	-	Max 150		APIA 2120C Method	Refer to water quality report
	Odor	TON	1	-	-		APIA 2150 B Method	
	Oil and Grease	mg/L	<3.1	10	Max 10		APHA 5520B Method	
	Mercury	mg/L	≤ 0.002	0.01	Max 0.005		APHA 3120 B Method	
	Zinc	mg/L	0.016	2	Max 2		APHA 3120 B Method	
	Arsenic	mg/L	≤ 0.010	0.1	Max 0.1		APHA 3120 B Method	
	Chromium	mg/L	≤ 0.002	0.5	Max 0.5		APHA 3120 B Method	



Location	Item	Unit	Measured Value (Max)	Country's Standard*2	Target value to be applied*1	Frequ-ency	Method	Note (Reason of excess of the standard)
SW-6	Cadmium	mg/L	≤ 0.002	0.1	Max 0.03		APHA 3120 B Method	
	Selenium	mg/L	≤ 0.010	0.1	Max 0.02		APHA 3120 B Method	
	Lead	mg/L	≤ 0.002	0.1	Max 0.1		APHA 3120 B Method	
	Copper	mg/L	≤ 0.002	0.5	Max 0.5		APHA 3120 B Method	
	Barium	mg/L	0.004	-	Max 1		APHA 3120 B Method	
	Nickel	mg/L	≤ 0.002	0.5	Max 0.2		APHA 3120 B Method	
	Cyanide	mg/L	< 0.002	0.1	Max 0.1		HACH 8027 Method	
	Total Cyanide	mg/L	0.005	1	Max 1		APHA 4500-CN-C Method	
	Free Chlorine	mg/L	1.1	-	Max 1		APHA 4500-CL G Method	
	Sulphide (S ₂ -)	mg/L	0.006	1	Max 1		HACH 8131 Method	
	Formaldehyde	mg/L	0.019	-	Max 1		HACII 8110 Method	
	Phenols	mg/L	< 0.002	0.5	Max 0.5		USEPA Method 420.1	
	Iron	mg/L	0.104	3.5	Max 3.5		APHA 3120 B Method	
	Total Dissolved Solids	mg/L	444	-	Max 2000		APHA 2540 C Method	
	Total Residual Chlorine	mg/L	1.6	0.2	Max 0.2		APHA 4500-CL G Method	
	Chromium (Hexavalent)	mg/L	< 0.05	0.1	Max 0.1		ISO 11083:1994 Method	
	Ammonia	mg/L	7.94	10	Max 10		HACH Method 10205 Method	



Location	Item	Unit	Measured Value (Max)	Country's Standard*2	Target value to be applied*1	Frequ-ency	Method	Note (Reason of excess of the standard)
SW-6	Fluoride	mg/L	3.517	20	Max 20		APHA 4110 B Method	
	Silver	mg/L	≤ 0.002	0.5	Max 0.5		APHA 3120 B Method	
	Temperature	°C	19	< 3 (increase)	≤ 35	Once per 6 months	Instrument Analysis Method	Refer to water quality report
	pH	-	7.2	6-9	6~9		Instrument Analysis Method	
	SS ⁵	mg/L	78	50	Max 50		APHA 2540 D Method	
	DO	mg/L	3.36	-	-		Instrument Analysis Method	
SW-2	BOD (5)	mg/L	7.99	50	Max 30		APHA 5210 B Method	
(Reference point)	COD (Cr)	mg/L	30.9	250	Max 125		APHA 5220D Method	
	Total Coliform ⁶	MPN/100 ml	92000	400	Max 400		APHA 9221B Method	
	T-N	mg/L	7	-	Max 80		HACH Method 10072 Method	
	T-P	mg/L	-	2	Max 2		APHA 4500-P E Method	
	Color	TCU	17.06	-	Max 150		APHA 2120C Method	
	Odor	TON	1	-	-		APHA 2150 B Method	
	Oil and Grease	mg/L	<3.1	10	Max 10		APHA 5520B Method	
	Mercury	mg/L	≤ 0.002	0.01	Max 0.005		APHA 3120 B Method	
	Zinc	mg/L	0.026	2	Max 2		APHA 3120 B Method	
	Arsenic	mg/L	≤ 0.010	0.1	Max 0.1		APHA 3120 B Method	



Location	Item	Unit	Measured Value (Max)	Country's Standard* ²	Target value to be applied* ¹	Frequency	Method	Note (Reason of excess of the standard)
SW-2 (Reference point)	Chromium	mg/L	≤ 0.002	0.5	Max 0.5		APIA 3120 B Method	
	Cadmium	mg/L	≤ 0.002	0.1	Max 0.03		APHA 3120 B Method	
	Selenium	mg/L	≤ 0.010	0.1	Max 0.02		APHA 3120 B Method	
	Lead	mg/L	≤ 0.002	0.1	Max 0.1		APHA 3120 B Method	
	Copper	mg/L	≤ 0.002	0.5	Max 0.5		APHA 3120 B Method	
	Barium	mg/L	0.062	-	Max 1		APHA 3120 B Method	
	Nickel	mg/L	≤ 0.002	0.5	Max 0.2		APIA 3120 B Method	
	Cyanide	mg/L	< 0.002	0.1	Max 0.1		HACH 8027 Method	
	Total Cyanide	mg/L	0.006	1	Max 1		APIA 4500-CN-C Method	
	Free Chlorine	mg/L	0.1	-	Max 1		APHA 4500-CL G Method	
	Sulphide (S2 -)	mg/L	0.068	1	Max 1		HACH 8131 Method	
	Formaldehyde	mg/L	0.015	-	Max 1		HACH 8110 Method	
	Phenols	mg/L	0.007	0.5	Max 0.5		USEPA Method 420.1	
	Iron	mg/L	1.632	3.5	Max 3.5		APHA 3120 B Method	
	Total Dissolved Solids	mg/L	1026	-	Max 2000		APHA 2540 C Method	
	Total Residual Chlorine	mg/L	0.2	0.2	Max 0.2		APHA 4500-CL G Method	
	Chromium (Hexavalent)	mg/L	< 0.05	0.1	Max 0.1		ISO 11083:1994 Method	



Location	Item	Unit	Measured Value (Max)	Country's Standard* ²	Target value to be applied* ¹	Frequency	Method	Note (Reason of excess of the standard)
SW-2 (Reference point)	Ammonia	mg/L	2.01	10	Max 10		HACH Method 10205 Method	
	Fluoride	mg/L	0.154	20	Max 20		APHA 4110 B Method	
	Silver	mg/L	≤ 0.002	0.5	Max 0.5		APIA 3120 B Method	
SW-4 (Reference point)	Temperature	°C	21	< 3 (increase)	≤ 35		Instrument Analysis Method	
	pH	-	7.2	6-9	6~9		Instrument Analysis Method	
	SS ^{*5}	mg/L	194	50	Max 50		APHA 2540 D Method	
	DO	mg/L	4.66	-	-		Instrument Analysis Method	
	BOD (5)	mg/L	3.42	50	Max 30		APHA 5210 B Method	
	COD (Cr)	mg/L	19.8	250	Max 125		APHA 5220D Method	Refer to water quality report
	Total Coliform ^{*6}	MPN/100 ml	>160000	400	Max 400		APHA 9221B Method	
	T-N	mg/L	6.4	-	Max 80		HACH Method 10072 Method	
	T-P	mg/L	-	2	Max 2		APHA 4500-P E Method	
	Color	TCU	7.86	-	Max 150		APHA 2120C Method	
	Odor	TON	1	-	-		APHA 2150 B Method	
	Oil and Grease	mg/L	< 3.1	10	Max 10		APHA 5520B Method	
	Mercury	mg/L	≤ 0.002	0.01	Max 0.005		APHA 3120 B Method	
	Zinc	mg/L	0.060	2	Max 2		APHA 3120 B Method	



Location	Item	Unit	Measured Value (Max)	Country's Standard*2	Target value to be applied*1	Frequency	Method	Note (Reason of excess of the standard)
SW-4 (Reference point)	Arsenic	mg/L	≤ 0.010	0.1	Max 0.1		APHA 3120 B Method	
	Chromium	mg/L	≤ 0.002	0.5	Max 0.5		APHA 3120 B Method	
	Cadmium	mg/L	≤ 0.002	0.1	Max 0.03		APHA 3120 B Method	
	Selenium	mg/L	≤ 0.01	0.1	Max 0.02		APHA 3120 B Method	
	Lead	mg/L	≤ 0.002	0.1	Max 0.1		APHA 3120 B Method	
	Copper	mg/L	≤ 0.002	0.5	Max 0.5		APHA 3120 B Method	
	Barium	mg/L	0.020	-	Max 1		APHA 3120 B Method	
	Nickel	mg/L	≤ 0.002	0.5	Max 0.2		APHA 3120 B Method	
	Cyanide	mg/L	0.002	0.1	Max 0.1		HACH 8027 Method	
	Total Cyanide	mg/L	0.015	1	Max 1		APHA 4500-CN-C Method	
	Free Chlorine	mg/L	< 0.1	-	Max 1		APHA 4500-CL G Method	
	Sulphide (S2 -)	mg/L	0.377	1	Max 1		HACH 8131 Method	
	Formaldehyde	mg/L	0.072	-	Max 1		HACH 8110 Method	
	Phenols	mg/L	0.002	0.5	Max 0.5		USEPA Method 420.1	
	Iron ⁷	mg/L	6.884	3.5	Max 3.5		APHA 3120 B Method	
	Total Dissolved Solids	mg/L	624	-	Max 2000		APHA 2540 C Method	
	Total Residual Chlorine	mg/L	0.1	0.2	Max 0.2		APHA 4500-CL G Method	
	Chromium	mg/L	< 0.05	0.1	Max 0.1		ISO 11083:1994 Method	



Location	Item	Unit	Measured Value (Max)	Country's Standard*2	Target value to be applied*1	Frequ-ency	Method	Note (Reason of excess of the standard)
SW-4 (Reference point)	(Hexavalent) Ammonia	mg/L	1.44	10	Max 10		HACH Method 10205 Method	
	Fluoride	mg/L	1.325	20	Max 20		APHA 4110 B Method	
	Silver	mg/L	≤ 0.002	0.5	Max 0.5		APHA 3120 B Method	
GW-1 (Reference point)	Temperature	°C	25	< 3 (increase)	≤ 35		Instrument Analysis Method	
	pH	-	7.8	6~9	6~9		Instrument Analysis Method	
	SS	mg/L	6	50	Max 50		APHA 2540 D Method	
	DO	mg/L	7.10	-	-		Instrument Analysis Method	
	BOD (5)	mg/L	4.57	50	Max 30		APHA 5210 B Method	
	COD (Cr)	mg/L	1.5	250	Max 125		APHA 5220D Method	
	Total Coliform	MPN/100 ml	13	400	Max 400	Once per 6 months	APHA 9221B Method	
	T-N	mg/L	9.3	-	Max 80		HACH Method 10072 Method	
	T-P	mg/L	-	2	Max 2		APHA 4500-P E Method	
	Color	TCU	1.52	-	Max 150		APHA 2120C Method	
	Odor	TON	1	-	-		APHA 2150 B Method	
	Oil and Grease	mg/L	< 3.1	10	Max 10		APHA 5520B Method	
	Mercury	mg/L	≤ 0.002	0.01	Max 0.005		APHA 3120 B Method	
	Zinc	mg/L	0.006	2	Max 2		APHA 3120 B Method	



Location	Item	Unit	Measured Value (Max)	Country's Standard*2	Target value to be applied*1	Frequency	Method	Note (Reason of excess of the standard)
GW-1 (Reference point)	Arsenic	mg/L	≤ 0.010	0.1	Max 0.1		APHA 3120 B Method	
	Chromium	mg/L	≤ 0.002	0.5	Max 0.5		APHA 3120 B Method	
	Cadmium	mg/L	≤ 0.002	0.1	Max 0.03		APHA 3120 B Method	
	Selenium	mg/L	≤ 0.010	0.1	Max 0.02		APHA 3120 B Method	
	Lead	mg/L	≤ 0.002	0.1	Max 0.1		APHA 3120 B Method	
	Copper	mg/L	≤ 0.002	0.5	Max 0.5		APHA 3120 B Method	
	Barium	mg/L	0.042	-	Max 1		APHA 3120 B Method	
	Nickel	mg/L	≤ 0.002	0.5	Max 0.2		APHA 3120 B Method	
	Cyanide	mg/L	< 0.002	0.1	Max 0.1		HACH 8027 Method	
	Total Cyanide	mg/L	< 0.002	1	Max 1		APHA 4500-CN-C Method	
	Free Chlorine	mg/L	< 0.1	-	Max 1		APHA 4500-CL G Method	
	Sulphide (S ₂ -)	mg/L	< 0.005	1	Max 1		HACH 8131 Method	
	Formaldehyde	mg/L	0.005	-	Max 1		HACH 8110 Method	
	Phenols	mg/L	< 0.002	0.5	Max 0.5		USEPA Method 420.1	
	Iron	mg/L	0.304	3.5	Max 3.5		APHA 3120 B Method	
	Total Dissolved Solids	mg/L	1330	-	Max 2000		APHA 2540 C Method	
	Total Residual Chlorine	mg/L	< 0.1	0.2	Max 0.2		APHA 4500-CL G Method	
	Chromium	mg/L	< 0.05	0.1	Max 0.1		ISO 11083:1994 Method	



Location	Item	Unit	Measured Value (Max)	Country's Standard ^{*2}	Target value to be applied ^{*1}	Frequency	Method	Note (Reason of excess of the standard)
GW-1 (Reference point)	(Hexavalent) Ammonia	mg/L	0.22	10	Max 10		HACH Method 10205 Method	
	Fluoride	mg/L	0.014	20	Max 20		APHA 4110 B Method	
	Silver	mg/L	≤ 0.002	0.5	Max 0.5		APHA 3120 B Method	

^{*1}Remark: Referred to the Vietnam Standard (EIA Report), Reference to the Water Quality Monitoring Report, December 2021.

^{*2}Remarks: There is no current country standard but Ministry of Natural Resources and Environmental Conservation submitted the National Emission Quality Guidelines (NEQG) for environmental guidelines. The guidelines filled as the country standards in the environmental monitoring form.

³Remark: At SW-1, SS higher than the target value due to expected reason i) surface water run-off from bare land in Zone A

⁴Remark: At SW-5, Total coliform are higher than the target value due to the expected reason-i) the potential expected reason might natural bacteria existed in all area of Zone-A because there are various kind of vegetation and creature such as birds, and small animals in and along the retention canals and retention ponds. Total coliform do not affect human health directly, self-monitoring for E.Coli analysis was carried out to identify health impact by coliform bacteria. As for the result of E.Coli for SW5 was 17 and they were under the reference under target value. It is considered that there is no significant impact to human health.

⁵ Remark: At SW-2 and SW-4, the results of SS are higher than the target value due to the expected reason i) delivered from upstream area such as natural origin and wastewater from local industrial zone which outside of Thilawa SEZ ii) influence by water from the downstream of monitoring points due to flow back by tidal effect.

⁶Remark: For reference monitoring points (SW-2 and SW-4), the result of total coliforms is higher than the standard due to two expected reasons: i) runoff of animal waste from the undeveloped area and delivered from local industrial zone and illegal dumping site from outside of Thilawa SEZ in the upstream area ii) delivered from surrounding area by tidal effect.

⁷ Remark: At SW4, the results of iron is higher than standard due to expected reason of i) naturally rich in iron. (iron can reach out from the soil by run-off). Japan set effluent standards for two items as follows; i) health item and ii) living environment item. In the health item, there is no standard value for iron. On the other hand, for the living



environment item, the standard value for soluble iron level is 10 mg/l. As the comparison with the living environment standard value in Japan, iron result in SW-4 is lower than the standard value. Therefore, it can be considered that there is no significant impact on the living environment.

3) Soil Contamination (only operation phase)

Situations environmental report from tenants

- Are there any serious issues regarding soil contamination in this monitoring period? Yes, No

If yes, please describe the contents of complains and its countermeasures to fill in below the table.

Contents of Issues on Soil Contamination	Countermeasures
Regular Soil Contamination Monitoring conducted and attached the Report in Appendix.	

4) Noise

Remarks: According to EIA report, Chapter 4- Table 4-2.2, monitoring plan is one time each in dry and wet season (First 3 years after operation stage). In the environmental monitoring report (Phase-1, operation phase) No.1, one time noise and vibration monitoring survey is finished as a record and there is no excess the standard in all of survey points. There is not much operation stage industry in current and monitoring will start after consult with environmental expert.

Noise Level (Along the Thilawa Development Road)

Location	Item	Unit	Measured Value (Mean)	Measured Value (Min~Max)	Country's Standard	Target value to be applied	*Referred International Standard	Frequency	Method	Note (Reason of excess of the standard)
NV-1	Leq (day)	dB(A)	58	57 - 59	N/A	75		One time each in dry and wet season	Sound Level Meter	
	Leq(eve)	dB(A)	-			70				



*Remark: Referred to the Target Noise Standard (Thilawa SEZ Zone-A EIA Report) and Reference to Noise and Vibration Monitoring Report (September 2021)

Noise Level (Living Environment)

Location	Item	Unit	Measured Value (Mean)	Measured Value (Min~Max)	Country's Standard	*Target value to be applied	Referred International Standard	Frequency	Method	Note (Reason of excess of the standard)
NV-2	Leq (day)	dB(A)	63	59 - 68	N/A	70		One time each in dry and wet season	Sound Level Meter	
	Leq(eve)	dB(A)	-			65				
	Leq(night)	dB(A)	-			60				
NV-3	Leq(day)	dB(A)	48	44 - 51	N/A	70			Sound level Meter	
	Leq(eve)	dB(A)	-			65				
	Leq(night)	dB(A)	-			60				

*Remark: Referred to the Target Noise Standard (Thilawa SEZ Zone-A EIA Report) and Reference to Noise and Vibration Monitoring Report (September 2021)

Remark: For safety and risk avoidance, we could monitor day time during this period. Please refer informed letter attachment.

Complaints from Residents

- Are there any complaints from residents regarding noise in this monitoring period? Yes, No

If yes, please describe the contents of complains and its countermeasures to fill in below the table.

Contents of Complaints from Residents	Countermeasures



5) Solid Waste (Disposal from admin complex compound)
Measuring Point: Construction Site (Construction Phase), Storage for Sludge (Operation Phase)

- Are there any wastes of sludge in this monitoring period? Yes, No

If yes, please report the amount of sludge and fill in the results of solid waste management Activities.

No.	Date	Description	No. of Kgs/L	Remarks
1	October 2021	General Waste Disposal	780kg	Golden Dowa Eco-system Myanmar Co.,Ltd
2	November 2021	General Waste Disposal	-	Golden Dowa Eco-system Myanmar Co.,Ltd
3	December 2021	General Waste Disposal	1620 kg	Golden Dowa Eco-system Myanmar Co.,Ltd
4	January 2022	General Waste Disposal	-	Golden Dowa Eco-system Myanmar Co.,Ltd
5	February 2022	General Waste Disposal	-	Golden Dowa Eco-system Myanmar Co.,Ltd
6	March 2022	General Waste Disposal	1120 kg	Golden Dowa Eco-system Myanmar Co.,Ltd

Remark: Attached general waste disposal record (Admin Complex Compound) in appendix.

Remark: Admin complex compound waste disposal reported in the Operation phase, Environmental Monitoring Report because the waste from common area of Thilawa SEZ is storing in the admin complex trash storage. Each locator will submit according to ECPP approval for the waste disposal record directly to the Environmental Section, One Stop Service Center, Thilawa SEZ Management Committee.

6) (a) Ground Subsidence and Hydrology- October 2021

Duration (Month)	Water Consumption		Ground Level		Frequency	Note
	Quantity	Unit	Quantity	Unit		
14-October -2021	-	m3/week	+7.132	m	Once per month	

* Remarks: Attached ground subsidence monitoring status (Operation Phase) in appendix. There is no ground water consumption in Zone-A industrial area and will monitor and descript the water consumption quantity if using the tube well. Location of Ground Subsidence Test : E=209545.508, N=1844669.443



(b) Ground Subsidence and Hydrology- November 2021

Duration (Month)	Water Consumption		Ground Level		Frequency	Note
	Quantity	Unit	Quantity	Unit		
15- November -2021	-	m3/week	+7.132	m	Once per month	

* Remarks: Attached ground subsidence monitoring status (Operation Phase) in appendix. Location of Ground Subsidence Test : E=209545.508, N=1844669.443

(c) Ground Subsidence and Hydrology- December 2021

Duration (Month)	Water Consumption		Ground Level		Frequency	Note
	Quantity	Unit	Quantity	Unit		
14- December -2021	-	m3/week	+7.132	m	Once per month	

* Remarks: Attached ground subsidence monitoring status (Operation Phase) in appendix. Location of Ground Subsidence Test : E=209545.508, N=1844669.443

(d) Ground Subsidence and Hydrology- January 2022

Duration (Month)	Water Consumption		Ground Level		Frequency	Note
	Quantity	Unit	Quantity	Unit		
18-January-2022	-	m3/week	+7.134	m	Once per month	

* Remarks: Attached ground subsidence monitoring status (Operation Phase) in appendix. Location of Ground Subsidence Test : E=209545.508, N=1844669.443

(e) Ground Subsidence and Hydrology- February 2022

Duration (Month)	Water Consumption		Ground Level		Frequency	Note
	Quantity	Unit	Quantity	Unit		
17-February-2022	-	m3/week	+7.134	m	Once per month	

* Remarks: Attached ground subsidence monitoring status (Operation Phase) in appendix. Location of Ground Subsidence Test : E=209545.508, N=1844669.443



(f) Ground Subsidence and Hydrology- March 2022

Duration (Month)	Water Consumption		Ground Level		Frequency	Note
	Quantity	Unit	Quantity	Unit		
8-March-2022	-	m ³ /week	+7.135	m	Once per month	

* Remarks: Attached ground subsidence monitoring status (Operation Phase) in appendix. Location of Ground Subsidence Test : E=209545.508, N=1844669.443

7) Offensive Odor (only operation phase) Not Applicable at Construction Phase Report
Complaints from Residents

- Are there any complaints from residents regarding offensive odor in this monitoring period? Yes, No

If yes, please describe the contents of complains and its countermeasures to fill in below the table.

Contents of Complaints from Residents	Countermeasures

Situations environmental report from tenants Not Applicable at Construction Phase Report

- Are there any serious issues regarding offensive odor in this monitoring period? Yes, No

If yes, please describe the contents of complains and its countermeasures to fill in below the table.

Contents of Issues on Soil Contamination	Countermeasures



8) Infectious disease, Working Environment, Accident

Information from contractor (construction phase) or tenants (operation phase)

- Are there any incidents regarding Infectious disease, Working Environment, Accident in this monitoring period? Yes, No

If yes, please describe the contents of complains and its countermeasures to fill in below the table.

Contents of Incidents	Countermeasures
An accident was occurred on 4th March 2022 in front of Marubeni (lot- B 22). The worker from MJTD was found seriously injured in front of Marubeni, his motorbike was away from him, near Kalbe Myanmar (Lot-23) and beer can was also found near him. Securities from Marubeni and Kalbe Myanmar gave him emergency treatment first.	MJTD take the action as per following: - We immediately called the ambulance -Ambulance took the patient (bike rider) to Thanlyin general hospital first - The patient was moved to Yangon General Hospital

Note: If emergency incidents are occurred, the information shall be reported to the relevant organizations and authorities immediately.

End of Document





MYANMAR JAPAN THILAWA DEVELOPMENT LIMITED

**Thilawa Special Economic Zone (Zone A)
Development Project (Operation Phase)**

Appendix -A

Water and Waste Water Monitoring Report

October, 2021

Environmental Monitoring Plan (Operation Phase)



**WATER QUALITY MONITORING REPORT
FOR DEVELOPMENT OF INDUSTRIAL AREA
IN THILAWA SEZ ZONE A
(OPERATION STAGE)**

(Bi-Monthly Monitoring)

October 2021
Myanmar Koei International Ltd.



TABLE OF CONTENTS

CHAPTER 1: INTRODUCTION	1
1.1 General.....	1
CHAPTER 2: WATER QUALITY MONITORING	2
2.1 Monitoring Items	2
2.2 Description of Sampling Points	2
2.3 Monitoring Method.....	4
2.4 Monitoring Period.....	4
2.5 Monitoring Results.....	5
CHAPTER 3: CONCLUSION AND RECOMMENDATIONS.....	8
APPENDIX-1 FIELD SURVEY PHOTOS	A1-1
APPENDIX-2 LABORATORY RESULTS.....	A2-1

LIST OF TABLES

Table 2.1-1 Monitoring Items for Water Quality.....	2
Table 2.2-1 Outline of Sampling Points.....	2
Table 2.3-1 Analytic Method for Water Quality.....	4
Table 2.4-1 Sampling Time of Each Station.....	4
Table 2.4-2 Tide Record for Yangon River, Myanmar.....	4
Table 2.5-1 Results of Water Quality Monitoring on All Discharges and Gates.....	6
Table 2.5-2 Result of Water Quality Survey for Reference Monitoring Points for Comparison with Discharging Points and Baseline of Discharged Creek.....	7

LIST OF FIGURES


Figure 1.1-1 Location of Sampling Points of Water Quality Monitoring	1
--	---



CHAPTER 1: INTRODUCTION

1.1 General

Thilawa Special Economic Zone (SEZ) is located in southern district of Yangon region and about 23 km southeast of Yangon city. As the developer of Thilawa SEZ, Myanmar Japan Thilawa Development Ltd. (MJTD) has a responsibility to carry out regular monitoring in the industrial area of Zone A in accordance with the approved Environmental Impact Assessment (EIA) report and Environmental Management Plan (EMP). MJTD has implemented monitoring various environmental items with the specified time frame to know the environmental conditions in and around the area. As for the monitoring of the water quality, total six sampling points are set for water quality survey, named SW-1, SW-2, SW-4, SW-5, SW-6, and GW-1 have been monitored in Thilawa SEZ and its surrounding area in timely manner. Among the six locations, SW-1 and SW-5 are main discharged points of Thilawa SEZ and SW-6 is discharged from centralized Sewage Treatment Plant (STP) which is required to monitor by Environmental Monitoring Plan (EMoP) in EIA report of Thilawa SEZ Zone A. The remaining points SW-2 and SW-4 are sampled as a reference monitoring for comparison with discharged points and baseline of discharged creek. Moreover, GW-1 is monitored as a reference of existing tube well which is located in the monastery compound. Location of sampling points for water quality monitoring is shown in Figure 1.1-1.



Source: Google Earth

Figure 1.1-1 Location of Sampling Points of Water Quality Monitoring



CHAPTER 2: WATER QUALITY MONITORING

2.1 Monitoring Items

Sampling points and parameters for water quality monitoring are determined so as to cover the environmental monitoring plan of the EIA report.

Water quality sampling was carried out at six locations. Among the six locations, water flow measurement carried out at five locations (SW-1, SW-2, SW-4, SW-5 and SW-6) where can be measured by Current Meter. Monitoring items and sampling points are summarized in Table 2.1-1.

Table 2.1-1 Monitoring Items for Water Quality

No.	Parameters	SW-1	SW-2	SW-4	SW-5	SW-6	GW-1	Remarks
1	Water Temperature	○	○	○	○	○	○	On-site measurement
2	pH	○	○	○	○	○	○	On-site measurement
3	DO	○	○	○	○	○	○	On-site measurement
4	BOD (5)	○	○	○	○	○	○	Laboratory analysis
5	COD (Cr)	○	○	○	○	○	○	Laboratory analysis
6	Total Nitrogen	○	○	○	○	○	○	Laboratory analysis
7	Suspended Solids	○	○	○	○	○	○	Laboratory analysis
8	Total Coliform	○	○	○	○	○	○	Laboratory analysis
9	Total Phosphorous	○	○	○	○	○	○	Laboratory analysis
10	Color	○	○	○	○	○	○	Laboratory analysis
11	Odor	○	○	○	○	○	○	Laboratory analysis
12	Oil and Grease (Self-monitoring)	○	○	○	○	○	○	Laboratory analysis
13	Total Dissolved Solids (Self-monitoring)	○	○	○	○	○	○	Laboratory analysis
14	Iron (Self-monitoring)	○	○	○	○	○	○	Laboratory analysis
15	Mercury (Self-monitoring)	○	○	○	○	○	○	Laboratory analysis
16	Escherichia Coli (Self- monitoring)	○	-	-	○	-	○	Laboratory analysis
17	Flow Rate	○	○	○	○	○	-	On-site measurement

Source: Myanmar Koei International Ltd.

2.2 Description of Sampling Points

The outline of sampling points is mentioned in Table 2.2-1. The photos of conducting field survey at each sampling points are mentioned in Appendix-1.

Table 2.2-1 Outline of Sampling Points

No.	Station	Detailed Information
1	SW-1	<p>Coordinate - N - 16° 40' 13.5", E - 96° 16' 39.8"</p> <p>Location - Outlet of Retention Pond</p> <p>Survey Item – Surface water sampling and water flow rate measurement</p>
2	SW-2	<p>Coordinate - N - 16° 40' 20.69", E - 96° 17' 18.04"</p> <p>Location - Upstream of Shwe Pyauk Creek</p> <p>Survey Item – Surface water sampling and water flow rate measurement</p>
3	SW-4	<p>Coordinate - N - 16° 39' 42.84", E - 96° 16' 27.42"</p> <p>Location - Downstream of Shwe Pyauk Creek</p> <p>Survey Item – Surface water sampling and water flow rate measurement</p>
4	SW-5	<p>Coordinate - N - 16° 40' 10.7", E - 96° 16' 22.6"</p> <p>Location - Outlet of Retention Canal</p> <p>Survey Item – Surface water sampling and water flow rate measurement</p>
5	SW-6	<p>Coordinate - N - 16° 40' 27.13", E - 96° 16' 30.68"</p> <p>Location - Outlet from STP to Retention Pond</p> <p>Survey Item – Surface water sampling and water flow rate measurement</p>
6	GW-1	<p>Coordinate - N - 16° 40' 16.96", E - 96° 16' 34.01"</p> <p>Location - In Moegyoe Swan Monastery</p> <p>Survey Item – Ground Water Sampling</p>

Source: Myanmar Koei International Ltd.



SW-1

SW-1 was collected at the discharge point of retention pond which is located in the east of Moegyoe Swan monastery. The distance is about 530 m downstream of SW-6. This drainage is flowing from north to south and then connected to the Shwe Pyauk creek through earth drain. The water quality of this monitoring point has been influenced by the water from downstream due to flow back by tidal fluctuation. In addition, it seems that a part of wastewater from monastery has reached to the culvert in the SEZ area and discharging to the retention pond.

SW-2 (Reference Point)

SW-2 was collected at the upstream of Shwe Pyauk creek. This sampling point is located in the southeast of Zone A area and at the south of Dagon-Thilawa road. The surrounding areas are Zone B in the southwest and local industrial zone in the east respectively.

SW-4 (Reference Point)

SW-4 was collected at the downstream of Shwe Pyauk creek, after mixing of discharge water from local industrial zone, construction site of Zone B and Zone A, which is flowing from east to west and then entering into the Yangon River. The distance is about 2.15 km downstream of SW-2. This sampling point is located in the southwest of Zone A area and in the south of Dagon-Thilawa road. The surrounding areas are Zone B and local industrial zone in the east respectively.

SW-5

SW-5 was collected at retention canal near main gate of Thilawa SEZ. Most of the water collected in this canal is rain water and plantation water from surrounding area. This canal is also connected to the Shwe Pyauk creek. The water quality of this monitoring point may have been influenced by the water from downstream due to flow back by tidal fluctuation.

SW-6

SW-6 was collected at the drain outlet of centralized STP which is located in the north of Moegyoe Swan monastery compound and retention pond (SW-1). Then the treated water is flowing to the retention pond. The distance is about 530 m upstream of (SW-1).

GW-1 (Reference of Existing Tube Well)

GW-1 was collected from tube well as ground water sample. It is located in the compound of Moegyoe Swan monastery. The surrounding areas are Zone A in the west, retention pond in the east and Dagon- Thilawa road in the south respectively.



2.3 Monitoring Method

All water samples were collected with cleaned sampling bottles and analyzed by the following standard method as shown in Table 2.3-1. All samples were kept in iced boxes keeping at 2-4° C and were transported to the laboratory. Among the parameters; water temperature, pH and DO were measured by the on-site instrument “Horiba, U-52” and water flow rate was also conducted by using the on-site instrument “JFE Digital Current Meter”.

Table 2.3-1 Analytic Method for Water Quality

No.	Parameter	Method
1	Water Temperature	Instrument Analysis Method (Horiba, U-52, Multi Water Quality Checker)
2	pH	Instrument Analysis Method (Horiba, U-52, Multi Water Quality Checker)
3	Suspended Solids (SS)	APHA 2540 D (Dry at 103-105°C Method)
4	Dissolved Oxygen (DO)	Instrument Analysis Method (Horiba, U-52, Multi Water Quality Checker)
5	BOD (5)	APHA 5210 B (5 Days BOD Test)
6	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)
7	Total Coliform	APIA 9221B (Standard Total Coliform Fermentation Technique)
8	Total Nitrogen (T-N)	IIACI Method 10072 (TNT Persulfate Digestion Method)
9	Total Phosphorous (T-P)	APHA 4500-P E (Ascorbic Acid Method)
10	Color	APHA 2120C (Spectrophotometric Method)
11	Odor	APHA 2150 B (Threshold Odor Test)
12	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)
13	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
14	Iron	APIA 3120 B (Inductively Coupled Plasma (ICP) Method)
15	Total Dissolved Solids	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)
16	Escherichia Coli	APHA 9221 F (Escherichia Coli Procedure Using Fluorogenic Substrate)
17	Flow Rate	Detection of Electromagnetic Elements (Real-time measurement by AEM 213-D Digital Current Meters)

Source: Myanmar Koei International Ltd.

2.4 Monitoring Period

Water quality and water flow rate monitoring were conducted on 6 October 2021 and sampling time is shown in Table 2.4-1 to avoid tidal effect. The tide record for Yangon River, Myanmar on 6 October 2021 is shown in Table 2.4-2.

Table 2.4-1 Sampling Time of Each Station

No.	Station	Sampling Time
1	SW-1	6/10/2021 10:08
2	SW-2	6/10/2021 08:15
3	SW-4	6/10/2021 07:21
4	SW-5	6/10/2021 09:05
5	SW-6	6/10/2021 09:33
6	GW-1	6/10/2021 10:59

Source: Myanmar Koei International Ltd.

Table 2.4-2 Tide Record for Yangon River, Myanmar

Date	Time	Height	Tide Conditions
6/10/2021	03:58	6.22	High Tide
	11:57	1.20	Low Tide
	16:05	6.26	High Tide

Source: Myanmar Port Authority, Tide Table for the Yangon River and Elephant Point, 2021.



2.5 Monitoring Results

Results of water quality monitoring are summarized in Table 2.5-1. Analytical results of the laboratory are described in Appendix-2. The results were compared with the target value of effluent water quality discharging to water body stipulated in the EIA report.

2.5.1 Results of Water Quality at the Outlet of Sewage Treatment Plant of Industrial Area of Thilawa SEZ and at the Point before Discharging to Creek

As the comparison with the target value, the results of Suspended Solid (SS) and total coliform exceeded than the target values.

As for the result of SS, the result at the outlet of the centralized STP (SW-6) complied with the target value. It implied that effluents from each locator was treated well by the STP. On the other hand, results at the monitoring points of retention canal (SW-5) before discharging to creek, exceeded the target value due to the surface water run-off from bare land in Zone A.

As for the result of total coliform of surface water, the result at the outlet of the centralized STP (SW-6) complied with the target value. It may prove that effluents from each locator was treated well by the STP. On the other hand, result at monitoring point of retention canal (SW-5) exceeded the target value due to the expected reason; the potential expected reason might be natural bacteria existed in all area of Zone A because there are various kinds of vegetation and creature such as birds, and small animals in and along the retention ponds and retention canals.

Since the composition of the total coliform include bacteria from natural origin, and even after total coliform do not affect human health directly, self-monitoring for E. Coli analysis was carried out to identify health impact by coliform bacteria. As for the result of E. Coli of surface water, all of results were under the reference value. Therefore, although the target value of total coliform exceeded at monitoring point of retention canal (SW-5), but it is considered that there is no significant impact on human health.



Table 2.5-1 Results of Water Quality Monitoring on All Discharges and Gates

No.	Parameters	Unit	SW-1	SW-5	SW-6	Target Value (Reference Value for Self- Monitoring)
1	Temperature	°C	28	27	27	< 35
2	pH	-	8.4	7.3	6.9	6~9
3	Suspended Solid (SS)	mg/L	16	78	18	50
4	Dissolved Oxygen (DO)	mg/L	6.22	4.26	4.20	-
5	BOD (5)	mg/L	11.41	9.74	19.38	30
6	COD (Cr)	mg/L	15.0	11.2	59.0	125
7	Total Coliform	MPN/ 100ml	350.0	9200	< 1.8	400
8	Total Nitrogen (T-N)	mg/L	0.8	1.6	8.4	80
9	Total Phosphorous (T-P)	mg/L	-	-	-	2
10	Color	TCU (True Color Unit)	0.48	0.37	2.25	150
11	Odor	TON (Threshold Odor Number)	1	1	1	-
12	Oil and Grease	mg/L	< 3.1	< 3.1	< 3.1	10
13	Mercury	mg/L	≤ 0.002	≤ 0.002	≤ 0.002	0.005
14	Iron	mg/L	0.852	2.734	0.602	3.5
15	Total Dissolved Solids	mg/L	148	150	382	2000
16	Escherichia Coli	MPN/100ml (SW)	< 1.8	< 1.8	-	(1000)* (CFU/100ml)
17	Flow Rate	m³/s	0.12	0.01	0.005	-

Note: Red color means exceeded value than target value. Total Phosphorous (T-P) can't be analyzed at the lab during this monitoring period.

*Note: Based on the water utilization at discharged creek, water quality C of quality standard for water baths in Japan, (Ministry of Environment, 1997) is set as a reference value for self-monitoring of E. coli for surface water monitoring. However, due to limitation of capacity for analytical laboratory in Myanmar, the method to analyze the "Colony Forming Unit (CFU)" is not available in Myanmar. Therefore, the results of "Most Probable Number (MPN)" are assumed similar to CFU values and compared with reference values. Once the method to analyze the CFU will be available in Myanmar, the analytical method will be changed.

According to the quality standard for water baths in Japan, (Ministry of Environment, 1997), in case of E.Coli result is exceeding 1,000 CFU/100 ml, since it is assumed unsafety, it is considered unsuitable for water baths.

Source: Myanmar Koei International Ltd.



2.5.2 Results of Reference Monitoring for Comparison with Discharged Points and Baseline of Discharged Creek

Results of water quality monitoring are summarized in Table 2.5-2. The results were compared with the target value of effluent water quality discharging to water body stipulated in the EIA report.

As the comparison with the target value, the results of Suspended Solid (SS), total coliform and iron exceeded than the target value.

As for the result of SS, result at the surface water monitoring point (SW-4) exceeded the target value. The exceed result for SS maybe due to two expected reasons; i) delivered from upstream area such as natural origin and wastewater from local industrial zone which outside of Thilawa SEZ, and ii) influence by water from the downstream of monitoring points due to flow back by tidal fluctuation.

As for the result of total coliform of surface water, results at surface water monitoring points (SW-2 and SW-4) exceeded the target value due to two expected reasons; i) runoff of animal waste from the undeveloped area and delivered from local industrial zone and illegal dumping site from outside of Thilawa SEZ in the upstream area, and ii) delivered from surrounding area by tidal effect.

As for the result of iron, the result at the monitoring point of surface water monitoring point (SW-2 and SW-4) exceeded the target value. The possible reasons may due to the influence of natural origin (iron can reach out from soil by run-off). In Yangon, soil is naturally rich in iron.

Table 2.5-2 Result of Water Quality Survey for Reference Monitoring Points for Comparison with Discharging Points and Baseline of Discharged Creek

No.	Parameters	Unit	SW-2	SW-4	GW-1	Target Value (Reference Value for Self-Monitoring)
1	Temperature	°C	26	26	27	< 35
2	pH	-	6.8	7.3	7.9	6~9
3	Suspended Solid (SS)	mg/L	50	302	8	50
4	Dissolved Oxygen (DO)	mg/L	2.57	4.35	5.36	-
5	BOD (5)	mg/L	10.45	3.58	2.81	30
6	COD (Cr)	mg/L	12.8	4.1	3.5	125
7	Total Coliform	MPN/100ml	> 160000	160000.0	4.5	400
8	Total Nitrogen (T-N)	mg/L	1.0	1.6	1.2	80
9	Total Phosphorous (T-P)	mg/L	-	-	-	2
10	Color	TCU (True Color Unit)	10.77	3.23	0.00	150
11	Odor	TON (Threshold Odor Number)	1	1	1	-
12	Oil and Grease	mg/L	< 3.1	< 3.1	< 3.1	10
13	Mercury	mg/L	≤ 0.002	≤ 0.002	≤ 0.002	0.005
14	Iron	mg/L	3.840	12.628	0.390	3.5
15	Total Dissolved Solids	mg/L	118	182	1366	2000
16	Escherichia Coli	MPN/100ml* (SW)	-	-	-	(1,000)* (CFU/100ml)
		MPN/100ml** (GW)	-	-	< 1.8	(100)** (MPN/100ml)
17	Flow Rate	m³/s	0.36	0.71	-	-

Note: Red color means the exceeded results than target value. Total Phosphorous (T-P) can't be analyzed at the lab during this monitoring period.

*Note: Based on the water utilization at discharged creek, water quality C of quality standard for water baths in Japan, (Ministry of Environment, 1997) is set as a reference value of self-monitoring for surface water monitoring. However, due to limitation of capacity for analytical laboratory in Myanmar, the method to analyze the "Colony Forming Unit (CFU)" is not available in Myanmar. Therefore, the results of "Most Probable Number (MPN)" are assumed similar to CFU values and compared with reference values. Once the method to analyze the CFU will be available in Myanmar, the analytical method will be changed.

According to the quality standard for water baths in Japan, (Ministry of Environment, 1997), in case of E.Coli result is exceeding 1,000 CFU/100 ml, since it is assumed unsafety, it is considered unsuitable for water baths.

**Note: Based on the water utilization at monitoring point for ground water, B1(Irrigation water) of National Technical Regulation on Surface Water Quality in Vietnam (No. QCVN 08: 2008/BTNMT) is set as a reference value of self-monitoring for ground water monitoring.

Source: Myanmar Koei International Ltd.



CHAPTER 3: CONCLUSION AND RECOMMENDATIONS

As for the result of SS and total coliform at the outlet of the centralized STP (SW-6) complied with the target value. It may prove that effluent from each locator was treated well by the STP. On the other hand, the parameters of SS, results at the monitoring point of retention canal (SW-5) before discharging to creek, exceeded the target value due to the surface water run-off from bare land in Zone A.

The parameter of total coliform at retention canal (SW-5) exceeded the target value in this period for main discharged points of Thilawa SEZ Zone A. In addition, according to the result of self-monitoring of E. coli at retention canal (SW-5), result was under the reference value. Therefore, although the target value of total coliform was exceeded at monitoring point (SW-5), but it is considered that there is no significant impact on human health.

As for parameters of Suspended Solid (SS), total coliform and iron in surface water exceeded the target values at reference monitoring points. The expected reasons for exceeding the target values of SS at (SW-4) is delivered from upstream area such as natural origin and wastewater from local industrial zone which is outside of Thilawa SEZ and influence by water from the downstream of monitoring points due to flow back by tidal fluctuation.

The expected reasons for exceeding the target values of total coliform at (SW-2 and SW-4) are by natural origin (natural bacteria existed).

The expected reasons for exceeding the target values of iron at (SW-2 and SW-4) may be due to the influence of natural origin (iron can reach out from soil by run-off). In Yangon, soil is naturally rich in iron.

As for future subject for main discharged points of Thilawa SEZ Zone A, the following action may be taken to achieve the target levels of SS and total coliform and appropriate water quality monitoring:

- To continue monitoring Escherichia coli (E. coli) level to identify health impact by coliform bacteria;
- To monitor the possibility of the overflow water from construction site and
- To monitor the possibility of the domestic wastewater from construction sites.

End of the Document



APPENDIX-1 FIELD SURVEY PHOTOS



FOR DISCHARGED POINTS OF THILAWA SEZ ZONE A



Surface water sampling and onsite measurement at SW-1



Surface water sampling and onsite measurement at SW-5



Surface water sampling and onsite measurement at SW-6




FOR REFERENCE MONITORING POINTS FOR COMPARISON WITH DISCHARGED POINTS AND BASELINE OF DISCHARGED CREEK



Surface water sampling and onsite measurement at SW-2



Surface water sampling and onsite measurement at SW-4



Ground water sampling and onsite measurement at GW-1

APPENDIX-2 LABORATORY RESULTS



FOR DISCHARGED POINTS AND AFTER CENTRALIZED STP

DOWA

601, 6th Zone, Dagon Eco System Myanmar Co., Ltd
Lat 16° 51' 11.500000000000001 N Long 95° 51' 27.000000000000001 E
Hokkien St, Zone A, Yangon Region, Myanmar
Phone: +95 1 2308051



Report No. GEM-LAB-202110056

Revision No. 1

Report Date : 25 October , 2021

Application No. : D001-C001

Analysis Report

Client Name	Myanmar Koei International LTD (MKI)	
Address	No, 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tarmwe Township, Yangon, Myanmar	
Project Name	Environment Monitoring report for Zone A & B	
Sample Description		
Sample Name	MKI-SW-1-1006	Sampling Date : 6 October, 2021
Sample No.	W-2110021	Sampling By : Customer
Waste Profile No.		Sample Received Date : 6 October, 2021


No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	16	-
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	11.41	0.00
3	CO ₂ (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	15.0	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	350.0	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	0.8	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	0.48	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	148	-
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.852	0.002
12	Escherichia Coli	APHA 9221 F Escherichia Coli Procedure Using Fluorogenic Substrate	MPN/100ml	< 1.8	1.8

Remark : 100 : Limit of Quantitation

APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition.

Analysed By

Cherry Myint Thein
Supervisor



Approved By :

Ni Ni Aye Lwin Oct 25, 2021
Assistant Manager



Water Quality Monitoring Report for Development of Industrial Area in Thilawa SEZ Zone A
(Bi-Monthly Monitoring in FY October - 2021)

DOWA

GOLDEN DOWA ECO-SYSTEM MYANMAR CO., LTD.
Unit No F2, Thilawa SEZ Zone A, Yangon Region, Myanmar
Phone No/Fax No: (+95) 1 2300951



Report No.: GEM-LAB-202110057

Revision No.: 1

Report Date: 25 October, 2021

Application No.: 0001-C001

Analysis Report

Client Name	: Myanmar Koei International LTD (MKI)		
Address	: No, 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tarmwe Township, Yangon, Myanmar.		
Project Name	: Environment Monitoring report for Zone A & B		
Sample Description			
Sample Name	: MKI-SW-5-1006	Sampling Date:	6 October, 2021
Sample No.	: W-2110022	Sampling By:	Customer
Waste Profile No.	:	Sample Received Date:	6 October, 2021

No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	78	-
2	BOD (S)	APHA 5210 B (5 Days BOD Test)	mg/l	9.74	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	11.2	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	9200	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	<3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	1.6	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	0.37	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	150	-
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	2.734	0.002
12	Escherichia Coli	APHA 9221 F Escherichia Coli Procedure Using Fluorogenic Substrate	MPN/100ml	<1.8	1.8

Remark : LOQ - Limit of Quantitation


APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By :

Cherry Myint Thein
Supervisor

Approved By :

Ni Ni Aye Lwin Oct 25, 2021
Assistant Manager



Water Quality Monitoring Report for Development of Industrial Area in Thilawa SEZ Zone A
(Bi-Monthly Monitoring in FY October - 2021)

DOWA

DOLDEN DOWNTEC-SYSTEM MIAHANAH (DTS) LTD
UK No 11, Phalay STZ Zone A, Yangon Region, Myanmar
Phone No: +95 1 7320651



Report No. : GEM-LAB-202110058

Revision No. : 1

Report Date : 25 October , 2021

Application No. : 0001-C001

Analysis Report


Client Name	Myanmar Koer International LTD (MKI)	
Address	No, 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar.	
Project Name	Environment Monitoring report for Zone A & B	
Sample Description		
Sample Name	MKI-SW-6-1006	Sampling Date : 6 October, 2021
Sample No	W-2110023	Sampling By : Customer
Waste Profile No	-	Sample Received Date : 6 October, 2021

No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	18	-
2	BOG (5)	APHA 5210 B (5 Days BOG Test)	mg/l	19.38	0.06
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	59.0	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100mL	<1.8	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	8.4	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	2.25	0.00
8	Oder	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	382	-
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	\$ 0.002	0.002
11	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.602	0.002

Remark : LOQ - Limit of Quantitation
APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By :

25-10-21



Approved By

Ni Ni Aye Lwin Oct 25, 2021
Assistant Manager



**FOR REFERENCE MONITORING POINTS FOR COMPARISON WITH DISCHARGED POINTS
 AND BASELINE OF DISCHARGED CREEK**

DOWA

GOLDEN DOWA ECO-SYSTEM MYANMAR CO., LTD.
 101 No.11, Thilawa SEZ Zone A, Yangon Region, Myanmar
 Phone No.: +95 1 5309051



Report No. : GEM-LAB-202110059

Revision No. : 2

Report Date : 28 October , 2021

Application No. : 0001-C001

Analysis Report


Client Name	Myanmar Koei International LTD (MKI)		
Address	No. 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar.		
Project Name	Environment Monitoring report for Zone A & B		
Sample Description			
Sample Name	MKI-SW-2-1006	Sampling Date	6 October, 2021
Sample No.	W-2110024	Sampling By	Customer
Waste Profile No.	-	Sample Received Date	6 October, 2021

No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	50	-
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	10.45	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	12.8	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	>160000	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	1.0	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	10.77	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	118	-
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	< 0.002	0.002
11	Chromium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	< 0.002	0.002
12	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	3.840	0.002

Remark : LOQ - Limit of Quantitation
 APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By :

 28-10-21
 Cherry Myint Thein
 Supervisor



Approved By :

 28-10-21
 Ni Ni Aye Lwin
 Assistant Manager



Water Quality Monitoring Report for Development of Industrial Area in Thilawa SEZ Zone A
(Bi-Monthly Monitoring in FY October - 2021)

DOWA

GOLDEN DOWA ECO-SYSTEM MYANMAR CO., LTD.
Site No. F1, Thilawa SEZ Zone A, Yangon Region, Myanmar
Phone No. Fax No. (+95) 1 2303051



Report No. : GEM-LAB-202110060

Revision No. : 2

Report Date : 28 October , 2021

Application No. : 0001-C001

Analysis Report

Client Name	Myanmar Koei International LTD (MKI)		
Address	No. 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar		
Project Name	Environment Monitoring report for Zone A & B		
Sample Description			
Sample Name	MKI-SW-4-1006	Sampling Date	6 October, 2021
Sample No.	W-2110025	Sampling By	Customer
Waste Profile No.		Sample Received Date	6 October, 2021


No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	302	-
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	3.58	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	4.1	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	160000.0	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	1.6	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	3.23	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	182	-
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Chromium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
12	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	12.628	0.002

Remark : LOQ - Limit of Quantitation

APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By :

Cherry Myint Thein
Supervisor
28.10.21



Approved By :

Ni Ni Aye Lwin
Assistant Manager
Oct 28, 2021



Water Quality Monitoring Report for Development of Industrial Area in Thilawa SEZ Zone A
(Bi-Monthly Monitoring in FY October - 2021)

DOWA

GOLDEN DOWA ECO-SYSTEM MYANMAR CO., LTD.
Unit No.1, Thilawa SEZ Zone A, Yangon Region, Myanmar
Phone No. Fax No. (+95) 1 2698251



Report No. : GEM-LAB-202110061

Revision No. : 1

Report Date : 25 October , 2021

Application No. : 0001-C001

Analysis Report

Client Name	: Myanmar Koei International LTD (MKI)		
Address	: No. 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar		
Project Name	: Environment Monitoring report for Zone A & B		
Sample Description			
Sample Name	: MKI-GW-1-1006		Sampling Date : 6 October, 2021
Sample No.	: W-2110026		Sampling By : Customer
Waste Profile No.	: -		Sample Received Date : 6 October, 2021


No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	8	-
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	2.81	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	3.5	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	4.5	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	1.2	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	0.00	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	1366	-
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	< 0.002	0.002
11	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.390	0.002
12	Escherichia Coli	APHA 9221 F Escherichia Coli Procedure Using Fluorogenic Substrate	MPN/100ml	<1.8	1.8

Remark : LOQ - Limit of Quantitation

APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By :

Cherry Myint Thein
Supervisor
25-10-21



Approved By :

Ni Ni Aye Lwin Oct 25, 2021
Assistant Manager





MYANMAR JAPAN THILAWA DEVELOPMENT LIMITED

**Thilawa Special Economic Zone (Zone A)
Development Project (Operation Phase)**

Appendix -B

Water and Waste Water Monitoring Report

December, 2021

Environmental Monitoring Plan (Operation Phase)



**WATER QUALITY MONITORING REPORT
FOR DEVELOPMENT OF INDUSTRIAL AREA
IN THILAWA SEZ ZONE A
(OPERATION STAGE)**

(Bi-Annually Monitoring)

December 2021
Myanmar Koei International Ltd.



TABLE OF CONTENTS

CHAPTER 1: INTRODUCTION	1
1.1 General	1
CHAPTER 2: WATER QUALITY MONITORING	2
2.1 Monitoring Items	2
2.2 Description of Sampling Points	3
2.3 Monitoring Method.....	5
2.4 Monitoring Period.....	6
2.5 Monitoring Results.....	6
CHAPTER 3: CONCLUSION AND RECOMMENDATIONS.....	10
APPENDIX-1 FIELD SURVEY PHOTOS	A1-1
APPENDIX-2 LABORATORY RESULTS	A2-1

LIST OF TABLES

Table 2.1-1 Monitoring Items for Water Quality.....	2
Table 2.2-1 Outline of Sampling Points.....	3
Table 2.3-1 Analytic Method for Water Quality.....	5
Table 2.4-1 Sampling Time of Each Station.....	6
Table 2.4-2 Tide Record for Yangon River, Myanmar.....	6
Table 2.5-1 Results of Water Quality Monitoring on All Discharges and Gates.....	7
Table 2.5-2 Result of Water Quality Survey for Reference Monitoring Points for Comparison with Discharging Points and Baseline of Discharged Creek.....	9

LIST OF FIGURES

Figure 1.1-1 Location of Sampling Points of Water Quality Monitoring	1
--	---



CHAPTER 1: INTRODUCTION

1.1 General

Thilawa Special Economic Zone (SEZ) is located in southern district of Yangon region and about 23 km southeast of Yangon city. As the developer of Thilawa SEZ, Myanmar Japan Thilawa Development Ltd. (MJTD) has a responsibility to carry out regular monitoring in the industrial area of Zone A in accordance with the approved Environmental Impact Assessment (EIA) report and Environmental Management Plan (EMP). MJTD has implemented monitoring various environmental items with the specified time frame to know the environmental conditions in and around the area. As for the monitoring of the water quality, total six sampling points are set for water quality survey, named SW-1, SW-2, SW-4, SW-5, SW-6, and GW-1 have been monitored in Thilawa SEZ and its surrounding area in timely manner. Among the six locations, SW-1 and SW-5 are main discharged points of Thilawa SEZ and SW-6 is discharged from centralized Sewage Treatment Plant (STP) which is required to monitor by Environmental Monitoring Plan (EMoP) in EIA report of Thilawa SEZ Zone A. The remaining points SW-2 and SW-4 are sampled as a reference monitoring for comparison with discharged points and baseline of discharged creek. Moreover, GW-1 is monitored as a reference of existing tube well which is located in the monastery compound. Location of sampling points for water quality monitoring is shown in Figure 1.1-1.




Figure 1.1-1 Location of Sampling Points of Water Quality Monitoring

CHAPTER 2: WATER QUALITY MONITORING

2.1 Monitoring Items

Sampling points and parameters for water quality monitoring are determined so as to cover the environmental monitoring plan of the EIA report.

Water quality sampling was carried out at six locations. Among the six locations, water flow measurement carried out at four locations (SW-1, SW-4, SW-5 and SW-6) where can be measured by Current Meter. Monitoring items and sampling points are summarized in Table 2.1-1.

Table 2.1-1 Monitoring Items for Water Quality

No.	Parameters	SW-1	SW-2	SW-4	SW-5	SW-6	GW-1	Remarks
1	Water Temperature	○	○	○	○	○	○	On-site measurement
2	pH	○	○	○	○	○	○	On-site measurement
3	DO	○	○	○	○	○	○	On-site measurement
4	BOD (5)	○	○	○	○	○	○	Laboratory analysis
5	COD (Cr)	○	○	○	○	○	○	Laboratory analysis
6	Total Nitrogen	○	○	○	○	○	○	Laboratory analysis
7	Suspended Solids	○	○	○	○	○	○	Laboratory analysis
8	Total Coliform	○	○	○	○	○	○	Laboratory analysis
9	Total Phosphorous	○	○	○	○	○	○	Laboratory analysis
10	Color	○	○	○	○	○	○	Laboratory analysis
11	Odor	○	○	○	○	○	○	Laboratory analysis
12	Zinc	○	○	○	○	○	○	Laboratory analysis
13	Arsenic	○	○	○	○	○	○	Laboratory analysis
14	Chromium	○	○	○	○	○	○	Laboratory analysis
15	Cadmium	○	○	○	○	○	○	Laboratory analysis
16	Selenium	○	○	○	○	○	○	Laboratory analysis
17	Lead	○	○	○	○	○	○	Laboratory analysis
18	Copper	○	○	○	○	○	○	Laboratory analysis
19	Barium	○	○	○	○	○	○	Laboratory analysis
20	Nickel	○	○	○	○	○	○	Laboratory analysis
21	Cyanide	○	○	○	○	○	○	Laboratory analysis
22	Total Cyanide	○	○	○	○	○	○	Laboratory analysis
23	Free Chlorine	○	○	○	○	○	○	Laboratory analysis
24	Sulphide	○	○	○	○	○	○	Laboratory analysis
25	Formaldehyde	○	○	○	○	○	○	Laboratory analysis
26	Phenols	○	○	○	○	○	○	Laboratory analysis
27	Total Residual Chlorine	○	○	○	○	○	○	Laboratory analysis
28	Chromium (Hexavalent)	○	○	○	○	○	○	Laboratory analysis
29	Ammonia	○	○	○	○	○	○	Laboratory analysis
30	Fluoride	○	○	○	○	○	○	Laboratory analysis
31	Silver	○	○	○	○	○	○	Laboratory analysis
32	Oil and Grease	○	○	○	○	○	○	Laboratory analysis
33	Total Dissolved Solids	○	○	○	○	○	○	Laboratory analysis
34	Iron	○	○	○	○	○	○	Laboratory analysis
35	Mercury	○	○	○	○	○	○	Laboratory analysis
36	Escherichia Coli (Self-monitoring)	○	-	-	○	-	○	Laboratory analysis
37	Flow Rate	○	-	○	○	○	-	On-site measurement

Source: Myanmar Koei International Ltd.

2.2 Description of Sampling Points

The outline of sampling points is mentioned in Table 2.2-1. The photos of conducting field survey at each sampling points are mentioned in Appendix-1.

Table 2.2-1 Outline of Sampling Points

No.	Station	Detailed Information
1	SW-1	Coordinate - N - 16° 40' 13.5", E - 96° 16' 39.8" Location - Outlet of Retention Pond Survey Item – Surface water sampling and water flow rate measurement
2	SW-2	Coordinate - N - 16° 40' 20.69", E - 96° 17' 18.04" Location - Upstream of Shwe Pyauk Creek Survey Item – Surface water sampling
3	SW-4	Coordinate - N - 16° 39' 42.84", E - 96° 16' 27.42" Location - Downstream of Shwe Pyauk Creek Survey Item – Surface water sampling and water flow rate measurement
4	SW-5	Coordinate - N - 16° 40' 10.7", E - 96° 16' 22.6" Location - Outlet of Retention Canal Survey Item – Surface water sampling and water flow rate measurement
5	SW-6	Coordinate - N - 16° 40' 27.13", E - 96° 16' 30.68" Location - Outlet from STP to Retention Pond Survey Item – Surface water sampling and water flow rate measurement
6	GW-1	Coordinate - N - 16° 40' 16.96", E - 96° 16' 34.01" Location - In Moegyoe Swan Monastery Survey Item – Ground Water Sampling

Source: Myanmar Koei International Ltd.



SW-1

SW-1 was collected at the discharge point of retention pond which is located in the east of Moegyoe Swan monastery. The distance is about 530 m downstream of SW-6. This drainage is flowing from north to south and then connected to the Shwe Pyauk creek through earth drain. The water quality of this monitoring point has been influenced by the water from downstream due to flow back by tidal fluctuation. In addition, it seems that a part of wastewater from monastery has reached to the culvert in the SEZ area and discharging to the retention pond.

SW-2 (Reference Point)

SW-2 was collected at the upstream of Shwe Pyauk creek. This sampling point is located in the southeast of Zone A area and at the south of Dagon-Thilawa road. The surrounding areas are Zone B in the southwest and local industrial zone in the east respectively.

SW-4 (Reference Point)

SW-4 was collected at the downstream of Shwe Pyauk creek, after mixing of discharge water from local industrial zone, construction site of Zone B and Zone A, which is flowing from east to west and then entering into the Yangon River. The distance is about 2.15 km downstream of SW-2. This sampling point is located in the southwest of Zone A area and in the south of Dagon-Thilawa road. The surrounding areas are Zone B and local industrial zone in the east respectively.

SW-5

SW-5 was collected at retention canal near main gate of Thilawa SEZ. Most of the water collected in this canal is rain water and plantation water from surrounding area. This canal is also connected to the Shwe Pyauk creek. The water quality of this monitoring point may have been influenced by the water from downstream due to flow back by tidal fluctuation.

SW-6

SW-6 was collected at the drain outlet of centralized STP which is located in the north of Moegyoe Swan monastery compound and retention pond (SW-1). Then the treated water is flowing to the retention pond. The distance is about 530 m upstream of (SW-1).

GW-1 (Reference of Existing Tube Well)

GW-1 was collected from tube well as ground water sample. It is located in the compound of Moegyoe Swan monastery. The surrounding areas are Zone A in the west, retention pond in the east and Dagon-Thilawa road in the south respectively.




2.3 Monitoring Method

All water samples were collected with cleaned sampling bottles and analyzed by the following standard method as shown in Table 2.3-1. All samples were kept in iced boxes keeping at 2-4° C and were transported to the laboratory. Among the parameters; water temperature, pH and DO were measured by the on-site instrument “Horiba, U-52” and water flow rate was also conducted by using the on-site instrument “JFE Digital Current Meter”.

Table 2.3-1 Analytic Method for Water Quality

No.	Parameter	Method
1	Water Temperature	Instrument Analysis Method (Horiba, U-52, Multi Water Quality Checker)
2	pH	Instrument Analysis Method (Horiba, U-52, Multi Water Quality Checker)
3	Suspended Solids (SS)	APHA 2540 D (Dry at 103-105°C Method)
4	Dissolved Oxygen (DO)	Instrument Analysis Method (Horiba, U-52, Multi Water Quality Checker)
5	BOD (5)	APHA 5210 B (5 Days BOD Test)
6	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)
7	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)
8	Total Nitrogen (T-N)	HACH Method 10072(TNT Persulfate Digestion Method)
9	Total Phosphorous (T-P)	APHA 4500-P E (Ascorbic Acid Method)
10	Color	APHA 2120C (Spectrophotometric Method)
11	Odor	APHA 2150 B (Threshold Odor Test)
12	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)
13	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
14	Zinc	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
15	Arsenic	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
16	Chromium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
17	Cadmium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
18	Selenium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
19	Lead	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
20	Copper	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
21	Barium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
22	Nickel	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
23	Cyanide	HACH 8027 (Pyridine-Pyrazalone Method)
24	Total Cyanide	Distillation process: APHA 4500-CN-C. Total Cyanide after Distillation, Determine Cyanide Concentration Process: HACH 8027 (Pyridine – Pyrazalone Method)
25	Free Chlorine	APHA 4500-CL G (DPD Colorimetric Method)
26	Sulphide	HACH 8131 (USEPA Methylene Blue Method)
27	Formaldehyde	HACH 8110 (MBTH Method)
28	Phenols	USEPA Method 420.1 (Phenolics (Spectrophotometric, Manual 4 AAP With Distillation))
29	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
30	Total Dissolved Solids	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)
31	Total Residual Chlorine	APHA 4500-CL G (DPD Colorimetric Method)
32	Chromium (Hexavalent)	ISO 11083:1994 (Determination of chromium (VI) Spectrometric method using 1,5-diphenylcarbazide)
33	Ammonia	HACH Method 10205 (Silicylate TNT Plus Method)
34	Fluoride	APHA 4110 B (Ion Chromatography with Chemical Suppression of Eluent Conductivity)
35	Silver	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
36	Escherichia Coli	APHA 9221 F (Escherichia Coli Procedure Using Fluorogenic Substrate)
37	Flow Rate	Detection of Electromagnetic Elements (Real-time measurement by AEM 213-D Digital Current Meters)

Source: Myanmar Koei International Ltd.



2.4 Monitoring Period

Water quality and water flow rate monitoring were conducted on 14 December 2021 and sampling time is shown in Table 2.4-1 to avoid tidal effect. The tide record for Yangon River, Myanmar on 14 December 2021 is shown in Table 2.4-2.

Table 2.4-1 Sampling Time of Each Station

No.	Station	Sampling Time
1	SW-1	14/12/2021 10:49
2	SW-2	14/12/2021 08:54
3	SW-4	14/12/2021 08:02
4	SW-5	14/12/2021 09:47
5	SW-6	14/12/2021 10:19
6	GW-1	14/12/2021 12:03

Source: Myanmar Koei International Ltd.

Table 2.4-2 Tide Record for Yangon River, Myanmar

Date	Time	Height	Tide Conditions
14/12/2021	01:10	4.84	High Tide
	08:25	1.11	Low Tide
	13:44	4.45	High Tide
	20:25	1.09	Low Tide

Source: Myanmar Port Authority, Tide Table for the Yangon River and Elephant Point, 2021.

2.5 Monitoring Results

Results of water quality monitoring are summarized in Table 2.5-1. Analytical results of the laboratory are described in Appendix-2. The results were compared with the target value of effluent water quality discharging to water body stipulated in the EIA report.

2.5.1 Results of Water Quality at the Outlet of Sewage Treatment Plant of Industrial Area of Thilawa SEZ and at the Point before Discharging to Creek

As the comparison with the target value, the results of suspended solids (SS), total coliform, free chlorine and total residual chlorine exceeded than the target values.

As for the result of SS, the result at the outlet of the centralized STP (SW-6) complied with the target value. It implied that effluents from each locator was treated well by the STP. On the other hand, results at the monitoring points of retention pond (SW-1) before discharging to creek, exceeded the target value due to the surface water run-off from bare land in Zone A.

As for the result of total coliform of surface water, the result at the outlet of the centralized STP (SW-6) complied with the target value. It may prove that effluents from each locator was treated well by the STP. On the other hand, result at monitoring point of retention canal (SW-5) exceeded the target value due to the expected reason; the potential expected reason might be natural bacteria existed in all area of Zone A because there are various kinds of vegetation and creature such as birds, and small animals in and along the retention canals.

Since the composition of the total coliform include bacteria from natural origin, and even after total coliform do not affect human health directly, self-monitoring for E. Coli analysis was carried out to identify health impact by coliform bacteria. As for the result of E.Coli of surface water, all of results were under the reference value. Therefore, although the target value of total coliform exceeded at monitoring point of retention canal (SW-5), but it is considered that there is no significant impact on human health.

As for the result of free chlorine and total residual chlorine, the results at the outlet of the centralized STP (SW-6) are 1.1 mg/l and 1.6 mg/l are higher than the target value. A possible reason for exceeding the target value is because of the chlorine remaining in the wastewater before discharged. However, the results of free chlorine and total residual chlorine at (SW-1) which is one of the final discharge points of Zone A is under



the target value of free chlorine (1 mg/l) and of total residual chlorine (0.2 mg/l). Therefore, it can be considered that there is no significant impact on the human health and living environment.

Table 2.5-1 Results of Water Quality Monitoring on All Discharges and Gates

No.	Parameters	Unit	SW-1	SW-5	SW-6	Target Value (Reference Value for Self- Monitoring)
1	Water Temperature	°C	23	22	25	≤ 35
2	pH	-	9.0	7.9	6.9	6~9
3	Suspended Solid (SS)	mg/L	100	28	14	50
4	Dissolved Oxygen (DO)	mg/L	11.92	6.17	5.48	-
5	BOD (5)	mg/L	8.05	3.91	3.84	30
6	COD (Cr)	mg/L	39.2	19.2	21.2	125
7	Total Coliform	MPN/100ml	240	1600	< 1.8	400
8	Total Nitrogen (T-N)	mg/L	4.6	1.7	8.9	80
9	Total Phosphorous (T-P)	mg/L	-	-	-	2
10	Color	TCU (True Color Unit)	9.41	7.46	5.13	150
11	Odor	TON (Threshold Odor Number)	1	1	1	-
12	Oil and Grease	mg/L	< 3.1	< 3.1	< 3.1	10
13	Mercury	mg/L	≤ 0.002	≤ 0.002	≤ 0.002	0.005
14	Zinc	mg/L	0.034	0.016	0.016	2
15	Arsenic	mg/L	≤ 0.010	≤ 0.010	≤ 0.010	0.1
16	Chromium	mg/L	≤ 0.002	≤ 0.002	≤ 0.002	0.5
17	Cadmium	mg/L	≤ 0.002	≤ 0.002	≤ 0.002	0.03
18	Selenium	mg/L	≤ 0.010	≤ 0.010	≤ 0.010	0.02
19	Lead	mg/L	≤ 0.002	≤ 0.002	≤ 0.002	0.1
20	Copper	mg/L	≤ 0.002	≤ 0.002	≤ 0.002	0.5
21	Barium	mg/L	0.018	0.022	0.004	1
22	Nickel	mg/L	≤ 0.002	≤ 0.002	≤ 0.002	0.2
23	Cyanide	mg/L	< 0.002	< 0.002	< 0.002	0.1
24	Total Cyanide	mg/L	0.009	0.003	0.005	1
25	Free Chlorine	mg/L	< 0.1	< 0.1	1.1	1
26	Sulphide	mg/L	0.151	0.044	0.006	1
27	Formaldehyde	mg/L	0.025	0.027	0.019	1
28	Phenols	mg/L	0.018	0.007	< 0.002	0.5
29	Iron	mg/L	0.246	0.802	0.104	3.5
30	Total Dissolved Solids	mg/L	390	214	444	2000
31	Total Residual Chlorine	mg/L	0.1	0.1	1.6	0.2
32	Chromium (Hexavalent)	mg/L	< 0.05	< 0.05	< 0.05	0.1
33	Ammonia	mg/L	0.70	0.18	7.94	10
34	Fluoride	mg/L	1.772	1.543	3.517	20
35	Silver	mg/L	≤ 0.002	≤ 0.002	≤ 0.002	0.5
36	Escherichia Coli	MPN/100ml (SW)	79.0	17.0	-	(1000)* (CFU/100ml)
37	Flow Rate	m ³ /s	0.11	0.09	0.01	-

Note: Red color means exceeded value than target value.

*Note: Based on the water utilization at discharged creek, water quality C of quality standard for water baths in Japan, (Ministry of Environment, 1997) is set as a reference value for self-monitoring of E. coli for surface water monitoring. However, due to the capacity of current reliable laboratory that we sent water samples (Dowa Laboratory), the method to analyze the "Colony Forming Unit (CFU)" is not available. Moreover, according to the experiences of laboratory technicians, the analytical method used for CFU is commonly used in drinking water. Therefore, the analytical method used for MPN is assumed to be more accurate and reliable for surface and discharged water. The results of "Most Probable Number (MPN)" are assumed similar to CFU values and compared with reference values. According to the quality standard for water baths in Japan, (Ministry of Environment, 1997), in case of E.Coli result is exceeding 1,000 CFU/100 ml, since it is assumed unsafety, it is considered unsuitable for water baths.

Source: Myanmar Koei International Ltd.



2.5.2 Results of Reference Monitoring for Comparison with Discharged Points and Baseline of Discharged Creek

Results of water quality monitoring are summarized in Table 2.5-2. The results were compared with the target value of effluent water quality discharging to water body stipulated in the EIA report.

As the comparison with the target value, the results of Suspended Solid (SS), total coliform and iron exceeded than the target value.

As for the result of SS, results at the surface water monitoring point (SW-2 and SW-4) exceeded the target value due to two expected reasons; i) delivered from upstream area such as natural origin and wastewater from local industrial zone which outside of Thilawa SEZ, and ii) influence by water from the downstream of monitoring points due to flow back by tidal fluctuation.

As for the result of total coliform of surface water, results at surface water monitoring points (SW-2 and SW-4) exceeded the target value due to two expected reasons; i) runoff of animal waste from the undeveloped area and delivered from local industrial zone and illegal dumping site from outside of Thilawa SEZ in the upstream area, and ii) delivered from surrounding area by tidal effect.

As for the result of iron, the result at the monitoring point of surface water monitoring point (SW-4) exceeded the target value due to the influence of natural origin (iron can reach out from the soil by run-off). Japan set effluent standards for two items as follows; i) health item and ii) living environment item. In the health item, there is no standard value for iron. On the other hand, for the living environment item, the standard value for soluble iron level is 10 mg/l. As the comparison with the living environment standard value in Japan, iron result in SW-4 is lower than the standard value. Therefore, it can be considered that there is no significant impact on the living environment.



Table 2.5-2 Result of Water Quality Survey for Reference Monitoring Points for Comparison with Discharging Points and Baseline of Discharged Creek

No.	Parameters	Unit	SW-2	SW-4	GW-1	Target Value (Reference Value for Self-Monitoring)
1	Water Temperature	°C	19	21	25	≤ 35
2	pH	-	7.2	7.2	7.8	6-9
3	Suspended Solid (SS)	mg/L	78	194	6	50
4	Dissolved Oxygen (DO)	mg/L	3.36	4.66	7.10	-
5	BOD (5)	mg/L	7.99	3.47	4.57	30
6	COD (Cr)	mg/L	30.9	19.8	1.5	125
7	Total Coliform	MPN/100ml	92000	> 160000	13.0	400
8	Total Nitrogen (T-N)	mg/L	7.0	6.4	9.3	80
9	Total Phosphorous (T-P)	mg/L	-	-	-	2
10	Color	TCU (True Color Unit)	17.06	7.86	1.52	150
11	Odor	TON (Threshold Odor Number)	1	1	1	-
12	Oil and Grease	mg/L	< 3.1	< 3.1	< 3.1	10
13	Mercury	mg/L	≤ 0.002	≤ 0.002	≤ 0.002	0.005
14	Zinc	mg/L	0.026	0.060	0.006	2
15	Arsenic	mg/L	≤ 0.010	≤ 0.010	≤ 0.010	0.1
16	Chromium	mg/L	≤ 0.002	≤ 0.002	≤ 0.002	0.5
17	Cadmium	mg/L	≤ 0.002	≤ 0.002	≤ 0.002	0.03
18	Selenium	mg/L	≤ 0.010	≤ 0.010	≤ 0.010	0.02
19	Lead	mg/L	≤ 0.002	≤ 0.002	≤ 0.002	0.1
20	Copper	mg/L	≤ 0.002	≤ 0.002	≤ 0.002	0.5
21	Barium	mg/L	0.062	0.020	0.042	1
22	Nickel	mg/L	< 0.002	≤ 0.002	≤ 0.002	0.2
23	Cyanide	mg/L	< 0.002	0.002	< 0.002	0.1
24	Total Cyanide	Mg/L	0.006	0.015	< 0.002	1
25	Free Chlorine	mg/L	0.1	< 0.1	< 0.1	1
26	Sulphide	mg/L	0.068	0.377	< 0.005	1
27	Formaldehyde	mg/L	0.015	0.072	0.005	1
28	Phenols	mg/L	0.007	0.002	< 0.002	0.5
29	Iron	mg/L	1.632	6.884	0.304	3.5
30	Total Dissolved Solids	mg/L	1026	624	1330	2000
31	Total Residual Chlorine	mg/L	0.2	0.1	< 0.1	0.2
32	Chromium (Hexavalent)	mg/L	< 0.05	< 0.05	< 0.05	0.1
33	Ammonia	mg/L	2.01	1.44	1.94	10
34	Fluoride	mg/L	0.154	1.325	≤ 0.014	20
35	Silver	mg/L	≤ 0.002	≤ 0.002	< 0.002	0.5
36	Escherichia Coli	MPN/100ml* (SW)	-	-	-	(1,000)* (CFU/100ml)
		MPN/100ml** (GW)	-	-	< 1.8	(100)** (MPN/100ml)
37	Flow Rate	m ³ /s	-	0.03	-	-

Note: Red color means the exceeded results than target value.

*Note: Based on the water utilization at discharged creek, water quality C of quality standard for water baths in Japan, (Ministry of Environment, 1997) is set as a reference value of self-monitoring for surface water monitoring. However, due the capacity of current reliable laboratory that we sent water samples (Dowa Laboratory), the method to analyze the "Colony Forming Unit (CFU)" is not available. Moreover, according to the experiences of laboratory technicians, the analytical method used for CFU is commonly used in drinking water. Therefore, the analytical method used for MPN is assumed to be more accurate and reliable for surface and discharged water.

According to the quality standard for water baths in Japan, (Ministry of Environment, 1997), in case of E.Coli result is exceeding 1,000 CFU/100 ml, since it is assumed unsafety, it is considered unsuitable for water baths.

**Note: Based on the water utilization at monitoring point for ground water, B1(Irrigation water) of National Technical Regulation on Surface Water Quality in Vietnam (No. QCVN 08: 2008/BTNMT) is set as a reference value of self-monitoring for ground water monitoring.

Source: Myanmar Koei International Ltd.

CHAPTER 3: CONCLUSION AND RECOMMENDATIONS

As for the result of SS and total coliform at the outlet of the centralized STP (SW-6) complied with the target value. It may prove that effluent from each locator was treated well by the STP. On the other hand, the parameters of SS, results at the monitoring point of retention pond (SW-1) before discharging to creek, exceeded the target value due to the surface water run-off from bare land in Zone A.

The parameter of total coliform at retention canal (SW-5) exceeded the target value in this period for main discharged points of Thilawa SEZ Zone A. In addition, according to the result of self-monitoring of E. coli at retention canal (SW-5), result was under the reference value. Therefore, although the target value of total coliform was exceeded at monitoring point (SW-5), but it is considered that there is no significant impact on human health.

As for the result of free chlorine and total residual chlorine, the results at the outlet of the centralized STP (SW-6) are higher than the target value. A possible reason for exceeding the target value is because of the chlorine remaining in the wastewater before discharged. However, the results of free chlorine and total residual chlorine at (SW-1) which is one of the final discharge points of Zone A is under the target value of free chlorine (1 mg/l) and of total residual chlorine (0.2 mg/l). Therefore, it can be considered that there is no significant impact on the human health and living environment.

As for parameters of Suspended Solid (SS), total coliform and iron in surface water exceeded the target values at reference monitoring points. The expected reasons for exceeding the target values of SS at (SW-2 and SW-4) is delivered from upstream area such as natural origin and wastewater from local industrial zone which is outside of Thilawa SEZ. The expected reasons for exceeding the target value of total coliform at (SW-2 and SW-4) are by natural origin (natural bacteria existed). The expected reasons for exceeding the target values of total coliform at (SW-2 and SW-4) are by natural origin (natural bacteria existed).

The expected reason for exceeding the target value of iron at SW-4 may be due to the influence of natural origin (iron can reach out from the soil by run-off). As the comparison with the living environment standard value in Japan, iron result in SW-4 is lower than the standard value. Therefore, it can be considered that there is no significant impact on the living environment.

As for future subject for main discharged points of Thilawa SEZ Zone A, the following action may be taken to achieve the target levels of SS, total coliform, free chlorine and total residual chlorine and appropriate water quality monitoring:

- To implement regular maintenance at the wastewater treatment plan;
- To continue monitoring Escherichia coli (E. coli) level to identify health impact by coliform bacteria;
- To monitor the possibility of the overflow water from construction sites; and
- To monitor the possibility of the domestic wastewater from construction sites.

End of the Document




APPENDIX-1 FIELD SURVEY PHOTOS



FOR DISCHARGED POINTS OF THILAWA SEZ ZONE A



Surface water sampling and onsite measurement at SW-1



Surface water sampling and onsite measurement at SW-5



Surface water sampling and onsite measurement at SW-6



FOR REFERENCE MONITORING POINTS FOR COMPARISON WITH DISCHARGED POINTS AND BASELINE OF DISCHARGED CREEK



Surface water sampling and onsite measurement at SW-2



Surface water sampling and onsite measurement at SW-4



Ground water sampling and onsite measurement at GW-1

APPENDIX-2 LABORATORY RESULTS



FOR DISCHARGED POINTS AND AFTER CENTRALIZED STP

DOWA

GOLDEN DOWA ECO SYSTEM MYANMAR CO., LTD
Lot No E1 Thilawa SEZ Zone A, Yangon Region, Myanmar
Phone No. / Fax No. (+95) 1 2329051



Report No. : GEM-LAB-202112140
Revision No. : 1
Report Date : 28 December, 2021
Application No. : 0001-C001

Analysis Report


Client Name	: Myanmar Kofi International LTD (MKI)		
Address	: No, 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar.		
Project Name	: Environment Monitoring report for Zone A & B		
Sample Description			
Sample Name	: MKI-SW-1-1214	Sampling Date :	14 December, 2021
Sample No.	: W-2112073	Sampling By :	Customer
Waste Profile No.		Sample Received Date :	14 December, 2021

No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	100	—
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	8.05	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	39.2	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	240	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 ("TNT Persulfate Digestion Method)	mg/l	4.6	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	9.41	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	390	—
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Zinc	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.034	0.002
12	Arsenic	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
13	Chromium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
14	Cadmium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
15	Selenium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
16	Lead	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
17	Copper	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
18	Barium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.018	0.002
19	Nickel	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
20	Silver	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
21	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.246	0.002
22	Cyanide	HACH 8027 (Pyridine - Pyrazalone Method)	mg/l	< 0.002	0.002
23	Total Cyanide	Distillation Process: APHA 4500-CN- C. Total Cyanide after Distillation, Determine Cyanide Concentration Process: HACH 8027 (Pyridine - Pyrazalone Method)	mg/l	0.009	0.002
24	Ammonia	HACH Method 10205 (Silicate TNT Plus Method)	mg/l	0.70	0.02
25	Hexavalent Chromium (Cr6+)	ISO 11083:1994 (Determination of chromium(VI) Spectrometric method using 1,5-diphenylcarbazide)	mg/l	< 0.05	0.05
26	Fluoride	APHA 4110 B (Ion Chromatography with Chemical Suppression of Eluent Conductivity)	mg/l	1.772	0.014
27	Free Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	< 0.1	0.1
28	Total Residual Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	0.1	0.1
29	Sulphide	HACH 8131 (USEPA Methylene Blue Method)	mg/l	0.151	0.005
30	Formaldehyde	HACH 8110 (MBTH Method)	mg/l	0.025	0.003
31	Escherichia Coli	APHA 9221 F Escherichia Coli Procedure Using Fluorogenic Substrate	MPN/100ml	79.0	1.8
32	Phenols	USEPA Method 420.1 (Phenolics (Spectrophotometric, Manual 4AAP With Distillation))	mg/l	0.018	0.002

Remark : LOQ - Limit of Quantitation
APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By :

Ni Ni Aye Lwin
Assistant Manager



Approved By :

Hideki Yamamoto
Managing Director

DEC 28, 2021



Water Quality Monitoring Report for Development of Industrial Area in Thilawa SEZ Zone A
(Bi-Annually Monitoring in FY December - 2021)

DOWA

GO-DEN DOWA ECO-SYSTEM MYANMAR CO., LTD
Lot No E1 Thilawa SEZ Zone A, Yangon Region, Myanmar
Phone No. Fax No. (+95) 1 2309051



Report No. : GEM-IAB-202112141
Revision No. : 1
Report Date : 28 December, 2021
Application No. : 0001-C001

Analysis Report

Client Name	:	Myanmar Koel International LTD (MKI)		
Address	:	No, 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar.		
Project Name	:	Environment Monitoring report for Zone A & B		
Sample Description				
Sample Name	:	MKI-SW-5-1214	Sampling Date :	14 December, 2021
Sample No.	:	W-2112074	Sampling By :	Customer
Waste Profile No.	:	-	Sample Received Date :	14 December, 2021

No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	28	—
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	3.91	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	19.2	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100mL	1600	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	1.7	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	7.46	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	214	—
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Zinc	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.016	0.002
12	Arsenic	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
13	Chromium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
14	Cadmium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
15	Selenium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
16	Lead	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
17	Copper	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
18	Barium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.022	0.002
19	Nickel	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
20	Silver	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
21	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.802	0.002
22	Cyanide	HACH 8027 (Pyridine - Pyrazalone Method)	mg/l	< 0.002	0.002
23	Total Cyanide	Distillation Process: APHA 4500-CN- C: Total Cyanide after Distillation, Determine Cyanide Concentration Process: HACH 8027 (Pyridine - Pyrazalone Method)	mg/l	0.003	0.002
24	Ammonia	HACH Method 10205 (Silicate TNT Plus Method)	mg/l	0.18	0.02
25	Hexavalent Chromium (Cr ⁶⁺)	ISO 11083:1994 (Determination of chromium(VI) Spectrometric method using 1,5-diphenylcarbazide)	mg/l	< 0.05	0.05
26	Fluoride	APHA 4110 B (Ion Chromatography with Chemical Suppression of Eluent Conductivity)	mg/l	1.543	0.014
27	Free Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	< 0.1	0.1
28	Total Residual Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	0.1	0.1
29	Sulphide	HACH 8131 (USEPA Methylene Blue Method)	mg/l	0.044	0.005
30	Formaldehyde	HACH 8110 (MBTH Method)	mg/l	0.027	0.003
31	Escherichia Coli	APHA 9221 F Escherichia Coli Procedure Using Fluorogenic Substrate	MPN/100mL	17.0	1.8
32	Phenols	USEPA Method 420.1 (Phenolics (Spectrophotometric, Manual 4AAP With Distillation))	mg/l	0.007	0.002


Remark : LOQ - Limit of Quantitation
APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By:

Ni Ni Aye Lwin
Assistant Manager

Approved By :

Hidolin Yoma
Managing Director



Water Quality Monitoring Report for Development of Industrial Area in Thilawa SEZ Zone A
(Bi-Annually Monitoring in FY December - 2021)

DOWA

GOLDEN DOWA ECO-SYSTEM MYANMAR CO., LTD.
Lot No E1 Thilawa SEZ Zone A, Yangon Region, Myanmar.
Phone No. Fax No. (+95) 1 2309051


motivate our planet
Doc No: GEM-L-B-R004/50
Page 01

Report No. : GEM-LAB-202112142
Revision No. : 1
Report Date : 28 December, 2021
Application No. : 0001-C001

Analysis Report


Client Name	Myanmar Koi International LTD (MKI)		
Address	No, 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar.		
Project Name	Environment Monitoring report for Zone A & B		
Sample Description			
Sample Name	MKI-SW-6-1214	Sampling Date :	14 December, 2021
Sample No.	W-2112075	Sampling By :	Customer
Waste Profile No.	-	Sample Received Date :	14 December, 2021

No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	14	—
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	3.84	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	21.2	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	< 1.8	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	8.9	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	5.13	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	444	—
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Zinc	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.016	0.002
12	Arsenic	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
13	Chromium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
14	Cadmium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
15	Selenium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
16	Lead	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
17	Copper	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
18	Barium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.004	0.002
19	Nickel	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
20	Silver	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
21	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.104	0.002
22	Cyanide	HACH 8027 (Pyridine - Pyrazalone Method)	mg/l	< 0.002	0.002
23	Total Cyanide	Distillation Process: APHA 4500-CN- C. Total Cyanide after Distillation, Determine Cyanide Concentration Process: HACH 8027 (Pyridine - Pyrazalone Method)	mg/l	0.005	0.002
24	Ammonia	HACH Method 10205 (Silicilate TNT Plus Method)	mg/l	7.94	0.02
25	Hexavalent Chromium (Cr6+)	ISO 11083:1994 (Determination of chromium(VI) Spectrometric method using 1,5 diphenylcarbazide)	mg/l	< 0.05	0.05
26	Fluoride	APHA 4110 B (Ion Chromatography with Chemical Suppression of Eluent Conductivity)	mg/l	3.517	0.014
27	Free Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	1.1	0.1
28	Total Residual Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	1.6	0.1
29	Sulphide	HACH 8131 (USEPA Methylene Blue Method)	mg/l	0.006	0.005
30	Formaldehyde	HACH 8110 (MBTH Method)	mg/l	0.019	0.003
31	Phenols	USEPA Method 420.1 (Phenolics (Spectrophotometric, Manual 4AAP Wt/ Distillation))	mg/l	< 0.002	0.002

Remark : LOQ - Limit of Quantitation
APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By:

Ni Ni Aye Lwin
Assistant Manager



Approved By:

Hideto Yomo
Managing Director
Dec 28, 2021



**Water Quality Monitoring Report for Development of Industrial Area in Thilawa SEZ Zone A
(Bi-Annually Monitoring in FY December - 2021)**

**FOR REFERENCE MONITORING POINTS FOR COMPARISON WITH DISCHARGED POINTS
AND BASELINE OF DISCHARGED CREEK**

DOWA

GOLDEN HOWA ECO-SYSTEM MYANMAR CO., LTD.
Lot No E1, Thilawa SEZ Zone A, Yangon Region, Myanmar
Phone No / Fax No: (+95) 1 2309051



Report No. : GEM-LAB-202112143
Revision No. : 1
Report Date : 28 December, 2021
Application No. : C001-C001

Analysis Report

Client Name : Myanmar Kobi International LTD (MKI)
Address : No. 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar.
Project Name : Environment Monitoring report for Zone A & B
Sample Description
Sample Name : MKI-SW-2-1214 **Sampling Date** : 14 December, 2023
Sample No. : W-2112076 **Sampling By** : Customer
Waste Profile No. : - **Sample Received Date** : 14 December, 2023

No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	78	—
2	BOD (5)	APIA 5210 B (5 Days BOD Test)	mg/l	7.99	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	30.9	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	92000	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	7.0	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	17.06	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	1026	—
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Zinc	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.026	0.002
12	Arsenic	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
13	Chromium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
14	Cadmium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
15	Selenium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
16	Lead	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
17	Copper	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
18	Banum	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.062	0.002
19	Nickel	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
20	Silver	APIA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
21	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	1.632	0.002
22	Cyanide	HACH 8027 (Pyridine - Pyrazalone Method)	mg/l	< 0.002	0.002
23	Total Cyanide	Distillation Process: APHA 4500-CN C, Total Cyanide after Distillation, Determine Cyanide Concentration Process: HACH 8027 (Pyridine - Pyrazalone Method)	mg/l	0.006	0.002
24	Ammonia	HACH Method 10205 (Silicilate TNT Plus Method)	mg/t	2.01	0.02
25	Hexavalent Chromium (Cr-6+)	ISO 11083:1994 (Determination of chromium(VI) Spectrometric method using 1,5-diphenylcarbazide)	mg/l	< 0.05	0.05
26	Fluoride	APIA 4110 B (Ion Chromatography with Chemical Suppression of Eluent Conductivity)	mg/l	0.154	0.014
27	Free Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	0.1	0.1
28	Total Residual Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	0.2	0.1
29	Sulphide	HACH 8131 (USEPA Methylene Blue Method)	mg/l	0.068	0.005
30	Formaldehyde	HACH 8110 (MBTH Method)	mg/l	0.015	0.003
31	Phenols	USEPA Method 420.1 (Phenolics (Spectrophotometric, Manual 144P with Distillation))	mg/l	0.007	0.002

Remark : LOQ - Limit of Quantitation
APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By :

Ni Ni Aye Lwin
Assistant Manager



Approved By :

Hiroki Yomo 28, Dec, 2021
Managing Director



Water Quality Monitoring Report for Development of Industrial Area in Thilawa SEZ Zone A
(Bi-Annually Monitoring in FY December - 2021)

DOWA

GOULDEN DOWA ECO-SYSTEM MYANMAR CO., LTD
Lot No E1, Thilawa SEZ Zone A, Yangon Region, Myanmar
Phone No. Fax No. (+95) 12309051


motivate our planet
Doc No: GEM-LB-R0047/00
Page 1 of 1

Report No. : GEM-LAB-202112144

Revision No. : 1

Report Date : 28 December, 2021

Application No. : 0001-C001


Analysis Report


Client Name	: Myanmar Koh International LTD (MKI)		
Address	: No, 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar.		
Project Name	: Environment Monitoring report for Zone A & B		
Sample Description			
Sample Name	: MKI-SW 4-1214	Sampling Date :	14 December, 2021
Sample No.	: W-2112077	Sampling By :	Customer
Waste Profile No.	: -	Sample Received Date :	14 December, 2021

No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	194	-
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	3.47	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	19.8	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	>160000	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	6.4	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	7.86	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	624	-
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Zinc	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.060	0.002
12	Arsenic	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
13	Chromium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
14	Cadmium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
15	Selenium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
16	Lead	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
17	Copper	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
18	Barium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.020	0.002
19	Nickel	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
20	Silver	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
21	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	6.884	0.002
22	Cyanide	HACH B027 (Pyridine - Pyrazalione Method)	mg/l	0.002	0.002
23	Total Cyanide	APHA 4500-CN C. Total Cyanide after Distillation, Determine Cyanide Concentration process: HACH B027 (Pyridine - Pyrazalione Method)	mg/l	0.015	0.002
24	Ammonia	HACH Method 10205 (Silicate TNT Plus Method)	mg/l	1.44	0.02
25	Hexavalent Chromium (Cr6+)	ISO 11083:1994 (Determination of chromium(VI) Spectrometric method using 1,5-diphenylcarbazide)	mg/l	< 0.05	0.05
26	Fluoride	APHA 4110 B (Ion Chromatography with Chemical Suppression of Eluent Conductivity)	mg/l	1.325	0.014
27	Free Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	< 0.1	0.1
28	Total Residual Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	0.1	0.1
29	Sulphide	HACH B131 (USEPA Methylene Blue Method)	mg/l	0.377	0.005
30	Formaldehyde	HACH B110 (MBTH Method)	mg/l	0.072	0.003
31	Phenols	USEPA Method 420.1 (Phenolics (Spectrophotometric, Manual 4AAP With Distillation))	mg/l	0.002	0.002


Remark : LOQ - Limit of Quantitation
APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By :


Ni Ni Aye Lwin
Assistant Manager



Approved By :


Hidaka Yone
Dec 28, 2021
Managing Director



Water Quality Monitoring Report for Development of Industrial Area in Thilawa SEZ Zone A
(Bi-Annually Monitoring in FY December - 2021)

DOWA

GOLDEN DOWA ECO-SYSTEM MYANMAR CO., LTD.
Lot No E1, Thilawa SLZ Zone A, Yangon Region, Myanmar
Phone No. Fax No. (+95) 1 2309052



Report No. : GEM-LAH-202112145
Revision No. : 1
Report Date : 28 December, 2021
Application No. : 0001-C-001

Analysis Report


Client Name	: Myanmar Koei International LTD (MKI)		
Address	: No, 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar.		
Project Name	: Environmental Monitoring report for Zone A & B		
Sample Description			
Sample Name	: MKI-GW-1-1214	Sampling Date :	14 December, 2021
Sample No.	: W-2112078	Sampling By :	Customer
Waste Profile No.	:	Sample Received Date :	14 December, 2021

No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	6	—
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	4.57	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	1.5	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	13.0	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	9.3	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	1.52	0.00
8	Oder	APHA 2150 B (Threshold Odor Test)	TDN	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	1330	—
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Zinc	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.006	0.002
12	Arsenic	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
13	Chromium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
14	Cadmium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
15	Selenium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
16	Lead	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
17	Copper	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
18	Barium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.042	0.002
19	Nickel	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
20	Silver	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
21	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.304	0.002
22	Cyanide	HACH 8027 (Pyridine-Pyrazalone Method)	mg/l	< 0.002	0.002
23	Total Cyanide	Distillation Process: APHA 4500 CN- C. Total Cyanide after Distillation, Determine Cyanide Concentration Process: HACH 8027 (Pyridine -	mg/l	< 0.002	0.002
24	Ammonia	HACH Method 10205 (Silicate TNT Plus Method)	mg/l	1.94	0.02
25	Hexavalent Chromium (Cr6+)	[ISO 11083:1994 (Determination of chromium(VI) Spectrometric method using 1,5-diphenylcarbazide)]	mg/l	< 0.05	0.05
26	Fluoride	APHA 4110 B (Ion Chromatography with Chemical Suppression of Eluent Conductivity)	mg/l	≤ 0.014	0.014
27	Free Chlorine	APHA 4500 CL G (DPPD Colorimetric Method)	mg/l	< 0.1	0.1
28	Total Residual Chlorine	APHA 4500 CL G (DPPD Colorimetric Method)	mg/l	< 0.1	0.1
29	Sulphide	HACH B131 (USEPA Methylene Blue Method)	mg/l	< 0.005	0.005
30	Formaldehyde	HACH B110 (MBTH Method)	mg/l	0.005	0.003
31	Escherichia Coli	APHA 9221 F Escherichia Coli Procedure Using Fluorogenic Substrate	MPN/100ml	< 1.8	1.8
32	Phenols	USEPA Method 420.1 (Phenols (Spectrophotometric, Manual 4AAP With Distillation))	mg/l	< 0.002	0.002

Remark : LOQ - Limit of Quantitation
APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By :

Ni Ni Aye Lwin
Assistant Manager



Approved By :

Hideki Yamada
Managing Director
Dec 28, 2021





MYANMAR JAPAN THILAWA DEVELOPMENT LIMITED

**Thilawa Special Economic Zone (Zone A)
Development Project (Operation Phase)**

Appendix - C

Air Quality Monitoring Report

September, 2021

Environmental Monitoring Plan (Operation Phase)



**AIR QUALITY MONITORING
REPORT
FOR DEVELOPMENT OF INDUSTRIAL AREA
THILAWA SEZ ZONE A
(OPERATION STAGE)**

(BI-ANNUALLY MONITORING)

September 2021
Myanmar Koei International Ltd.



TABLE OF CONTENTS

CHAPTER 1: OUTLINES AND SUMMARY OF MONITORING PLAN	1
1.1 General	1
1.2 Outlines of Monitoring Plan.....	1
CHAPTER 2: AIR QUALITY MONITORING.....	2
2.1 Monitoring Item	2
2.2 Monitoring Location.....	2
2.3 Monitoring Period	2
2.4 Monitoring Method	3
2.5 Monitoring Results	3
CHAPTER 3: CONCLUSION AND RECOMMENDATION	5
APPENDIX 1: HOURLY AIR RESULT	A1-1

LIST OF TABLES

Table 1.2-1 Outlines of Air Quality Monitoring Plan.....	1
Table 2.5-1 Air Quality Monitoring Result (Daily Average)	3

LIST OF FIGURES

Figure 2.2-1 Location of Air Quality Monitoring Point	2
Figure 2.4-1 Status of Air Quality Monitoring Point.....	3
Figure 2.5-1 Status of Air Quality Monitoring Point and Wind Direction at AQ-1	4



CHAPTER 1: OUTLINES AND SUMMARY OF MONITORING PLAN

1.1 General

Thilawa Special Economic Zone (TSEZ) is located in the southern district of Yangon region and about 23 km southeast of Yangon city. As the developer of Thilawa SEZ, Myanmar Japan Thilawa Development Ltd. (MJTD) has a responsibility to carry out regular environmental monitoring in the industrial area of Zone A in accordance with the approved Environmental Impact Assessment (EIA) report with Environmental Management Plan (EMP). MJTD has implemented monitoring of various environmental items with the specified time frame to know about the environmental conditions in and around the area.

1.2 Outlines of Monitoring Plan

To assess the environmental condition under the operation of industrial area in and around Thilawa SEZ Zone A, air quality had been monitored from 7 September 2021 – 14 September 2021 as follows;

Table 1.2-1 Outlines of Air Quality Monitoring Plan

Monitoring Date	Monitoring Item	Parameters	Number of Point	Duration	Monitoring Methodology
From 7 September – 14 September, 2021	Air Quality	CO, NO ₂ , TSP, PM ₁₀ and SO ₂	1	7 Days	On site measurement by Haz-Scanner Environmental Perimeter Air Station (EPAS)

Source: Myanmar Koei International Ltd.



CHAPTER 2: AIR QUALITY MONITORING

2.1 Monitoring Item

The parameters for air quality monitoring were CO, NO₂, TSP, PM₁₀ and SO₂.

2.2 Monitoring Location

The air quality measurement equipment, "Haz-Scanner Environmental Perimeter Air Station (EPAS) was set up inside the centralized Sewage Treatment Plant (STP) compound which is southeast of the Thilawa SEZ Zone A, N: 16°40'28.07", E: 96°16'34.06". It is surrounded by the factories of Thilawa SEZ Zone A, north of Dagon-Thilawa road and northeast of Moegyoe Swan monastery respectively. Possible emission sources are dust emissions from construction activities of surrounding Zone A's locators and exhaust gas emissions from surrounded factories. The location of air quality monitoring is shown in the Figure 2.2-1.



Source: Google Earth

Figure 2.2-1 Location of Air Quality Monitoring Point

2.3 Monitoring Period

Air quality monitoring was conducted seven consecutive days from 7 September – 14 September, 2021.



2.4 Monitoring Method

Monitoring of CO, NO₂, TSP, PM₁₀ and SO₂ were conducted by referring to the recommendation of the United States Environmental Protection Agency (U.S. EPA). The Haz-Scanner EPAS was used to collect ambient air pollutants. The EPAS measures automatically every one minute and directly reads and records onsite for CO, NO₂, PM₁₀ and SO₂. Air quality monitoring equipment is maintained for the proper conditions for the measurement. Due to the limitation of the analytical equipment in Myanmar, TSP results were calculated as predicted value which is based on the results of PM₁₀. Therefore, the result of TSP was evaluated using the estimated TSP concentration values. The state of air quality monitoring is shown in Figure 2.4-1.



Source: Myanmar Koei International Ltd.

Figure 2.4-1 Status of Air Quality Monitoring Point

2.5 Monitoring Results

The daily average value of air quality monitoring results of CO, NO₂, TSP, PM₁₀ and SO₂ are described in Table 2.5-1. Comparing with the target value of CO, NO₂, TSP, PM₁₀ and SO₂ prescribed in EIA report for Thilawa SEZ development project Zone A, concentration of CO, NO₂, TSP, PM₁₀ and SO₂ were lower than the target value.

Regarding the calculation of predicted TSP concentration, the correlation value between PM₁₀ and TSP of ambient air quality guideline value in Thailand as below;

330 µg/m³ (TSP standard value in Thailand) / 120 µg/m³ (PM₁₀ standard value in Thailand) = 2.75 (Correlation value)

Table 2.5-1 Air Quality Monitoring Result (Daily Average)

Date	CO mg/m ³	NO ₂ mg/m ³	TSP mg/m ³	PM ₁₀ mg/m ³	SO ₂ mg/m ³
07-08 Sep, 2021	0.049	0.041	0.034	0.012	0.093
08-09 Sep, 2021	0.046	0.038	0.052	0.019	0.067
09-10 Sep, 2021	0.056	0.091	0.029	0.011	0.025
10-11 Sep, 2021	0.038	0.099	0.026	0.009	0.013
11-12 Sep, 2021	0.033	0.080	0.036	0.013	0.013
12-13 Sep, 2021	0.044	0.066	0.057	0.021	0.019
13-14 Sep, 2021	0.032	0.033	0.070	0.025	0.037
7 Days Average Value	0.043	0.064	0.043	0.016	0.038
Target Value	11.45	0.11	<0.33	<0.12	0.11


Note: The target value of CO, NO₂ and SO₂ were converted from ppm unit to mg/m³. The conversion equation are as follows;

1. (CO, mg/m³) = (CO, ppm) * (Molecular Weight of CO (28)) / 24.45 at 25°C and 1 atm condition
2. (NO₂, mg/m³) = (NO₂, ppm) * (Molecular Weight of NO₂ (46)) / 24.45 at 25°C and 1 atm condition
3. (SO₂, mg/m³) = (SO₂, ppm) * (Molecular Weight of SO₂ (64)) / 24.45 at 25°C and 1 atm condition

Source: Myanmar Koei International Ltd.



Wind direction and wind speed were measured at AQ-1. Hourly average values of measured wind direction and wind speed data are described in Appendix 1. Status of air quality monitoring point and wind direction are described in Figure 2.5-1.



Source: Google Earth

Figure 2.5-1 Status of Air Quality Monitoring Point and Wind Direction at AQ-1

Remark: **N** North **NNE** North-Northeast **NE** Northeast **ENE** East-Northeast **E** East **ESE** East-Southeast **SE** Southeast **SSE** South-Southeast
S South **SSW** South-Southwest **SW** Southwest **WSW** West-Southwest **W** West **WNW** West-Northwest **NW** Northwest



CHAPTER 3: CONCLUSION AND RECOMMENDATION

The result of air quality at AQ-1, concentration of CO, NO₂, TSP, PM₁₀ and SO₂ during seven days monitoring was not exceeded the target value, thus there is no impacts from the operation activities of Zone A.

In conclusion of this environmental survey periodical monitoring will be necessary to grasp the environmental conditions in Thilawa SEZ Zone A and to show the compliance status in the operation stage of Thilawa SEZ Zone A. The mitigation measures for environmental management will be considered in collected periodical environmental data and has to be reviewed in future.




APPENDIX 1: HOURLY AIR RESULT



Air Quality Monitoring Report for Development of Industrial Area Thilawa SEZ Zone A
(Operation Stage, FY September 2021)

Date	Time	CO	NO ₂	TSP	PM ₁₀	SO ₂	Wind Speed	Wind Direction	
		mg/m ³	m/s	Deg.	Direction				
		Hourly	Hourly	Hourly	Hourly	Hourly	Hourly	Hourly	Hourly
07 Sep, 2021	11:00 ~ 11:59	0.024	0.004	0.097	0.035	0.433	3.59	218.84	SW
07 Sep, 2021	12:00 ~ 12:59	0.023	0.004	0.070	0.025	0.393	3.63	226.34	SW
07 Sep, 2021	13:00 ~ 13:59	0.023	0.004	0.009	0.003	0.368	5.32	231.11	SW
07 Sep, 2021	14:00 ~ 14:59	0.023	0.004	0.045	0.016	0.400	4.33	237.10	WSW
07 Sep, 2021	15:00 ~ 15:59	0.023	0.004	0.135	0.049	0.197	4.71	194.04	SSW
07 Sep, 2021	16:00 ~ 16:59	0.041	0.004	0.025	0.009	0.026	3.57	169.02	S
07 Sep, 2021	17:00 ~ 17:59	0.103	0.004	0.008	0.003	0.013	3.35	160.16	SSE
07 Sep, 2021	18:00 ~ 18:59	0.039	0.006	0.013	0.005	0.013	2.45	197.94	SSW
07 Sep, 2021	19:00 ~ 19:59	0.038	0.040	0.011	0.004	0.013	3.18	202.60	SSW
07 Sep, 2021	20:00 ~ 20:59	0.062	0.055	0.016	0.006	0.013	3.84	229.79	SW
07 Sep, 2021	21:00 ~ 21:59	0.023	0.012	0.012	0.004	0.013	6.17	266.19	W
07 Sep, 2021	22:00 ~ 22:59	0.030	0.052	0.032	0.011	0.013	2.93	271.48	W
07 Sep, 2021	23:00 ~ 23:59	0.037	0.064	0.036	0.013	0.013	1.21	241.76	WSW
08 Sep, 2021	0:00 ~ 0:59	0.025	0.067	0.057	0.021	0.013	2.34	282.51	WNW
08 Sep, 2021	1:00 ~ 1:59	0.031	0.081	0.012	0.005	0.013	2.61	277.41	W
08 Sep, 2021	2:00 ~ 2:59	0.034	0.090	0.029	0.011	0.013	2.55	278.72	W
08 Sep, 2021	3:00 ~ 3:59	0.023	0.088	0.043	0.016	0.013	1.46	244.74	WSW
08 Sep, 2021	4:00 ~ 4:59	0.029	0.092	0.025	0.009	0.013	1.31	232.26	SW
08 Sep, 2021	5:00 ~ 5:59	0.049	0.096	0.032	0.012	0.013	1.26	265.73	W
08 Sep, 2021	6:00 ~ 6:59	0.097	0.097	0.029	0.011	0.013	1.35	327.69	NNW
08 Sep, 2021	7:00 ~ 7:59	0.171	0.076	0.008	0.003	0.013	1.49	327.33	NNW
08 Sep, 2021	8:00 ~ 8:59	0.145	0.038	0.017	0.006	0.013	1.82	237.92	WSW
08 Sep, 2021	9:00 ~ 9:59	0.052	0.004	0.039	0.014	0.049	2.34	93.98	E
08 Sep, 2021	10:00 ~ 10:59	0.028	0.004	0.008	0.003	0.154	2.22	203.12	SSW

Max	0.171	0.097	0.135	0.049	0.433
Avg	0.049	0.041	0.034	0.012	0.093
Min	0.023	0.004	0.008	0.003	0.013





Air Quality Monitoring Report for Development of Industrial Area Thilawa SEZ Zone A
(Operation Stage, FY September 2021)


Date	Time	CO	NO ₂	TSP	PM ₁₀	SO ₂	Wind Speed	Wind Direction	
		mg/m ³	m/s	Deg.	Hourly				
		Hourly	Hourly	Hourly	Hourly	Hourly			Hourly
08 Sep, 2021	11:00 ~ 11:59	0.026	0.004	0.015	0.005	0.286	2.60	276.81	W
08 Sep, 2021	12:00 ~ 12:59	0.026	0.004	0.174	0.063	0.250	4.91	280.66	W
08 Sep, 2021	13:00 ~ 13:59	0.023	0.004	0.029	0.011	0.212	8.33	266.67	W
08 Sep, 2021	14:00 ~ 14:59	0.023	0.004	0.047	0.017	0.206	5.45	282.16	WNW
08 Sep, 2021	15:00 ~ 15:59	0.023	0.004	0.119	0.043	0.107	6.94	272.97	W
08 Sep, 2021	16:00 ~ 16:59	0.032	0.004	0.041	0.015	0.053	4.41	278.48	W
08 Sep, 2021	17:00 ~ 17:59	0.032	0.004	0.030	0.011	0.067	2.78	289.08	WNW
08 Sep, 2021	18:00 ~ 18:59	0.056	0.004	0.024	0.009	0.015	3.53	270.50	W
08 Sep, 2021	19:00 ~ 19:59	0.023	0.004	0.007	0.002	0.013	4.92	271.13	W
08 Sep, 2021	20:00 ~ 20:59	0.037	0.004	0.005	0.002	0.013	2.09	294.09	WNW
08 Sep, 2021	21:00 ~ 21:59	0.056	0.027	0.008	0.003	0.013	2.10	270.25	W
08 Sep, 2021	22:00 ~ 22:59	0.063	0.056	0.010	0.004	0.013	2.72	278.90	W
08 Sep, 2021	23:00 ~ 23:59	0.029	0.065	0.032	0.012	0.013	2.22	284.08	WNW
09 Sep, 2021	0:00 ~ 0:59	0.034	0.073	0.076	0.028	0.013	1.80	281.77	WNW
09 Sep, 2021	1:00 ~ 1:59	0.039	0.091	0.021	0.008	0.013	0.42	127.64	SF
09 Sep, 2021	2:00 ~ 2:59	0.035	0.091	0.056	0.020	0.013	0.83	171.08	S
09 Sep, 2021	3:00 ~ 3:59	0.034	0.090	0.065	0.024	0.013	1.46	250.70	WSW
09 Sep, 2021	4:00 ~ 4:59	0.038	0.091	0.052	0.019	0.013	1.84	286.33	WNW
09 Sep, 2021	5:00 ~ 5:59	0.047	0.104	0.038	0.014	0.013	1.23	244.67	WSW
09 Sep, 2021	6:00 ~ 6:59	0.107	0.113	0.043	0.016	0.013	1.41	232.19	SW
09 Sep, 2021	7:00 ~ 7:59	0.224	0.067	0.083	0.030	0.013	2.60	282.75	WNW
09 Sep, 2021	8:00 ~ 8:59	0.029	0.005	0.048	0.017	0.013	3.43	275.65	W
09 Sep, 2021	9:00 ~ 9:59	0.043	0.004	0.007	0.002	0.091	2.87	287.50	WNW
09 Sep, 2021	10:00 ~ 10:59	0.025	0.004	0.220	0.080	0.135	4.11	266.84	W

Max	0.224	0.113	0.220	0.080	0.286
Avg	0.046	0.038	0.052	0.019	0.067
Min	0.023	0.004	0.005	0.002	0.013

Air Quality Monitoring Report for Development of Industrial Area Thilawa SEZ Zone A
(Operation Stage, FY September 2021)

Date	Time	CO	NO ₂	TSP	PM ₁₀	SO ₂	Wind Speed	Wind Direction	
		mg/m ³	m/s	Deg.	Hourly				
		Hourly	Hourly	Hourly	Hourly	Hourly			Hourly
09 Sep, 2021	11:00 ~ 11:59	0.023	0.004	0.080	0.029	0.119	4.43	263.03	W
09 Sep, 2021	12:00 ~ 12:59	0.023	0.004	0.025	0.009	0.152	5.10	263.13	W
09 Sep, 2021	13:00 ~ 13:59	0.029	0.004	0.164	0.060	0.045	3.25	263.76	W
09 Sep, 2021	14:00 ~ 14:59	0.116	0.064	0.008	0.003	0.013	1.57	64.97	ENE
09 Sep, 2021	15:00 ~ 15:59	0.125	0.100	0.008	0.003	0.013	2.97	190.52	S
09 Sep, 2021	16:00 ~ 16:59	0.107	0.061	0.004	0.001	0.013	1.44	106.40	ESE
09 Sep, 2021	17:00 ~ 17:59	0.056	0.061	0.003	0.001	0.013	2.71	182.06	S
09 Sep, 2021	18:00 ~ 18:59	0.044	0.083	0.044	0.016	0.013	2.18	194.44	SSW
09 Sep, 2021	19:00 ~ 19:59	0.165	0.082	0.003	0.001	0.013	2.65	223.29	SW
09 Sep, 2021	20:00 ~ 20:59	0.076	0.152	0.014	0.005	0.013	1.89	194.34	SSW
09 Sep, 2021	21:00 ~ 21:59	0.033	0.140	0.008	0.003	0.013	1.63	176.63	S
09 Sep, 2021	22:00 ~ 22:59	0.039	0.148	0.003	0.001	0.013	1.94	133.60	SE
09 Sep, 2021	23:00 ~ 23:59	0.048	0.146	0.013	0.005	0.013	0.25	35.78	NE
10 Sep, 2021	0:00 ~ 0:59	0.037	0.140	0.026	0.010	0.013	1.65	71.62	ENE
10 Sep, 2021	1:00 ~ 1:59	0.029	0.140	0.007	0.003	0.013	1.67	78.72	ENE
10 Sep, 2021	2:00 ~ 2:59	0.025	0.138	0.024	0.009	0.013	1.61	73.88	ENE
10 Sep, 2021	3:00 ~ 3:59	0.025	0.131	0.065	0.024	0.013	2.29	81.76	E
10 Sep, 2021	4:00 ~ 4:59	0.045	0.140	0.019	0.007	0.013	2.45	84.73	E
10 Sep, 2021	5:00 ~ 5:59	0.049	0.138	0.044	0.016	0.013	2.83	94.98	E
10 Sep, 2021	6:00 ~ 6:59	0.075	0.148	0.039	0.014	0.013	2.26	92.80	E
10 Sep, 2021	7:00 ~ 7:59	0.103	0.124	0.027	0.010	0.013	4.75	117.05	ESE
10 Sep, 2021	8:00 ~ 8:59	0.023	0.017	0.004	0.001	0.013	7.92	135.94	SE
10 Sep, 2021	9:00 ~ 9:59	0.023	0.004	0.004	0.001	0.013	8.88	135.50	SE
10 Sep, 2021	10:00 ~ 10:59	0.023	0.020	0.064	0.023	0.013	9.42	141.59	SE

Max	0.165	0.152	0.164	0.060	0.152
Avg	0.056	0.091	0.029	0.011	0.025
Min	0.023	0.004	0.003	0.001	0.013





Air Quality Monitoring Report for Development of Industrial Area Thilawa SEZ Zone A
(Operation Stage, FY September 2021)


Date	Time	CO	NO ₂	TSP	PM ₁₀	SO ₂	Wind Speed	Wind Direction	
		mg/m ³	m/s	Deg.	Hourly				
Hourly	Hourly	Hourly	Hourly	Hourly	Hourly	Hourly	Hourly	Hourly	Hourly
10 Sep, 2021	11:00 ~ 11:59	0.073	0.045	0.035	0.013	0.013	8.80	144.52	SE
10 Sep, 2021	12:00 ~ 12:59	0.035	0.023	0.064	0.023	0.013	13.73	138.30	SE
10 Sep, 2021	13:00 ~ 13:59	0.076	0.115	0.005	0.002	0.013	10.70	134.52	SE
10 Sep, 2021	14:00 ~ 14:59	0.057	0.045	0.175	0.064	0.013	10.83	143.92	SE
10 Sep, 2021	15:00 ~ 15:59	0.038	0.033	0.080	0.029	0.013	9.57	135.88	SE
10 Sep, 2021	16:00 ~ 16:59	0.036	0.064	0.014	0.005	0.013	8.38	160.66	SSE
10 Sep, 2021	17:00 ~ 17:59	0.028	0.128	0.002	0.001	0.013	7.38	163.21	SSE
10 Sep, 2021	18:00 ~ 18:59	0.026	0.117	0.000	0.000	0.013	5.42	163.17	SSE
10 Sep, 2021	19:00 ~ 19:59	0.041	0.125	0.003	0.001	0.013	3.51	163.93	SSE
10 Sep, 2021	20:00 ~ 20:59	0.025	0.122	0.007	0.003	0.013	2.63	172.72	S
10 Sep, 2021	21:00 ~ 21:59	0.039	0.126	0.034	0.012	0.013	1.81	198.74	SSW
10 Sep, 2021	22:00 ~ 22:59	0.029	0.121	0.009	0.003	0.013	2.06	210.16	SSW
10 Sep, 2021	23:00 ~ 23:59	0.031	0.113	0.005	0.002	0.013	1.85	226.88	SW
11 Sep, 2021	0:00 ~ 0:59	0.031	0.121	0.007	0.002	0.013	1.19	191.04	S
11 Sep, 2021	1:00 ~ 1:59	0.036	0.126	0.004	0.002	0.013	0.96	53.04	NE
11 Sep, 2021	2:00 ~ 2:59	0.029	0.131	0.010	0.003	0.013	2.76	94.30	E
11 Sep, 2021	3:00 ~ 3:59	0.039	0.127	0.031	0.011	0.013	2.33	98.50	E
11 Sep, 2021	4:00 ~ 4:59	0.024	0.072	0.067	0.024	0.013	4.35	235.18	SW
11 Sep, 2021	5:00 ~ 5:59	0.030	0.065	0.025	0.009	0.013	4.45	242.35	WSW
11 Sep, 2021	6:00 ~ 6:59	0.041	0.067	0.015	0.006	0.013	4.19	249.37	WSW
11 Sep, 2021	7:00 ~ 7:59	0.028	0.157	0.014	0.005	0.013	3.25	244.30	WSW
11 Sep, 2021	8:00 ~ 8:59	0.043	0.132	0.010	0.004	0.013	1.83	198.15	SSW
11 Sep, 2021	9:00 ~ 9:59	0.051	0.116	0.002	0.001	0.013	1.81	171.33	S
11 Sep, 2021	10:00 ~ 10:59	0.029	0.078	0.000	0.000	0.013	2.25	161.77	SSE

Max	0.076	0.157	0.175	0.064	0.013
Avg	0.038	0.099	0.026	0.009	0.013
Min	0.024	0.023	0.000	0.000	0.013

Air Quality Monitoring Report for Development of Industrial Area Thilawa SEZ Zone A
(Operation Stage, FY September 2021)

Date	Time	CO	NO ₂	TSP	PM ₁₀	SO ₂	Wind Speed	Wind Direction	
		mg/m ³	m/s	Deg.	Direction				
		Hourly	Hourly	Hourly	Hourly	Hourly	Hourly	Hourly	Hourly
11 Sep, 2021	11:00 ~ 11:59	0.026	0.072	0.002	0.001	0.013	3.91	161.15	SSE
11 Sep, 2021	12:00 ~ 12:59	0.033	0.090	0.007	0.003	0.013	5.27	163.51	SSE
11 Sep, 2021	13:00 ~ 13:59	0.023	0.036	0.063	0.023	0.013	4.86	165.00	SSE
11 Sep, 2021	14:00 ~ 14:59	0.040	0.068	0.005	0.002	0.013	5.09	210.67	SSW
11 Sep, 2021	15:00 ~ 15:59	0.043	0.091	0.012	0.004	0.013	4.08	203.10	SSW
11 Sep, 2021	16:00 ~ 16:59	0.023	0.079	0.028	0.010	0.013	3.50	180.97	S
11 Sep, 2021	17:00 ~ 17:59	0.024	0.083	0.007	0.002	0.013	3.33	173.12	S
11 Sep, 2021	18:00 ~ 18:59	0.030	0.095	0.015	0.005	0.013	3.57	174.02	S
11 Sep, 2021	19:00 ~ 19:59	0.023	0.097	0.021	0.008	0.013	4.01	163.32	SSE
11 Sep, 2021	20:00 ~ 20:59	0.028	0.092	0.023	0.008	0.013	2.95	150.45	SSE
11 Sep, 2021	21:00 ~ 21:59	0.031	0.090	0.043	0.015	0.013	2.39	127.59	SE
11 Sep, 2021	22:00 ~ 22:59	0.025	0.091	0.055	0.020	0.013	2.24	116.78	ESE
11 Sep, 2021	23:00 ~ 23:59	0.023	0.088	0.067	0.025	0.013	0.97	84.34	E
12 Sep, 2021	0:00 ~ 0:59	0.023	0.101	0.053	0.019	0.013	0.14	6.39	N
12 Sep, 2021	1:00 ~ 1:59	0.023	0.099	0.067	0.024	0.013	0.91	95.72	E
12 Sep, 2021	2:00 ~ 2:59	0.023	0.080	0.080	0.029	0.013	2.89	170.99	S
12 Sep, 2021	3:00 ~ 3:59	0.027	0.106	0.046	0.017	0.013	3.29	169.78	S
12 Sep, 2021	4:00 ~ 4:59	0.041	0.071	0.031	0.011	0.013	2.21	141.90	SE
12 Sep, 2021	5:00 ~ 5:59	0.063	0.114	0.061	0.022	0.013	1.04	149.65	SSE
12 Sep, 2021	6:00 ~ 6:59	0.078	0.048	0.033	0.012	0.013	1.82	131.72	SE
12 Sep, 2021	7:00 ~ 7:59	0.074	0.091	0.015	0.006	0.013	1.74	140.73	SE
12 Sep, 2021	8:00 ~ 8:59	0.026	0.073	0.028	0.010	0.013	3.79	153.84	SSE
12 Sep, 2021	9:00 ~ 9:59	0.023	0.049	0.070	0.025	0.013	4.76	164.60	SSE
12 Sep, 2021	10:00 ~ 10:59	0.023	0.021	0.032	0.012	0.013	4.60	170.83	S

Max	0.078	0.114	0.080	0.029	0.013
Avg	0.033	0.080	0.036	0.013	0.013
Min	0.023	0.021	0.002	0.001	0.013






Air Quality Monitoring Report for Development of Industrial Area Thilawa SEZ Zone A
(Operation Stage, FY September 2021)

Date	Time	CO	NO ₂	TSP	PM ₁₀	SO ₂	Wind Speed	Wind Direction	
		mg/m ³	m/s	Deg.	Direction				
		Hourly	Hourly	Hourly	Hourly	Hourly	Hourly	Hourly	Hourly
12 Sep, 2021	11:00 ~ 11:59	0.023	0.004	0.014	0.005	0.019	5.67	172.52	S
12 Sep, 2021	12:00 ~ 12:59	0.023	0.004	0.006	0.002	0.102	5.54	183.29	S
12 Sep, 2021	13:00 ~ 13:59	0.023	0.004	0.228	0.083	0.068	6.64	181.59	S
12 Sep, 2021	14:00 ~ 14:59	0.023	0.004	0.166	0.060	0.016	6.69	184.83	S
12 Sep, 2021	15:00 ~ 15:59	0.023	0.004	0.004	0.001	0.013	6.96	223.25	SW
12 Sep, 2021	16:00 ~ 16:59	0.059	0.031	0.008	0.003	0.013	3.79	282.25	WNW
12 Sep, 2021	17:00 ~ 17:59	0.107	0.004	0.005	0.002	0.013	2.70	267.93	W
12 Sep, 2021	18:00 ~ 18:59	0.071	0.022	0.023	0.008	0.013	0.86	108.84	ESE
12 Sep, 2021	19:00 ~ 19:59	0.064	0.095	0.071	0.026	0.013	2.76	111.91	ESE
12 Sep, 2021	20:00 ~ 20:59	0.023	0.075	0.066	0.024	0.013	3.13	138.23	SE
12 Sep, 2021	21:00 ~ 21:59	0.023	0.104	0.052	0.019	0.013	3.09	136.24	SE
12 Sep, 2021	22:00 ~ 22:59	0.023	0.098	0.070	0.025	0.013	3.09	100.12	E
12 Sep, 2021	23:00 ~ 23:59	0.023	0.091	0.101	0.037	0.013	3.82	122.95	ESE
13 Sep, 2021	0:00 ~ 0:59	0.030	0.107	0.127	0.046	0.013	3.73	109.29	ESE
13 Sep, 2021	1:00 ~ 1:59	0.024	0.108	0.116	0.042	0.013	4.47	134.93	SE
13 Sep, 2021	2:00 ~ 2:59	0.023	0.093	0.009	0.003	0.013	7.36	135.88	SE
13 Sep, 2021	3:00 ~ 3:59	0.024	0.101	0.108	0.039	0.013	3.23	134.67	SE
13 Sep, 2021	4:00 ~ 4:59	0.027	0.085	0.096	0.035	0.013	3.30	200.03	SSW
13 Sep, 2021	5:00 ~ 5:59	0.031	0.029	0.008	0.003	0.013	2.33	318.69	NW
13 Sep, 2021	6:00 ~ 6:59	0.101	0.079	0.009	0.003	0.013	1.20	161.78	SSE
13 Sep, 2021	7:00 ~ 7:59	0.185	0.100	0.008	0.003	0.013	1.57	58.10	ENE
13 Sep, 2021	8:00 ~ 8:59	0.024	0.117	0.023	0.008	0.013	2.37	96.44	E
13 Sep, 2021	9:00 ~ 9:59	0.027	0.119	0.021	0.008	0.013	2.54	102.99	ESE
13 Sep, 2021	10:00 ~ 10:59	0.049	0.107	0.032	0.012	0.013	3.08	131.84	SE

Max	0.185	0.119	0.228	0.083	0.102
Avg	0.044	0.066	0.057	0.021	0.019
Min	0.023	0.004	0.004	0.001	0.013

Date	Time	CO	NO ₂	TSP	PM ₁₀	SO ₂	Wind Speed	Wind Direction	
		mg/m ³	m/s	Deg.	Hourly				
		Hourly	Hourly	Hourly	Hourly	Hourly	Hourly	Hourly	Hourly
13 Sep, 2021	11:00 ~ 11:59	0.023	0.004	0.015	0.006	0.113	3.73	157.17	SSE
13 Sep, 2021	12:00 ~ 12:59	0.023	0.004	0.040	0.015	0.163	3.54	178.26	S
13 Sep, 2021	13:00 ~ 13:59	0.023	0.004	0.220	0.080	0.083	3.09	207.72	SSW
13 Sep, 2021	14:00 ~ 14:59	0.023	0.004	0.034	0.012	0.036	3.63	171.20	S
13 Sep, 2021	15:00 ~ 15:59	0.023	0.004	0.055	0.020	0.033	3.82	161.46	SSE
13 Sep, 2021	16:00 ~ 16:59	0.023	0.004	0.100	0.036	0.015	4.49	159.54	SSE
13 Sep, 2021	17:00 ~ 17:59	0.025	0.004	0.091	0.033	0.013	3.43	175.19	S
13 Sep, 2021	18:00 ~ 18:59	0.024	0.004	0.003	0.001	0.013	7.39	258.87	W
13 Sep, 2021	19:00 ~ 19:59	0.040	0.035	0.009	0.003	0.013	4.36	264.75	W
13 Sep, 2021	20:00 ~ 20:59	0.033	0.042	0.031	0.011	0.013	1.80	247.45	WSW
13 Sep, 2021	21:00 ~ 21:59	0.085	0.053	0.055	0.020	0.013	1.42	200.83	SSW
13 Sep, 2021	22:00 ~ 22:59	0.023	0.062	0.080	0.029	0.013	0.34	109.15	ESE
13 Sep, 2021	23:00 ~ 23:59	0.032	0.065	0.112	0.041	0.013	0.54	77.79	ENE
14 Sep, 2021	0:00 ~ 0:59	0.063	0.073	0.101	0.037	0.013	0.57	74.34	ENE
14 Sep, 2021	1:00 ~ 1:59	0.032	0.071	0.124	0.045	0.013	0.32	59.61	ENE
14 Sep, 2021	2:00 ~ 2:59	0.040	0.070	0.134	0.049	0.013	0.23	69.84	ENE
14 Sep, 2021	3:00 ~ 3:59	0.036	0.072	0.099	0.036	0.013	0.01	26.07	NNE
14 Sep, 2021	4:00 ~ 4:59	0.023	0.059	0.098	0.036	0.013	0.76	46.27	NE
14 Sep, 2021	5:00 ~ 5:59	0.038	0.060	0.103	0.037	0.013	0.86	63.86	ENE
14 Sep, 2021	6:00 ~ 6:59	0.042	0.061	0.054	0.020	0.013	1.50	86.03	E
14 Sep, 2021	7:00 ~ 7:59	0.023	0.025	0.012	0.004	0.013	3.04	87.58	E
14 Sep, 2021	8:00 ~ 8:59	0.023	0.004	0.009	0.003	0.044	2.30	69.13	ENE
14 Sep, 2021	9:00 ~ 9:59	0.024	0.004	0.027	0.010	0.097	2.13	200.50	SSW
14 Sep, 2021	10:00 ~ 10:59	0.029	0.004	0.072	0.026	0.101	3.79	258.00	WSW

Max	0.085	0.073	0.220	0.080	0.163
Avg	0.032	0.033	0.070	0.025	0.037
Min	0.023	0.004	0.003	0.001	0.013





MYANMAR JAPAN THILAWA DEVELOPMENT LIMITED

**Thilawa Special Economic Zone (Zone A)
Development Project (Operation Phase)**

Appendix - D

Noise and Vibration Monitoring Report

September, 2021

Environmental Monitoring Plan (Operation Phase)



**NOISE AND VIBRATION
MONITORING REPORT
FOR DEVELOPMENT OF INDUSTRIAL AREA
THILAWA SEZ ZONE A
(OPERATION STAGE)**

(BI-ANNUALLY MONITORING)

September 2021
Myanmar Koei International Ltd.



TABLE OF CONTENTS

CHAPTER 1: OUTLINES AND SUMMARY OF MONITORING PLAN	1
1.1 General	1
1.2 Outlines of Monitoring Plan.....	1
CHAPTER 2: NOISE AND VIBRATION LEVEL MONITORING.....	2
2.1 Monitoring Item	2
2.2 Monitoring Location	2
2.3 Monitoring Method	4
2.4 Monitoring Results.....	5
CHAPTER 3: CONCLUSION AND RECOMMENDATION.....	14

LIST OF TABLES

Table 1.2-1 Outlines of Noise and Vibration Level Monitoring	1
Table 2.1-1 Monitoring Parameters for Noise and Vibration Level.....	2
Table 2.2-1 Location of Noise and Vibration Monitoring Station.....	2
Table 2.4-1 Results of Noise Levels ($L_{A_{eq}}$) Monitoring at NV-1.....	5
Table 2.4-2 Results of Noise Levels ($L_{A_{eq}}$) Monitoring at NV-2.....	5
Table 2.4-3 Results of Noise Levels ($L_{A_{eq}}$) Monitoring at NV-3.....	6
Table 2.4-4 Hourly Noise Level ($L_{A_{eq}}$) Monitoring Results at NV-1	6
Table 2.4-5 Hourly Noise Level ($L_{A_{eq}}$) Monitoring Results at NV-2	7
Table 2.4-6 Hourly Noise Level ($L_{A_{eq}}$) Monitoring Results at NV-3	7
Table 2.4-7 Results of Vibration Levels (L_{v10}) Monitoring at NV-1	9
Table 2.4-8 Results of Vibration Levels (L_{v10}) Monitoring at NV-2.....	9
Table 2.4-9 Results of Vibration Levels (L_{v10}) Monitoring at NV-3.....	10
Table 2.4-10 Results of Hourly Vibration Levels (L_{v10}) Monitoring at NV-1	10
Table 2.4-11 Results of Hourly Vibration Levels (L_{v10}) Monitoring at NV-2	11
Table 2.4-12 Results of Hourly Vibration Levels (L_{v10}) Monitoring at NV-3	11

LIST OF FIGURES

Figure 2.2-1 Location of Noise and Vibration Level Monitoring Points	3
Figure 2.3-1 Status of Noise and Vibration Level Monitoring at NV-1, NV-2 and NV-3	5
Figure 2.4-1 Results of Noise Levels ($L_{A_{eq}}$) Monitoring at NV-1	8
Figure 2.4-2 Results of Noise Levels ($L_{A_{eq}}$) Monitoring at NV-2	8
Figure 2.4-3 Results of Noise Levels ($L_{A_{eq}}$) Monitoring at NV-3	9
Figure 2.4-4 Results of Vibration Levels (L_{v10}) Monitoring at NV-1	12
Figure 2.4-5 Results of Vibration Levels (L_{v10}) Monitoring at NV-2	12
Figure 2.4-6 Results of Vibration Levels (L_{v10}) Monitoring at NV-3	13



CHAPTER 1: OUTLINES AND SUMMARY OF MONITORING PLAN

1.1 General

Thilawa Special Economic Zone (TSEZ) is located in southern district of Yangon region and about 23 km southeast of Yangon city. As the developer of Thilawa SEZ, Myanmar Japan Thilawa Development Ltd. (MJTD) has a responsibility to carry out regular environmental monitoring in the industrial area of Zone A in accordance with the approved Environmental Impact Assessment (EIA) report with Environmental Management Plan (EMP). MJTD has implemented monitoring various environmental items with the specified time frame to know the environmental conditions in and around the area.

1.2 Outlines of Monitoring Plan

To assess the environmental conditions under the operation of industrial area in and around Thilawa SEZ Zone A, noise and vibration levels had been monitored from 7 September 2021 – 9 September 2021 as follows;

Table 1.2-1 Outlines of Noise and Vibration Level Monitoring

Monitoring Date	Monitoring Item	Parameters	Number of Points	Duration	Monitoring Methodology
7 September, 2021	Noise Level	L _{Aeq} (dB)	1 (NV-1)	8 hours	On-site measurement by "Rion NL-42 sound level meter"
9 September, 2021	Noise Level	L _{Aeq} (dB)	1 (NV-2)	8 hours	On-site measurement by "Rion NL-42 sound level meter"
8 September, 2021	Noise Level	L _{Aeq} (dB)	1 (NV-3)	8 hours	On-site measurement by "Rion NL-42 sound level meter"
7 September, 2021	Vibration Level	L _{v10} (dB)	1 (NV-1)	8 hours	On-site measurement by "Vibration Level Meter- VM-53A"
9 September, 2021	Vibration Level	L _{v10} (dB)	1 (NV-2)	8 hours	On-site measurement by "Vibration Level Meter- VM-53A"
8 September, 2021	Vibration Level	L _{v10} (dB)	1 (NV-3)	8 hours	On-site measurement by "Vibration Level Meter- VM-53A"

Source: Myanmar Koei International Ltd.



CHAPTER 2: NOISE AND VIBRATION LEVEL MONITORING

2.1 Monitoring Item

The noise and vibration level monitoring items are shown in Table 2.1-1.

Table 2.1-1 Monitoring Parameters for Noise and Vibration Level

No.	Item	Parameter
1	Noise	A-weighted loudness equivalent (L_{Aeq})
2	Vibration	Vibration level, vertical, percentile (L_{V10})

Source: Myanmar Koei International Ltd.

2.2 Monitoring Location


The locations of noise and vibration level points are shown in Table 2.2-1. The detail of each sampling point is described below. The location of the noise and vibration monitoring points are shown in Figure 2.2-1.

Table 2.2-1 Location of Noise and Vibration Monitoring Station

Sampling Point	Coordinates	Description of Sampling Point
NV-1	N: 16°40'11.50", E: 96°16'32.00"	In front of administrative building, Thilawa SEZ Zone A
NV-2	N: 16°40'52.50", E: 96°16'55.50"	In the east of the Thilawa SEZ Zone A
NV-3	N: 16°40'46.20", E: 96°15'30.10"	In the west of the Thilawa SEZ Zone A, where is the nearest to the residential houses of Alwan sok village

Source: Myanmar Koei International Ltd.





Source: Google Earth

Figure 2.2-1 Location of Noise and Vibration Level Monitoring Points

NV-1

NV-1 is located in front of administrative building, Thilawa SEZ and next to Dagon-Thilawa road which is paved with moderate to highly traffic volume during the day and night by passing of loader vehicles and dump trucks. Possible sources of noise and vibration is generated from vehicle traffic during the day and night time.

NV-2

NV-2 is located in the east of the Thilawa SEZ Zone A, Thilawa dam in west and construction of factories in Thilawa SEZ Zone A in northwest. Possible sources of noise and vibration is generated from operation activities of Zone A's locators and road traffic. There is an access road situated in the east of NV-2.

NV-3

NV-3 is located in the west of the Thilawa SEZ Zone A, surrounded by the residential houses of Alwan sok village in north and northwest and garment factory in northeast, construction of factories in Thilawa SEZ Zone A in east respectively. Possible sources of noise and vibration is generated from operation and construction activities of surrounding Zone A's locators. In addition, daily human activities nearby Alwan sok village and road traffic might be noise and vibration sources. There is an access road situated in the northeast of NV-3.

2.3 Monitoring Method

Noise level was measured by "Rion NL-42 sound level meter" and automatically recorded every 10 minutes in a memory card. The vibration level meter was, VM-53A (Rion Co. Ltd., Japan), accompanied by a 3-axis accelerometer PV-83C (Rion Co., Ltd.) was placed on solid soil ground. Vertical vibration (Z axis), L_v , was measured every 10 minutes within the adaptable range of (10-70) dB at NV-1, (10-70) dB at NV-2, and (10-70) dB at NV-3 and recorded to a memory card.

The measurement period of noise and vibration was 8 hours for each monitoring point. The status of the noise and vibration level monitoring on NV-1, NV-2 and NV-3 are shown in Figure 2.3-1.





Source: Myanmar Koei International Ltd.

Figure 2.3-1 Status of Noise and Vibration Level Monitoring at NV-1, NV-2 and NV-3

2.4 Monitoring Results

Noise Monitoring Results

Noise monitoring results are separated daytime (6:00 AM to 10:00 PM), night time (10:00 PM to 6:00 AM) time frames for NV-1, daytime (7:00 AM to 7:00 PM), evening time (7:00 PM to 10:00 PM) and night time (10:00 PM to 7:00 AM) time frames respectively for NV-2 and NV-3. Noise measurement was carried out on an 8-hour as working time (8:00 AM to 4:00 PM) at the designated one location instead of 24-hours due to the safety reason and risk avoidance. The monitoring results are summarized in Table 2.4-1, Table 2.4-2 and Table 2.4-3 respectively. Hourly noise level monitoring results for NV-1, NV-2 and NV-3 are shown in Table 2.4-4, Table 2.4-5 and Table 2.4-6. Comparing with the target value of noise level in operation stage prescribed in EIA report for Thilawa SEZ development project Zone A, all results were under the target values at NV-1, NV-2 and NV-3.

Table 2.4-1 Results of Noise Levels (L_{Aeq}) Monitoring at NV-1

Date	(Traffic Noise Level) Equivalent Noise Level (L_{Aeq} , dB)	
	Day Time (6:00 AM – 10:00 PM)	
	Day Time (6:00 AM – 10:00 PM)	Night Time (10:00 PM – 6:00 AM)
7 September, 2021	58	-
Target Value	75	70

Note: Target value is applied to the noise standard along main road stipulated in the Noise Regulation Law (Japan)
(Law No. 98 of 1968, Latest Amendment by Law No.91 of 2000).

Source: Myanmar Koei International Ltd.

Table 2.4-2 Results of Noise Levels (L_{Aeq}) Monitoring at NV-2

Date	(Commercial and Industrial Areas) Equivalent Noise Level (L_{Aeq} , dB)		
	Day Time (7:00 AM – 7:00 PM)		Night Time (10:00 PM – 7:00 AM)
	Day Time (7:00 AM – 7:00 PM)	Evening Time (7:00 PM – 10:00 PM)	Night Time (10:00 PM – 7:00 AM)
9 September, 2021	63	-	-
Target Value	70	65	60

Note: Target value is applied to the noise level during the operation stage in the EIA Report for Thilawa SEZ Development Project (Industrial Area of Zone A).

Source: Myanmar Koei International Ltd.

Noise and Vibration Monitoring Report for Development of Industrial Area Thilawa SEZ Zone A
(Operation Stage, FY September 2021)

Table 2.4-3 Results of Noise Levels (L_{Aeq}) Monitoring at NV-3

Date	(Commercial and Industrial Areas) Equivalent Noise Level (L_{Aeq} , dB)		
	Day Time (7:00 AM – 7:00 PM)	Evening Time (7:00 PM – 10:00 PM)	Night Time (10:00 PM – 7:00 AM)
8 September, 2021	48	-	-
Target Value	70	65	60

Note: Target value is applied to the noise level during the operation stage in the EIA Report for Thilawa SEZ Development Project (Industrial Area of Zone A).

Source: Myanmar Koei International Ltd.

Table 2.4-4 Hourly Noise Level (L_{Aeq}) Monitoring Results at NV-1

Date	Time	(L_{Aeq} , dB)	(L_{Aeq} , dB) Each Category	(L_{Aeq} , dB) Target Value
7 September, 2021	6:00-7:00	-	58	75
	7:00-8:00	-		
	8:00-9:00	58		
	9:00-10:00	57		
	10:00-11:00	58		
	11:00-12:00	58		
	12:00-13:00	59		
	13:00-14:00	58		
	14:00-15:00	58		
	15:00-16:00	59		
	16:00-17:00	-		
	17:00-18:00	-		
	18:00-19:00	-		
	19:00-20:00	-		
	20:00-21:00	-		
	21:00-22:00	-		
	22:00-23:00	-		
	23:00-24:00	-		
	24:00-1:00	-		
	1:00-2:00	-		
	2:00-3:00	-		70
	3:00-4:00	-		
	4:00-5:00	-		
	5:00-6:00	-		

Source: Myanmar Koei International Ltd.



Table 2.4-5 Hourly Noise Level (L_{Aeq}) Monitoring Results at NV-2

Date	Time	(L_{Aeq} , dB)	(L_{Aeq} , dB) Each Category	(L_{Aeq} , dB) Target Value
9 September, 2021	7:00-8:00	-	63	70
	8:00-9:00	64		
	9:00-10:00	62		
	10:00-11:00	63		
	11:00-12:00	60		
	12:00-13:00	60		
	13:00-14:00	68		
	14:00-15:00	59		
	15:00-16:00	62		
	16:00-17:00	-		
	17:00-18:00	-		
	18:00-19:00	-		
	19:00-20:00	-		65
	20:00-21:00	-		
	21:00-22:00	-		
	22:00-23:00	-	-	60
	23:00-24:00	-		
	24:00-1:00	-		
	1:00-2:00	-		
	2:00-3:00	-		
	3:00-4:00	-		
	4:00-5:00	-		
	5:00-6:00	-		
	6:00-7:00	-		

Source: Myanmar Koei International Ltd.

Table 2.4-6 Hourly Noise Level (L_{Aeq}) Monitoring Results at NV-3

Date	Time	(L_{Aeq} , dB)	(L_{Aeq} , dB) Each Category	(L_{Aeq} , dB) Target Value
8 September, 2021	7:00-8:00	-	48	70
	8:00-9:00	48		
	9:00-10:00	47		
	10:00-11:00	46		
	11:00-12:00	45		
	12:00-13:00	44		
	13:00-14:00	46		
	14:00-15:00	50		
	15:00-16:00	51		
	16:00-17:00	-		
	17:00-18:00	-		
	18:00-19:00	-		
	19:00-20:00	-		65
	20:00-21:00	-		
	21:00-22:00	-		
	22:00-23:00	-	-	60
	23:00-24:00	-		
	24:00-1:00	-		
	1:00-2:00	-		
	2:00-3:00	-		
	3:00-4:00	-		
	4:00-5:00	-		
	5:00-6:00	-		
	6:00-7:00	-		

Source: Myanmar Koei International Ltd.






Figure 2.4-1 Results of Noise Levels ($L_{A_{eq}}$) Monitoring at NV-1





Figure 2.4-2 Results of Noise Levels ($L_{A_{eq}}$) Monitoring at NV-2





Source: Myanmar Koei International Ltd.

Figure 2.4-3 Results of Noise Levels (L_{Aeq}) Monitoring at NV-3

Vibration Monitoring Results

Vibration monitoring results are separated daytime (7:00 AM to 7:00 PM), evening time (7:00 PM to 10:00 PM) and night time (10:00 PM to 7:00 AM) time frames respectively for NV-1, NV-2 and NV-3. Vibration measurement was carried out on an 8-hour as working time (8:00 AM to 4:00 PM) at the designated one location instead of 24-hours due to the safety reason and risk avoidance. The results of vibration level are shown in Table 2.4-7, Table 2.4-8 and Table 2.4-9 respectively. Results of hourly vibration level monitoring for NV-1, NV-2 and NV-3 are summarized in Table 2.4-10, Table 2.4-11 and Table 2.4-12. By comparing with the target vibration level in operation stage in EIA report for Thilawa SEZ development project Zone A, all of results were under the target values.

Table 2.4-7 Results of Vibration Levels (L_{v10}) Monitoring at NV-1

Date	(Office, commercial facilities, and factories) Equivalent Vibration Level (L _{v10} , dB)		
	Day Time (7:00 AM – 7:00 PM)	Evening Time (7:00 PM – 10:00 PM)	Night Time (10:00 PM – 7:00 AM)
7 September, 2021	45	-	-
Target Value	70	65	65

Note: Target value is applied to the vibration level during the operation stage in the EIA Report for Thilawa SEZ Development Project (Industrial Area of Zone A).

Source: Myanmar Koei International Ltd.

Table 2.4-8 Results of Vibration Levels (L_{v10}) Monitoring at NV-2

Date	(Office, commercial facilities, and factories) Equivalent Vibration Level (L _{v10} , dB)		
	Day Time (7:00 AM – 7:00 PM)	Evening Time (7:00 PM – 10:00 PM)	Night Time (10:00 PM – 7:00 AM)
9 September, 2021	36	-	-
Target Value	70	65	65

Note: Target value is applied to the vibration level during the operation stage in the EIA Report for Thilawa SEZ Development Project (Industrial Area of Zone A).

Source: Myanmar Koei International Ltd.



Table 2.4-9 Results of Vibration Levels (L_{v10}) Monitoring at NV-3

Date	(Office, commercial facilities, and factories) Equivalent Vibration Level (L_{v10} , dB)		
	Day Time (7:00 AM – 7:00 PM)	Evening Time (7:00 PM – 10:00 PM)	Night Time (10:00 PM – 7:00 AM)
8 September, 2021	27	-	-
Target Value	70	65	65

Note: Target value is applied to the vibration level during the operation stage in the EIA Report for Thilawa SEZ Development Project (Industrial Area of Zone A).

Source: Myanmar Koei International Ltd.

Table 2.4-10 Results of Hourly Vibration Levels (L_{v10}) Monitoring at NV-1

Date	Time	(L_{v10} , dB)	(L_{v10} , dB) Each Category	(L_{v10} , dB) Target Value
7 September, 2021	7:00-8:00	-	45	70
	8:00-9:00	45		
	9:00-10:00	45		
	10:00-11:00	45		
	11:00-12:00	46		
	12:00-13:00	45		
	13:00-14:00	46		
	14:00-15:00	46		
	15:00-16:00	45		
	16:00-17:00	-		
	17:00-18:00	-		
	18:00-19:00	-		
	19:00-20:00	-	-	65
	20:00-21:00	-		
	21:00-22:00	-		
	22:00-23:00	-		
	23:00-24:00	-	-	65
	24:00-1:00	-		
	1:00-2:00	-		
	2:00-3:00	-		
	3:00-4:00	-		
	4:00-5:00	-		
	5:00-6:00	-		
	6:00-7:00	-		

Source: Myanmar Koei International Ltd.



Table 2.4-11 Results of Hourly Vibration Levels (L_{v10}) Monitoring at NV-2

Date	Time	(L_{v10} , dB)	(L_{v10} , dB) Each Category	(L_{v10} , dB) Target Value
9 September, 2021	7:00-8:00	-	36	70
	8:00-9:00	39		
	9:00-10:00	38		
	10:00-11:00	34		
	11:00-12:00	34		
	12:00-13:00	35		
	13:00-14:00	33		
	14:00-15:00	32		
	15:00-16:00	34		
	16:00-17:00	-		
	17:00-18:00	-		
	18:00-19:00	-		
	19:00-20:00	-		
	20:00-21:00	-		65
	21:00-22:00	-		
	22:00-23:00	-		
	23:00-24:00	-		
	24:00-1:00	-		
	1:00-2:00	-		
	2:00-3:00	-		65
	3:00-4:00	-		
	4:00-5:00	-		
	5:00-6:00	-		
	6:00-7:00	-		

Source: Myanmar Koei International Ltd.

Table 2.4-12 Results of Hourly Vibration Levels (L_{v10}) Monitoring at NV-3

Date	Time	(L_{v10} , dB)	(L_{v10} , dB) Each Category	(L_{v10} , dB) Target Value
8 September, 2021	7:00-8:00	-	27	70
	8:00-9:00	29		
	9:00-10:00	26		
	10:00-11:00	26		
	11:00-12:00	26		
	12:00-13:00	25		
	13:00-14:00	26		
	14:00-15:00	27		
	15:00-16:00	27		
	16:00-17:00	-		
	17:00-18:00	-		
	18:00-19:00	-		
	19:00-20:00	-		
	20:00-21:00	-		65
	21:00-22:00	-		
	22:00-23:00	-		
	23:00-24:00	-		
	24:00-1:00	-		
	1:00-2:00	-		
	2:00-3:00	-		65
	3:00-4:00	-		
	4:00-5:00	-		
	5:00-6:00	-		
	6:00-7:00	-		

Source: Myanmar Koei International Ltd.




Figure 2.4-4 Results of Vibration Levels (L_{v10}) Monitoring at NV-1




Figure 2.4-5 Results of Vibration Levels (L_{v10}) Monitoring at NV-2






Figure 2.4-6 Results of Vibration Levels (L_{v10}) Monitoring at NV-3

CHAPTER 3: CONCLUSION AND RECOMMENDATION

By comparing with the target noise and vibration level in operation stage in EIA report for Thilawa SEZ development project Zone A, all results were under the target values at NV-1, NV-2, and NV-3. (Referred to section 2.4).

In conclusion of this environmental monitoring, there are no specific noise and vibration impacts on the surrounding area of industrial area of Thilawa SEZ Zone A during this monitoring period.





MYANMAR JAPAN THILAWA DEVELOPMENT LIMITED

**Thilawa Special Economic Zone (Zone A)
Development Project (Operation Phase)**

Appendix -E

Soil contamination survey in Thilawa SEZ

December 2021





SOIL CONTAMINATION SURVEY IN THILAWA SEZ (ZONE A)

December 2021



Resource & Environment Myanmar Ltd. B-702/401 Delta Plaza Building,
Shwegondaing Rd., Bahan, Yangon. MYANMAR

Tel: (959) 7301 3448; Fax: (951) 552901

www.enviromyanmar.net



Soil Contamination Survey in Thilawa SEZ (Zone-A)

Purpose of Survey

Soil contamination survey in Thilawa SEZ (Zone-A) is required to conduct twice a year as described in Environmental Monitoring Plan (EMoP) of Environmental Impact Assessment (EIA) report of Thilawa SEZ Zone A. Soil contamination or soil pollution as part of land degradation is caused by the presence of xenobiotics (human-made) chemicals or other alteration in the natural soil environment. It is typically caused by industrial activity, agricultural chemicals or improper disposal of waste.

The purpose of this survey is to monitor the concentration level of chemical in the soil and to perform the mitigation measure if the concentration level is higher than standard value.

Survey Item

Parameter for soil contamination survey is determined by referring to the parameter of soil content observation of Japan and other countries as shown in Table 1.

Table 1 Survey parameter for soil quality

No.	Parameter	Unit	Standard		
			Japan	Thailand	Vietnam
1	pH	-	-	-	-
2	Mercury	ppm	15	610	-
3	Arsenic	ppm	150	27	12
4	Lead	ppm	150	750	300
5	Cadmium	ppm	150	810	10
6	Copper	ppm	125	-	100
7	Zinc	ppm	150	-	300
8	Chromium	ppm	250	640	-
9	Fluoride	ppm	4000	-	-
10	Boron	ppm	4000	-	-
11	Selenium	ppm	150	10,000	-

Source: Japan: Ministry of Environment, Government of Japan (2002), "Regulation for Implementing the Law on Soil Contamination Countermeasures"

Thailand: Notification of National Environmental Board No.25, B.E. Thailand (2004), "other purpose" class"

Vietnam: QCVN 03:2008/BTNMT, Applied "industrial land", Vietnam.

Summary of survey points

The survey location is situated in Thilawa Special Economic Zone (Zone-A) areas, Thanyin Township, Yangon. There are five samples collected for soil quality survey.





Figure 1 Location map of the soil sampling points

The locations of survey points are shown in following table. The detail of each survey point is described below.

Table 2 Summary of survey points

Sampling Point	Coordinates	Description of Sampling Point
S-1	16° 40' 13.49" N 96° 16' 29.89" E	About 40 m northeast of administration building.
S-2	16° 40' 10.74" N 96° 16' 22.01" E	At the embankment area of the drain, near main gate of Thilawa SEZ.
S-3	16° 40' 30.25" N 96° 16' 34.86" E	At the drain from sewage treatment plant.
S-4	16° 40' 24.29" N 96° 15' 49.55" E	At damping area near retention pond.
S-5	16° 40' 32.36" N 96° 15' 49.81" E	At the drain from the retention pond.

S-1

S-1 is situated in the southern part of the Thilawa SEZ Zone (A) area, and distanced about 40 m from administration building. It was collected beside of the Trash Storage Building. Sometimes, wastewater after cleaning that domestic waste is leaked and may sink into the ground. The soil condition is fine to medium grained, reddish brown colored silty clay.





Figure 2 Soil quality sampling at S-1

S-2

S-2 was collected at the slope area of the retention canal, which is situated near the main gate of Thilawa SEZ (Zone-A). It is beside of the Thilawa SEZ car road and intended to plant the trees along the slop. The soil condition is fine to medium grained, reddish brown colored silty clay.



Figure 3 Soil quality sampling at S-2

S-3

S-3 is collected in the retention canal where wastewater from the centralized sewage treatment plant is flowing into the retention canal. It is distanced about 5 m away from the junction of wastewater discharge drainage and main rain water drainage. The soil condition is fine to medium grained, yellowish brown colored silty clay.





Figure 4 Soil quality sampling at S-3

S-4

S-4 is collected from the soil disposing site which is located near Plot No.E-1 of TSEZ Zone-A retention pond, about 40 m in distance. This dumping site is about 16,500 square meters where soil from Thilawa SEZ Zone-A (Phase-2). The soil condition is fine to medium grained, reddish brown colored silty caly.



Figure 5 Soil quality sampling at S-4

S-5

It is collected at the retention canal where wastewater is discharged from the retention pond of Plot No.E-1 of Thilawa SEZ Zone-A. S-5 is distanced about 100 m from this retention pond. The soil condition is fine grained, yellowish brown colored silty clay.





Figure 6 Soil quality monitoring at S-5

Survey Period

Soil sampling was conducted on 22th December 2021.

Survey Method

For soil sampling, the standard environmental sampler (soil auger) was applied. The sampler is a stainless-steel tube that is sharpened on one end and fitted with a long, T-shaped handle. This tube is approximately three inches inside diameter. In order to refrain from contamination, about 20 cm of topsoil was removed by the sampler before sampling. Then sample was taken and collected in cleaned plastic bag. Chemical preservation of soil is not generally recommended. Samples were cooled in an ice box which temperature was under 4°C. Samples were protected from sunlight to minimize any potential reaction.

Field equipment used on site are also shown in the table.

Table 3 Field Equipment for Sediment and Soil Quality Survey

No.	Equipment	Originate Country	Model
1	Soil Auger (for soil sampling)	U.S.A	AMS

The analysis method for each parameter is also shown in the following table.

Table 4 Analysis methods of soil quality

No.	Parameter	Analysis Method
1	pH	Atomic Absorption Spectrophotometer, Aqua-regia
2	Mercury (Hg)	Atomic Absorption Spectrophotometer, Aqua-regia
3	Arsenic (As)	Atomic Absorption Spectrophotometer, Aqua-regia

4	Lead (Pb)	Atomic Absorption Spectrophotometer, Aqua-regia
5	Cadmium (Cd)	Atomic Absorption Spectrophotometer, Aqua-regia
6	Copper (Cu)	Atomic Absorption Spectrophotometer, Aqua-regia
7	Zinc (Zn)	Atomic Absorption Spectrophotometer, Aqua-regia
8	Chromium (VI)	Atomic Absorption Spectrophotometer, Aqua-regia
9	Fluoride (F)	Atomic Absorption Spectrophotometer, Aqua-regia
10	Boron (B)	Atomic Absorption Spectrophotometer, Aqua-regia
11	Selenium (Se)	Atomic Absorption Spectrophotometer, Aqua-regia

Survey Result

Chemical properties for soil were analyzed in the laboratory of United Analyst and Engineering Consultant Co., Ltd. (UAE) in Thailand.

The result of soil quality analysis is presented as follow. Most of the results are complied with the proposed standard value of contamination whereas arsenic concentration at S-1, S-4 and S-5 are slightly higher than the Thailand and Vietnam standard.

Table 4 Soil quality result

No.	Parameter	Unit	S-1	S-2	S-3	S-4	S-5	Standard		
								Japan	Thailand	Vietnam
1	pH	-	6	5.1	7.1	4.6	6.5	-	-	-
2	Mercury	Mg/kg	ND	ND	ND	ND	ND	15	610	-
3	Arsenic	Mg/kg	28.9	9.79	10.8	18.8	21.0	150	27	12
4	Lead	Mg/kg	24.2	11.8	14.2	21.9	18.8	150	750	300
5	Cadmium	Mg/kg	ND	ND	ND	ND	ND	150	810	10
6	Copper	Mg/kg	33.6	18.3	26.7	21.2	27.3	125	-	100
7	Zinc	Mg/kg	37.6	31.7	87.0	43.0	56.7	150	-	300
8	Chromium	Mg/kg	121	39.6	58.8	104	97.5	250	640	-
9	Fluoride	Mg/kg	2.86	1.10	2.67	ND	3.10	4000	-	-
10	Boron	Mg/kg	37.5	13.6	22.6	25.1	30.6	4000	-	-
11	Selenium	Mg/kg	0.811	0.159	ND	0.387	0.476	150	10,000	-



Appendix

Lab Result



ANALYSIS REPORT

PROJECT NAME : SOIL CONTAMINATION SURVEY IN THILAWA SEZ (ZONE A)
CUSTOMER NAME : RESOURCE AND ENVIRONMENT MYANMAR CO., LTD.
ADDRESS : B702 DELTA PLAZA, SHWEGONDAING ROAD, BAHAN, YANGON MYANMAR
CONTACT INFORMATION : TEL : +959 799855808 e-mail : toetoehlaing@rem-uaeconsultant.com
SAMPLING SOURCE : THILAWA
SAMPLE TYPE : SOIL **RECEIVED DATE** : JANUARY 7, 2022
SAMPLING DATE : DECEMBER 22, 2021 **ANALYTICAL DATE** : JANUARY 7-21, 2022
SAMPLING TIME : 10:10 HOUR **REPORT NO.** : 2022-U005675
SAMPLING METHOD : - **WORK NO.** : 2022-000193
SAMPLING BY : CUSTOMER **ANALYSIS NO.** : T22AA311-0001
ANALYZED BY : MISS JINTASUPA PLIANSRI

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			S-1 T22AA311-0001	
pH (1:1) ^b	-	ELECTROMETRIC METHOD (US EPA 2004: 9045D)	6.0 (25°C)	-
METALS				
ARSENIC (As) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1992: 7061A)	28.9	0.100
BORON (B) ^c	mg/kg	ACID DIGESTION AND INDUCTIVELY COUPLED PLASMA (ICP) METHOD (US EPA 1996: 3050B AND 2018: 6010D)	37.5	0.250
CADMIUM (Cd) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	ND	0.300
CHROMIUM (Cr) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	121	0.500
COPPER (Cu) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	33.6	0.300
LEAD (Pb) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	24.2	1.55
MERCURY (Hg) ^c	mg/kg	ACID DIGESTION AND COLD VAPOUR AAS METHOD (US EPA 2007: 7471B)	ND	0.100
SELENIUM (Se) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1994: 7742)	0.811	0.100
ZINC (Zn) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	37.6	0.350



• DO NOT COPY PARTIAL OF THIS ANALYSIS REPORT WITHOUT OFFICIAL APPROVAL .
 • REPORTED ANALYSIS REFERS TO SUBMITTED SAMPLE ONLY.





United Analyst and Engineering Consultant Co., Ltd.

3 Soi Udomsuk 41, Sukhumvit Road, Bangchak, Phrakanong, Bangkok 10260

Tel 0 2763 2828 Fax 0 2763 2800 www.uaeconsultant.com E-mail: uae@uaeconsultant.com



TESTING
No.0063

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT		DETECTION LIMIT
			S-1	T22AA311-0001	
TOTAL THRESHOLD LIMIT CONCENTRATION (T TLC)					
FLUORIDE ^a	mg/kg	ION SELECTIVE ELECTRODE METHOD (US EPA 1996: 9214)	2.86		0.80
SAMPLE CONDITION					
BROWN SOIL					

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT STILL NOT ACCREDITED

ND : NON-DETECTABLE.

SAMPLE (S) ANALYSED ON AS RECEIVED BASIS. RESULT (S) REPORTED ON A DRY WEIGHT BASIS.

*United Analyst Engineering Consultant Co., Ltd is Sub-contractor of REM-UAE Laboratory and Consultant Co., Ltd



(MR BHUCHONK PANICHLERTUMPI)
LABORATORY SUPERVISOR

JANUARY 26, 2022

- DO NOT COPY PARTIAL OF THIS ANALYSIS REPORT WITHOUT OFFICIAL APPROVAL .
- REPORTED ANALYSIS REFERS TO SUBMITTED SAMPLE ONLY.



United Analyst and Engineering Consultant Co., Ltd.

3 Soi Udomsuk 41, Sukhumvit Road, Bangchak, Phrakanong, Bangkok 10260

Tel: 0 2763 2828 Fax: 0 2763 2800 www.uaeconsultant.com E-mail: uae@uaeconsultant.com



TESTING
No.0063

ANALYSIS REPORT


PROJECT NAME : SOIL CONTAMINATION SURVEY IN THILAWA SEZ (ZONE A)
CUSTOMER NAME : RESOURCE AND ENVIRONMENT MYANMAR CO., LTD.
ADDRESS : B702 DELTA PLAZA, SHWEGONDAING ROAD, BAHAN, YANGON MYANMAR
CONTACT INFORMATION : TEL : +959 799855808 e-mail : toetoeblaing@rem-uaeconsultant.com
SAMPLING SOURCE : THILAWA
SAMPLE TYPE : SOIL **RECEIVED DATE** : JANUARY 7, 2022
SAMPLING DATE : DECEMBER 22, 2021 **ANALYTICAL DATE** : JANUARY 7-21, 2022
SAMPLING TIME : 11:05 HOUR **REPORT NO.** : 2022-U005676
SAMPLING METHOD : - **WORK NO.** : 2022-000193
SAMPLING BY : CUSTOMER **ANALYSIS NO.** : T22AA311-0002
ANALYZED BY : MISS JINTASUPA PLIANSRI

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			S-2 T22AA311-0002	
pH (1:1) ^b	-	ELECTROMETRIC METHOD (US EPA 2004: 9045D)	5.1 (25°C)	-
METALS				
ARSENIC (As) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1992: 7061A)	9.79	0.100
BORON (B) ^c	mg/kg	ACID DIGESTION AND INDUCTIVELY COUPLED PLASMA (ICP) METHOD (US EPA 1996: 3050B AND 2018: 6010D)	13.6	0.250
CADMIUM (Cd) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	ND	0.300
CHROMIUM (Cr) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	39.6	0.500
COPPER (Cu) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	18.3	0.300
LEAD (Pb) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	11.8	1.55
MERCURY (Hg) ^c	mg/kg	ACID DIGESTION AND COLD VAPOUR AAS METHOD (US EPA 2007: 7471B)	ND	0.100
SELENIUM (Se) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1994: 7742)	0.159	0.100
ZINC (Zn) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	31.7	0.350



• DO NOT COPY PARTIAL OF THIS ANALYSIS REPORT WITHOUT OFFICIAL APPROVAL .

• REPORTED ANALYSIS REFERS TO SUBMITTED SAMPLE ONLY.





United Analyst and Engineering Consultant Co., Ltd.

3 Soi Udomsuk 41, Sukhumvit Road, Bangchak, Phrakanong, Bangkok 10260
Tel. 0 2763 2828 Fax 0 2763 2800 www.uaeconsultant.com E-mail: uae@uaeconsultant.com



TESTING
No.0063

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			S-2 T22AA311-0002	
TOTAL THRESHOLD LIMIT CONCENTRATION (TTL)C				
FLUORIDE °	mg/kg	ION SELECTIVE ELECTRODE METHOD (US EPA 1996: 9214)	1.10	0.80
SAMPLE CONDITION			BROWN SOIL	

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT STILL NOT ACCREDITED

ND : NON-DETECTABLE

SAMPLE (S) ANALYSED ON AS RECEIVED BASIS. RESULT (S) REPORTED ON A DRY WEIGHT BASIS.

*United Analyst Engineering Consultant Co., Ltd is Sub-contractor of REM-UAE Laboratory and Consultant Co., Ltd



Bhuchonk P.

(MR BHUCHONK PANICHLERTUMPI)
LABORATORY SUPERVISOR

JANUARY 26, 2022

• DO NOT COPY PARTIAL OF THIS ANALYSIS REPORT WITHOUT OFFICIAL APPROVAL .
• REPORTED ANALYSIS REFERS TO SUBMITTED SAMPLE ONLY.

ISO 9001:2015 CERTIFIED
ISO 14001:2015 CERTIFIED
BY BSI GROUP (THAILAND) CO.,LTD.

ANALYSIS REPORT

PROJECT NAME : SOIL CONTAMINATION SURVEY IN THILAWA SEZ (ZONE A)
CUSTOMER NAME : RESOURCE AND ENVIRONMENT MYANMAR CO., LTD.
ADDRESS : B702 DELTA PLAZA, SHWEGONDAING ROAD, BAHAN, YANGON MYANMAR
CONTACT INFORMATION : TEL : +959 799855808 e-mail : toetoehlaing@rem-uaeconsultant.com
SAMPLING SOURCE : THILAWA
SAMPLE TYPE : SOIL **RECEIVED DATE** : JANUARY 7, 2022
SAMPLING DATE : DECEMBER 22, 2021 **ANALYTICAL DATE** : JANUARY 7-21, 2022
SAMPLING TIME : 11:40 HOUR **REPORT NO.** : 2022-U005677
SAMPLING METHOD : - **WORK NO.** : 2022-000193
SAMPLING BY : CUSTOMER **ANALYSIS NO.** : T22AA311-0003
ANALYZED BY : MISS JINTASUPA PLIANSRI

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			S-3 T22AA311-0003	
pH (1:1) ^b	-	ELECTROMETRIC METHOD (US EPA 2004: 9045D)	7.1 (25°C)	-
METALS				
ARSENIC (As) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1992: 7061A)	10.8	0.100
BORON (B) ^c	mg/kg	ACID DIGESTION AND INDUCTIVELY COUPLED PLASMA (ICP) METHOD (US EPA 1996: 3050B AND 2018: 6010D)	22.6	0.250
CADMIUM (Cd) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	ND	0.300
CHROMIUM (Cr) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	58.8	0.500
COPPER (Cu) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	26.7	0.300
LEAD (Pb) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	14.2	1.55
MERCURY (Hg) ^c	mg/kg	ACID DIGESTION AND COLD VAPOUR AAS METHOD (US EPA 2007: 7471B)	ND	0.100
SELENIUM (Se) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1994: 7742)	ND	0.100
ZINC (Zn) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	87.0	0.350



• DO NOT COPY PARTIAL OF THIS ANALYSIS REPORT WITHOUT OFFICIAL APPROVAL .
 • REPORTED ANALYSIS REFERS TO SUBMITTED SAMPLE ONLY.





United Analyst and Engineering Consultant Co., Ltd.

UNITED ANALYST AND ENGINEERING
CONSULTANT COMPANY LIMITED

3 Soi Udomsuk 41, Sukhumvit Road, Bangchak, Phrakanong, Bangkok 10260
Tel. 0 2763 2828 Fax 0 2763 2800 www.uaeconsultant.com E-mail: uae@uaeconsultant.com



TESTING
No. 0063

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT		DETECTION LIMIT
			S-3	T22AA311-0003	
TOTAL THRESHOLD LIMIT CONCENTRATION (T TLC)					
FLUORIDE ^c	mg/kg	ION SELECTIVE ELECTRODE METHOD (US EPA 1996: 9214)	2.67		0.80
SAMPLE CONDITION				GREY SOIL	

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT STILL NOT ACCREDITED

ND : NON-DETECTABLE.

SAMPLE (S) ANALYSED ON AS RECEIVED BASIS. RESULT (S) REPORTED ON A DRY WEIGHT BASIS.

*United Analyst Engineering Consultant Co., Ltd is Sub-contractor of REM-UAE Laboratory and Consultant Co., Ltd



Bhuchonk

(MR BHUCHONK PANICHLERTUMPI)
LABORATORY SUPERVISOR

JANUARY 26, 2022

- DO NOT COPY PARTIAL OF THIS ANALYSIS REPORT WITHOUT OFFICIAL APPROVAL .
- REPORTED ANALYSIS REFERS TO SUBMITTED SAMPLE ONLY.

ANALYSIS REPORT

PROJECT NAME : SOIL CONTAMINATION SURVEY IN THILAWA SEZ (ZONE A)
CUSTOMER NAME : RESOURCE AND ENVIRONMENT MYANMAR CO., LTD.
ADDRESS : B702 DELTA PLAZA, SHWEGONDAING ROAD, BAHAN, YANGON MYANMAR
CONTACT INFORMATION : TEL : +959 799855808 e-mail : toetoehlaing@rem-uaeconsultant.com
SAMPLING SOURCE : THILAWA
SAMPLE TYPE : SOIL **RECEIVED DATE** : JANUARY 7, 2022
SAMPLING DATE : DECEMBER 22, 2021 **ANALYTICAL DATE** : JANUARY 7-21, 2022
SAMPLING TIME : 12:00 HOUR **REPORT NO.** : 2022-U005678
SAMPLING METHOD : - **WORK NO.** : 2022-000193
SAMPLING BY : CUSTOMER **ANALYSIS NO.** : T22AA311-0004
ANALYZED BY : MISS JINTASUPA PLIANSRI

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			S-4 T22AA311-0004	
pH (1:1) ^b	-	ELECTROMETRIC METHOD (US EPA 2004: 9045D)	4.6 (25°C)	-
METALS				
ARSENIC (As) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1992: 7061A)	18.8	0.100
BORON (B) ^c	mg/kg	ACID DIGESTION AND INDUCTIVELY COUPLED PLASMA (ICP) METHOD (US EPA 1996: 3050B AND 2018: 6010D)	25.1	0.250
CADMIUM (Cd) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	ND	0.300
CHROMIUM (Cr) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	104	0.500
COPPER (Cu) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	212	0.300
LEAD (Pb) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	21.9	1.55
MERCURY (Hg) ^c	mg/kg	ACID DIGESTION AND COLD VAPOUR AAS METHOD (US EPA 2007: 7471B)	ND	0.100
SELENIUM (Se) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1994: 7742)	0.387	0.100
ZINC (Zn) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	43.0	0.350





United Analyst and Engineering Consultant Co., Ltd.

3 Soi Udomsuk 41, Sukhumvit Road, Bangchak, Phrakanong, Bangkok 10260

Tel. 0 2763 2828 Fax 0 2763 2800 www.uaeconsultant.com E-mail: uae@uaeconsultant.com



TESTING
No. 0063

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			S-4 T22AA311-0004	
TOTAL THRESHOLD LIMIT CONCENTRATION (TTL)				
FLUORIDE ^a	mg/kg	ION SELECTIVE ELECTRODE METHOD (US EPA 1996: 9214)	ND	0.80
SAMPLE CONDITION			BROWN SOIL	

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT STILL NOT ACCREDITED

ND : NON-DETECTABLE.

SAMPLE (S) ANALYSED ON AS RECEIVED BASIS. RESULT (S) REPORTED ON A DRY WEIGHT BASIS.

*United Analyst Engineering Consultant Co., Ltd is Sub-contractor of REM-UAE Laboratory and Consultant Co., Ltd



Bhuchonk P.

(MR. BHUCHONK PANICHLERTUMPI)
LABORATORY SUPERVISOR

JANUARY 26, 2022

• DO NOT COPY PARTIAL OF THIS ANALYSIS REPORT WITHOUT OFFICIAL APPROVAL .

• REPORTED ANALYSIS REFERS TO SUBMITTED SAMPLE ONLY.

ANALYSIS REPORT

PROJECT NAME : SOIL CONTAMINATION SURVEY IN THILAWA SEZ (ZONE A)
CUSTOMER NAME : RESOURCE AND ENVIRONMENT MYANMAR CO., LTD.
ADDRESS : B702 DELTA PLAZA, SHWEGONDAING ROAD, BAHAN, YANGON MYANMAR
CONTACT INFORMATION : TEL : +959 799855808 e-mail : toetoehlaing@rem-uaeconsultant.com
SAMPLING SOURCE : THILAWA
SAMPLE TYPE : SOIL **RECEIVED DATE** : JANUARY 7, 2022
SAMPLING DATE : DECEMBER 22, 2021 **ANALYTICAL DATE** : JANUARY 7-21, 2022
SAMPLING TIME : 12:20 HOUR **REPORT NO.** : 2022-U005679
SAMPLING METHOD : - **WORK NO.** : 2022-000193
SAMPLING BY : CUSTOMER **ANALYSIS NO.** : T22AA311-0005
ANALYZED BY : MISS JINTASUPA PLIANSRI

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			S-5 T22AA311-0005	
pH (1:1) ^b	-	ELECTROMETRIC METHOD (US EPA 2004: 9045D)	6.5 (25°C)	-
METALS				
ARSENIC (As) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1992: 7061A)	210	0.100
BORON (B) ^c	mg/kg	ACID DIGESTION AND INDUCTIVELY COUPLED PLASMA (ICP) METHOD (US EPA 1996: 3050B AND 2018: 6010D)	30.6	0.250
CADMIUM (Cd) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	ND	0.300
CHROMIUM (Cr) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	97.5	0.500
COPPER (Cu) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	27.3	0.300
LEAD (Pb) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	18.8	1.55
MERCURY (Hg) ^c	mg/kg	ACID DIGESTION AND COLD VAPOUR AAS METHOD (US EPA 2007: 7471B)	ND	0.100
SELENIUM (Se) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1994: 7742)	0.476	0.100
ZINC (Zn) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	56.7	0.350





United Analyst and Engineering Consultant Co., Ltd.

3 Soi Udomsuk 41, Sukhumvit Road, Bangchak, Phrakanong, Bangkok 10260

Tel. 0 2763 2828 Fax 0 2763 2800 www.uaeconsultant.com E-mail: uae@uaeconsultant.com



TESTING
No.0063

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			S-5 T22AA311-0005	
TOTAL THRESHOLD LIMIT CONCENTRATION (T TLC)				
FLUORIDE ^c	mg/kg	ION SELECTIVE ELECTRODE METHOD (US EPA 1996: 9214)	3.10	0.80
SAMPLE CONDITION			BROWN SOIL	

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT STILL NOT ACCREDITED

ND : NON-DETECTABLE.

SAMPLE (S) ANALYSED ON AS RECEIVED BASIS. RESULT (S) REPORTED ON A DRY WEIGHT BASIS.

*United Analyst Engineering Consultant Co., Ltd is Sub-contractor of REM-UAE Laboratory and Consultant Co., Ltd



Bhuchonk P.

(MR BHUCHONK PANICHLERTUMPI)
LABORATORY SUPERVISOR

JANUARY 26, 2022

- DO NOT COPY PARTIAL OF THIS ANALYSIS REPORT WITHOUT OFFICIAL APPROVAL .
- REPORTED ANALYSIS REFERS TO SUBMITTED SAMPLE ONLY.



MYANMAR JAPAN THILAWA DEVELOPMENT LIMITED

**Thilawa Special Economic Zone (Zone A)
Development Project (Operation Phase)**

Appendix -F

**Ground Subsidence Monitoring Status
(Location- Admin Complex Compound)**

October 2021 to March 2022



Environmental Monitoring Plan (Operation Phase)

Subsidence Monitoring Status (Operation Phase)

Admin Complex Compound

oints

E=209545.508

N=1844669.443

Date	Predefined Level (m)-ASL	Weekly Reading Level (m)-ASL	Subsidence (m)	Remark
15-Jul-16	+7.137	+7.137	0.000	
22-Jul-16	+7.137	+7.136	-0.001	
29-Jul-16	+7.137	+7.136	-0.001	
05-Aug-16	+7.137	+7.136	-0.001	
12-Aug-16	+7.137	+7.136	-0.001	
19-Aug-16	+7.137	+7.136	-0.001	
26-Aug-16	+7.137	+7.136	-0.001	
02-Sep-16	+7.137	+7.136	-0.001	
09-Sep-16	+7.137	+7.136	-0.001	
16-Sep-16	+7.137	+7.136	-0.001	
23-Sep-16	+7.137	+7.136	-0.001	
30-Sep-16	+7.137	+7.136	-0.001	
07-Oct-16	+7.137	+7.136	-0.001	
14-Oct-16	+7.137	+7.136	-0.001	
21-Oct-16	+7.137	+7.136	-0.001	
28-Oct-16	+7.137	+7.136	-0.001	
04-Nov-16	+7.137	+7.136	-0.001	
11-Nov-16	+7.137	+7.136	-0.001	
18-Nov-16	+7.137	+7.136	-0.001	
25-Nov-16	+7.137	+7.138	+0.001	
02-Dec-16	+7.137	+7.136	-0.001	
09-Dec-16	+7.137	+7.136	-0.001	
16-Dec-16	+7.137	+7.135	-0.002	
23-Dec-16	+7.137	+7.133	-0.004	
30-Dec-16	+7.137	+7.133	-0.004	
06-Jan-17	+7.137	+7.134	-0.003	
13-Jan-17	+7.137	+7.134	-0.003	
20-Jan-17	+7.137	+7.134	-0.003	
27-Jan-17	+7.137	+7.134	-0.003	
03-Feb-17	+7.137	+7.134	-0.003	
10-Feb-17	+7.137	+7.134	-0.003	
17-Feb-17	+7.137	+7.134	-0.003	
24-Feb-17	+7.137	+7.134	-0.003	
03-Mar-17	+7.137	+7.134	-0.003	
10-Mar-17	+7.137	+7.134	-0.003	
17-Mar-17	+7.137	+7.128	-0.009	After earthquake
24-Mar-17	+7.137	+7.128	-0.009	
31-Mar-17	+7.137	+7.128	-0.009	
7-Apr-17	+7.137	+7.128	-0.009	
21-Apr-17	+7.137	+7.126	-0.011	
28-Apr-17	+7.137	+7.126	-0.011	
5-May-17	+7.137	+7.126	-0.011	
12-May-17	+7.137	+7.129	-0.008	
19-May-17	+7.137	+7.131	-0.006	
26-May-17	+7.137	+7.135	-0.002	
9-Jun-17	+7.137	+7.135	-0.002	
16-Jun-17	+7.137	+7.134	-0.003	
23-Jun-17	+7.137	+7.134	-0.003	
30-Jun-17	+7.137	+7.136	-0.001	
7-Jul-17	+7.137	+7.136	-0.001	
14-Jul-17	+7.137	+7.136	-0.001	
21-Jul-17	+7.137	+7.138	+0.001	
28-Jul-17	+7.137	+7.136	-0.001	
3-Aug-17	+7.137	+7.136	-0.001	
10-Aug-17	+7.137	+7.137	+0.000	
17-Aug-17	+7.137	+7.136	-0.001	
24-Aug-17	+7.137	+7.137	+0.000	



Date	Predefined Level (m)-ASL	Weekly Reading Level (m)-ASL	Subsidence (m)	Remark
1-Sep-17	+7.137	+7.136	-0.001	
8-Sep-17	+7.137	+7.136	-0.001	
15-Sep-17	+7.137	+7.136	-0.001	
22-Sep-17	+7.137	+7.136	-0.001	
29-Sep-17	+7.137	+7.136	-0.001	
2-Oct-17	+7.137	+7.136	-0.001	
9-Oct-17	+7.137	+7.136	-0.001	
16-Oct-17	+7.137	+7.136	-0.001	
23-Oct-17	+7.137	+7.136	-0.001	
30-Oct-17	+7.137	+7.136	-0.001	
6-Nov-17	+7.137	+7.136	-0.001	
13-Nov-17	+7.137	+7.136	-0.001	
20-Nov-17	+7.137	+7.135	-0.002	
27-Nov-17	+7.137	+7.135	-0.002	
04-Dec-17	+7.137	+7.135	-0.002	
11-Dec-17	+7.137	+7.135	-0.002	
18-Dec-17	+7.137	+7.134	-0.003	
26 Dec-17	+7.137	+7.134	-0.003	
2-Jan-18	+7.137	+7.134	-0.003	
8-Jan-18	+7.137	+7.133	-0.004	
15-Jan-18	+7.137	+7.133	-0.004	
22-Jan-18	+7.137	+7.132	-0.005	
29-Jan-18	+7.137	+7.132	-0.005	
5-Feb-18	+7.137	+7.132	-0.005	
13-Feb-18	+7.137	+7.132	-0.005	
19-Feb-18	+7.137	+7.132	-0.005	
26-Feb-18	+7.137	+7.132	-0.005	
5-Mar-18	+7.137	+7.132	-0.005	
12-Mar-18	+7.137	+7.132	-0.005	
19-Mar-18	+7.137	+7.132	-0.005	
26-Mar-18	+7.137	+7.130	-0.007	
2-Apr-18	+7.137	+7.130	-0.007	
9-Apr-18	+7.137	+7.130	-0.007	
23-Apr-18	+7.137	+7.129	-0.008	
30-Apr-18	+7.137	+7.129	-0.008	
07-May-18	+7.137	+7.129	-0.008	
14-May-18	+7.137	+7.129	-0.008	
21-May-18	+7.137	+7.13	-0.007	
28-May-18	+7.137	+7.13	-0.007	
04-Jun-18	+7.137	+7.13	-0.007	
11-Jun-18	+7.137	+7.131	-0.006	
18-Jun-18	+7.137	+7.131	-0.006	
25-Jun-18	+7.137	+7.132	-0.005	
02-Jul-18	+7.137	+7.134	-0.003	
09-Jul-18	+7.137	+7.134	-0.003	
16-Jul-18	+7.137	+7.134	-0.003	
24-Jul-18	+7.137	+7.135	-0.002	
03-Aug-18	+7.137	+7.135	-0.002	
13-Aug-18	+7.137	+7.135	-0.002	
20-Aug-18	+7.137	+7.134	-0.003	
27-Aug-18	+7.137	+7.135	-0.002	
03-Sep-18	+7.137	+7.135	-0.002	
10-Sep-18	+7.137	+7.136	-0.001	
17-Sep-18	+7.137	+7.136	-0.001	
28-Sep-18	+7.137	+7.136	-0.001	
08-Oct-18	+7.137	+7.136	-0.001	
15-Oct-18	+7.137	+7.136	-0.001	
20-Oct-18	+7.137	+7.135	-0.001	
31-Oct-18	+7.137	+7.135	-0.001	
09-Nov-18	+7.137	+7.136	-0.001	
16-Nov-18	+7.137	+7.136	-0.001	
23-Nov-18	+7.137	+7.135	-0.002	



Date	Predefined Level (m)-ASL	Weekly Reading Level (m)-ASL	Subsidence (m)	Remark
03-Dec-18	+7.137	+7.135	-0.002	
13-Dec-18	+7.137	+7.135	-0.002	
20-Dec-18	+7.137	+7.135	-0.002	
27-Dec-18	+7.137	+7.135	-0.002	
08-Jan-19	+7.137	+7.135	-0.002	
19-Jan-19	+7.137	+7.135	-0.002	
26-Jan-19	+7.137	+7.135	-0.002	
01-Feb-19	+7.137	+7.135	-0.002	
08-Feb-19	+7.137	+7.134	-0.003	
15-Feb-19	+7.137	+7.134	-0.003	
23-Feb-19	+7.137	+7.135	-0.002	
04-Mar-19	+7.137	+7.135	-0.002	
16-Mar-19	+7.137	+7.136	-0.001	
23-Mar-19	+7.137	+7.136	-0.001	
30-Mar-19	+7.137	+7.136	-0.001	
08-Apr-19	+7.137	+7.134	-0.003	
22-Apr-19	+7.137	+7.133	-0.004	
30-Apr-19	+7.137	+7.131	-0.006	
03-May-19	+7.137	+7.132	-0.005	
10-May-19	+7.137	+7.132	-0.005	
22-May-19	+7.137	+7.131	-0.006	
31-May-19	+7.137	+7.131	-0.006	
07-Jun-19	+7.137	+7.130	-0.007	
14-Jun-19	+7.137	+7.131	-0.006	
21-Jun-19	+7.137	+7.132	-0.005	
28-Jun-19	+7.137	+7.132	-0.005	
05-Jul-19	+7.137	+7.132	-0.005	
12-Jul-19	+7.137	+7.133	-0.004	
24-Jul-19	+7.137	+7.133	-0.004	
31-Jul-19	+7.137	+7.133	-0.004	
05-Aug-19	+7.137	+7.133	-0.004	
12-Aug-19	+7.137	+7.134	-0.003	
20-Aug-19	+7.137	+7.133	-0.004	
30-Aug-19	+7.137	+7.134	-0.003	
06-Sep-19	+7.137	+7.135	-0.002	
13-Sep-19	+7.137	+7.135	-0.002	
20-Sep-19	+7.137	+7.136	-0.001	
30-Sep-19	+7.137	+7.136	-0.001	
08-Oct-19	+7.137	+7.136	-0.001	
20-Oct-19	+7.137	+7.135	-0.002	
30-Oct-19	+7.137	+7.135	-0.002	
08-Nov-19	+7.137	+7.135	-0.002	
28-Nov-19	+7.137	+7.135	-0.002	
13-Dec-19	+7.137	+7.135	-0.002	
20-Dec-20	+7.137	+7.135	-0.002	
30-Dec-20	+7.137	+7.135	-0.002	
10-Jan-20	+7.137	+7.135	-0.002	
20-Jan-20	+7.137	+7.136	-0.001	
31-Jan-20	+7.137	+7.135	-0.002	
07-Feb-20	+7.137	+7.134	-0.003	
28-Feb-20	+7.137	+7.135	-0.002	
09-Mar-20	+7.137	+7.136	-0.001	
18-Mar-20	+7.137	+7.136	-0.001	
28-Apr-20	+7.137	+7.133	-0.003	
28-May-20	+7.137	+7.131	-0.006	
30-Jun-20	+7.137	+7.130	-0.007	
29-Junly-20	+7.137	+7.130	-0.007	
18-Aug-20	+7.137	+7.131	-0.006	
25-Sep-20	+7.137	+7.132	-0.005	
09-Oct-20	+7.137	+7.133	-0.004	
19-Nov-20	+7.137	+7.134	-0.003	
29-Dec-20	+7.137	+7.134	-0.003	
10-Jan-21	+7.137	+7.135	-0.002	
28-Feb-21	+7.137	+7.135	-0.002	



Date	Predefined Level (m)-ASL	Weekly Reading Level (m)-ASL	Subsidence (m)	Remark
18-Mar-21	+7.137	+7.136	-0.001	
27-Apr-21	+7.137	+7.135	-0.002	
28-May-21	+7.137	+7.133	-0.004	
29-Jun-21	+7.137	+7.130	-0.007	
27-Jul-21	+7.137	+7.131	-0.006	
12-Aug-21	+7.137	+7.131	-0.006	
23-Sep-21	+7.137	+7.132	-0.005	
14-Oct-21	+7.137	+7.132	-0.005	
15-Nov-21	+7.137	+7.132	-0.005	
14-Dec-21	+7.137	+7.132	-0.005	
18-Jan-22	+7.137	+7.134	-0.003	
17-Feb-22	+7.137	+7.134	-0.003	
08-Mar-22	+7.137	+7.135	-0.002	





MYANMAR JAPAN THILAWA DEVELOPMENT LIMITED

**Thilawa Special Economic Zone- B
(Phase-1 Operation Phase)**

Appendix -G

**General Waste Disposal Record
(October 2021 to March 2022)**



13.12.2022

Code	Description	Date	Date of Sampling
Waste	<input checked="" type="checkbox"/> Non-Hazardous		
	<input checked="" type="checkbox"/> Hazardous	Quantity (t/m)	Remark
	<input type="checkbox"/> Others	5240	
Customer code	0001	Waste Profile code	L1
Trace	PIC (Name & Sign)	Date of Completion	
Transportation company	(Name & Sign) 71.12.2022	(Day Month Year)	
Waste service company	(Name & Sign) 2022.12.13	(Day Month Year)	

Designed by GOEDEN DOWA ECO-SYSTEM MYANMAR CO.,LTD. GEM-SL-R 010E/00

Customer: Golden Dowa Eco-System Myanmar Co., LTD

Materials: GW

5180kg G
4340kg PT
840kg N



Manifest

C-Slip

*Transportation company to Waste Generator

Date of issuance	(Day Month, Year) 28.10.2021	Issuer Ri	(Name & Sign) Thiri San Amin
Number of issuance	2021-2005-0001		
Contractors	Waste generator	Transportation company	Waste service company
Company Name	GEM	GEM	GEM
Tel			
	Kind	Name	Style of packing
Waste	<input checked="" type="checkbox"/> Non-Hazardous	General waste	
	<input type="checkbox"/> Hazardous	Quantity (Unit)	Remark
	<input type="checkbox"/> Others	780 kg	GNHT-01
Customer code	0001	Waste Profile code	X001 - NHS 2001
Trace	PIC (Name & Sign)	Date of Completion	
Transportation company	(Name & Sign) EAT-8558	(Day Month, Year)	
Waste service company	(Name & Sign) Chophys 2 Aug	(Day Month, Year)	

Designed by GOLDEN DOWA ECO-SYSTEM MYANMAR CO.,LTD.

GEM-SL-R 010E/00



Manifest		C-Slip		*Transportation company to Waste Generator
Date of issuance	(Day Month, Year)		Issuer	(Name & Sign)
Number of issuance	0001			Pearl Snow Indus
Contractors	Waste generator	Transportation company	Waste service company	
Company Name	Golden Dowa	GEM	GEM	
Tel				
	Kind	Name	Style of packing	
Waste	<input checked="" type="checkbox"/> Non-Hazardous	General waste		
	<input type="checkbox"/> Hazardous	Quantity (Unit)	Remark	
	<input type="checkbox"/> Others	480kg	B-44+G-NH7-01	
Customer code	0001	Waste Profile code	B-44+NHSZ001	
Trace	PIC (Name & Sign)		Date of Completion	
Transportation company	(Name & Sign)		(Day Month, Year)	
Waste service company	(Name & Sign)		(Day Month, Year)	
Designed by GOLDEN DOWA ECO-SYSTEM MYANMAR CO., LTD. GEM-SL-R 010E/00				

Customer: Golden Dowa Eco-System Myanmar Co., LTD

Materials: GW

4640kg G
3860kg PT
780kg N



Manifest

C-Slip

*Transportation company to Waste Generator

Date of issuance	(Day Month Year) 13 2022		Issuer R:	(Name & Sign)
Number of issuance	2021 - 2005 - 0001			
Contractors	Waste generator	Transportation company	Waste service company	
Company Name	MJTD	GEM	GEM	
Tel				
	Kind	Name	Style of packing	
Waste	<input type="checkbox"/> Non-Hazardous	General Waste		
	<input type="checkbox"/> Hazardous	Quantity (Unit) 1,120kg	Remark GNH-01 Boat	
	<input type="checkbox"/> Others		NHS 2001	
Customer code	0001	Waste Profile code	A001	
Trace	PIC (Name & Sign)	Date of Completion		
Transportation company	71-15-6 May	(Day Month Year)		
Waste service company	O. Mya Thet Ma	(Day Month Year)		

Designed by GOLDEN DOWA ECO-SYSTEM MYANMAR CO.,LTD.

GEM-SL-R 010E/00

Veh. No: 7L-1028

Customer: Golden Dowa Eco-System Myanmar Co., LTD

Materials: G10

5500kg G
4380kg PT
1120kg N





MYANMAR JAPAN THILAWA DEVELOPMENT LIMITED

**Thilawa Special Economic Zone (Zone A)
Development Project (Operation Phase)**

Appendix -H

**Sewage Treatment Plant Monitoring Record
(October 2021 to March 2022)**



Daily Self Monitoring of STP Inlet, Outlet and Aeration

Monthly	Date	Inlet (Zone B)				Inlet -1				Inlet -2				Outlet - 1				Outlet - 2			
		pH	TDS	Tem	COD	pH	TDS	Tem	COD	pH	TDS	Tem	COD	pH	TDS	Tem	COD	pH	TDS	Tem	COD
Standard	6 - 9	2000	≤35	400	6 - 9	2000	≤35	400	6 - 9	2000	≤35	400	6 - 9	2000	≤35	125	6 - 9	2000	≤35	125	
Unit	-	mg/L	°C	mg/L	-	mg/L	°C	mg/L	-	mg/L	°C	mg/L	-	mg/L	°C	mg/L	-	mg/L	°C	mg/L	-
Oct	01-10-21	6.49	568.8	27	1952	6.82	227.5	27.2	-	6.86	302.4	25.9	353	7.08	271	26.6	41	7.05	255.3	26.3	58
Oct	02-10-21	6.41	342.3	25.1	-	6.66	174.4	25.5	-	6.7	179.4	25.3	-	6.79	270.8	25.2	-	6.79	264.8	25.2	-
Oct	03-10-21	7.11	236.9	25.5	-	6.91	219.4	25.5	-	6.76	277.4	25.4	-	7.01	275.9	25.7	-	6.84	290.6	25.4	-
Oct	04-10-21	7.06	338.2	28.5	-	6.95	267.7	29.1	92	7.06	327.7	28.8	-	6.92	293	28.6	49	6.91	280.9	29.7	22
Oct	05-10-21	6.79	266.8	26.2	100	6.74	344.3	26.4	-	6.77	341.1	25.7	82	6.94	325.3	24.9	40	6.76	304.5	25.5	14
Oct	06-10-21	7.08	605.7	29.3	-	6.91	396	29	138	6.9	390	29	-	7.08	335.3	29.3	68	6.82	293.2	29.5	20
Oct	07-10-21	7.11	339.5	27.2	131	6.76	281.9	27.6	-	7.15	460.9	27.3	217	7.03	355.4	26.8	43	6.58	329.3	27	26
Oct	08-10-21	7.01	411	26.7	42	7.15	407.5	26.5	-	7.06	413	26.1	213	6.67	332.1	25.8	27	6.7	332.7	26.7	75
Oct	09-10-21	6.34	888.8	25.9	-	6.96	443.1	26	-	6.88	444.4	26	-	6.88	294.5	25.7	-	7.06	307	26.3	-
Oct	10-10-21	6.93	962.4	25.9	-	6.76	300.1	25.9	-	6.83	428.4	25.9	-	6.99	350.7	25.7	-	7.17	320.7	25.8	-
Oct	11-10-21	7.25	885.5	30.7	-	6.97	524	29.8	62	7.02	668.9	29.3	-	7	389.7	30	22	6.88	329.7	29.6	36
Oct	12-10-21	6.14	1525	26.4	1889	6.88	293.2	27.8	-	6.18	946.5	27.8	1905	7.03	407.7	26.7	26	7.05	404	26.2	32
Oct	13-10-21	6.03	882.9	24.4	-	6.81	172.1	24.7	202	6.76	174.4	24.8	-	7.49	383.5	24.4	49	7.47	498.8	24.6	205
Oct	14-10-21	6.01	782.1	24.1	1848	6.71	186.9	24.8	-	6.68	183.6	25.4	254	7.11	239.2	24.3	43	7.23	337.8	25.3	183
Oct	15-10-21	5.93	681.5	25.5	1977	6.73	442.8	25.3	-	6.66	441.3	25.5	1002	7.03	279.8	25.4	37	7.38	310.8	26	130
Oct	16-10-21	6.66	263.5	23.3	-	6.82	233.7	23.2	-	6.81	259.3	23.4	-	6.94	297.7	23.1	-	6.99	311.9	23.3	-
Oct	17-10-21	6.03	491.5	24.7	-	6.64	148.4	24.8	-	6.78	156.1	24.8	-	6.84	234.1	24.7	-	6.82	231.8	24.8	-
Oct	18-10-21	7.3	169	24.9	-	7.13	128.9	24.5	204	7.15	132.3	25.8	-	6.99	172.6	24.8	15	7.05	198.9	25.5	32
Oct	19-10-21	6.78	586.2	23.5	-	6.97	318.7	23.5	-	7.02	322.9	23.8	-	6.84	215.6	23.2	-	7	211.7	23.5	-
Oct	20-10-21	7.08	201	23.1	-	6.71	193.2	23.1	-	6.67	345.9	23.2	-	6.9	245	23.7	-	6.98	292.4	23.3	-
Oct	21-10-21	7.02	269.9	22.9	-	6.83	238.8	22.8	-	6.84	232.1	22.5	-	6.84	308.3	23.4	-	6.9	309	23.3	-
Oct	22-10-21	7.23	159.8	26.9	29	7.05	308.2	25.7	-	7.04	288.2	25.9	143	6.77	292.2	26.1	24	6.84	338.2	26.3	23
Oct	23-10-21	6.8	815.5	20.9	-	6.63	305.3	19.3	-	6.55	226.1	20.7	-	6.97	296.1	19.6	-	6.79	348.8	20.4	-
Oct	24-10-21	6.58	873.2	21.6	-	6.5	581	20.8	-	6.52	573.9	21.1	-	6.71	289.9	21.1	-	6.64	302	20.7	-
Oct	25-10-21	7.03	271.6	22.3	-	6.77	201.3	22.9	43	6.68	207.5	21.1	-	6.76	316.5	20.9	33	6.97	360	22.6	41
Oct	26-10-21	6.95	827.7	27.2	895	6.84	235.1	27.8	-	6.9	290.2	28.5	236	6.69	327.8	28.5	60	7.04	349.6	26.8	42
Oct	27-10-21	7	617.2	26.7	-	6.77	277	26.3	36	6.88	269.1	27.2	-	6.92	372.6	26.6	39	6.94	368.7	27.7	26
Oct	28-10-21	6.95	394.5	25.8	590	6.74	517.6	24.6	-	6.72	522.3	24.8	607	6.98	381.3	24.2	51	7	381.5	24.9	15
Oct	29-10-21	6.95	936.2	27	278	7.07	288.7	27.6	-	6.97	324.2	27.1	170	7.01	383.1	27.8	27	6.98	377.5	27.6	43
Oct	30-10-21	6.9	359.8	26.1	-	6.89	365.1	25.7	-	6.78	353	25.9	-	6.75	408.3	25.7	-	7.02	456.1	25.7	-
Oct	31-10-21	7.17	120.5	19.5	-	6.82	296.5	19.8	-	7.52	341.6	19.2	-	6.91	271.7	20.3	-	6.88	247.1	19.6	-
Nov	01-11-21	7.53	165.7	26.4	-	6.81	354.1	25	7.3	6.87	368.1	25.9	-	7.01	283.9	26	24	7.06	287.1	26.4	18
Nov	02-11-21	7.37	330.5	26.5	145	6.84	336.9	25.9	-	7.17	326.9	24.9	397	6.85	326.9	27.5	21	6.92	337.6	26.6	13
Nov	03-11-21	7.2	233.7	24.5	-	7.29	233.7	24.9	161	7.27	255.9	25.1	-	7.28	386.3	25.5	35	7.1	286.9	25.4	60
Nov	04-11-21	7.2	352.9	22.3	-	7	247.7	22.1	-	7.24	303.5	22	-	6.83	282.3	22.1	-	7.11	324.7	21.6	-
Nov	05-11-21	7.31	391	27.6	935	7.24	316	27.7	-	7.32	323.7	27.6	60	6.91	246.6	27.5	13	7.28	321.1	28.1	68
Nov	06-11-21	6.84	300.2	25.4	-	6.65	198.7	25.2	-	6.69	201.5	25.2	-	6.87	250.8	25.2	-	7.16	294.9	25.3	-
Nov	07-11-21	6.91	134.4	25.2	-	6.96	311.9	25.4	-	6.98	607.5	25.3	-	7.08	320.2	25	-	6.98	267.6	25.4	-
Nov	08-11-21	7.19	213	25.6	-	6.41	257.5	26	48	6.67	244.1	26.6	-	7.15	314.6	26	17	7.07	325.3	26.5	18
Nov	09-11-21	7.12	286.1	28.5	548	6.99	455.5	28.7	-	7.01	408.4	28.2	667	6.77	347.5	28.8	58	7.03	374.5	28.4	14
Nov	10-11-21	6.82	308.4	28.7	-	7.21	439.9	28.5	53	7.3	373.4	28.1	-	7.07	417.7	28.1	71	7.03	417.1	28.2	29
Nov	11-11-21	7.09	273.9	26.4	397	7	414.4	26.4	-	7.32	412.7	26.5	517	7.36	410.5	26.7	73	7.25	400.6	26.5	21
Nov	12-11-21	6.52	298.7	28.7	712	6.63	253.9	29.2	-	6.71	521.9	29.1	627	7.11	393.2	29.3	64	6.99	411	28.2	31
Nov	13-11-21	6.73	152.1	24.7	-	6.79	509.8	23.9	-	6.74	364.9	24.1	-	7.04	402.1	23.6	-	6.89	409.9	23.9	-
Nov	14-11-21	7.05	211.5	22.3	-	6.85	196.3	22.1	-	6.76	221.2	22.6	-	7.1	392.9	22.4	-	7	417.5	22.3	-
Nov	15-11-21	7.12	307.1	24.6	-	6.68	247.1	26.2	80	6.67	237.8	26	-	7.07	432.5	25.9	75	6.91	374.1	25	29
Nov	16-11-21	6.96	298.5	27.5	69	6.96	172.5	27.8	-	6.87	168	27.5	88	7.09	400	28	58	6.86	456.8	27.4	29
Nov	17-11-21	6.66	367.8	24.6	-	6.78	347.6	23.1	-	6.7	327	24	-	6.95	389.6	23.3	-	6.79	415.7	23.4	-
Nov	18-11-21	6.98	205.8	24.1	-	6.78	341.4	24.1	-	6.79	225.8	24.1	-	7.04	427.3	24.2	-	6.83	447.2	23.9	-
Nov	19-11-21	6.97	237.1	26.9	392	6.93	633.7	27.7	-	7.2	539.1	27.3	193	6.52	402.7	28.6	23	6.57	477.4	27.7	17
Nov	20-11-21	6.39	942.5	22.7	-	6.68	289.9	22.8	-	6.69	293	22.8	-	6.71	404.4	22.9	-	6.62	436.4	22.7	-
Nov	21-11-21	6.43	815.5	21.8	-	6.72	351.4	21.8	-	6.88	272.5	22	-	6.97	431.4	21.6	-	6.56	433.2	21.7	-
Nov	22-11-21	7.1	222.2	24.9	-	6.76	281.5	2													

Monthly	Date	Inlet (Zone B)				Inlet -1				Inlet -2				Outlet - 1				Outlet - 2			
		pH	TDS	Tem	COD	pH	TDS	Tem	COD	pH	TDS	Tem	COD	pH	TDS	Tem	COD	pH	TDS	Tem	COD
	Standard	6 - 9	2000	≤35	400	6 - 9	2000	≤35	400	6 - 9	2000	≤35	400	6 - 9	2000	≤35	125	6 - 9	2000	≤35	125
Dec	01-12-21	6.87	585.4	23.3	-	6.9	207.6	23.9	211	6.9	226.5	23.9	-	6.84	289.2	23.7	11	6.58	344.1	23.3	30
Dec	02-12-21	6.74	510.1	25.5	876	6.88	559.9	26	-	6.96	404.1	25.6	427	6.87	310.4	27.1	39	6.63	337.5	27.2	33
Dec	03-12-21	6.85	630.7	26.2	251	6.99	349.8	27	-	7.05	463	27	485	7.08	280	26.7	50	6.74	394.7	26.9	8
Dec	04-12-21	6.88	412.1	22.8	-	6.91	481.4	20.6	-	6.54	571.5	22.8	-	7.02	373.3	22.8	-	6.54	449.1	22.7	-
Dec	05-12-21	6.36	865.5	23.5	-	7.06	387.7	24.1	-	6.71	294.3	25.1	-	7.17	405.1	23.5	-	6.66	462	25.1	-
Dec	06-12-21	7.12	298.7	25.8	-	6.71	436.3	25.4	78	6.95	426.4	26.5	-	6.76	616.8	27.4	32	6.55	478.3	26.8	23
Dec	07-12-21	6.86	502.5	27.4	248	6.88	487.9	27.4	-	6.86	495.6	27.2	457	6.83	388.5	26.9	39	6.52	493.9	26.3	21
Dec	08-12-21	7.2	512.2	21.5	-	7.1	445.3	21.6	212	7.16	644.7	21.8	-	6.83	404.3	21.8	29	7.26	664.8	21.7	62
Dec	09-12-21	6.85	364.1	25.7	1053	6.86	388.8	26.5	-	6.83	380.9	26.5	860	6.78	476.2	26.5	50	6.75	481.2	26.6	26
Dec	10-12-21	6.61	149.1	21.6	-	6.73	377.6	21.6	-	6.8	526.5	21.7	-	7.1	471.1	21.7	-	6.92	476.1	21.5	-
Dec	11-12-21	6.64	343.6	24	-	7.15	656.2	23.8	-	6.97	506.5	23.8	-	7.15	468.9	23.9	-	6.91	523.8	24	-
Dec	12-12-21	6.06	371.2	21.5	62	6.91	539.2	21.4	-	6.94	535.9	21.4	605	7.22	402.3	21.4	137	6.95	482.8	21.9	34
Dec	13-12-21	7.14	268.3	25	-	6.98	433.9	25.7	165	7.11	436	25.3	-	7.03	449.1	25.9	47	7	435.8	23.7	52
Dec	14-12-21	6.97	314.4	24.1	507	7.12	521.8	27.8	-	7.09	463	27.6	592	6.82	455.2	27.2	38	6.9	505.3	27.6	42
Dec	15-12-21	6.62	542.3	26.5	-	6.85	378.4	26.3	92	6.94	410.6	27	-	7.05	440	26.6	31	7	449.7	26.5	40
Dec	16-12-21	6.65	333.1	27.7	630	7	470.6	29.7	-	6.98	457.4	29.6	203	6.85	430	29.2	84	6.91	441.3	29.8	65
Dec	17-12-21	6.19	393.3	24.9	959	6.95	386.1	24.8	-	6.73	611.8	24.7	909	6.95	420.6	23.8	45	7.14	459.5	24.7	49
Dec	18-12-21	6.69	153.4	21.1	-	6.98	453.1	21.7	-	7.03	439.7	21.7	-	6.77	530.1	21.5	-	7.06	447.1	21.5	-
Dec	19-12-21	6.15	402.3	21.5	-	6.76	455.2	21.4	-	6.91	545.4	21.5	-	7.24	449.3	21.5	-	7.2	466.1	21.8	-
Dec	20-12-21	6.75	299.9	22.1	-	6.81	366	22.1	71	6.9	335	22.5	-	7.25	425.5	22.3	83	7.06	401.3	23.1	25
Dec	21-12-21	6.15	323.8	25	851	6.99	485.2	25.2	-	6.97	461.5	25.4	664	7.13	377.4	25	152	7.14	332.9	24.8	27
Dec	22-12-21	5.89	307.2	23.6	-	6.93	237.8	23.3	178	6.89	363.8	23.5	-	7.25	373.9	23.9	65	7.15	366.2	23.9	24
Dec	23-12-21	6.44	457.3	25.4	987	6.84	562.3	26	-	6.85	562.8	26.2	54	7.05	373.4	25.9	116	7.16	409.8	26.1	31
Dec	24-12-21	6.25	584	23.3	-	6.72	667.4	24.8	-	6.86	584.3	24	-	7.11	433.2	25	-	7.29	430.9	23.2	-
Dec	25-12-21	6.56	603.1	21.4	-	6.85	278.6	21.1	-	6.86	286.4	21.1	-	7.11	393.2	20.1	-	7.25	409.6	20	-
Dec	26-12-21	7.04	445.5	23.1	-	6.78	374.6	23.4	-	6.73	370.8	23.6	-	6.99	398.7	23.2	-	7.34	403.2	23.5	-
Dec	27-12-21	7.37	245.2	24.3	-	7.11	356.6	23.3	214	7.5	589.9	23.4	-	7.01	433.9	23	31	7.32	387.6	23.7	27
Dec	28-12-21	6.94	384.4	24.7	936	7.1	600.4	25.4	-	7.21	535.6	25	693	6.65	414.3	25.3	46	7.31	427.6	25.4	66
Dec	29-12-21	5.98	446.9	24.3	-	6.95	380.8	24.7	523	6.77	499.5	24.7	-	7.17	427.7	24.3	22	7.25	464.1	25	64
Dec	30-12-21	5.8	435.2	25.5	1312	6.9	342.6	25.8	-	6.5	493.9	25.9	172	7.24	431.1	26.5	55	7.37	479	26.6	60
Jan	01-01-22	6.56	381.2	23	-	6.54	275.5	23.4	-	6.3	364.3	23.6	-	7.15	430.6	22.6	-	7	473.8	23.4	-
Jan	01-01-22	6.88	160.8	20.8	-	6.76	334	20.6	-	6.82	393.2	20.5	-	7.33	435.8	20.7	-	7.16	440.9	20.6	-
Jan	02-01-22	6.58	820.7	23	-	6.79	249.9	23.4	-	6.84	260.1	23.5	-	7.38	421.3	23.4	-	7.33	461	22.9	-
Jan	03-01-22	7.42	279.6	23.8	-	7.19	639.2	22.8	167	6.81	624.8	22.1	-	7.11	422.1	22.6	20	7.24	432.1	22.7	49
Jan	04-01-22	6.49	714	20.6	-	6.88	287.8	20.8	-	6.96	598.1	20.8	-	7.16	427.2	20.7	-	7.09	405.3	20.8	-
Jan	05-01-22	7.35	182	25.4	-	7.16	428.7	26	21	7.1	360.1	25.4	-	7.21	438.4	26.6	45	7.12	462.7	26.5	33
Jan	06-01-22	7.31	320	22	387	6.96	317	24.8	-	7.32	405.8	23.3	764	6.94	382.3	24.7	33	7.2	437.7	25.5	37
Jan	07-01-22	7.1	325.9	24	520	6.92	595.4	24	-	6.94	646.9	24.2	381	6.86	380.7	24.9	51	7.32	421.5	24	28
Jan	08-01-22	6.7	229.9	21.2	-	6.89	377.7	20.8	-	6.76	462.1	20.9	-	6.85	399.5	21.2	-	7.26	434.9	21	-
Jan	09-01-22	6.88	220.3	22.9	-	6.81	258.6	22.8	-	6.75	259.8	23.1	-	6.85	421.6	23	-	7.24	441.7	22.8	-
Jan	10-01-22	7.15	239.8	25.2	-	6.92	335.8	25.6	43	7.04	405.4	25.6	-	6.68	428.2	23.8	26	6.99	423.6	25.5	27
Jan	11-01-22	7	217.7	25	-	6.92	418.3	26.4	-	7.12	411	26	363	6.4	379.6	26.8	27	7.06	424.2	26.5	21
Jan	12-01-22	6.93	277.6	25	-	7.07	509.3	25.8	389	7.04	512	25.3	-	6.81	373.2	25.5	63	6.99	437.7	25.6	35
Jan	13-01-22	6.99	272.7	25	388	7.02	430.7	25.4	-	7.06	413.6	24.1	268	7.09	418.9	25	68	7.04	432.1	24.2	61
Jan	14-01-22	6.55	235	674	6.74	458.1	26.5	-	6.76	456.2	26.8	543	7.13	414.1	27	17	7.02	416.5	26.7	35	
Jan	15-01-22	5.56	331.3	23.7	-	6.51	442	23.7	-	6.45	422.8	23.9	-	7.02	404.8	24.2	-	7.07	404.7	24.1	-
Jan	16-01-22	6.39	329.1	23.8	-	6.7	496.6	24.1	-	6.49	625.3	23.7	-	6.93	444.1	23.7	-	7.15	445	23.8	-
Jan	17-01-22	7.31	312.9	24.5	-	6.96	376.2	25.9	256	6.84	492.3	25.7	-	7.13	445.1	26.1	97	7.12	440.2	25.9	34
Jan	18-01-22	6.81	270.8	22.6	989	7	361.8	22.4	-	7.02	381	23.2	311	7.16	458.5	23.1	55	6.98	429.5	23.7	8
Jan	19-01-22	6.16	287.2	23.6	-	6.8	407.5	23.6	1079	6.73	415.6	23.4	-	7.07	442.2	22.9	81	6.95	422.7	24	59
Jan	20-01-22	6.72	232.6	23.5	407	6.96	543.7	23.3	-	6.64	467.7	21.8	1037	7.14	443.7	23.3	60	7.18	460.5	23.7	74
Jan	21-01-22	5.57	381.3	24.7	2038	7.09	392	25.3	-	6.57	538.2	25.5	974	7.08	443.1	25.4	130	7.11	461.3	25.5	45
Jan	22-01-22	6.64	257.7	22	-	6.42	564.1	21.9	-	6.03	552.9	21.8	-	7.12	453.5	21.6	-	7.16	400.9</td		

Monthly	Date	Inlet (Zone B)				Inlet -1				Inlet -2				Outlet - 1				Outlet - 2			
		pH	TDS	Tem	COD	pH	TDS	Tem	COD	pH	TDS	Tem	COD	pH	TDS	Tem	COD	pH	TDS	Tem	COD
	Standard	6 - 9	2000	≤35	400	6 - 9	2000	≤35	400	6 - 9	2000	≤35	400	6 - 9	2000	≤35	125	6 - 9	2000	≤35	125
Feb	01-02-22	6.94	331.3	21.3	1088	6.79	425.4	21.4	-	6.85	345.3	21.4	654	7.16	431.6	21.4	20	7.03	414.3	21.6	68
Feb	02-02-22	6.94	278.2	24.6	-	6.92	440.8	24.9	266	6.93	474.9	24.6	-	7.07	439.9	25	50	7.14	458	24.1	37
Feb	03-02-22	6.91	260.4	21	595	6.95	352.6	21.2	-	7	349.4	21.8	455	7.23	472.3	21.7	53	7.11	484.3	21.9	53
Feb	04-02-22	6.97	309.5	23.7	803	6.89	484.3	24.5	-	6.85	483.2	24.2	107	6.74	415.8	24.5	26	7.13	485.5	24.5	19
Feb	05-02-22	6.79	598	20.7	-	6.67	547.5	21	-	6.54	399	20.7	-	6.57	390	20.7	-	7.07	449.2	20.9	-
Feb	06-02-22	6.75	311.9	21.8	-	6.81	311.5	21.3	-	6.83	315.5	21.2	-	6.46	394.2	20.9	-	7.23	446	21.4	-
Feb	07-02-22	6.25	318.8	24.1	-	6.97	258.4	23.5	119	7.19	246.5	24.7	-	6.81	372.6	25.2	39	7.12	454.1	24.9	22
Feb	08-02-22	7.19	363.2	23.7	702	7.02	385.8	23.6	-	7.16	495.3	23.9	345	6.86	374	23.3	68	6.91	400.5	24.3	87
Feb	09-02-22	7.16	336.1	24	-	7.04	361.9	26.3	205	7.11	347.5	26.7	-	6.32	364.7	26.7	51	6.99	446.5	26.7	40
Feb	10-02-22	7.19	382.9	23.3	466	7.12	529.1	24.4	-	7.09	531.4	24.4	513	6.87	412.4	24.9	71	6.84	408.9	24.9	66
Feb	11-02-22	6.39	355.3	24.7	1078	6.96	425.7	26.6	-	7.06	399.7	26.1	160	6.73	426.5	26.1	76	7.01	437.7	25.2	81
Feb	12-02-22	6.95	309.8	23	-	6.83	288.6	23.1	-	6.89	309.6	22.9	-	6.84	424.1	22.7	-	6.78	435.4	22.9	-
Feb	13-02-22	6.79	361.8	23	-	6.84	503.2	23.3	-	6.84	527.7	23	-	6.67	431.8	22.9	-	6.87	458.3	23	-
Feb	14-02-22	7.14	369.6	25.6	-	6.91	284.1	25.6	229	6.95	340.4	25.3	-	6.75	461.5	25.6	59	6.76	485.3	25.8	57
Feb	15-02-22	7.04	378.5	22.6	1204	7.34	519.6	24.1	-	7.26	447.4	24.6	794	6.57	436.6	24.5	73	6.51	485.9	24.6	97
Feb	16-02-22	6.87	345	26.9	-	7.04	493.4	27.3	217	7.08	450.1	27.1	-	6.89	553.9	27.1	67	6.52	474.6	27.2	31
Feb	17-02-22	6.73	287	25.4	500	6.75	885	25.4	-	6.8	615.6	25.5	568	6.9	497.8	25.6	47	6.66	472	25.5	36
Feb	18-02-22	6.35	354.9	23.4	754	6.59	409.7	23.3	-	6.54	412.1	23.5	785	6.92	471.2	23.4	86	6.86	466.8	23.4	53
Feb	19-02-22	6.6	313.6	23.6	-	6.58	623.1	23.3	-	6.57	639.1	22.9	-	7.03	455.6	23.2	-	7.1	485.1	22.9	-
Feb	20-02-22	7.1	349.2	23.1	-	6.98	530.1	23.3	-	6.87	460.6	23.7	-	6.75	457	23.4	-	7.06	461.8	23.6	-
Feb	21-02-22	7.36	276.0	24.7	-	7	416.4	24.6	180	7.09	502.7	24.5	-	6.57	502.3	24.7	80	7.17	467	24.4	20
Feb	22-02-22	7.11	330.6	24.8	-	6.69	560.5	27.5	-	6.92	528.6	27.7	432	6.93	488.8	27.7	29	6.27	489.2	27.4	40
Feb	23-02-22	7.1	331.8	24	-	7.05	417.5	24.6	387	6.97	456.5	24.4	-	6.83	457.2	24	19	6.9	463.5	24.2	43
Feb	24-02-22	6.99	363	19.1	531	6.98	400.6	21.9	-	7.01	404.7	22.4	107	6.81	476.2	21.7	62	6.71	497.5	22.2	36
Feb	25-02-22	6.98	364.4	26.6	546	6.41	449.3	27.3	-	7.03	520.1	27.5	792	7.12	467.6	27.2	54	6.7	597.5	27.2	84
Feb	26-02-22	6.5	365.2	21.8	-	6.84	315.7	21.4	-	6.59	314.6	21.6	-	6.75	425.4	21.4	-	6.75	451.3	21.6	-
Feb	27-02-22	7.02	429.6	22	-	7.03	389.6	22.1	-	7.05	357.6	20.5	-	6.79	465.1	22.6	-	6.68	452.9	22.3	-
Feb	28-02-22	7.36	310	23.5	-	7.07	285.5	23.1	256	7.05	288.4	23.9	-	6.68	405.1	23.9	60	6.41	466.1	24.1	31
Mar	01-03-22	6.94	223	25.9	480	7.05	368.9	25.7	-	7.08	396.4	26	346	6.72	326.3	25.5	-	6.17	392.5	25.8	-
Mar	02-03-22	7.1	315.9	22.9	-	7.06	339.8	23.7	-	6.95	426.9	23.2	-	6.64	332.9	24	27	6.7	360.7	24.1	35
Mar	03-03-22	7.23	319.2	24.5	336	7.01	427.8	25.4	-	7.29	418.9	24.8	184	6.58	392.9	25.9	49	6.58	358.9	25.9	26
Mar	04-03-22	7.11	296.6	22.8	529	7.12	355.7	21.8	-	7.17	414.5	21.5	541	6.46	399.4	23.4	24	6.56	369.4	23	36
Mar	05-03-22	6.87	319	22	-	6.88	563.9	22	-	6.82	57.6	22.1	-	6.35	389.4	22	-	6.67	393.4	22	-
Mar	06-03-22	7.01	389.1	23.1	-	7.12	525.4	23.1	-	6.8	415.4	23.1	-	6.28	463.4	23	-	6.83	409.7	23.1	-
Mar	07-03-22	7.4	371.3	26.3	-	7.03	350.8	24.9	279	7.09	301.7	25	-	6.41	492.3	25.1	41	6.82	412.3	25.2	111
Mar	08-03-22	7.29	384.9	26.3	698	7.04	336.6	26.3	-	7.05	336.8	25.9	655	6.17	462.4	26.4	49	6.24	473	26.4	59
Mar	09-03-22	7.27	352.6	23.7	-	7.08	412.1	22.3	164	7.11	416.7	23.3	-	6.33	436.7	23.9	49	6.68	382.7	22.9	100
Mar	10-03-22	7.13	342.2	28.5	475	7.01	369.8	29.7	-	6.98	342.5	29	341	6.48	446.4	29.5	53	6.4	375.8	29.3	57
Mar	11-03-22	6.95	307.1	30.5	443	6.87	261.4	30.2	-	6.86	250.1	30.4	134	6.39	409.9	30.5	97	6.63	428.9	30.5	72
Mar	12-03-22	7	296.9	22	-	7.06	470.9	22.6	-	7.13	487.8	22.4	-	6.51	415.5	22.1	-	6.79	408.5	22.5	-
Mar	13-03-22	6.87	301	21.9	-	6.62	452.6	22.5	-	6.55	457	22.5	-	6.34	420.7	22.6	-	6.93	428.5	22.6	-
Mar	14-03-22	7.21	339.8	29.5	-	6.95	384.4	29.4	146	7.14	375.6	29.2	-	6.35	426	28.9	74	6.71	475.6	28.8	18
Mar	15-03-22	7.08	394.5	27.3	203	7.03	396.1	27.2	-	7.11	425.5	27	341	6.21	368.3	27.3	39	6.72	435.2	28	103
Mar	16-03-22	6.89	384	21.1	-	6.76	496.2	20.9	-	6.74	478.5	22.1	-	6.25	356.9	20.8	-	6.7	395.5	20.7	-
Mar	17-03-22	6.89	305.6	23.4	151	6.95	277.4	24.5	-	7.05	343.5	25.1	269	6.06	392.9	24.8	60	6.48	389.6	24.8	11
Mar	18-03-22	6.84	274.3	23.9	230	6.98	322.1	24	-	6.95	343.7	24.8	85	6.01	393.8	24.1	53	6.48	375.4	23.9	46
Mar	19-03-22	6.56	194.1	19.4	-	6.63	362.6	20.1	-	6.64	350.1	19.1	-	5.75	350.8	20	-	6.02	373.1	19.5	-
Mar	20-03-22	6.96	228.1	20.2	-	5.97	453.4	19.9	-	6.99	448.6	20.3	-	5.93	358.4	20.3	-	6.44	351	20.2	-
Mar	21-03-22	5.94	218.5	24.4	-	6.81	315.9	23.8	145	5.48	176.7	23.4	-	6.21	375.4	24.2	95	5.88	396.7	23.5	63
Mar	22-03-22	7.25	231.6	25.3	502	6.86	330.4	26.2	-	6.89	314.8	26	56	5.91	399.7	26.5	49	6.6	360.3	26.6	48
Mar	23-03-22	8.94	263.1	27.9	-	7.09	401.3	28.8	67	6.86	484.4	28.9	-	6.03	404.1	28.3	47	6.24	323.5	28.1	125
Mar	24-03-22	7	220.6	25.6	375	6.87	366.3	26.4	-	6.86	343.4	26.5	255	6.08	391	26.4	23	6.35	411.5	26.3	31
Mar	25-03-22	6.9	276.6	25.4	189	6.9	645.7	25.3	-	6.89	434	24.4	504	5.92	390.5	23.9	66	6.34	406	24.3	50
Mar																					

Weekly STP Water Analysis Results

Month	Date	Zone A (Inlet) -1			Zone A (Inlet) -2			Outlet - 1										Outlet - 2									
		SS	BOD	T-P	SS	BOD	T-P	SS	BOD	T-N	T-P	O&G	T-Coli	E-Coli	Free Chlorine	SS	BOD	T-N	T-P	O&G	T-Coli	E-Coli	Free Chlorine				
Standard		Max 200	Max 200	Max8	Max 200	Max 200	Max8	Max 50	Max 30	Max 80	Max 2	Max 10	Max 400	Max 1000	Max 1	Max 50	Max 30	Max 80	Max 2	Max 10	Max 400	Max 1000	Max 1				
Unit		ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	MNP/100ml	MNP/100ml	mg/L	ppm	ppm	ppm	ppm	ppm	MNP/100ml	MNP/100ml	mg/L					
Oct	06-10-21	16	38.39	-	-	-	-	4	2.63	6	0.926	0.2	< 1	< 1	0.5	2	3.31	5	1.74	0.3	< 1	< 1	0.92				
Oct	13-10-21	-	-	-	30	42.74	-	25	1.06	2	0.958	0.2	2	< 1	0.15	80	1.26	6	2.04	0.4	< 1	< 1	0.12				
Oct	27-10-21	-	-	-	90	148.59	-	20	1.85	10	1.27	0.5	< 1	< 1	0.12	4	2.25	5	1.38	0.1	< 1	< 1	0.54				
Nov	03-11-21	90	15.19	-	-	-	-	10	4.5	7	0.708	0.6	< 1	< 1	0.32	12	3.11	5	2.02	0.4	< 1	1	0.67				
Nov	10-11-21	-	-	-	40	87.69	-	1	2.33	4	0.725	0	< 1	< 1	0.44	2	2.75	7	1.69	0.2	< 1	1	1.04				
Nov	16-11-21	13	13.74	-	-	-	-	4	3.43	6	0.875	0.1	< 1	< 1	0.9	2	3.35	3	1.68	0.1	< 1	1	0.75				
Nov	24-11-21	-	-	-	50	60.14	-	12	3.1	10	0.396	0.1	759	238	0.07	4	3.46	12	0.373	0.1	474	154	0.1				
Dec	01-12-21	85	109.44	0.351	-	-	-	5	2.52	20	0.389	0.5	< 1	< 1	0.76	2	2.32	23	0.391	0.2	< 1	< 1	0.17				
Dec	07-12-21	-	-	-	317	121.04	1.58	2	1.93	24	1.54	0	< 1	< 1	0.29	8	3.19	21	2.84	0	< 1	< 1	0.27				
Dec	15-12-21	30	68.84	5.42	-	-	-	16	1.19	13	1.7	0	< 1	< 1	0.45	4	1.46	18	3.02	0	< 1	< 1	0.35				
Dec	22-12-22	-	-	-	225	210.94	6.06	27	7.97	17	1.33	0	< 1	< 1	0.64	2	2.06	10	2.61	0	< 1	< 1	0.33				
Dec	28-12-21	40	42.59	1.5	-	-	-	10	1.05	10	1.8	0	< 1	< 1	0.98	15	2.31	11	1.66	0	< 1	< 1	0.66				
Jan	05-01-22	6	49.88	1.15	-	-	-	6	1.1	4	1.35	0	< 1	< 1	1.85	12	1.35	3	2.11	0	< 1	< 1	1.44				
Jan	12-01-22	-	-	-	40	57.24	1.77	4	1.27	20	1.97	0	< 1	< 1	0.12	2	1.87	8	3.28	0	< 1	< 1	0.81				
Jan	19-01-22	90	48.54	2.84	-	-	-	14	6.83	8	1.61	0.3	< 1	< 1	0.05	2	4.57	12	2.72	0.4	< 1	< 1	0.25				
Jan	25-01-22	-	-	-	390	451.64	5.01	50	2.58	17	3.52	0	< 1	< 1	0.26	30	3.33	8	2.47	0.2	< 1	< 1	0.69				
Feb	02-02-22	-	91.35	2.6	220	-	-	40	6.16	5	0.737	0.1	< 1	< 1	0.58	40	6.49	15	2.1	0	< 1	< 1	0.41				
Feb	08-02-22	-	-	-	50	126	3.02	20	7.7	21	2.72	0	< 1	< 1	0.37	10	7.3	17	3.33	0	< 1	< 1	0.51				
Feb	16-02-22	280	180	3.57	-	-	-	20	8.2	17	1.67	0.4	< 1	< 1	0.3(test)	50	8.6	19	2.42	0.3	< 1	< 1	0.07 (test)				
Feb	23-02-22	-	-	-	160	213	4.7	20	5.1	29	1.64	0.1	< 1	< 1	0.42	10	5	27	4.46	0.1	< 1	< 1	0.36				
Mar	03-03-22	80	126	7.22	-	-	-	20	8.2	12	2.5	0.1	< 1	< 1	0.63	40	6.8	14	4.73	0.2	< 1	< 1	0.54				
Mar	09-03-22	-	-	-	80	243	6.22	40	7.8	27	3.35	0	< 1	< 1	0.26	80	9.1	13	4.08	0	< 1	< 1	0.54				
Mar	17-03-22	30	75	2.65	-	-	-	20	10	13	3.68	0	< 1	< 1	0.17	10	6.1	5	5.35	0.3	< 1	< 1	0.22				
Mar	23-03-22	-	-	-	240	177	5.11	40	8.3	12	2.45	0.4	< 1	< 1	0.35	10	8.2	16	3.3	0.5	< 1	< 1	0.22				
Mar	30-03-22	80	99	4.72	-	-	-	10	8.3	10	2.15	0	< 1	< 1	0.14	20	7.4	11	4.24	0.6	< 1	< 1	0.16				



MJTD-FRM-WAT-M-032



MJTD-FRM-WAT-M-032



Monitoring Parameters Result for STP

Month	Date	Zone B - Inlet												Zone A - Inlet -1												Zone A - Inlet -2												Outlet -1								Outlet -2							
		SS	BOD	TP	TN	O & G	Cyanide	Formal-dehyde	Free Chlorine	Color	Iron	Ammonia	TN	O & G	Cyanide	Formal-dehyde	Free Chlorine	Color	Iron	Ammonia	TN	O & G	Cyanide	Formal-dehyde	Free Chlorine	Color	Iron	Ammonia	Cyanide	Formal-dehyde	Total Chlorine	Color	Iron	Ammonia	Cyanide	Formal-dehyde	Total Chlorine	Color	Iron	Ammonia													
Standard		Max 200	Max 200	Max 8	Max 80	Max 40	Max 0.1	Max 1	Max 1	150	Max3.5	Max80	Max 80	Max 40	Max 0.1	Max 1	Max 1	150	Max3.5	Max80	Max 80	Max 40	Max 0.1	Max 1	Max 1	150	Max3.5	Max80	Max 0.1	Max 1	Max 0.2	Max 150	Max3.5	Max10	Max 0.1	Max 1	Max 0.2	Max 150	Max3.5	Max10													
Unit		mg/l	mg/l	mg/l	mg/l	mg/l	mg/l	TCU	mg/l	mg/l	mg/l	mg/l	TCU	mg/l	mg/l	mg/l	TCU	mg/l	mg/l	mg/l	TCU	mg/l	mg/l	mg/l	TCU	mg/l	mg/l	mg/l	TCU	mg/l	mg/l	mg/l	TCU	mg/l	mg/l	TCU	mg/l	mg/l	TCU	mg/l	mg/l												
Oct	05-10-21	-	-	-	-	-	-	-	-	-	-	-	11	0.2	0.006	0.101	9.24	1.86	0.131	-	-	-	-	-	-	-	-	-	0.002	0.044	0.26	5.14	0.52	0.163	0.004	0.008	0.2	3.56	0.06	0.141													
Nov	03-11-21	180	64.49	4.87	14	0.8	0.06	0.49	0.03	45.54	0.94	1.43	-	-	-	-	-	-	-	12	0.8	0.008	0.1	0	25.36	1.01	2.75	0	0.018	0.91	13.92	0.35	0.804	0.005	0.097	1.1	7.52	0.1	0.155														
Dec	01-12-21	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	31	1.3	-	-	-	24.18	0.78	1.9	-	-	-	6.06	0.06	0.125	-	-	-	4.33	0.08	0.149														
Dec	08-12-21	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	0.078	1.36	0	-	-	-	-	-	0.003	0.024	0.7	-	-	-	0.005	0.05	0.61	-	-	-													
Jan	05-01-22	-	-	-	-	-	-	-	-	-	-	-	3 (5-1-22) 10(17-1-22)	0.9	0.004	0.046	0	9.86	0.568	1.05	-	-	-	-	-	-	-	-	0.003	0.035	0.8	9.25	0.269	0.579	0.002	0.072	0.67	8.91	0.486	0.587													
Feb	02-02-22	200	102.95	3.88	27	0.2	0.008	0.293	0.07	17.38	0.308	0.836	-	-	-	-	-	-	-	24	0.1	0.05	0.402	0.75	12.79	0.556	0.632	0.005	0.074	3.45	8.37	0.433	0.504	0.002	0.071	1.2	11.12	1.668	0.864														
Mar	03-03-22	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	39	0.4	0.002	0.188	0.05	16.18	1.421	2.74	0.008	0.035	1.26	6.69	0.611	3.5	0.005	0.058	1.08	5.95	1.084	1.2														
Apr	05-04-22	180	-	2.58	30	0.5	0.022	0.167	0.18	18.48	1.012	1.26	36	0.1	0.006	0.185	0	18.35	2.003	0.396	-	-	-	-	-	-	-	-	0.009	0.047	0.56	2.48	0.063	0.142	0.005	0.106	3.43	3.22	0.059	0.152													





MYANMAR JAPAN THILAWA DEVELOPMENT LIMITED

**Thilawa Special Economic Zone (Zone A)
Development Project (Operation Phase)**

Appendix -I

Requested Letter Attachments



2897
13/12
Date : 9 December 2021
Ref : MJTD/TSMC/21-12-1553

To : HEAD OF ENVIRONMENT SECTION
One Stop Service Center
Thilawa Special Economic Zone Management Committee

Subject: Information that Analysis supplier cannot analyze Total Phosphorous

Dear Sir/Madam

We would like to express our sincere appreciation for your continuous support for Thilawa SEZ project.

We, MJTD would like to give information that our analysis service provider, cannot analyze the Total Phosphorous (TP) in December 2021. With these, MJTD is requesting to skip the submittal of Total Phosphorous analysis results to TSMC-OSSC-ENV while our provider is still out of stock of reagent chemicals. Kindly refer to the attached mail document that our provider had informed to us.

It would be highly appreciated if you could accept the above information.

Yours Truly,



Yuki Kondo

Officer and General Manager
Operations Department
Myanmar Japan Thilawa Development Limited

CC: Thilawa SEZ Management Committee

13.12.2021
Received by
Front Office
Thilawa SEZ

Date : 30 August 2021
Ref : MJTD/TSMC/21-08-1471

To : HEAD OF ENVIRONMENT SECTION
One Stop Service Center
Thilawa Special Economic Zone Management Committee

Subject: Information about Environmental Quality Monitoring of Air, Noise and Vibration to re-start in September 2021 at Thilawa SEZ-A.

Dear Sir/Madam

We would like to express our sincere appreciation for your continuous support for Thilawa SEZ project.

We, MJTD would like to give information that Environmental Quality Monitoring of Air, Noise and Vibration of Thilawa SEZ-A will be done in September instead of August 2021, because we could not monitor with our normal schedule at Thilawa SEZ-A due to long holidays in August and high COVID-19 effect.

Be informed that Air Quality Monitoring at Thilawa SEZ-A will be monitored 24hrs - 7days continuously as it will be monitored inside Sewage Treatment Plant compound.

For Noise and Vibration, we will monitor during day time 8hrs because monitoring points are beside the road.

With these, please kindly be informed that MJTD will re-start the Environmental Quality Monitoring activities this September 2021 and it would be highly appreciated if you could accept the above information.

Yours Truly,



Yuki Kondo

Officer and General Manager
Operations Department
Myanmar Japan Thilawa Development Ltd.

CC: Thilawa SEZ Management Committee

Date : 10 September 2021
Ref : MJTD/TSMC/21-09-1540

To : HEAD OF ENVIRONMENT SECTION
One Stop Service Center
Thilawa Special Economic Zone Management Committee

Subject: Information that DOWA could not be able to analyze Total Phosphorous in September and October 2021

Dear Sir/Madam

We would like to express our sincere appreciation for your continuous support for Thilawa SEZ project.

We, MJTD would like to give information that our provider, Golden Dowa Eco-System Myanmar Co., Ltd, could not be able to analyze the Total Phosphorous (TP) in September and October 2021. With these, MJTD is requesting to skip the submittal of Total Phosphorous analysis results to TSMC-OSSC-ENV while our provider is still out of stock of reagent chemicals. Kindly refer to the attached mail document that our provider had informed to us.

It would be highly appreciated if you could accept the above information.

Yours Truly,



Yuki Kondo
Officer and General Manager
Operations Department
Myanmar Japan Thilawa Development Limited

Attachment: Mail Document

CC: Thilawa SEZ Management Committee

သီလဝါအထူးစီးပွားရေးဇုန် အပိုင်း(က)ရှိ
စက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်ရေးအတွက်
ရေအရည်အသွေးစောင့်ကြည့်လေ့လာခြင်းအစီအရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ)

(နှစ်လတစ်ကြိမ် စောင့်ကြည့်လေ့လာခြင်း)

၂၀၂၁ ခုနှစ်၊ အောက်တို့ဘာလ^{၁၃}
မြန်မာနိုင်အဲအင်တာနေရာင်နယ်လီမိတက်



မာတိကာ

အခန်း ၁ နိဒါန်း	c
၁.၁ ယော့ယျဖော်ပြချက်	c
အခန်း ၂ ရေအရည်အသွေးစောင့်ကြည့်လေ့လာခြင်း	၃
၂.၁ စောင့်ကြည့်လေ့လာသည့်အမျိုးအစား	၃
၂.၂ ရေနှမူနာယူသည့်နေရာများ၏တည်နေရာနှင့်အချက်အလက်များဖော်ပြချက်	၅
၂.၃ စောင့်ကြည့်လေ့လာသည့်နည်းလမ်း	၇
၂.၄ စောင့်ကြည့်လေ့လာသည့်ကာလ	၈
၂.၅ စောင့်ကြည့်လေ့လာမှုရလဒ်များ	၉
အခန်း ၃ နိဂုံးချုပ် နှင့် အကြံပြချက်များ	၁၄
၃.၁ နောက်ဆက်တဲ့ ၁ ရေနှမူနာကောက်ယူသည့် မှတ်တမ်းဓာတ်ပုံများ	၁၁-၁
၃.၂ နောက်ဆက်တဲ့ ၂ ဓာတ်ခွဲခန်းရလဒ်များ	၁၂-၁

အယားများစာရင်း

အယား ၂.၁-၁ စောင့်ကြည့်လေ့လာသည့်အမျိုးအစား	၃
အယား ၂.၂-၁ ရေနှမူနာကောက်ယူသည့်နေရာများ	၅
အယား ၂.၃-၁ ရေအရည်အသွေးစစ်ဆေးသည့် နည်းလမ်းများ	၇
အယား ၂.၄-၁ နေရာတစ်ခုချင်းစီအတွက် နှမူနာကောက်ယူသည့်အချိန်	၈
အယား ၂.၄-၂ မြန်မာနိုင်ငံ၊ ရန်ကုန်မြစ်၏ ဒီဇင်ဘာမှတ်တမ်း	၈
အယား ၂.၅-၁ ရေထွက်ပေါက်နှင့်ရေထိန်းဂိတ်အားလုံး၏ ရေထွက်အရည်အသွေး စောင့်ကြည့်လေ့လာမှု ရလဒ်များ	၁၀
အယား ၂.၅-၂ စွန်းထုတ်ရေထွက်ရှိသောနေရာများနှင့် စွန်းထုတ်ရေရောက်ရှိနိုင်သည့်ချောင်း၏ အခြေခံအချက်အလက်များကို နှိမ်နှုန်းယူဉ်ရန်အတွက် ရည်ညွှန်းစောင့်ကြည့်လေ့လာမှု ရေအရည်အသွေးရလဒ်များ	၂၂

ပုံများစာရင်း

ပုံ ၁.၁-၁ ရေအရည်အသွေးစောင့်ကြည့် လေ့လာမှုအတွက် နှမူနာကောက်ယူသော နေရာများ၏ တည်နေရာပြုပုံ	J
---	---



အခန်း ၁ နိဂုံး


၁.၁ ယေဘုယျဖော်ပြချက်

သီလဝါအထူးစီးပွားရေးဇုန်သည် ရန်ကုန်တိုင်းဒေသကြီး၏ တောင်ပိုင်းခါ်င်တွင်တည်ရှိပြီး ရန်ကုန်မြို့၏ အရှေ့တောင်ဘက် ၂၃ ကိုလိုမီတာတွင် တည်ရှုပါသည်။ သီလဝါအထူးစီးပွားရေးဇုန်၏ အကောင်အထည်ဖော်ဆောင်သူအနေဖြင့် ဇုန်အဖိုင်း(က)အတွင်းရှိ စက်မှုမြေနေရာအတွက် ခွင့်ပြုချက်ရရှိထားသော ပတ်ဝန်းကျင်ထိခိုက်မှုဆန်းစစ်ခြင်း အစီရင်ခံစာနှင့် ပတ်ဝန်းကျင်ဆိုင်ရာစီမံခန့်ခွဲမှုအစီအစဉ်အတိုင်း ပုံမှန်စောင့်ကြည့်စစ်ဆေးခြင်းကို ဆောင်ရွက်ရန် မြန်မာ-ဂျပန် သီလဝါဖွံ့ဖြိုးရေးလီမိတက်တွင် တာဝန်ရရှုပါသည်။ မြန်မာ-ဂျပန် သီလဝါဖွံ့ဖြိုးရေးလီမိတက်သည် ဇုန်အတွင်း နှင့် အနီးပတ်ဝန်းကျင်ရှိ သဘာဝပတ်ဝန်းကျင် အခြေအနေများကို သိရှိစေရန် သဘာဝပတ်ဝန်းကျင်နှင့်သာ အချက်အလက် စောင့်ကြည့်လေ့လာမှုများကို ရေးဆွဲထားပြီး ထိအစီအစဉ်များအရ အကောင်အထည်ဖော် ဆောင်ရွက်ခဲ့ပါသည်။

ရေအရည်အသွေး စောင့်ကြည့်လေ့လာမှုအား စစ်တမ်းကောက်ယူရာတွင် သီလဝါအထူးစီးပွားရေးဇုန်အတွင်းနှင့် အနီးပတ်ဝန်းကျင်ရှိ စုစုပေါင်းနေရာ၊ နာမည်အားဖြင့် (မြေပေါ်ရေနမူနာယူသည့်နေရာ-၁ (SW-1))၊ မြေပေါ်ရေနမူနာယူသည့်နေရာ-၂ (SW-2)၊ မြေပေါ်ရေနမူနာယူသည့်နေရာ-၄ (SW-4)၊ မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅ (SW-5)၊ မြေပေါ်ရေနမူနာယူသည့်နေရာ-၆ (SW-6) နှင့် မြေအောက်ရေနမူနာယူသည့်နေရာ-၁ (GW-1)) တို့တွင် စောင့်ကြည့်လေ့လာခဲ့ပါသည်။ ထိုနေရာ ခြောက်နေရာမှ မြေပေါ်ရေနမူနာယူသည့်နေရာ-၁ (SW-1) နှင့် မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅ (SW-5) မှာ သီလဝါအထူးစီးပွားရေးဇုန်၏ အဓိကစွန်းထုတ်ရေ ထွက်ပေါက်များဖြစ်ကြပြီး မြေပေါ်ရေနမူနာယူသည့်နေရာ-၆ (SW-6) မှာ ဗဟိုစွန်းထုတ်ရေသနစင်စက်ရုံး၏ နောက်ဆုံးစွန်းထုတ်ရေ ထွက်ရှိရာနေရာဖြစ်ပြီး သီလဝါအထူးစီးပွားရေးဇုန်အပိုင်း(က)၏ ပတ်ဝန်းကျင် ထိခိုက်မှုဆန်းစစ်ခြင်းအစီအရင်ခံစာ တွင်ပါဝင်သော ပတ်ဝန်းကျင် စောင့်ကြည့်လေ့လာမှု အစီအစဉ်အရ စောင့်ကြည့်ရမည့်စက်ရုံး ဖြစ်ပါသည်။ ကျန်ရှိသော မြေပေါ်ရေနမူနာယူသည့်နေရာ-၂ (SW-2) နှင့် မြေပေါ်ရေနမူနာယူသည့်နေရာ-၄ (SW-4) မှာ စွန်းထုတ်ရေ ထွက်ရှိသောနေရာများနှင့် စွန်းထုတ်ရေ ရောက်ရှိသည့်ချောင်း၏ အခြေခံအချက်အလက်တို့အား နှုင်းယူဉ်နိုင်ရန် ကိုးကားစောင့်ကြည့်လေ့လာမှု အဖြစ် နမူနာကောက်ယူခဲ့ပါသည်။ ထိုအပြင် မြေအောက်ရေနမူနာယူသည့်နေရာ-၁ (GW-1)အား ဘုန်းကြီးကျောင်း ပရောက်အတွင်းရှိ ရေတွင်းအား ရည်ညွှန်းနိုင်ရန် စောင့်ကြည့်လေ့လာခဲ့သည်။ ရေအရည်အသွေး စောင့်ကြည့်လေ့လာမှုအတွက် နမူနာကောက်ယူသော နေရာများ၏ တည်နေရာများကို ပုံ ၁.၁-၁ တွင်ဖော်ပြထားပါသည်။



သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုဇုန်ဖြူးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(နှစ်လတစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း အောက်တိုဘာလ ၂၀၂၁ ခုနှစ်)



မူရင်း။ ဂုဏ်ထုတ်

ပုံ C.C-C ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအတွက်နှမူနာကောက်ယူသောနေရာများ၏ တည်နေရာပြု



အခန်း J ရေအရည်အသွေးစောင့်ကြည့်လေ့လာခြင်း

J.၁ စောင့်ကြည့်လေ့လာသည့်အမျိုးအစား

ရေအရည်အသွေး စောင့်ကြည့်လေ့လာမှုအတွက် ရေနမူနာကောက်ယူသောနေရာများနှင့် ရေအရည်အသွေး အမျိုးအစားများ(parameters)ကို ပတ်ဝန်းကျင်ထိခိုက်မှုဆန်းစစ်ခြင်းဆိုင်ရာ အစီအရင်ခံစာပါ ပတ်ဝန်းကျင်ဆိုင်ရာ စောင့်ကြည့်လေ့လာမှု အစီအစဉ်အား ခြိုင့်မိစေရန်အလိုက် ဆောင်ရွက်ထားပါသည်။

ရေအရည်အသွေးနမူနာစစ်တမ်းကောက်ယူမှုအား နေရာခြောက်နေရာတွင် ဆောင်ရွက်ခဲ့ပါသည်။ ထိုနေရာ ခြောက်နေရာမှ ရေစီးဆင်းမှုတိုင်းတာခြင်းကို ရေစီးနှုန်းတိုင်းကိုရိယာဖြင့် တိုင်းတာနိုင်သော နေရာပါးနေရာ (မြေပေါ်ရေနမူနာယူသည့်နေရာ-၁ (SW-1))၊ မြေပေါ်ရေနမူနာယူသည့်နေရာ-J (SW-2)၊ မြေပေါ်ရေနမူနာယူသည့်နေရာ-၄ (SW-4)၊ မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅ (SW-5)နှင့် မြေပေါ်ရေနမူနာယူသည့်နေရာ-၆ (SW-6)) တို့တွင် တိုင်းတာခဲ့ပါသည်။ စောင့်ကြည့်လေ့လာသော ရေအရည်အသွေး အမျိုးအစားများ(parameters)နှင့် ရေနမူနာကောက်ယူသော နေရာများကို ယေား J.၁-၁ တွင် အကျဉ်းချုပ် ဖော်ပြထားပါသည်။

ယေား J.၁-၁ စောင့်ကြည့်လေ့လာသည့်အမျိုးအစား:

စဉ်	ရေအရည်အသွေး အမျိုးအစား (parameters)	မြေပေါ်ရေ နှုန်းယူသည့်နေရာ-၁ (SW-1)	မြေပေါ်ရေ နှုန်းယူသည့်နေရာ-J (SW-2)	မြေပေါ်ရေ နှုန်းယူသည့်နေရာ-၆ (SW-4)	မြေပေါ်ရေ နှုန်းယူသည့်နေရာ-၅ (SW-5)	မြေပေါ်ရေ နှုန်းယူသည့်နေရာ-၆ (SW-6)	မြေအောက် ရေ နှုန်းယူသည့်နေရာ-၁ (GW-1)	မှတ်ချက်
C	ရေအပူချိန် (Water Temperature)	○	○	○	○	○	○	ရေနမူနာကောက်ယူသည့်နေရာတွင်တိုက်ရှိက်တိုင်းတာခြင်း
J	pH ချွေးစီးပွားရေး (pH)	○	○	○	○	○	○	ရေနမူနာကောက်ယူသည့်နေရာတွင် တိုက်ရှိက်တိုင်းတာခြင်း
R	ပျော်ဝင်အောက်စီဂျင် (DO)	○	○	○	○	○	○	ရေနမူနာကောက်ယူသည့်နေရာတွင် တိုက်ရှိက်တိုင်းတာခြင်း
D	စိတ်နည်းဖြူးဖြူးခွဲရန် အောက်စီဂျင် လိုအပ်ချက် (ဃာရက်) (BOD ₍₅₎)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
G	ဓာတ်နည်းဖြူးဖြူးခွဲရန် အောက်စီဂျင် လိုအပ်ချက် (COD _(Cr))	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
N	နိုက်ထရိုဂျင်စုစုပေါင်း (Total Nitrogen)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
S	ဆိုင်းကြွာအနယ်များ (Suspended Solids)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း



သီလဝါအတူးပွားရေးဦးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုဇုနစ်ဖွံ့ဖြိုးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(နှစ်လတစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း အောက်တိုဘာလ ၂၀၂၁ ခုနှစ်)

စဉ်	ရေအရည်အသွေး အမျိုးအစား (parameters)	မြေပေါ်ရေ နမ္မနာ ယူသည့် နေရာ-၁ (SW-1)	မြေပေါ်ရေ နမ္မနာ ယူသည့် နေရာ-၂ (SW-2)	မြေပေါ်ရေ နမ္မနာ ယူသည့် နေရာ-၄ (SW-4)	မြေပေါ်ရေ နမ္မနာ ယူသည့် နေရာ-၅ (SW-5)	မြေပေါ်ရေ နမ္မနာ ယူသည့် နေရာ-၆ (SW-6)	မြေအောက် ရေ နမ္မနာ ယူသည့် နေရာ-၁ (GW-1)	မှတ်ချက်
၈	ကိုလိုဖောင်း စုစုပေါင်း (Total Coliform)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၉	ဖော့စဖော်ရှုက်စုစုပေါင်း (Total Phosphorus)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၁၀	အရောင်(Color)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၁၁	အနီး(Odor)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၁၂	ဆီနှင့်အဲခဲ့ခါ (Oil and Grease) (ကိုယ်တိုင်စောင့်ကြည့် လေ့လာခြင်း)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၁၃	ပျော်ဝင်အနည်းငါးပေါင်း (Total Dissolved Solids) (ကိုယ်တိုင်စောင့်ကြည့် လေ့လာခြင်း)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၁၄	သံခာတ် (Iron) (ကိုယ်တိုင်စောင့်ကြည့် လေ့လာခြင်း)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၁၅	မြှေးခာတ် (Mercury) (ကိုယ်တိုင်စောင့်ကြည့် လေ့လာခြင်း)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၁၆	ဝါးကိုက်ရောဂါကိုဖြစ် စေသော ကိုလိုဖောင်း ဘက်တီးရိုးယား (Escherichia Coli) (ကိုယ်တိုင်စောင့်ကြည့် လေ့လာခြင်း)	○	-	-	○	-	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၁၇	ရေစီးဆင်းနှင့်	○	○	-	○	○	-	ရေစီးဆင်းနှင့် နေရာတွင် တိုက်ရှိက်တိုင်းတာခြင်း

မူရင်း။ မြန်မာနိုင်အောင်တာနေရာရှင်နယ်လီမိတက်



J.J ရေနမူနာယူသည့်နေရာများ၏တည်နေရာနှင့်အချက်အလက်များဖော်ပြချက်

ရေနမူနာယူသည့်နေရာများကို ယေား J.J-၁ တွင် ဖော်ပြထားပါသည်။ ရေနမူနာယူသည့်နေရာ တစ်ခုစီတွင် စစ်တမ်းကောက်ယူခဲ့သည့် မှတ်တမ်းပုံများကို နောက်ဆက်တွဲ-၁ တွင်ဖော်ပြထားသည်။

ယေား J.J-၁ ရေနမူနာကောက်ယူသည့်နေရာများ

စဉ်	တည်နေရာ	အသေးစိတ်အချက်အလက်
၁	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၁ (SW-1)	ကိုဉ်ခိုခိုဒ် - မြောက်လတ္ထိတွဲ - ၁၆°၄၀'၁၃.၅"၊ အရွှေလောင်ရှို့တွဲ - ၉၆°၁၆' ၃၉.၈" တည်နေရာ - ရေထိန်းကန်ထွက်ပေါက် စစ်တမ်းကောက်ယူသောအမျိုးအစား - မြေပေါ်ရေစစ်တမ်းကောက်ယူခြင်းနှင့်ရေစီးနှုန်းတိုင်းတာခြင်း
J	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၂ (SW-2)	ကိုဉ်ခိုခိုဒ် - မြောက်လတ္ထိတွဲ - ၁၆° ၄၀' ၂၀.၆"၊ အရွှေလောင်ရှို့တွဲ - ၉၆° ၁၇' ၁၈.၀" တည်နေရာ - ရွှေပျောက်ချောင်းအထက်ပိုင်း စစ်တမ်းကောက်ယူသော အမျိုးအစား - မြေပေါ်ရေစစ်တမ်းကောက်ယူခြင်းနှင့်ရေစီးနှုန်းတိုင်းတာခြင်း
၃	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၄ (SW-4)	ကိုဉ်ခိုခိုဒ် - မြောက်လတ္ထိတွဲ - ၁၆° ၃၉' ၄၂.၈"၊ အရွှေလောင်ရှို့တွဲ - ၉၆° ၁၆' ၂၇.၄" တည်နေရာ - ရွှေပျောက်ချောင်းအောက်ပိုင်း စစ်တမ်းကောက်ယူသော အမျိုးအစား - မြေပေါ်ရေစစ်တမ်းကောက်ယူခြင်းနှင့်ရေစီးနှုန်းတိုင်းတာခြင်း
၅	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၅ (SW-5)	ကိုဉ်ခိုခိုဒ် - မြောက်လတ္ထိတွဲ - ၁၆° ၄၀' ၁၀.၇"၊ အရွှေလောင်ရှို့တွဲ - ၉၆° ၁၆' ၂၂.၆" တည်နေရာ - ရေထိန်းမြောင်းထွက်ပေါက် စစ်တမ်းကောက်ယူသော အမျိုးအစား - မြေပေါ်ရေစစ်တမ်းကောက်ယူခြင်းနှင့်ရေစီးနှုန်းတိုင်းတာခြင်း
၆	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၆ (SW-6)	ကိုဉ်ခိုခိုဒ် - မြောက်လတ္ထိတွဲ - ၁၆° ၄၀' ၂၇.၃"၊ အရွှေလောင်ရှို့တွဲ - ၉၆° ၁၆' ၃၀.၆" တည်နေရာ - ဗဟိုစွဲနှင့်ထုတ်ရောန့်စင်စက်ရုံမှ ရေထိန်းကန်သို့ အထွက် ထွက်ပေါက် စစ်တမ်းကောက်ယူသော အမျိုးအစား - မြေပေါ်ရေစစ်တမ်းကောက်ယူခြင်းနှင့်ရေစီးနှုန်းတိုင်းတာခြင်း
၆	မြေအောက်ရေ နမူနာယူသည့် နေရာ-၁ (GW-1)	ကိုဉ်ခိုခိုဒ် - မြောက်လတ္ထိတွဲ - ၁၆° ၄၀' ၁၆.၉"၊ အရွှေလောင်ရှို့တွဲ - ၉၆° ၁၆' ၃၄.၀၀" တည်နေရာ - မြို့ကြိုးခွမ်းကျောင်းတိုက်ပရဝဏ်အတွင်း စစ်တမ်းကောက်ယူသော အမျိုးအစား - မြေအောက်ရေစစ်တမ်းကောက်ယူခြင်း

မူရင်း၊ မြန်မာစိအောင်တာနေရာင်နယ်လိမ့်တက်

မြေပေါ်ရေနမူနာယူသည့်နေရာ-၁ (SW-1)

မြေပေါ်ရေနမူနာယူသည့်နေရာ-၁ (SW-1) အား မိုးကြိုးစွမ်းကျောင်းတိုက်၏ အရွှေအရပ်တွင်တည်ရှိသော ရေထိန်းကန်၏ ရေထွက်ပေါက်မှ ကောက်ယူခြင်း ဖြစ်ပါသည်။ ငြင်းသည် မြေပေါ်ရေနမူနာယူသည့်နေရာ-၆ (SW-6)၏ မြစ်အောက်ပိုင်း ၅၃၀ မီတာ အကွာတွင် တည်ရှိပါသည်။ အဆိုပါရေနှင်းမြောင်းသည် မြောက်မှ တောင်သို့ စီးဆင်းပြီး ရွှေပျောက်ချောင်းအတွင်း စီးဝင်သွားပါသည်။ အထက်ပါ စောင့်ကြည့်လေ့လာသည့်နေရာ၏ ရေထွက်အရည်အသွေးသည် မြစ်အောက်ပိုင်းမှ ဒီရေအတက်အကျ၏ လွမ်းမိုးများရှိနေပါသည်။ ထိုအပြင်ကျောင်းတိုက်အတွင်းမှ စွန်းထုတ်ရောတစ်စိတ်တစ်ပိုင်းသည်လည်း သီလဝါအထူးစီးပွားရေးဇုန်၏ ရေမြောင်းအတွင်းသို့ရောက်ရှိပြီး ရေထိန်းကန်အတွင်းသို့စီးဝင်မှုရှိကြောင်း ယူဆရပါသည်။

မြေပေါ်ရေနမူနာယူသည့်နေရာ-၂ (J) (ရည်ညွှန်းအမှတ်)

မြေပေါ်ရေနမူနာယူသည့်နေရာ-၂ (SW-2) အား ရွှေပျောက်ချောင်း၏ အထက်ပိုင်းတွင် ကောက်ယူခဲ့ခြင်းဖြစ်သည်။ အဆိုပါ အမှတ်သည် ဇုန်အပိုင်း(က)အော်ယာ၏ အရွှေတောင်ဘက်၊ ဒရိုးသီလဝါအလိုက်တွင် တည်ရှိပါသည်။ အနောက်တောင်တွင် ဇုန်အပိုင်း(ခ) နှင့် အရွှေဘက်တွင် ပြည်တွင်းစက်မှုဇုန်တိုက အသီးသီးဝန်းရုံလျက်ရှိသည်။



မြေပေါ်ရေနမူနာယူသည့်နေရာ-၄ (SW-4) (ရည်ညွှန်းအမှတ်)

ပြည်တွင်းစက်မှုဇုန်၊ ဇုန်အပိုင်း(က) နှင့် ဇုန်အပိုင်း(ခ)ရှို့ ဆောက်လုပ်ရေးလုပ်ငန်းခွင်များမှ စွန်ထုတ်လိုက်သောရေများ ပေါင်းစပ်းရောနောသွားသောနေရာ၊ ရွှေပျောက်ချောင်း၏ အောက်ပိုင်းတွင် မြေပေါ်ရေ နမူနာယူသည့်နေရာ-၄ (SW-4) တွင်ကောက်ယူခဲ့ခြင်းဖြစ်သည်။ ရွှေပျောက်ချောင်းသည် အရှေ့မှ အနောက်သို့ စီးဆင်းပြီး ရန်ကုန်မြစ်အတွင်းသို့စီးဝင်သည်။ မြေပေါ်ရေနမူနာယူသည့်နေရာ-၄ (SW-4) သည် မြေပေါ်ရေနမူနာယူသည့်နေရာ-၂ (SW-2)၏ ချောင်းအောက်ပိုင်း J.၁၅ ကိုလိုမိတာအကွာတွင် တည်ရှုပါသည်။ အဆိုပါ ရေနမူနာကောက်ယူသည့်နေရာသည် ဇုန်အပိုင်း(က) ရော်ယာ၏ အနောက်တောင်ဘက်တွင်တည်ရှုပြီး ဒုက္ခ-သီလဝါလမ်း၏ တောင်ဘက်တွင်တည်ရှုပါသည်။ ပတ်ဝန်းကျင်အနီးအနားတွင် ဇုန်အပိုင်း(ခ) နှင့် အရှေ့ဘက်တွင် ပြည်တွင်းစက်မှုဇုန်တို့ အသီးသီးတည်ရှုပါသည်။

မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅ (SW-5)

မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅ (SW-5) အား သိလဝါအထူးစီးပွားရေးဗိန်၏ ပင်မဂိတ်ပေါက်အနီးရှိ ရေထိန်းတူးမြောင်းမှ ကောက်ယူခဲ့သည်။ အဆိုပါ တူးမြောင်းအတွင်း စုဆောင်းထားသော ရေအများစုမှာ မြို့ရေ နှင့် အနီးအနားတွင် အပင်များရေလောင်းခြင်းမှ ထွက်၍လာသော ရေများ ဖြစ်ပါသည်။ အဆိုပါတူးမြောင်းသည်လည်း ရွှေပျောက်ချောင်းဖြင့် ဆက်သွယ်ထားပါသည်။ မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅ (SW-5) ၏ရေအရည်အသွေးသည် ချောင်းအောက်ဘက်မှ ဒီရေအတက်အကျ၏ လွမ်းမိုးမှုများစွာ ရှိနိုင်ပါသည်။

မြေပေါ်ရေနမူနာယူသည့်နေရာ-၆ (SW-6)

မြေပေါ်ရေနမူနာယူသည့်နေရာ-၆ (SW-6) အား မြို့ကြီးစွမ်းကျောင်းတိုက်ပရာဏ်အတွင်း နှင့် ရေထိန်းကန် မြေပေါ်ရေနမူနာယူသည့်နေရာ-၁(SW-1)၏ မြောက်ဘက်ရှိ ပင်မစွန်ထုတ်ရေသနစင်စက်ရုံး၏ ထွက်ပေါက်မှ ကောက်ယူခြင်းဖြစ်ပါသည်။ ထိုသန်စင်ပြီးသောစွန်ထုတ်ရေအား ရေထိန်းကန်အတွင်းသို့ စီးဝင်စေသည်။ ငါးရေထွက်ပေါက်သည် မြေပေါ်ရေနမူနာယူသည့်နေရာ-၁ (SW-1)၏ အထက်ဘက် ၅၃၀ မီတာခန့် အကွာအဝေးတွင်ရှုပါသည်။

မြေအောက်ရေနမူနာယူသည့်နေရာ-၁(GW-1) (မူလတည်ရှုနေသောရေတွင်းအားရည်ညွှန်းခြင်း)

မြေအောက်ရေနမူနာယူသည့်နေရာ-၁ (GW-1)အား တူးဖော်ထားသော ရေတွင်းမှ ကောက်ယူခဲ့ပါသည်။ အဆိုပါ ရေနမူနာကောက်ယူသည့် နေရာသည် မြို့ကြီးစွမ်းကျောင်းတိုက် ပရာဏ်အတွင်းတွင် တည်ရှုပါသည်။ အနောက်ဘက်တွင် ဇုန်အပိုင်း (က)၊ အရှေ့ဘက်တွင် ရေထိန်းကန် နှင့် တောင်ဘက်တွင် ဒုက္ခ-သီလဝါလမ်းတို့အသီးသီးရှုပါသည်။



J.2 စောင့်ကြည့်လေ့လာသည့်နည်းလမ်း

ရေနှစ်မှာများကို ကောက်ယူပြီး သန္တစင်ထားသောဖန်ပုလင်းသို့များဖြင့် သိမ်းဆည်းပြီး ပေါ်သော နည်းလမ်းများဖြင့် ဓာတ်ခွဲခန်း၌ စစ်ဆေးပါသည်။ ရေနှစ်မှာများကို ရေခဲပုံးများဖြင့် J-4 ဒီဂရီ ဆဲလ်စီးရပ် တွင်သိမ်းဆည်းထားပြီး ဓာတ်ခွဲခန်းသို့ ပို့ဆောင်ပါသည်။ တိုင်းတာသည် ရေအရည်အသွေး အမျိုးအစားများ၌ ရေအပူချိန်၊ ချွှေ့ဖန်ဂိန်းနှင့် ပျော်ဝင်အောက်စီဂျင်တို့အား ရေအရည်အသွေးတိုင်းတာသောစက်ကိရိယာ (Horiba U-52)ကို အသုံးပြု၍ ရေနှစ်မှာကောက်ယူသည့်နေရာ၌ပင် တိုက်ရိုက် တိုင်းတာခဲ့ပါသည်။ ထိုအပြင် ရေစီးဆင်းမှုနှင့်နှုန်းတိုင်းကိရိယာ (JFE Digital Current Meter)ဖြင့် ရေနှစ်မှာကောက်ယူသည့်နေရာ၌ တိုင်းတာ ခဲ့ပါသည်။

ပေါ်သော နည်းလမ်းများ

စဉ်	အမျိုးအစားများ	နည်းလမ်း
၁	ရေအပူချိန် (Temperature)	Instrument Analysis Method (Horiba, U-52, Multi Water Quality Checker)
၂	ချွှေ့ဖန်ဂိန်း (pH)	Instrument Analysis Method (Horiba, U-52, Multi Water Quality Checker)
၃	ဆိုင်းကြွေအနုတ် (Suspended Solids)	APHA 2540 D (Dry at 103-105°C Method)
၄	ပျော်ဝင်အောက်စီဂျင် (Dissolved Oxygen)	Instrument Analysis Method (Horiba, U-52, Multi Water Quality Checker)
၅	မိုးနည်းဖြင့်ဖြဲ့ရန် အောက်စီဂျင် လိုအပ်ချက် (ဌာရ်) (BOD ₍₅₎)	APHA 5210 B (5 Days BOD Test)
၆	ဓာတ်နည်းဖြင့်ဖြဲ့ရန် အောက်စီဂျင် လိုအပ်ချက် (COD _(Cr))	APHA 5220D (Close Reflux Colorimetric Method)
၇	ကိုလိုဖောင်း စုစုပေါင်း (Total Coliform)	APHA 9221B (Standard Total Coliform Fermentation Technique)
၈	နိုက်ထရိုဂျင်စုစုပေါင်း (Total Nitrogen)	HACH Method 10072 (TNT Persulfate Digestion Method)
၉	ဖော့စဖော်ရှက်စုစုပေါင်း (Total Phosphorus)	APHA 4500-P E (Ascorbic Acid Method)
၁၀	အရောင် (Color)	APHA 2120C (Spectrophotometric Method)
၁၁	အနီး (Odor)	APHA 2150 B (Threshold Odor Test)
၁၂	သီနှင့် အမဲဆီ (Oil and Grease)	APHA 5520B (Partition-Gravimetric Method)
၁၃	မြှေးခေါ် (Mercury)	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
၁၄	သံဓာတ် (Iron)	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
၁၅	ပျော်ဝင်အနည်စုစုပေါင်း (Total Dissolved Solids)	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)
၁၆	ဝမ်းကိုက်ရောက်ကိုဖြစ်စေသော ဘက်တီးရီးယား (Escherichia Coli)	APHA 9221 F (Escherichia Coli Procedure Using Fluorogenic Substrate)



သီလဝအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုဇုန်ဖြုံးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(နှစ်လတစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း အောက်တိုဘာလ ၂၀၂၁ ခုနှစ်)

စဉ်	အမျိုးအစားများ	နည်းလမ်း
၁၇	စီးဆင်းနှုန်း (Flow Rate)	Detection of Electromagnetic Elements (Real-time measurement by AEM 213-D Digital Current Meters)

မူရင်း။ မြန်မာနိုင်ငံအင်တာနေရာင်နယ်လိမ့်တက်

J.၄ စောင့်ကြည့်လေ့လာသည့်ကာလ

ရေအရည်အသွေးနှင့် ရေစီးဆင်းမှုနှုန်းအား အောက်တိုဘာလ ၆ ရက်နေ့ ၂၀၂၁ ခုနှစ်တွင် ဆောင်ရွက်ခဲ့ပြီး ဒီဇင်ဘာ၏ ဖြစ်ပေါ်လာနိုင်သော သက်ရောက်မှုများကိုရှောင်ရှားနိုင်ရန် အောက်ပါ ပေါ်လား J.၄-၁ အတိုင်း ရေနှုန်းကောက်ယူခဲ့သည်။ မြန်မာနိုင်ငံ၊ ရန်ကုန်မြစ်၏ အောက်တိုဘာလ ၆ ရက်နေ့ ၂၀၂၁ ခုနှစ် အတွက်ဒီဇင်ဘာ၏ မှတ်တမ်းကို ပေါ်လားပါသည်။

ပေါ်လား J.၄-၁ နေရာတစ်ခုချင်းစီအတွက် နမူနာကောက်ယူသည့်အချိန်

စဉ်	နမူနာကောက်ယူသည့်နေရာ	နမူနာကောက်ယူသည့်အချိန်
၁	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၁ (SW-1)	အောက်တိုဘာလ ၆ ရက်နေ့ ၂၀၂၁ ခုနှစ် (၁၀ နာရီ : ၀၈ မိနစ်)
၂	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၂ (SW-2)	အောက်တိုဘာလ ၆ ရက်နေ့ ၂၀၂၁ ခုနှစ် (၀၈ နာရီ : ၁၅ မိနစ်)
၃	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၄ (SW-4)	အောက်တိုဘာလ ၆ ရက်နေ့ ၂၀၂၁ ခုနှစ် (၀၇ နာရီ : ၂၁ မိနစ်)
၄	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၅ (SW-5)	အောက်တိုဘာလ ၆ ရက်နေ့ ၂၀၂၁ ခုနှစ် (၀၉ နာရီ : ၀၅ မိနစ်)
၅	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၆ (SW-6)	အောက်တိုဘာလ ၆ ရက်နေ့ ၂၀၂၁ ခုနှစ် (၀၉ နာရီ : ၃၃ မိနစ်)
၆	မြေအောက်ရေ နမူနာယူသည့် နေရာ-၁ (GW-1)	အောက်တိုဘာလ ၆ ရက်နေ့ ၂၀၂၁ ခုနှစ် (၁၀ နာရီ : ၅၉ မိနစ်)

မူရင်း။ မြန်မာနိုင်ငံအင်တာနေရာင်နယ်လိမ့်တက်

ပေါ်လား J.၄-၂ မြန်မာနိုင်ငံ၊ ရန်ကုန်မြစ်၏ ဒီဇင်ဘာ၏ မှတ်တမ်း:

ရက်စွဲ	အချိန်	အမြင့်	ဒီဇင်ဘာ၏ မှတ်တမ်း
အောက်တိုဘာလ ၆ ရက်နေ့ ၂၀၂၁ ခုနှစ်	၀၃:၅၈	၆.၂၂	ဒီဇင်ဘာ၏ မှတ်တမ်း
	၁၁:၅၇	၁.၂၀	ဒီဇင်ဘာ၏ မှတ်တမ်း
	၁၆:၀၅	၆.၂၆	ဒီဇင်ဘာ၏ မှတ်တမ်း

မူရင်း။ မြန်မာနိုင်ငံအင်တာနေရာင်နယ်လိမ့်တက် ရန်ကုန်မြစ်၏ ဒီဇင်ဘာ၏ မှတ်တမ်း:



J-၂ စောင့်ကြည့်လေ့လာမှုရလဒ်များ

ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုရလဒ်များကို ပေါ်ပြုထားသည်။ ဓာတ်ခွဲခန်းဆန်းစစ်မှု ရလဒ်များကို နောက်ဆက်တွဲ-၂ တွင်ဖော်ပြထားသည်။ ရလဒ်များကို ပတ်ဝန်းကျင်ထိခိုက်မှု ဆန်းစစ်ခြင်း အစီအရင်ခံစာတွင်ပါရှိသည့် ရေအရည်အသွေးရည်မှန်းတန်ဖိုးများနှင့် နှိုင်းယဉ်ထားပါသည်။

J-၃ သီလဝါအထူးစီးပွားရေးဇုန်ရှိစက်မှုစနစ်ဖွံ့ဖြိုးတိုးတက်ရေးနှင့် ရေအရည်အသွေးရလဒ်များ

ရည်မှန်းတန်ဖိုးများဖြင့် နှိုင်းယဉ်ရာတွင် ဆိုင်းကြွာအနယ် နှင့် ကိုလီဖောင်းစုစုပေါင်း တို့မှာ ရည်မှန်းတန်ဖိုးများထက် ကျော်လွှန်နေကြောင်းတွေ့ရှုပါသည်။

ဆိုင်းကြွာအနယ်ရလဒ်အနေဖြင့် ဗဟိုစွန်းထုတ်ရေး သန္တစင်စက်ရုံ၏ ထွက်ပေါက် မြေပေါ်ရေး နမူနာယူသည့်နေရာ-၆ (SW-6) မှရလဒ်သည် ရည်မှန်းထားသော တန်ဖိုးအတွင်းရှိကြောင်း တွေ့ရှုရသည်။ ထိုကြောင့် စက်ရုံတစ်ရုံချင်းစီမှ စွန်းထုတ်ရေးများအား ပင်မစွန်းထုတ်ရေး သန္တစင်စက်ရုံမှ ကောင်းမွန်စွာသန္တစင်ထားသည်ဟု ဆိုလိုနိုင်ပါသည်။ အခြားတစ်ဖက်တွင်လည်း ချောင်းအတွင်းသို့ မစွန်းထုတ်ခေါ်ရာ၌ရှုရသော စောင့်ကြည့်လေ့လာနေသော ရေထိန်းတူးမြောင်း မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅ (SW-5) မှ ရလဒ်များသည် ရည်မှန်းတန်ဖိုးထက် ကျော်လွှန်နေကြောင်းတွေ့ရှုရပါသည်။ ဖြစ်နိုင်ချောင်းအတွင်းအရင်းမှာ ဇုန်အပိုင်း(က)ရှိ မြေလွှတ်များမှ မြေမျက်နှာပြင် စီးဆင်းရေးများကြောင့် ဖြစ်နိုင်ပါသည်။

ကိုလီဖောင်းစုစုပေါင်း ရလဒ်အနေဖြင့် ဗဟိုစွန်းထုတ်ရေးသန္တစင်စက်ရုံ၏ ထွက်ပေါက် မြေပေါ်ရေနမူနာယူသည့်နေရာ-၆ (SW-6) မှရလဒ်သည် ရည်မှန်းထားသော တန်ဖိုးအတွင်းရှိကြောင်း တွေ့ရှုရသည်။ ထိုကြောင့် စက်ရုံတစ်ရုံချင်းစီမှ စွန်းထုတ်ရေးများအား ပင်မစွန်းထုတ်ရေး သန္တစင်စက်ရုံမှ ကောင်းမွန်စွာသန္တစင်ထားသည်ဟု ဆိုလိုနိုင်ပါသည်။ အခြားတစ်ဖက်တွင် ရလဒ်များသည် ရေထိန်းတူးမြောင်း မြေပေါ်ရေးနမူနာယူသည့်နေရာ-၅ (SW-5)တွင် ရလဒ်များမှာရည်မှန်းတန်ဖိုးထက် ကျော်လွှန်နေကြောင်းတွေ့ရှုရပါသည်။ ဖြစ်နိုင်ချောင်းအလားအလာရှိသည့်အကြောင်းရင်းများမှာ ရေထိန်းတူးမြောင်း၏ အတွင်းနှင့်အပြင်တလျောက်တွင် အပင်များနှင့်ငြက်များ၊ တိဇ္ဇာန်ယ်များကြောင့် ဇုန်အပိုင်း(က)၏ ဧရိယာတွင် သဘာဝအလျောက် ဘက်တီးရီးယားများ ရှိနေသောကြောင့် ဖြစ်နိုင်ပါသည်။

ကိုလီဖောင်းစုစုပေါင်း၏ဖြစ်တည်မှုတွင် သဘာဝအလျောက်ဘက်တီးရီးယားများ ပါဝင်ပြီး စုစုပေါင်း ကိုလီဖောင်းသည် လူတို့၏ကျန်းမာရေးကို တိုက်ရှိက်ထိခိုက်မှုမရှိသော်ပြားလည်း ကိုလီဖောင်းဘက်တီးရီးယားများ၏ ကျန်းမာရေး အပေါ်သက်ရောက်မှုကိုဖော်ထုတ်ရန် စစ်ကိုရောဂါကိဖြစ်စေသော ကိုလီဖောင်းဘက်တီးရီးယား (E. Coli) အားသုံးသပ်ခြင်းအတွက် ကိုယ်တိုင်စောင့်ကြည့် လေ့လာမှုကို ပြုလုပ်ခဲ့ပါသည်။ ဤဝစ်းကိုက်ရောဂါကိဖြစ်စေသော ကိုလီဖောင်းဘက်တီးရီးယား(E. Coli) ရလဒ်အရ တန်ဖိုးများအားလုံးသည် ရည်မှန်းတန်ဖိုးများအောက် နည်းပါးကြောင်းတွေ့ရှုရပါသည်။ ထိုကြောင့် ရေထိန်းတူးမြောင်း မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅ (SW-5)ရှိ စောင့်ကြည့်လေ့လာသော နေရာများတွင် ကိုလီဖောင်းစုစုပေါင်းသည် ရည်မှန်းတန်ဖိုးထက်များနေသော်လည်း လူ၏ကျန်းမာရေးကို သိသာထင်ရှားစွာ သက်ရောက်မှုမရှိနိုင်ကြောင်း သတ်မှတ်နိုင်ပါသည်။



သိလတိအထူးဖီးပျားရေးနှစ်အပိုင်း(က)ရှိစက်မှုနှစ်ဖြံ့ဖြိုးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(နှစ်လတစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း အောက်တိုဘာလ ၂၀၂၁ ခုနှစ်)

ယေား ၂၅-၁ ရေထွက်ပေါက်နှင့်ရေထိန်းဂိတ်အားလုံး၏ ရေထွက်အရည်အသွေး စောင့်ကြည့်လေ့လာမှု ရလဒ်များ

စဉ်	ရေအရည်အသွေး အမျိုးအစား (parameters)	ယူနစ်	မြေပေါ်ရေနှုန်း နေရာ-၁ (SW-1)	မြေပေါ်ရေနှုန်း နေရာ-၅ (SW-5)	မြေပေါ်ရေနှုန်း နေရာ-၆ (SW-6)	ရည်မှန်းတန်ဖိုး (ကိုယ်တိုင်စောင့်ကြည့် လေ့လာခြင်း အတွက် ရည်မှန်းတန်ဖိုး)
၁	ရေအဗ္ဗားချိန် (water temperature)	°C	J	J	J	≤ ၃၅
၂	ချွှေ့ဖွန်ကိန်း (pH)	-	၈.၄	၇.၃	၆.၉	၆ - ၉
၃	ခိုင်းကြွေအနယ် (suspended solid)	mg/L	၁၆	၇၀	၁၈	၅၀
၄	ပျော်ဝင်အောက်စိုက် (Dissolved Oxygen)	mg/L	၆.၂၂	၄.၂၆	၄.၂၀	-
၅	မိုးနည်းဖြစ်ဖြော်ရန် အောက်စိုက် လိုအပ်ချက် (၅-ရက်) (BOD ₍₅₎)	mg/L	၁၁.၄၁	၉.၇၄	၁၉.၃၈	၂၀
၆	ဓာတ်နည်းဖြစ် ဖြော်ရန် အောက်စိုက် လိုအပ်ချက် (COD _(Cr))	mg/L	၁၅.၀	၁၁.၂	၁၉.၀	၁၂၅
၇	ကိုယ်ဖောင်းစွာပေါင်း (Total Coliform)	MPN/ 100ml	၂၇၀.၀	၈၂၀၀	< ၁.၈	၄၀၀
၈	နိုက်ထရိုဂုဏ်စွာပေါင်း (Total Nitrogen)	mg/L	၀.၈	၁.၆	၁.၄	၈၀
၉	ဖော်စွောရှုံးစွာပေါင်း (Total Phosphorus)	mg/L	-	-	-	J
၁၀	အရောင် (Color)	TCU (True Color Unit)	၀.၄၈	၀.၃၇	J-J၅	၁၅၀
၁၁	အနဲ့ (Odor)	TON (Threshold Odor Number)	၁	၁	၁	-
၁၂	ဆီနှင့် အမဲဆီ (Oil and Grease)	mg/L	< ၃.၀	< ၃.၀	< ၃.၀	၁၀
၁၃	ပြဒါးဓာတ် (Mercury)	mg/L	≤ ၀.၀၀၂	≤ ၀.၀၀၂	≤ ၀.၀၀၂	၀.၀၀၅
၁၄	သံတတ် (Iron)	mg/L	၀.၈၅၂	J-၂၃၄	၀.၆၀၂	၃.၅
၁၅	ပျော်ဝင်အနည်းစွာပေါင်း (Total Dissolved Solids)	mg/L	၁၄၈	၁၅၀	၂၈၂	J၀၀၀
၁၆	ဝါးကိုက်ရောဂါကိုပြစ်စေသော ကိုယ်ဖောင်းဘက်တိုးရှုံးယူး (Escherichia Coli)	MPN/100ml (SW)	< ၁.၈	< ၁.၈	-	(၁၀၀၀)* (CFU/၁၀၀ml)
၁၇	စီးဆင်းနှုန်း (Flow Rate)	m ³ /s	၀.၁၂	၀.၀၁	၀.၀၀၅၂	-

မှတ်ချက်။ အနီးရောင်ဖြင့်ဖော်ပြထားသောတာနိုးများသည်သတ်မှတ်ထားသည့် တန်ဖိုးများထက်ကျော်လွန်နေသည်။ စောင့်ကြည့်လေ့လာသည့်
အချိန်အတွင်း ဖော်စွောရှုံးစွာပေါင်း (T-P)အား တော်ခွဲခွဲး၌ စမ်းသပ်၍ မရရှိပါ။



*မှတ်ချက်။ စွန့်ထုတ်ရေများစွန့်ထုတ်လိုက်သောချောင်း၏ အသုံးပြုမှုပေါ်မှတ်ည်၍ ဂျပန်နိုင်ငံ၏ ချိုးရေစီချိုးစီးညွှန်း (ပတ်ဝန်းကျင်ဆိုင်ရာဝန်ကြီးဌာန၊ ၁၉၉၇)တို့ ဝင်းကိုတ်ရောဂါတိဖြစ်စေသော ကိုလိုဖောင်းသာက်တိုးယား(E.coli)၏ ရည်မှန်းတန်ဖိုးအဖြစ်သတ်မှတ်ထားပါသည်။ သို့သော်လည်း ဖြန့်မာနိုင်ငံရှိ စာတိခွဲနှင့်များ၏ လုပ်ဆောင်ရွက်မှု ကန့်သတ်ချက်များကြောင့် စီအက်ပိုလူတန်ဖိုး "Colony Forming Unit (CFU)" အား တိုင်းတာ၍မရပါ။ ထို့ကြောင့် အမ်းအနှစ် "Most Probable Number (MPN)" ရလဒ်များကို စီအက်ပိုလူတန်ဖိုးနှင့် တူညီသည်ဟုယူဆပြီး ရည်မှန်းတန်ဖိုးနှင့် မျှော်ပါသည်။ မြန်မာနိုင်ငံတွင် စီအက်ပိုလူတန်ဖိုးကို သုံးသပ်နိုင်သည့်နှင့် တစ်ပြိုင်နှင့် သုံးသပ်သည့်နှင့်လစ်များ ပြောင်းလဲမည်ဖြစ်သည်။

J.၅.၂ စွန့်ထုတ်ရေထွက်ရှိသောနေရာများနှင့် စွန့်ထုတ်ရေရောက်ရှိနိုင်သည့်ချောင်း၏ အခြေခံအချက်အလက်များကို နှင့်ယူဉ်ရန်အတွက် ရည်ညွှန်းစောင့်ကြည့်လေ့လာမှု ရလဒ်များ


ရေရှည်အသွေးစောင့်ကြည့်လေ့လာမှုရလဒ်များကို ယေား J.၅-၂ တွင်ဖော်ပြထားပါသည်။ ရလဒ်များအား ပတ်ဝန်းကျင်ထိခိုက်မှ ဆန်းစစ်ခြင်းအစီအရင်ခံစာတွင် ပါဝင်သော ရေအရည်အသွေး၏ ရည်မှန်းတန်ဖိုးများနှင့် နှင့်ယူဉ် ထားပါသည်။

ရည်မှန်းတန်ဖိုးနှင့်နှင့်ယူဉ်ရာတွင် ဆိုင်းကြွာအနည်းများ၊ ကိုလိုဖောင်း စုစုပေါင်း နှင့် သံဓာတ်တို့မှာ ရည်မှန်းတန်ဖိုးထုက် ကျော်လွန်နောက်ပေါ်ပါသည်။

ဆိုင်းကြွာအနည်းများ၏ ရလဒ်များအရ မြေပေါ်ရေနမူနာယူသည့် နေရာ-၄ (SW-4) တို့၏ ရလဒ်များသည် ရည်မှန်းတန်ဖိုးထုက် ကျော်လွန်နေပါသည်။ ဆိုင်းကြွာအနည်းများ၏ ရလဒ်များသည် ရည်မှန်းတန်ဖိုးထုက် ကျော်လွန်နေခြင်းမှာ (၁) သဘာဝအလျောက် ချောင်းအထက်ပိုင်းမှ စီးဆင်းလာခြင်းနှင့် သီလဝါအထူးစီးပွားရေးဇုန် ပြင်ပရှိ ပြည်တွင်းစက်မှုဇုန်မှ စွန့်ထုတ်လိုက်သော ရေများကြောင့်လည်းကောင်း၊ (၂) ချောင်းအောက်ဘက်ရှိ ရေများသည် ဒီရေအတက်အကျောက် အထက်သို့ ပြန်လည်စီးဆင်းလာခြင်းကြောင့်လည်းကောင်း ဖြစ်နိုင်ပါသည်။

ကိုလိုဖောင်းစုစုပေါင်းရလဒ်အရ (မြေပေါ်ရေနမူနာယူသည့်နေရာ-၂ (SW-2) နှင့် မြေပေါ်ရေနမူနာယူသည့်နေရာ-၄ (SW-4)) တို့၏ ရလဒ်များသည် ရည်မှန်းတန်ဖိုးထုက် ကျော်လွန်နေခြင်းမှာ (၁) ချောင်းအထက်ပိုင်းတွင် တည်ရှိသော ဖွံ့ဖြိုးတိုးတက်မှုမရှိသေးသည့် ဧရိယာမှ တိရိစ္ဆာန်များ၏ စွန့်ပစ်အညွစ်အကြေးများ နှင့် ပြည်တွင်းစက်မှုဇုန်မှ စီးဆင်းလာသောရေများနှင့် သီလဝါအထူးစီးပွားရေးဇုန် ပြင်ပတွင်ရှိသော တရားမဝင်စွန့်ပစ်ရာနေရာများမှ လည်းကောင်း၊ (၂) ဒီရေသက်ရောက်မှုဖြင့် ပတ်ဝန်းကျင်ဧရိယာမှ ရေများ စီးဝင်လာခြင်းကြောင့်လည်းကောင်း ဖြစ်နိုင်ပါသည်။

သံဓာတ်ရလဒ်အနေဖြင့် (မြေပေါ်ရေနမူနာယူသည့်နေရာ-၂ (SW-2) နှင့် မြေပေါ်ရေနမူနာယူသည့်နေရာ-၄ (SW-4)) တို့၏ ရလဒ်သည် ရည်မှန်းတန်ဖိုးထုက် ကျော်လွန်နေကြောင်း တွေ့ရှိရပါသည်။ ဖြစ်နိုင်သောအကြောင်းအရာများမှာ သဘာဝ သံဓာတ် အရင်းအမြစ်၏ လွမ်းမိုးမှု ကြောင့် ဖြစ်နိုင်ပါသည် (သံဓာတ်သည်ရေစီးဆင်းမှုကြောင့် မြေဆီလွှာအတွင်းမှ ထွက်လာနိုင်ပါသည်)။ ရန်ကုန်မြို့၏ မြေဆီလွှာသည် သဘာဝအားဖြင့်သံဓာတ် ကြွယ်ဝပါသည်။



သီလဝါအတွေးစီးပွားရေးဗုဏ်အပိုင်း(က)ရှိစက်မှုဖုန်းဖြူးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအဖိုင်ခံစာ
(နှစ်လတစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း အောက်တိုဘာလ ၂၀၂၁ ခုနှစ်)

ယေား ၂၂-၂ စွန့်ထုတ်ရေထွက်ရှိသောနေရာများနှင့် စွန့်ထုတ်ရေရောက်ရှိနှိမ်သည့်ချောင်း၏
အခြေခံအချက်အလက်များကို နှိုင်းယူဉ်ရန်အတွက် ရည်ညွှန်းစောင့်ကြည့်လေ့လာမှု ရေအရည်အသွေးရလဒ်များ

စဉ်	ရေအရည်အသွေးအချို့ အစား (parameters)	ယူနစ်	မြေပေါ်ရှု နမူနာယူသည့် နေရာ-၂ (SW-2)	မြေပေါ်ရှု နမူနာယူသည့် နေရာ-၄ (SW- 4)	မြေအောက်ရှုနှုန်း မူနာယူသည့် နေရာ-၁ (GW-1)	ရည်မှန်းတန်ဖိုး (ကိုယ်တိုင်စောင့်ကြည့် လေ့လာခြင်းအတွက် ရည်ညွှန်းတန်ဖိုး)
၁	ရေအပ္ပါဒ် (water temperature)	°C	-	-	-	≤ 27
၂	ချွှေ့ဖန်ကိန်း (pH)	-	6.0	7.2	7.0	6 - 8
၃	ဆိုင်းကြွေအနှစ် (suspended solid)	mg/L	၅၀	၃၀၂	၈	၅၀
၄	ပျော်ဝင်အောက်စိုက် (Dissolved Oxygen)	mg/L	၇.၀၇	၆.၃၅	၅.၃၆	-
၅	မိုးနည်းဖြင့်ဖြော်ရန် အောက်စိုက် လိုအပ်ချက် (၅- ရက်) (BOD ₅)	mg/L	၁၀.၄၅	၃.၅၈	၂.၀၁	၂၀
၆	ဓာတုနည်းဖြင့်ဖြော်ရန် အောက်စိုက် လိုအပ်ချက် (COD _{Cr})	mg/L	၁၂.၈	၄.၁	၂.၅	၂၂၅
၇	ကိုလိုဖောင်းစုစုပေါင်း (Total Coliform)	MPN/ 100ml	> ၁၆၀၀၀၀	၁၆၀၀၀၀.၀	၄.၅	၄၀၀
၈	နိုက်တရိုဂုံစုစုပေါင်း (Total Nitrogen)	mg/L	၁.၀	၁.၆	၁.၂	၈၀
၉	ဖော်ဖော်ရောက်စုစုပေါင်း (Total Phosphorus)	mg/L	-	-	-	J
၁၀	အရောင် (Color)	TCU (True Color Unit)	၁၀.၇၇	၂.၂၃	၀.၀၀	၁၅၀
၁၁	အနဲ့ (Odor)	TON (Threshold Odor Number)	၁	၁	၁	-
၁၂	ဆိုနှင့် အမဲဆီ (Oil and Grease)	mg/L	< ၂.၀	< ၂.၀	< ၂.၀	၁၀
၁၃	မြေဒီးခာတ် (Mercury)	mg/L	≤ ၀.၀၀၂	≤ ၀.၀၀၂	≤ ၀.၀၀၂	၀.၀၀၅
၁၄	သံခာတ် (Iron)	mg/L	၃.၁၄၀	၁၂.၆၇၈	၀.၃၉၀	၃၅
၁၅	ပျော်ဝင်အနည်စုစုပေါင်း (Total Dissolved Solids)	mg/L	၁၁၈	၁၈၂	၁၃၆	၂၀၀၀
၁၆	ဝမ်းကိုက်ရောဂါရိဖြစ်စေသော ကိုလိုဖောင်းဘက်တိုးဒီးယား	MPN/100ml*(SW)	-	-	-	(၁,၀၀၀)* (CFU/100ml)



သီလဝါအထူးစီးပွားရေးဦးစီးပွဲနှင့်ဖြိုးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(နှစ်လတစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း အောက်တိုဘာလ ၂၀၂၁ ခုနှစ်)

စဉ်	ရေအရည်အသွေးအပျိုးအစား (parameters)	ယူနစ်	မြေပေါ်ရေ နှုန်းယူယည် နေရာ-၂ (SW-2)	မြေပေါ်ရေ နှုန်းယူယည် နေရာ-၄ (SW-4)	မြေအောက်ရေနှုန်းယူယည် နေရာ-၁ (GW-1)	ရည်မှန်းတန်ဖိုး (ကိုယ်တိုင်စောင့်ကြည့် လေ့လာခြင်းအတွက် ရည်မှန်းတန်ဖိုး)
	(Escherichia Coli)	MPN/100ml** (GW)	-	-	< ၁.၈	(၁၀၀)** (MPN/100ml)
၁၇	စီးဆင်းနှုန်း (Flow Rate)	m ³ /s	၀.၃၆	၀.၉၁	-	-


*မှတ်ချက်။ အနီရောင်ပြုင့်ဖော်ပြထားသောတန်ဖိုးများသည်သတ်မှတ်ထားသည့်တန်ဖိုးများထက်ကျော်လွန်နေသည်ကိစ္စလိပ်ပါသည်။ စောင့်ကြည့်လေ့လာသည့်အချို့အတွင်း ဖွေ့စေလောရိုက်စွာပေါင်း (T-P)အား မာတ်ခွဲခန်း၌ စမ်းသပ်၍ မရှိခိုင်ပါ။

*မှတ်ချက်။ စွမ့်ထုတ်ရော့ခွဲနှင့်ထုတ်လိုက်သောချောင်း၏ အသုံးပြုမှုပေါ်မှုတည်၍ ဂျပန်နိုင်ငံ၏ ချီးရေစီခိုန်စီးညွှန်း (ပတ်ဝန်းကျင်ဆိုင်ရာဝန်ကြီးဌာန၊ ၁၉၉၇)ကို ဝမ်းကိုက်ရော်ကိုပြစ်စေသော ကိုလီဖောင်းဘက်တီးရှိယား(E.coli)၏ ရည်မှန်းတန်ဖိုးအဖြစ်သတ်မှတ်လိုက်ပါသည်။ ထို့သော်လည်း မြန်မာနိုင်ငံ၏ ဓာတ်ခွဲခန်းများ၏ လုပ်ဆောင်နိုင်မှု ကန့်သတ်ချက်များကြောင့် စီအကိမ်းယူတန်ဖိုး "Colony Forming Unit (CFU)" အား တိုင်းတာရှုံးမရပါ။ ထို့ကြောင့် အဓိဒီအန် "Most Probable Number (MPN)" ရလဒ်များကို စီအကိမ်းယူတန်ဖိုးနှင့် တူညီသည်ဟုယူဆပြီး ရည်မှန်းတန်ဖိုးနှင့် နိုင်းယူးပါသည်။ မြန်မာနိုင်ငံတွင် စီအကိမ်းယူတန်ဖိုးကို သုံးသပ်နိုင်သည့်နှင့် တစ်ပြုင်နက် သုံးသပ်သည့်နည်းလမ်းများ ပြောင်းလဲမည်ဖြစ်သည်။

ဂျပန်နိုင်ငံ၏ ချီးရေ ရေစီခိုန်စီးညွှန်း (ပတ်ဝန်းကျင်ဆိုင်ရာဝန်ကြီးဌာန၊ ၁၉၉၇)အရ ဝမ်းကိုက်ရော်ကိုပြစ်စေသော ကိုလီဖောင်းဘက်တီးရှိယား (E. coli) တန်ဖိုး ၁၀၀၀ CFU/၁၀၀ ml ထက်ကျော်လွန်နေသည်မှာ ချီးရေအဖြစ်သုံးရန် မသင့်တော်ဟုယူဆပါသည်။

**မှတ်ချက်။ မြေအောက်ရေစောင့်ကြည့်လေ့လာသောနေရာတွင် ရေအသုံးပြုမှုပေါ်မှုတည်၍ စီယာက်နမ်နိုင်ငံ၏ မြေအောက်ရေအရည်အသွေးဆိုင်ရာ အချိုးသားနည်းပညာစည်းမျဉ်းဗြပ်ဒေ B1 (ဆည်ပြောင်းရေ) (No. QCVN 08: 2008/BTNMT) ကို မြေအောက်ရေကိုယ်တိုင်စောင့်ကြည့်လေ့လာခြင်းအတွက် ရည်မှန်းတန်ဖိုးအဖြစ်သတ်မှတ်ပါသည်။

မူရင်း။ မြန်မာနိုင်ငံအင်တာနေရာင်နယ်လီမိတက်



အခန်း ၃ နိဂုံးချုပ် နှင့် အကြံပြေချက်များ

သီလဝါအထူးစီးပွားရေးနှင့် အပိုင်း(က)၏ အဓိကရေတွက်ပေါက်များဖြစ်သော ရေတိန်းတူးမြောင်း
မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅ (SW-5) တွင် စုစုပေါင်းကိုလိုဖောင်း အမျိုးအစားမှာ
ယခုစောင့်ကြည့်လေ့လာသည့် အချိန်တွင် ရည်မှန်းတန်ဖိုးထက်များနေကြောင်း တွေ့ရှုရပါသည်။ ထို့အပြင်
ရေတိန်းတူးမြောင်း မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅ (SW-5) တွင် ဝမ်းကိုက်ရောဂါကို ဖြစ်စေသော
ကိုလိုဖောင်းဘက်တိုးရီးယား(E.Coli) အတွက် ကိုယ်တိုင်စောင့်ကြည့်လေ့လာမှုအရ ရလဒ်သည်
ရည်မှန်းတန်ဖိုးအောက် နည်းပါးကြောင်းတွေ့ရှုရပါသည်။ ထို့ကြောင့် ရေတိန်းတူးမြောင်း
မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅ (SW-5)ရှိ စောင့်ကြည့်လေ့လာသော နေရာများတွင် ကိုလိုဖောင်းစုစုပေါင်းသည်
ရည်မှန်းတန်ဖိုးထက်များနေသော်လည်း လူ၏ကျိုးမာရေးကို သိသာထင်ရှားစွာ သက်ရောက်မှုမရှိနိုင်ကြောင်း
သတ်မှတ်နိုင်ပါသည်။

ရည်မှန်းစောင့်ကြည့်လေ့လာသည့် မြေပေါ်ရေနမူနာယူသည့်နေရာများတွင် ဆိုင်းကြွာအနယ်များ၊
ကိုလိုဖောင်းစုစုပေါင်း နှင့် သံဓာတ် တို့၏ ရလဒ်များသည် ရည်မှန်းတန်ဖိုးထက် ကျော်လွန်နေ ကြောင်း
တွေ့ရှိရသည်။ ဖြစ်နိုင်ချေ အလားအလာရှိသည့်အကြောင်းအရင်မှာ မြေပေါ်ရေနမူနာယူသည့် နေရာ-၄ (SW-4) ရှိ၍
ဆိုင်းကြွာအနည်းများ ၏ ရလဒ်များသည် ရည်မှန်းတန်ဖိုးထက် ကျော်လွန်နေခြင်းမှာ သဘာဝအလျောက်
ချောင်းအထက်ပိုင်းမှ စီးဆင်းလာခြင်းနှင့် သီလဝါအထူးစီးပွားရေးဇားနှင့် ပြင်ပရှိ ပြည်တွင်းစက်မှုဇာန်မှ
စွမ်းထဲတဲ့လိုက်သော ရေများကြောင့်လည်းကောင်း၊ ချောင်းအောက်သာက်ရှိ ရေများသည်
ဒီရေအတက်အကျေကြောင့် အထက်သို့ ပြန်လည်စီးဆင်းလာခြင်းကြောင့် လည်းကောင်း ဖြစ်နိုင်ပါသည်။

ကိုလိုဖောင်းစွမ်းအနေဖြင့် (မြေပေါ်ရေနမူနာယူသည့်) နေရာ-J (SW-2) နှင့် မြေပေါ်ရေနမူနာယူသည့် နေရာ-C (SW-4) တွင် ရည်မှန်းတန်ဖိုးထက် ကျော်လွန်နေရခြင်းမှာ သဘာဝအလျောက် ရှိနေသော ဘက်တိုးဒီးယားမှား ကြောင့်ဖြစ်နိုင်ပါသည်။

သံဓာတ်ရလဒ်အနေဖြင့် (မြေပေါ်ရေနမူနာယဉ်သည့်နေရာ-၂ (SW-2) နှင့် မြေပေါ်ရေနမူနာယဉ်သည့် နေရာ-၄ (SW-4))တို့မှ ရလဒ်များသည် ရည်မှန်းတန်ဖိုးထက် ကျော်လွန်နေကြောင်း တွေ့ရှိရပါသည်။ ဖြစ်နိုင်သောအကြောင်းအရာများမှာ သဘာဝ သံဓာတ် အရင်အမြစ်၏ လွမ်းမိုးမှ ကြောင့် ဖြစ်နိုင်ပါသည် (သံဓာတ်သည်ရေးဆင်းမှုကြောင့် မြေဆီလွှာအတွင်းမှ ထွက်လာနိုင်ပါသည်)။ ရန်ကုန်မြို့၏ မြေဆီလွှာသည် သဘာဝအားဖြင့်သံဓာတ်ကြွယ်ဝပါသည်။



သီလဝါအထူးစီးပွားရေးဇုန်အပိုင်း(က)ရှိစက်မှုဇုန်ဖြီးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(နှစ်လတစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း အောက်တိုဘာလ ၂၀၂၁ ခုနှစ်)

အနာဂတ်တွင် သီလဝါအထူးစီးပွားရေးဇုန် အပိုင်း (က) ၇၅ အမိကစွန်ထုတ်ရေ ထွက်ရှိသောနေရာများမှ
ထွက်ရှိလာသော ရေအရည်အသွေးများဖြစ်သည့် ဆိုင်းကြွေအနည်းငါးစုစုပေါင်း တို့၏ သင့်တော်သော
ရည်မှန်းအဆင့်ရရှိနိုင်ရန် အောက်ပါဆောက်ချက်များကိုလုပ်ဆောင်သင့်ပါသည်။

- ကိုလီဖောင်းဘက်တီးရီးယားများ၏ ကျိန်းမာရေးအပေါ်သက်ရောက်မှုကို သိရှိနိုင်ရန် ဝမ်းကိုက်ရောဂါကို
ဖြစ်စေသော ကိုလီဖောင်းဘက်တီးရီးယား (E Coli) ကို ဆက်လက်စောင့်ကြည့်ရန်။
- ဆောက်လုပ်ရေးလုပ်ငန်းများမှရေများစီးဆင်းမှု အခြေအနေ ကိုစောင့်ကြည့်လေ့လာရန် နှင့်
- ဆောက်လုပ်ရေးလုပ်ငန်းများမှအထွေထွေသုံးစွန်ထုတ်ရေများ၏ အခြေအနေ ကိုစောင့်ကြည့်လေ့လာရန်။

ဤတင်စာတမ်းပြီးဆုံးပါသည်။



နောက်ဆက်တဲ့ ၁ ရေနမူနာကောက်ယူသည့် မှတ်တမ်းစာတိပုံများ



သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုနှင့်ဖြူးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေလာမှုအစီရင်ခံစာ
(နှစ်လတစ်ကြိမ်၊ စောင့်ကြည့်လေလာခြင်း အောက်တိုဘာလ ၂၀၂၁ ခုနှစ်)

သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုနှင့်ဖြူးတိုးတက်မှုအတွက်ယဉ်ယူသည့်နေရာများ



မြေပေါ်ရေ နမူနာယဉ်ယူသည့်နေရာ-၁ (SW-1) ၌ ရေနမူနာကောက်ယူခြင်းနှင့်တိုင်းတာခြင်း




မြေပေါ်ရေ နမူနာယဉ်ယူသည့်နေရာ-၅ (SW-5) ၌ ရေနမူနာကောက်ယူခြင်းနှင့်တိုင်းတာခြင်း



မြေပေါ်ရေ နမူနာယဉ်ယူသည့်နေရာ-၆ (SW-6) ၌ ရေနမူနာကောက်ယူခြင်းနှင့်တိုင်းတာခြင်း

သီလဝါအတူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုမှုနှင့်ဖြိုးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(နှစ်လတစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း အောက်တိုဘာလ ၂၀၂၁ ခုနှစ်)

စွန့်ထဲတ်ရေ့ထွက်ရှိသောနေရာများနှင့်စွန့်ထဲတ်ရေ့ရောက်ရှိနှိမ်သည့်ချောင်း၏အခြေခံအချက်အလက်
များကို မိမ်းယဉ်ရန်အတွက် ရည်ညွှန်းစောင့်ကြည့်လေ့လာသည့် နေရာများ



မြေပေါ်ရေ နမူနာယူသည့်နေရာ-၂ (SW-2) ြှာ ရေနမူနာကောက်ယူခြင်းနှင့်တိုင်းတာခြင်း



မြေပေါ်ရေ နမူနာယူသည့်နေရာ-၄ (SW-4) ြှာ ရေနမူနာကောက်ယူခြင်းနှင့်တိုင်းတာခြင်း



မြေအောက်ရေ နမူနာယူသည့်နေရာ-၁ (GW-1) ြှာ ရေနမူနာကောက်ယူခြင်းနှင့်တိုင်းတာခြင်း

နောက်ဆက်တွဲ ၂ စာတိခွဲခန်းရလဒ်များ



သီလဝါအထူးစီးပွားရေးဇုန်အပိုင်း(က)ရှိစက်မှုဇုန်ဖြူးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေလာမှုအစီရင်ခံစာ
(နှစ်လတစ်ကြိမ်၊ စောင့်ကြည့်လေလာခြင်း အောက်တိဘာလ ၂၁၂၁ ခုနှစ်)

စွန်ထုတ်ရေ့ထွက်ရှိသည့်နေရာများနှင့်ပဟိုစွန်ထုတ်ရေ့သိန်စင်စက်ရုံအတွက်

DOWA

GOLDEN DOWA ECO-SYSTEM MYANMAR CO., LTD
Lot No E1, Thilawa SEZ Zone A, Yangon Region, Myanmar.
Phone No/Fax No: (+95) 1 2809051



Report No. : GEM-LAB-202110056

Revision No. : 1

Report Date : 25 October , 2021

Application No. : 0001-C001

Analysis Report

Client Name	: Myanmar Koei International LTD (MKI)
Address	: No, 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar.
Project Name	: Environment Monitoring report for Zone A & B
Sample Description	
Sample Name	: MKI-SW-1-1006
Sampling Date	: 6 October, 2021
Sample No.	: W-2110021
Sampling By	: Customer
Waste Profile No.	: -
	Sample Received Date : 6 October, 2021


No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	16	-
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	11.41	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	15.0	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	350.0	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	0.8	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	0.48	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	148	-
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.852	0.002
12	Escherichia Coli	APHA 9221 F Escherichia Coli Procedure Using Fluorogenic Substrate	MPN/100ml	<1.8	1.8

Remark : LOQ - Limit of Quantitation

APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By :

 Cherry Myint Thein
 Supervisor



Approved By :

 Ni Ni Aye Lwin Oct 25, 2021
 Assistant Manager



C-J CO

သီလဝါအထူးစီးပွားရေးဇုန်အဖိုင်း(က)ရှိစက်မှုနှင့်ဖြူးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(နှစ်လတစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း အောက်တိုဘာလ ၂၀၂၁ ခုနှစ်)

DOWA

GOLDEN DOWA ECO-SYSTEM MYANMAR CO., LTD
Lot No E1 Thilawa SEZ Zone A, Yangon Region, Myanmar
Phone No. Fax No: (+95) 1 2309051


motivate our planet
Doc No: GEM-LB-R004E/00
Page 01

Report No. : GEM-LAB-202110057

Revision No. : 1

Report Date : 25 October , 2021

Application No. : 0001-C001

Analysis Report


Client Name	: Myanmar Koei International LTD (MKI)	
Address	: No, 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar.	
Project Name	: Environment Monitoring report for Zone A & B	
Sample Description		
Sample Name	: MKI-SW-5-1006	Sampling Date : 6 October, 2021
Sample No.	: W-2110022	Sampling By : Customer
Waste Profile No.	: -	Sample Received Date : 6 October, 2021


No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	78	-
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	9.74	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	11.2	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	9200	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	<3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	1.6	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	0.37	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	150	-
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	2.734	0.002
12	Escherichia Coli	APHA 9221 F Escherichia Coli Procedure Using Fluorogenic Substrate	MPN/100ml	<1.8	1.8

Remark : LOQ - Limit of Quantitation


APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By :


Cherry Myint Thein
Supervisor



Approved By :


Ni Ni Aye Lwin Oct 26, 2021
Assistant Manager



J-J-C

သိလဝါအတူးစီးပွားရေးဇုန်အပိုင်း(က)ရှိစက်မှုဇုန်ဖြုံတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအဖွဲ့ရင်ခံစာ
(နှစ်လတစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း အောက်တိဘာလ ၂၀၂၁ ခုနှစ်)



GOLDEN DOWA ECO-SYSTEM MYANMAR CO., LTD.
Lot No E1, Thihawa SEZ Zone A, Yangon Region, Myanmar
Phone No. Fax No: (+95) 1 2309051

motivate our planet
Doc No: GEM-L-B-R004E/00
Page 1 of 1

Report No. : GEM-LAB-202110058

Revision No. : 1

Report Date : 25 October , 2021

Application No. : 0001-C001

Analysis Report


Client Name	: Myanmar Koel International LTD (MKI)		
Address	: No, 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar.		
Project Name	: Environment Monitoring report for Zone A & B		
Sample Description			
Sample Name	: MKI-SW-6-1006	Sampling Date :	6 October, 2021
Sample No.	: W-2110023	Sampling By :	Customer
Waste Profile No.	: -	Sample Received Date :	6 October, 2021

No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105'C Method)	mg/l	18	-
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	19.38	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	59.0	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	<1.8	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	8.4	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	2.25	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180'C Method)	mg/l	382	-
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.602	0.002

Remark : LOQ - Limit of Quantitation
 APHA - American Public Health Association (APHA), the American Water Works Association (AWWA),
 and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and
 Wastewater, 22nd edition

Analysed By :

 Cherry Myint Thein
 Supervisor



Approved By :

 Ni Ni Aye Lwin Oct 25, 2021
 Assistant Manager



MO-J-R

သီလဝါအထူးစီးပွားရေးစုန်အပိုင်း(က)ရှိစက်မှုဇုန်ဖွံ့ဖြိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေလာမှုအစီရင်ခံစာ
(နှစ်လတစ်ကြိမ်၊ စောင့်ကြည့်လေလာခြင်း အောက်တိဘာလ ၂၀၂၁ ခုနှစ်)

စွန့်ထုတ်ရေထွက်ရှိသောနေရာများနှင့် စွန့်ထုတ်ရေရောက်ရှိနိုင်သည့်ချောင်း၏ အခြေခံအချက်အလက်များကို နှိမ်းယူဉ်ရန်အတွက် ရည်ညွှန်းစောင့်ကြည့်လေလာသည့် နေရာများ

DOWA

GOLDEN DOWA ECO-SYSTEM MYANMAR CO., LTD
Lot No E1 Thilawa SEZ Zone A, Yangon Region, Myanmar
Phone No. Fax No. (+95) 1 7499651


motivate our planet
Doc No.: GEM-LB-R004/E/00
Page 1 of 1

Report No. : GEM-LAB-202110059

Revision No. : 2

Report Date : 28 October , 2021


Application No. : 0001-C001


Analysis Report

Client Name	:	Myanmar Koei International LTD (MKI)		
Address	:	No, 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar.		
Project Name	:	Environment Monitoring report for Zone A & B		
Sample Description				
Sample Name	:	MKI-SW-2-1006	Sampling Date :	6 October, 2021
Sample No.	:	W-2110024	Sampling By :	Customer
Waste Profile No.	:	-	Sample Received Date :	6 October, 2021

No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105'C Method)	mg/l	50	-
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	10.45	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	12.8	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	>160000	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	1.0	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	10.77	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180'C Method)	mg/l	118	-
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Chromium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
12	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	3.840	0.002

Remark : LOQ - Limit of Quantitation
APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition .

Analysed By :

Cherry Myint Thein
Supervisor



Approved By :

Ni Ni Aye Lwin Oct 28, 2021
Assistant Manager



cc-J-C

သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုနှင့်ဖြီးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအဖို့ရင်္ခစာ
(နှစ်လတစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း အောက်တိဘာလ ၂၀၂၁ ခုနှစ်)

DOWA

GOLDEN DOWA ECO-SYSTEM MYANMAR CO., LTD
Lot No. E1, Thilawa SEZ Zone A, Yangon Region, Myanmar
Phone No. Fax No.: (+95) 1 2309051



Innovate our planet
Doc No: GEM-LB-R004E/00
Page 1 of 2

Report No. : GEM-LAB-202110060

Revision No. : 2

Report Date : 28 October , 2021

Application No. : 0001-C001

Analysis Report


Client Name	: Myanmar Koei International LTD (MKI)		
Address	: No, 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar.		
Project Name	: Environment Monitoring report for Zone A & B		
Sample Description			
Sample Name	: MKI-SW-4-1006		Sampling Date : 6 October, 2021
Sample No.	: W-2110025		Sampling By : Customer
Waste Profile No.	:		Sample Received Date : 6 October, 2021

No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105'C Method)	mg/l	302	—
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	3.58	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	4.1	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	160000.0	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	1.6	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	3.23	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180'C Method)	mg/l	182	—
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Chromium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
12	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	12.628	0.002


Remark : LOQ - Limit of Quantitation

APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition


Analysed By :


28.10.21

Cherry Myint Thein
Supervisor



Approved By :


Ni Ni Aye Lwin Oct 28, 2021
Assistant Manager



CC-J-G

သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိမက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(နှစ်လတန်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း အောက်တိုဘာလ ၂၁၂၁ ခုနှစ်)

DOWA

GOLDEN DOWA ECO-SYSTEM MYANMAR CO., LTD.
Lot No E1, Thilawa SEZ Zone A, Yangon Region, Myanmar
Phone No/Fax No: (+95) 1 2309051



motivate our planet
Doc No: GEM-LB-R004E/00
Page 1 of 1

Report No. : GEM-LAB-202110061

Revision No. : 1

Report Date : 25 October , 2021

Application No. : 0001-C001


Analysis Report


Client Name	: Myanmar Koei International LTD (MKT)		
Address	: No, 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar.		
Project Name	: Environment Monitoring report for Zone A & B		
Sample Description			
Sample Name	: MKI-GW-1-1006		Sampling Date : 6 October, 2021
Sample No.	: W-2110026		Sampling By : Customer
Waste Profile No.	: -		Sample Received Date : 6 October, 2021

No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	8	-
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	2.81	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	3.5	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	4.5	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	1.2	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	0.00	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	1366	-
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.390	0.002
12	Escherichia Coli	APHA 9221 F Escherichia Coli Procedure Using Fluorogenic Substrate	MPN/100ml	< 1.8	1.8

Remark : LOQ - Limit of Quantitation

APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By :

 Cherry Myint Thein
 Supervisor
 25-10-21



Approved By :

 Ni Ni Aye Lwin Oct 25, 2021
 Assistant Manager



cc-j-6

သီလဝါအထူးစီးပွားရေးဇုန် အပိုင်း(က)ရှိ
စက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်ရေးအတွက်
ရေအရည်အသွေးစောင့်ကြည်လေ့လာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ)

(တစ်နှစ် နှစ်ကြိမ် စောင့်ကြည့်လေ့လာခြင်း)

၂၀၂၁ ခုနှစ်၊ ဒီဇင်ဘာလ^{၂၀၂၁}
မြန်မာနိုင်အဲအင်တာနေရာင်နယ်လီမိတက်



မာတိကာ

အခန်း ၁ နိဒါန်း	၃
၁.၁ ယေဘုယျဖော်ပြချက်	၃
အခန်း ၂ ရေအရည်အသွေးစောင့်ကြည့်လေလာခြင်း	၃
၂.၁ စောင့်ကြည့်လေလာသည့်အမျိုးအစား	၃
၂.၂ ရေနမူနာယူသည့်နေရာများ၏တည်နေရာနှင့်အချက်အလက်များဖော်ပြချက်	၆
၂.၃ စောင့်ကြည့်လေလာသည့်နည်းလမ်း	၈
၂.၄ စောင့်ကြည့်လေလာသည့်ကာလ	၁၀
၂.၅ စောင့်ကြည့်လေလာမှုရလဒ်များ	၁၁
အခန်း ၃ နိဂုံးချုပ် နှင့် အကြံပြချက်များ	၁၈
နောက်ဆက်တဲ့ ၁ ရေနမူနာကောက်ယူသည့် မှတ်တမ်းဓာတ်ပုံများ	၁၁၁-၁
နောက်ဆက်တဲ့ ၂ ဓာတ်ခွဲခန်းရလဒ်များ	၁၂၂-၁

ပေါ်များစာရင်း

ပေါ်များ ၂-၁ စောင့်ကြည့်လေလာသည့်အမျိုးအစား	၃
ပေါ်များ ၂-၂ ရေနမူနာကောက်ယူသည့်နေရာများ	၆
ပေါ်များ ၂-၃ ရေအရည်အသွေးစိတ်ဆေးသည့် နည်းလမ်းများ	၈
ပေါ်များ ၂-၄ နေရာတစ်ခုချင်းစီအတွက် နမူနာကောက်ယူသည့်အချိန်	၁၀
ပေါ်များ ၂-၅ မြန်မာနိုင်ငံ၊ ရန်ကုန်မြစ်၏ ဒီဇင်ဘာမှတ်တမ်း	၁၀
ပေါ်များ ၂-၆ ရေထွက်ပေါက်နှင့်ရေထိန်းကိုတ်အားလုံး၏ ရေထွက်ရေအရည်အသွေး စောင့်ကြည့်လေလာမှု ရလဒ်များ	၁၂
ပေါ်များ ၂-၇ စွန်းထုတ်ရေထွက်ရှိသောနေရာများနှင့် စွန်းထုတ်ရေ ရောက်ရှိနိုင်သည့်ချောင်း၏ အခြေခံ အချက်အလက်များကို နှိုင်းယူဉ်ရန်အတွက် ရည်ညွှန်းစောင့်ကြည့် လေလာမှုရေအရည်အသွေးရလဒ်များ	၁၅

ပုံများစာရင်း

ပုံ ၁.၁-၁ ရေအရည်အသွေးစောင့်ကြည့် လေလာမှုအတွက် နမူနာကောက်ယူသော နေရာများ၏ တည်နေရာပြပုံ	၂
--	---



(က)

အခန်း ၁ နိဂုံး


၁.၁ ယေဘုယျဖော်ပြချက်

သီလဝါအထူးစီးပွားရေးဇုန်သည် ရန်ကုန်တိုင်းဒေသကြီး၏ တောင်ပိုင်းခရိုင်တွင်တည်ရှိပြီး ရန်ကုန်မြို့၏ အရှေ့တောင်ဘက် ၂၃ ကိုလိုမီတာတွင် တည်ရှိပါသည်။ သီလဝါအထူးစီးပွားရေးဇုန်၏ အကောင်အထည်ဖော်ဆောင်သူအနေဖြင့် ဇုန်အပိုင်း(က)အတွင်းရှိ စက်မှုမြေနေရာအတွက် ခွင့်ပြချက်ရရှိထားသော ပတ်ဝန်းကျင်ထိခိုက်မှုဆန်းစစ်ခြင်း အစီရင်ခံစာနှင့် ပတ်ဝန်းကျင်ဆိုင်ရာစီမံခန့်ခွဲမှုအစီအစဉ်အတိုင်း ပုံမှန်စောင့်ကြည့်စစ်ဆေးခြင်းကို ဆောင်ရွက်ရန် မြန်မာ-ဂျပန် သီလဝါဖွံ့ဖြိုးရေးလီမိတက်တွင် တာဝန်ရှိပါသည်။ မြန်မာ-ဂျပန် သီလဝါဖွံ့ဖြိုးရေးလီမိတက်သည် ဇုန်အတွင်း နှင့် အနီးပတ်ဝန်းကျင်ရှိ သဘာဝပတ်ဝန်းကျင် အခြေအနေများကို သိရှိစေရန် သဘာဝပတ်ဝန်းကျင်နှင့်သက်ဆိုင်သော အချက်အလက် စောင့်ကြည့်လေလာမှုများကို ရေးဆွဲထားပြီး ထိုအစီအစဉ်များအရ အကောင်အထည်ဖော် ဆောင်ရွက်ခဲ့ပါသည်။

ရေအရည်အသွေး စောင့်ကြည့်လေလာမှုအား စစ်တမ်းကောက်ယူရာတွင် သီလဝါအထူးစီးပွားရေးဇုန်အတွင်းနှင့် အနီးပတ်ဝန်းကျင်ရှိ စုစုပေါင်းနေရာ၊ ခြားခြားနေရာ၊ နာမည်အားဖြင့် (မြေပေါ်ရေနမူနာယူသည့်နေရာ-၁ (SW-1)၊ မြေပေါ်ရေနမူနာယူသည့်နေရာ-၂ (SW-2)၊ မြေပေါ်ရေနမူနာယူသည့်နေရာ-၄ (SW-4))၊ မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅ (SW-5)၊ မြေပေါ်ရေနမူနာယူသည့်နေရာ-၆ (SW-6) နှင့် မြေအောက်ရေနမူနာယူသည့်နေရာ-၁ (GW-1)) တို့တွင် စောင့်ကြည့်လေလာခဲ့ပါသည်။ ထိုနေရာ ခြားခြားနေရာမှ မြေပေါ်ရေနမူနာယူသည့်နေရာ-၁ (SW-1) နှင့် မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅ (SW-5) မှာ သီလဝါ အထူးစီးပွားရေးဇုန်၏ အဓိကစွမ်းထုတ်ပေါက်များဖြစ်ကြပြီး မြေပေါ်ရေနမူနာယူသည့်နေရာ-၆ (SW-6) မှာ ပဟိုစွန်းထုတ်ရေသနစင်စက်ရုံး၏ နောက်ဆုံးစွန်းထုတ်ပေါက်ရှိရှိရေးရှိရေးနှင့် အပိုင်း(က)၏ ပတ်ဝန်းကျင် ထိခိုက်မှုဆန်းစစ်ခြင်းအစီအရင်ခံစာ တွင်ပါဝင်သော ပတ်ဝန်းကျင် စောင့်ကြည့်လေလာမှု အစီအစဉ်အရ စောင့်ကြည့်ရမည့်စက်ရုံး ဖြစ်ပါသည်။ ကျန်ရှိသော မြေပေါ်ရေနမူနာယူသည့်နေရာ-၂ (SW-2) နှင့် မြေပေါ်ရေနမူနာယူသည့်နေရာ-၄ (SW-4) မှာ စွန်းထုတ်ပေါက်ရေးရှိရေးနှင့် စွန်းထုတ်ပေါက်ရေးနှင့် စွန်းထုတ်ပေါက်ရေးနှင့် စွန်းထုတ်ပေါက်ရေးနှင့် အခြေခံအချက်အလက်တို့အား နှိုင်းယူဉ်နိုင်ရန် ကိုးကားစောင့်ကြည့်လေလာမှု အဖြစ် နမူနာကောက်ယူခဲ့ပါသည်။ ထိုအပြင် မြေအောက်ရေနမူနာယူသည့်နေရာ-၁ (GW-1)အား ဘုန်းကြီးကျောင်း ပရဝဏ်အတွင်းရှိ ရေတွင်းအား ရည်ညွှန်းနိုင်ရန် စောင့်ကြည့်လေလာခဲ့သည်။ ရေအရည်အသွေး စောင့်ကြည့်လေလာမှုအတွက် နမူနာကောက်ယူသော နေရာများ၏ တည်နေရာများကို ပုံ ၁.၁-၁ တွင်ဖော်ပြထားပါသည်။



သိလပတ်အထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှုစက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်မှုအတွက်ရေအလည်အသွေးစောင့်ကြည့်လျေလာမှုအစီရင်ပါဘာ
(တစ်နှစ် နှစ်ကြိမ်၊ စောင့်ကြည့်လျေလာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)



ပုံ ၁.၁-၁ ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအတွက်နမ်နာကောက်ယူသောနေရာများ၏ တည်နေရာပြုပုံ



သီလဝါအထူးစီးပွားရေးဌာနအပိုင်း(က)ရှိစက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(တစ်နှစ် နှစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)

အခန်း J ရေအရည်အသွေးစောင့်ကြည့်လေ့လာခြင်း

J.၁ စောင့်ကြည့်လေ့လာသည့်အမျိုးအစား

ရေအရည်အသွေး စောင့်ကြည့်လေ့လာမှုအတွက် ရေနှစ်မှုနာကောက်ယူသောနေရာများနှင့် ရေအရည်အသွေး အမျိုးအစားများ(parameters)ကို ပတ်ဝန်းကျင်ထိခိုက်မှုဆန်းစစ်ခြင်းဆိုင်ရာ အစီအရင်ခံစာပါ ပတ်ဝန်းကျင်ဆိုင်ရာ စောင့်ကြည့်လေ့လာမှု အစီအစဉ်အား ခြိုင့်မိစေရန်အလိုက် ဆောင်ရွက်ထားပါသည်။

ရေအရည်အသွေးနှစ်မှုနာစစ်တမ်းကောက်ယူမှုအား နေရာခြောက်နေရာတွင် ဆောင်ရွက်ခဲ့ပါသည်။ ထိုနေရာ ခြောက်နေရာမှ ရေစီးဆင်းမှုတိုင်းတာခြင်းကို ရေစီးနှင့်တိုင်းကိုရိုက်ယူဖြင့် တိုင်းတာနှင့်သော နေရာလေးနေရာ (မြေပေါ်ရေနှစ်မှုနာယူသည့်နေရာ-၁ (SW-1))၊ မြေပေါ်ရေနှစ်မှုနာယူသည့်နေရာ-၄ (SW-4))၊ မြေပေါ်ရေနှစ်မှုနာယူသည့်နေရာ-၅ (SW-5)နှင့် မြေပေါ်ရေနှစ်မှုနာယူသည့်နေရာ-၆ (SW-6)) တို့တွင် တိုင်းတာခဲ့ပါသည်။ စောင့်ကြည့်လေ့လာသော ရေအရည်အသွေး အမျိုးအစားများ(parameters)နှင့် ရေနှစ်မှုနာကောက်ယူသော နေရာများကို ယေား J.၁-၁ တွင် အကျဉ်းချုပ် ဖော်ပြထားပါသည်။

ယေား J.၁-၁ စောင့်ကြည့်လေ့လာသည့်အမျိုးအစား

စဉ်	ရေအရည်အသွေး အမျိုးအစား (parameters)	မြေပေါ်ရေ နှစ်မှု ယူသည့် နေရာ-၁ (SW-1)	မြေပေါ်ရေ နှစ်မှု ယူသည့် နေရာ-၂ (SW-2)	မြေပေါ်ရေ နှစ်မှု ယူသည့် နေရာ-၄ (SW-4)	မြေပေါ်ရေ နှစ်မှု ယူသည့် နေရာ-၅ (SW-5)	မြေပေါ်ရေ နှစ်မှု ယူသည့် နေရာ-၆ (SW-6)	မြေအောက် ရေ နှစ်မှု ယူသည့် နေရာ-၈ (GW-1)	မှတ်ချက်
C	ရေအပ်ချိန် (Water Temperature)	○	○	○	○	○	○	ရေနှစ်မှုနာကောက်ယူသည့် နေရာတွင်တိုက်ရှိက်တိုင်းတာခြင်း
J	pH ခွဲ့ဖွဲ့ကိန်း (pH)	○	○	○	○	○	○	ရေနှစ်မှုနာကောက်ယူသည့် နေရာတွင် တိုက်ရှိက်တိုင်းတာခြင်း
R	ပျော်ဝင်အောက်စီဂျင် (DO)	○	○	○	○	○	○	ရေနှစ်မှုနာကောက်ယူသည့် နေရာတွင် တိုက်ရှိက်တိုင်းတာခြင်း
D	ပိုင်းပိုင်းဖြောက်စီဂျင် လိုအပ်ချက် (ဤ-ရက်) (BOD ₍₅₎)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
G	ဓာတ်နည်းဖြောက်စီဂျင် လိုအပ်ချက် (COD _(Cr))	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
N	နိုက်ထရိုဂျင်စုစုပေါင်း (Total Nitrogen)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
S	ဆိုင်းကြွားအနယ်များ (Suspended Solids)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
T	ကိုလိုဖောင်းစုစုပေါင်း	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း



သီလဝါအတူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုအဖွဲ့မြို့တော်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လျှောမှုအစီရင်ခံစာ
(တစ်နှစ် နှစ်ကြိမ်၊ စောင့်ကြည့်လျှောခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)

စဉ်	ရေအရည်အသွေး အမျိုးအစား (parameters)	မြေပေါ်ရေ နမ္မနာ ယူသည့် နေရာ-၁ (SW-1)	မြေပေါ်ရေ နမ္မနာ ယူသည့် နေရာ-၂ (SW-2)	မြေပေါ်ရေ နမ္မနာ ယူသည့် နေရာ-၄ (SW-4)	မြေပေါ်ရေ နမ္မနာ ယူသည့် နေရာ-၅ (SW-5)	မြေပေါ်ရေ နမ္မနာ ယူသည့် နေရာ-၆ (SW-6)	မြေအောက် ရေ နမ္မနာ ယူသည့် နေရာ-၁ (GW-1)	မှတ်ချက်
	(Total Coliform)							
၉	ဖော်စောရက်စုစုပေါင်း (Total Phosphorus)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၁၀	အရောင်(Color)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၁၁	အနှစ်(Odor)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၁၂	ဘွဲ့ (Zinc)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၁၃	အာဆီနှစ် (Arsenic)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၁၄	ခရိုミိုစ် (Chromium)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၁၅	ကမ်းဒီးယား (Cadmium)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၁၆	ဆယ်လီနှစ်ယား (Selenium)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၁၇	ပဲ (Lead)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၁၈	ကြော် (Copper)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၁၉	ဘေးယား (Barium)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၂၀	နှစ်ကယ် (Nickel)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၂၁	ဆိုင်ယာနှစ်ယား (Cyanide)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၂၂	ဆိုင်ယာနှစ်စုစုပေါင်း (Total Cyanide)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၂၃	လွှတ်လပ်ကရိုရင်း (Free Chlorine)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၂၄	ဆာလနိုင် (Sulphide)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၂၅	ဖော်မယ်ဒီဟိုက် (Formaldehyde)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၂၆	ဓါန်း (Phenols)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၂၇	ကြွေးကျော်သောကလို ရှင်းစုစုပေါင်း (Total Residual Chlorine)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၂၈	ခရိုမိုစ်ယား (Hexavalent Chromium)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၂၉	အမိုးနှီးယား (Ammonia)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၃၀	ဖလူးအိုဂျိုက် (Fluoride)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း



သီလဝါအထူးစီးပွားရေးဦးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုဇုန်ဖြိုးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(တစ်နှစ် နှစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)

စဉ်	ရေအရည်အသွေး အမျိုးအစား (parameters)	မြေပေါ်ရေ နှမါးသည့် နေရာ-၁ (SW-1)	မြေပေါ်ရေ နှမါးသည့် နေရာ-၂ (SW-2)	မြေပေါ်ရေ နှမါးသည့် နေရာ-၄ (SW-4)	မြေပေါ်ရေ နှမါးသည့် နေရာ-၅ (SW-5)	မြေပေါ်ရေ နှမါးသည့် နေရာ-၆ (SW-6)	မြေအောက် ရေ နှမါးသည့် နေရာ-၁ (GW-1)	မှတ်ချက်
၃၁	ရွှေ (Silver)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၃၂	ဆီနှင့်အမဲဆီ (Oil and Grease)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၃၃	ပျော်ဝင်အနည်းစုစုပေါင်း (Total Dissolved Solids)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၃၄	သံဓာတ် (Iron)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၃၅	မြို့ဒေသ (Mercury)	○	○	○	○	○	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၃၆	ဝစ်းကိုက်ရောဂါကိုဖြစ် စေသော ကိုလိုဖောင်းဘက်တိုးရီး ယား (Escherichia Coli) (ကိုယ်တိုင်စောင့်ကြည့် လေ့လာခြင်း)	○	-	-	○	-	○	ဓာတ်ခွဲစမ်းသပ်ခြင်း
၃၇	ရေစီးဆင်းနှင့်	○	-	○	○	○	-	ရေနှမါးနာကာက်ယူသည့် နေရာတွင် တိုက်ရှိက်တိုင်းတာခြင်း

မှရင်း။ မြန်မာနိုင်ငြခံအင်တာနှုပ်နယ်လီမိတ်



J-J ရေနမူနာယူသည့်နေရာများ၏တည်နေရာနှင့်အချက်အလက်များဖော်ပြချက်

ရေနမူနာယူသည့်နေရာများကို ဧယား J-J-၁ တွင် ဖော်ပြထားပါသည်။ ရေနမူနာယူသည့်နေရာ တစ်ခုစီတွင် စစ်တမ်းကောက်ယူခဲ့သည့် မှတ်တမ်းပုံများကို နောက်ဆက်တွဲ-၁ တွင်ဖော်ပြထားသည်။

ဧယား J-J-၁ ရေနမူနာကောက်ယူသည့်နေရာများ

စဉ်	တည်နေရာ	အသေးစိတ်အချက်အလက်
၁	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၁ (SW-1)	ကိုဥုံးပို့နိုင် - မြောက်လွှားတွေ့ - ၁၆° ၄၀' ၁၉.၅"၊ အရှေ့လောင်ဂျီတွေ့ - ၉၆°၁၆' ၃၉.၈"
J	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-J (SW-2)	ကိုဥုံးပို့နိုင် - မြောက်လွှားတွေ့ - ၁၆° ၄၀' ၂၀.၆"၊ အရှေ့လောင်ဂျီတွေ့ - ၉၆°၁၇' ၁၈.၀"
၂	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၄ (SW-4)	ကိုဥုံးပို့နိုင် - မြောက်လွှားတွေ့ - ၁၆° ၃၉' ၄၂.၄"၊ အရှေ့လောင်ဂျီတွေ့ - ၉၆°၁၆' ၂၇.၄"
၄	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၅ (SW-5)	ကိုဥုံးပို့နိုင် - မြောက်လွှားတွေ့ - ၁၆° ၄၀' ၁၀.၇"၊ အရှေ့လောင်ဂျီတွေ့ - ၉၆°၁၆' ၂၂.၆"
၅	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၆ (SW-6)	ကိုဥုံးပို့နိုင် - မြောက်လွှားတွေ့ - ၁၆° ၄၀' ၂၇.၃"၊ အရှေ့လောင်ဂျီတွေ့ - ၉၆°၁၆' ၃၀.၆"
၆	မြေအောက်ရေ နမူနာယူသည့် နေရာ-၁ (GW-1)	ကိုဥုံးပို့နိုင် - မြောက်လွှားတွေ့ - ၁၆° ၄၀' ၁၉.၉"၊ အရှေ့လောင်ဂျီတွေ့ - ၉၆°၁၆' ၃၄.၀"

မူရင်း၊ မြှင့်မာစိအဲအင်ဘာနေရှင်နယ်လိမ့်တက်

မြေပေါ်ရေနမူနာယူသည့်နေရာ-၁ (SW-1)

မြေပေါ်ရေနမူနာယူသည့်နေရာ-၁ (SW-1) အား မိုးကြီးစွမ်းကျောင်းတိုက်၏ အရှေ့အရပ်တွင်တည်ရှိသော ရေထိန်းကန်၏ ရေထွက်ပေါက်မှ ကောက်ယူခြင်း ဖြစ်ပါသည်။ ငါးသည် မြေပေါ်ရေနမူနာယူသည့်နေရာ-၆ (SW-6)၏ မြစ်အောက်ပိုင်း ၅၃၀ မီတာ အကွာတွင် တည်ရှိပါသည်။ အဆိုပါရေနတ်မြောင်းသည် မြောက်မှ တောင်သို့ စီးဆင်းပြီး ရွှေပျောက်ချောင်းအတွင်း စီးဝင်သွားပါသည်။ အထက်ပါ စောင့်ကြည့်လေ့လာသည့်နေရာ၏ ရေထွက်အရည်အသွေးသည် မြစ်အောက်ပိုင်းမှ ဒီရေအတက်အကျော် လွှမ်းမိုးမှုများရှိနေပါသည်။ ထိုအပြင်ကျောင်းတိုက်အတွင်းမှ စွန့်ထုတ်ရေတစ်စိတ်ပိုင်းသည်လည်း သီလဝါအထူးစီးပွားရေးဇုန်၏ ရေမြောင်းအတွင်းသို့ရောက်ရှိပြီး ရေထိန်းကန်အတွင်းသို့စီးဝင်မှုရှိကြောင်း ယူဆရပါသည်။

မြေပေါ်ရေနမူနာယူသည့်နေရာ-J (SW-2) (ရည်ညွှန်းအမှတ်)

မြေပေါ်ရေနမူနာယူသည့်နေရာ-J (SW-2) အား ရွှေပျောက်ချောင်း၏ အထက်ပိုင်းတွင် ကောက်ယူခဲ့ခြင်းဖြစ်ပါသည်။ အဆိုပါ အမှတ်သည် ဇုန်အပိုင်း(က)ရေ့ယာ၏ အရှေ့တောင်ဘက်၊ ဒုက္ခ-သီလဝါလမ်း၏ တောင်ဘက်တွင် တည်ရှိပါသည်။ အနောက်တောင်တွင် ဇုန်အပိုင်း(ခ) နှင့် အရှေ့ဘက်တွင် ပြည်တွင်းစက်မှုဇုန်တိုက် အသီးသီးဝန်းရုံလျက်ရှိသည်။



သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က) ရှိစက်မှုနှင့်ဖြီးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(တစ်နှစ် နှစ်ကြိမ် စောင့်ကြည့်လေ့လာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)

မြေပေါ်ရေနမူနာယူသည့်နေရာ-၄ (SW-4) (ရည်ညွှန်းအမှတ်)

ပြည်တွင်းစက်မှုနှစ်၊ နှင့် ရှိစက်မှုပိုင်း(က) ရှိစက်မှုပိုင်း(ခ)ရှိ ဆောက်လုပ်ရေးလုပ်ငန်းခွင်များမှ စွန့်ထဲတဲ့က်သောရေများ ပေါင်းစည်းရောနောသွားသောနေရာ၊ ရွှေပျောက်ချောင်း၏ အောက်ပိုင်းတွင် မြေပေါ်ရေ နမူနာယူသည့်နေရာ-၄ (SW-4) တွင်ကောက်ယူခဲ့ခြင်းဖြစ်သည်။ ရွှေပျောက်ချောင်းသည် အရှေ့မှ အနောက်သို့ စီးဆင်းပြီး ရန်ကုန်မြှေစိအတွင်းသို့စီးဝင်သည်။ မြေပေါ်ရေနမူနာယူသည့်နေရာ-၄ (SW-4) သည် မြေပေါ်ရေနမူနာယူသည့်နေရာ-၂ (SW-2)၏ ချောင်းအောက်ပိုင်း ၂.၁၅ ကီလိမ့်တာအကွာတွင် တည်ရှိပါသည်။ အဆိုပါ ရေနမူနာကောက်ယူသည့်နေရာသည် ရှိစက်မှုပိုင်း(က) ဇုံယာ၏ အနောက်တောင်ဘက်တွင်တည်ရှိပြီး ဒုက္ခ-သီလဝါလမ်း၏ တောင်ဘက်တွင်တည်ရှိပါသည်။ ပတ်ဝန်းကျင်အနီးအနားတွင် ရှိစက်မှုပိုင်း(ခ) နှင့် အရှေ့ဘက်တွင် ပြည်တွင်းစက်မှုနှစ်တို့ အသီးသီးတည်ရှိပါသည်။

မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅ (SW-5)

မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅ (SW-5) အား သီလဝါအထူးစီးပွားရေးနှင့်၏ ပင်မဂိတ်ပေါက်အနီးရှိ ရေထိန်းတူးမြောင်းမှ ကောက်ယူခဲ့သည်။ အဆိုပါ တူးမြောင်းအတွင်း စုဆောင်းထားသော ရေအများစုမှာ မိုးရေ နှင့် အနီးအနားတွင် အပင်များရေလောင်းခြင်းမှ ထွက်၍လာသော ရေများ ဖြစ်ပါသည်။ အဆိုပါတူးမြောင်းသည်လည်း ရွှေပျောက်ချောင်းဖြင့် ဆက်သွယ်ထားပါသည်။ မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅ (SW-5) ၏ရေအရည်အသွေးသည် ချောင်းအောက်ဘက်မှ ဒီရေအတက်အကျ၏ လွမ်းမိုးမှုများစွာ ရှိနိုင်ပါသည်။

မြေပေါ်ရေနမူနာယူသည့်နေရာ-၆ (SW-6)

မြေပေါ်ရေနမူနာယူသည့်နေရာ-၆ (SW-6) အား မိုးကြိုးစွမ်းကျောင်းတိုက်ပရာဝဏ်အတွင်း နှင့် ရေထိန်းကန် မြေပေါ်ရေနမူနာယူသည့်နေရာ-၁(SW-1)၏ မြောက်ဘက်ရှိ ပင်မစွန့်ထဲတဲ့ရေသန့်စင်စက်ရုံ၏ ထွက်ပေါက်မှ ကောက်ယူခြင်းဖြစ်ပါသည်။ ထိုသန့်စင်ပြီးသောစွန့်ထဲတဲ့ရေအား ရေထိန်းကန်အတွင်းသို့ စီးဝင်စေသည်။ ငွေးရေထွက်ပေါက်သည် မြေပေါ်ရေနမူနာယူသည့်နေရာ-၁ (SW-1)၏ အထက်ဘက် ၅၃၀ မီတာခန့် အကွာအဝေးတွင်ရှိပါသည်။

မြေအောက်ရေနမူနာယူသည့်နေရာ-၁(GW-1) (မူလတည်ရှိနေသောရေတွင်းအားရည်ညွှန်းခြင်း)

မြေအောက်ရေနမူနာယူသည့်နေရာ-၁ (GW-1)အား တူးဖော်ထားသော ရေတွင်းမှ ကောက်ယူခဲ့ပါသည်။ အဆိုပါ ရေနမူနာကောက်ယူသည့် နေရာသည် မိုးကြိုးစွမ်းကျောင်းတိုက် ပရာဝဏ်အတွင်းတွင် တည်ရှိပါသည်။ အနောက်ဘက်တွင် ရှိစက်မှုပိုင်း (က)၊ အရှေ့ဘက်တွင် ရေထိန်းကန် နှင့် တောင်ဘက်တွင် ဒုက္ခ-သီလဝါလမ်းတို့အသီးသီးရှိပါသည်။



သိလဝါအထူးစီးပွားရေးဇွန်အပိုင်း(က)ရှိစက်မှုဇွန်ဖြုံးတိုးတက်မှုအတွက်ရေအရည်အသွေးပေါင်းကြည့်လေ့လာမှုအစီရင်ခံစာ
(တစ်နှစ် နှစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)

J.၃ စောင့်ကြည့်လေ့လာသည့်နည်းလမ်း

ရေနမူနာများကို ကောက်ယူပြီး သန္တစင်ထားသောဖန်ပုလင်းညီများဖြင့် သိမ်းဆည်းပြီး ယော် J.၃-၁ တွင် ဖော်ပြထားသော နည်းလမ်းများဖြင့် ဓာတ်ခွဲခန်း၌ စစ်ဆေးပါသည်။ ရေနမူနာများကို ရေခဲပုံးများဖြင့် J-၄ ဒီဂရိ ဆဲလ်စီးရပ် တွင်သိမ်းဆည်းထားပြီး ဓာတ်ခွဲခန်းသို့ ပို့ဆောင်ပါသည်။ တိုင်းတာသည့် ရေအရည်အသွေး အမျိုးအစားများ၏ ရေအပူပျိန်၊ ချဉ်ဖန်ကိန်း နှင့် ပျော်ဝင်အောက်စီဂျင်တို့အား ရေအရည်အသွေးတိုင်းတာသောစက်ကိရိယာ (Horiba U-52)ကို အသုံးပြု၍ ရေနမူနာကောက်ယူသည့်နေရာ၌ပင် တိုက်ရှိက် တိုင်းတာခဲ့ပါသည်။ ထိုအပြင် ရေစီးဆင်းမှုနှင့်နှုန်းတိုင်းကိရိယာ (JFE Digital Current Meter)ဖြင့် ရေနမူနာကောက်ယူသည့်နေရာ၌ တိုင်းတာ ခဲ့ပါသည်။

ယော် J.၃-၁ ရေအရည်အသွေးစစ်ဆေးသည့် နည်းလမ်းများ

စဉ်	အမျိုးအစားများ	နည်းလမ်း
၁	ရေအပူချိန် (Temperature)	Instrument Analysis Method (Horiba, U-52, Multi Water Quality Checker)
၂	ချဉ်ဖန်ကိန်း (pH)	Instrument Analysis Method (Horiba, U-52, Multi Water Quality Checker)
၃	ဆိုင်းကြွာအနယ် (Suspended Solids)	APHA 2540 D (Dry at 103-105°C Method)
၄	ပျော်ဝင်အောက်စီဂျင် (Dissolved Oxygen)	Instrument Analysis Method (Horiba, U-52, Multi Water Quality Checker)
၅	မိုဝင်ညှိုးပြုခြဲရန် အောက်စီဂျင် လိုအပ်ချက် (ဤရာက်) (BOD ₅)	APHA 5210 B (5 Days BOD Test)
၆	ဓာတုနည်းဖြင့် ဖြို့ခွဲရန် အောက်စီဂျင် လိုအပ်ချက် (COD _{C₂})	APHA 5220D (Close Reflux Colorimetric Method)
၇	ကိုလိုဖောင်းစုစုပေါင်း (Total Coliform)	APHA 9221B (Standard Total Coliform Fermentation Technique)
၈	နိုက်ထရိုဂျင်စုစုပေါင်း (Total Nitrogen)	HACH Method 10072 (TNT Persulfate Digestion Method)
၉	ဓာတုစောက်စုစုပေါင်း (Total Phosphorus)	APHA 4500-P E (Ascorbic Acid Method)
၁၀	အရောင် (Color)	APHA 2120C (Spectrophotometric Method)
၁၁	အနီး (Odor)	APHA 2150 B (Threshold Odor Test)
၁၂	ဆီနှင့် အမဲဆီ (Oil and Grease)	APHA 5520B (Partition-Gravimetric Method)
၁၃	ပြဒါးဓာတ် (Mercury)	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
၁၄	ဘွဲ့ (Zinc)	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
၁၅	အာဆီနှစ် (Arsenic)	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
၁၆	ခရီးမြို့ယမ် (Chromium)	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
၁၇	ကက်ဒို့ယမ် (Cadmium)	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
၁၈	ဆယ်လီနှစ်ယမ် (Selenium)	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)



သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(တစ်နှစ် နှစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)

စဉ်	အမျိုးအစားများ	နည်းလမ်း
၁၉	ပဲ (Lead)	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
၂၀	ကြေးနီ (Copper)	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
၂၁	ဗျာရှိယမ် (Barium)	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
၂၂	နှစ်ကယ် (Nickel)	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
၂၃	ဆိုင်ယာနိုဒ် (Cyanide)	HACH 8027 (Pyridine-Pyrazalone Method)
၂၄	ဆိုင်ယာနိုဒ်စုစုပေါင်း (Total Cyanide)	Distillation process: APHA 4500-CN-C. Total Cyanide after Distillation, Determine cyanide Concentration Process: HACH 8027 (Pyridine – Pyrazalone Method)
၂၅	လွှာတ်လင်ကလိုဂုဏ် (Free Chlorine)	APHA 4500-CL G (DPD Colorimetric Method)
၂၆	ဆာလစိုဒ် (Sulphide)	HACH 8131 (USEPA Methylene Blue Method)
၂၇	ဖော်မယ်ဒီဟိုက် (Formaldehyde)	HACH 8110 (MBTH Method)
၂၈	ဖိန္ဓာ (Phenols)	USEPA Method 420.1 (Phenolics (Spectrophotometric, Manual 4 AAP With Distillation))
၂၉	သံခာဝ် (Iron)	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
၃၀	ပျော်ဝင်အနည်းစုစုပေါင်း (Total Dissolved Solids)	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)
၃၁	ကြွင်းကျွန်းသောကလိုဂုဏ်စုစုပေါင်း (Total Residual Chlorine)	APHA 4500-CL G (DPD Colorimetric Method)
၃၂	ခရှိမိယမ် (Chromium Hexavalent)	ISO 11083:1994 (Determination of chromium (VI) Spectrometric method using 1,5-diphenylcarbazide)
၃၃	အမိုးနီးယား (Ammonia)	HACH Method 10205 (Silicylate TNT Plus Method)
၃၄	ဖလူအုံရှိုက် (Fluoride)	APHA 4110 B (Ion Chromatography with Chemical Suppression of Eluent Conductivity)
၃၅	ရွှေ (Silver)	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)
၃၆	ဝမ်းကိုက်ရောဂါကိုဖြစ်စေသော ဘက်တီးရီးယား (Escherichia Coli)	APHA 9221 F (Escherichia Coli Procedure Using Fluorogenic Substrate)
၃၇	စီးဆင်းနှုန်း (Flow Rate)	Detection of Electromagnetic Elements (Real-time measurement by AEM 213-D Digital Current Meters)

မူရင်း။ မြန်မာစီးအင်တာနေရာင်နယ်လီမိတ်

သီလဝါအထူးစီးပွားရေးဇုန်အပိုင်း(က)ရှိစက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(တစ်နှစ် နှစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)

J.၄ စောင့်ကြည့်လေ့လာသည့်ကာလ

ရေအရည်အသွေးနှင့် ရေစီးဆင်းမှုနှစ်းအား ဒီဇင်ဘာလ ၁၄ ရက်နေ့ ၂၀၂၁ ခုနှစ်တွင် ဆောင်ရွက်ခဲ့ပြီး ဒီရေအတက်အကျကြောင့် ဖြစ်ပေါ်လာနိုင်သော သက်ရောက်မှုများကိုရှောင်ရှားနိုင်ရန် အောက်ပါ ယေား J.၄-၁ အတိုင်း ရေနမူနာကောက်ယူခဲ့သည်။ မြန်မာနိုင်ငံ၊ ရန်ကုန်မြို့၏ ဒီဇင်ဘာလ ၁၄ ရက်နေ့ ၂၀၂၁ ခုနှစ် အတွက်ဒီရေ မှတ်တမ်းကို ယေား J.၄-၂ တွင်ဖော်ပြထားပါသည်။

ယေား J.၄-၁ နေရာတစ်ခုချင်းစီအတွက် နမူနာကောက်ယူသည့်အချိန်

စဉ်	နမူနာကောက်ယူသည့်နေရာ	နမူနာကောက်ယူသည့်အချိန်
၁	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၁ (SW-1)	ဒီဇင်ဘာလ ၁၄ ရက်နေ့ ၂၀၂၁ ခုနှစ် (၁၀ နာရီ : ၄၉ မိန့်)
၂	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၂ (SW-2)	ဒီဇင်ဘာလ ၁၄ ရက်နေ့ ၂၀၂၁ ခုနှစ် (၁၈ နာရီ : ၅၄ မိန့်)
၃	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၄ (SW-4)	ဒီဇင်ဘာလ ၁၄ ရက်နေ့ ၂၀၂၁ ခုနှစ် (၁၈ နာရီ : ၀၂ မိန့်)
၄	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၅ (SW-5)	ဒီဇင်ဘာလ ၁၄ ရက်နေ့ ၂၀၂၁ ခုနှစ် (၁၉ နာရီ : ၄၇ မိန့်)
၅	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၆ (SW-6)	ဒီဇင်ဘာလ ၁၄ ရက်နေ့ ၂၀၂၁ ခုနှစ် (၁၀ နာရီ : ၁၉ မိန့်)
၆	မြေအောက်ရေ နမူနာယူသည့် နေရာ-၁ (GW-1)	ဒီဇင်ဘာလ ၁၄ ရက်နေ့ ၂၀၂၁ ခုနှစ် (၁၂ နာရီ : ၀၃ မိန့်)

မူရင်း၊ မြန်မာနိုင်အင်တာနှင့်နယ်လီလိတ်

ယေား J.၄-၂ မြန်မာနိုင်ငံ၊ ရန်ကုန်မြို့၏ ဒီရေမှတ်တမ်း

ရက်စွဲ	အချိန်	အမြဲ့	ဒီရေအခြေအနေ
ဒီဇင်ဘာလ ၁၄ ရက်နေ့ ၂၀၂၁ ခုနှစ်	၀၀:၁၀	၄.၃၄	ဒီရေအတက်
	၀၈:၂၅	၁.၁၁	ဒီရေအကျ
	၁၃:၄၄	၄.၄၅	ဒီရေအတက်
	၂၀:၂၅	၁.၀၉	ဒီရေအကျ

မူရင်း၊ မြန်မာနိုင်အင်တာနှင့်နယ်လီလိတ်

J-၅ စောင့်ကြည့်လေ့လာမှုရလဒ်များ

ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုရလဒ်များကို ယေား J-၁ တွင် ဖော်ပြထားသည်။ ဓာတ်ခွဲခန်းဆန်းစစ်မှု ရလဒ်များကို နောက်ဆက်တွဲ-၂ တွင်ဖော်ပြထားသည်။ ရလဒ်များကို ပတ်ဝန်းကျင်ထိခိုက်မှု ဆန်းစစ်ခြင်း အစီအရင်ခံစာတွင်ပါရှိသည့် ရေအရည်အသွေးရည်မှန်းတန်ဖိုးများနှင့် နှိုင်းယဉ်ထားပါသည်။

J-၅.၁ သီလဝါအထူးစီးပွားရေးနှင့်ရှိစက်မှုဇုန်၏ စွမ်းထုတ်ရေသနစင်စက်ရုံးတွက်ပေါက်နှင့် ချောင်းအတွင်းသို့ မဖွန့်ထုတ်ခင်နေရာရှိ ရေအရည်အသွေးရလဒ်များ

ရည်မှန်းတန်ဖိုးများဖြင့် နှိုင်းယဉ်ရာတွင် ဆိုင်းကြွာအနယ်၊ ကိုလိုဖောင်းစုစုပေါင်း၊ လွတ်လပ်ကလိုရင်း နှင့် ကြွင်းကျော်သောကလိုရင်း စုစုပေါင်း တို့မှာ ရည်မှန်းတန်ဖိုးများထက် ကျော်လွန်နေကြောင်းတွေ့ရှုပါသည်။

ဆိုင်းကြွာအနယ် ရလဒ်အနေဖြင့် ဗဟိုစွန့်ထုတ်ရေ သနစင်စက်ရုံး၏ ထွက်ပေါက် မြေပေါ်ရေ နမူနာ ယူသည့်နေရာ-၆ (SW-6) မှရလဒ်သည် ရည်မှန်းထားသော တန်ဖိုးအတွင်းရှုံးကြောင်း တွေ့ရှုရသည်။ ထို့ကြောင့် စက်ရုံးတစ်ရုံချင်းစီမှ ထွက်ရှိလာသော စွန့်ထုတ်ရေများအား ပင်မဖွန့်ထုတ်ရေ သနစင်စက်ရုံးမှ ကောင်းမွန်စွာ သနစင်ထားသည်ဟု ဆိုလိုနိုင်ပါသည်။ အခြားတစ်ဖက်တွင်လည်း စောင့်ကြည့်လေ့လာနေသော ရေထိန်းကန် မြေပေါ်ရေ နမူနာယူသည့်နေရာ-၁ (SW-1) မှ ရလဒ်များသည် ရည်မှန်းတန်ဖိုးထက် ကျော်လွန်နေကြောင်း တွေ့ရှုရသည်။ ဖြစ်နိုင်ချေ အလားအလာရှိသည့် အကြောင်းအရင်းမှာ ဇုန်အပိုင်း(က)ရှိ မြေလွတ်များမှ မြေမျက်နှာပြင် စီးဆင်းရေ များကြောင့် ဖြစ်နိုင်ပါသည်။

ကိုလိုဖောင်းစုစုပေါင်း ရလဒ်အနေဖြင့် ဗဟိုစွန့်ထုတ်ရေသနစင်စက်ရုံး၏ ထွက်ပေါက် မြေပေါ်ရေနမူနာယူသည့်နေရာ-၆ (SW-6) မှရလဒ်သည် ရည်မှန်းထားသော တန်ဖိုးအတွင်းရှုံးကြောင်း တွေ့ရှုရသည်။ ထို့ကြောင့် စက်ရုံးတစ်ရုံချင်းစီမှ စွန့်ထုတ်ရေများအား ပင်မဖွန့်ထုတ်ရေ သနစင်စက်ရုံးမှ ကောင်းမွန်စွာ သနစင်ထားသည်ဟု ဆိုလိုနိုင်ပါသည်။ အခြားတစ်ဖက်တွင် စောင့်ကြည့်လေ့လာသော နေရာများဖြစ်သည့် ရေထိန်းတူးမြေပေါ်ရေ မြေပေါ်ရေ နမူနာယူသည့်နေရာ-၅ (SW-5)တွင် ရလဒ်များမှာရည်မှန်းတန်ဖိုးထက် ကျော်လွန်နေကြောင်းတွေ့ရှုပါသည်။ ဖြစ်နိုင်ချေအလားအလာရှိသည့် အကြောင်းရင်းများမှာ ရေထိန်းတူးမြေပေါ်ရေ၏ အတွင်းနှင့်အပြင်တလျောက်တွင် အပင်များနှင့်ငုံက်များ၊ တိရစ္ဆာန်ပေါ်ရေများကြောင့် ဇုန်အပိုင်း(က)၏ ဧရိယာတွင် သဘာဝအလျောက် ဘက်တီးရှိယားများ ရှိနေသောကြောင်းတွေ့ရှုပါသည်။

ကိုလိုဖောင်းစုစုပေါင်း၏ဖြစ်တည်မှုတွင် သဘာဝအလျောက်ဘက်တီးရှိယားများ ပါဝင်ပြီး စုစုပေါင်း ကိုလိုဖောင်းသည် လူတို့၏ကျော်းမာရေးကို တိုက်ရှိက်ထိခိုက်မှုမရှိသော်ငြားလည်း ကိုလိုဖောင်းဘက်တီးရှိယားများ၏ ကျော်းမာရေး အပေါ်သက်ရောက်မှုကိုဖော်ထုတ်ရန် ဝမ်းကိုက်ရောဂါကိုဖြစ်စေသော ကိုလိုဖောင်းဘက်တီးရှိယား (E. Coli) အားသုံးသပ်ခြင်းအတွက် ကိုယ်တိုင်စောင့်ကြည့် လေ့လာမှုကို ပြုလုပ်ခဲ့ပါသည်။ ဤဝမ်းကိုက်ရောဂါကိုဖြစ်စေသော ကိုလိုဖောင်းဘက်တီးရှိယား(E. Coli) ရလဒ်အရ တန်ဖိုးများအားလုံးသည် ရည်မှန်းတန်ဖိုးများအောက် နည်းပါးကြောင်းတွေ့ရှုပါသည်။ ထို့ကြောင့် ရေထိန်းတူးမြေပေါ်ရေ မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅ (SW-5)၏ စောင့်ကြည့်လေ့လာသော နေရာများတွင် ကိုလိုဖောင်းစုစုပေါင်းသည် ရည်မှန်းတန်ဖိုးထက်များနေသော်လည်း လူ၏ကျော်းမာရေးကို သိသာထင်ရှားစွာ သက်ရောက်မှုမရှိနိုင်ကြောင်း သတ်မှတ်နိုင်ပါသည်။



သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(တစ်နှစ် နှစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)

လွတ်လပ်ကလိုရင်း နှင့် ကြွင်းကျေန်သောကလိုရင်းစုစုပေါင်း ရလဒ်အနေဖြင့် ဗဟိုစွန်းထုတ်ရေ သန္တစင်စက်ရုံ၏ ထွက်ပေါက် မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၆ (SW-6) မှရလဒ် ၁.၁ မီလီဂရမ်/လီတာ နှင့် ၁.၆ မီလီဂရမ်/လီတာ သည် ရည်မှန်းထားသော တန်ဖိုးထက် ကျော်လွန်နေကြောင်းတွေ့ရသည်။ ရည်မှန်းထားသော တန်ဖိုးထက် ကျော်လွန်နေခြင်းမှာ စက်ရုံမှုမစွန်းထုတ်ခင် စွန်းထုတ်ရေများတွင် ကလိုရင်းများကျေန်ရှိနေခြင်းကြောင့် ဖြစ်နိုင်သည်။ သို့သော်လည်း ရှိန်အပိုင်း(က)၏ နောက်ဆုံး စွန်းထုတ်ရာနေရာတစ်ခွဲဖြစ်သော မြေပေါ်ရေနမူနာယူသည့် နေရာ-၁ (SW-1)၏ လွတ်လပ်ကလိုရင်းသည် ရည်မှန်းတန်ဖိုး (၁.၂ မီလီဂရမ်/လီတာ) နှင့် ကြွင်းကျေန်သောကလိုရင်းစုစုပေါင်းသည် ရည်မှန်းတန်ဖိုး (၀.၂ မီလီဂရမ်/လီတာ) အောက် နည်းပါးနေကြောင်း တွေ့ရှုရပါသည်။ ထို့ကြောင့် ရရှိထားသော ရလဒ်များသည် လူ၏ကျေန်းမာရေးနှင့် သက်ရှိပတ်ဝန်းကျင်တွင် သိသာထင်ရှားသောထိခိုက်မှုမရှိနိုင်ပေါ်ကြောင်း သတ်မှတ်နိုင်ပါသည်။

ယေား J.၅-၁ ရေထွက်ပေါက်နှင့်ရေထိန်းဂိတ်အားလုံး၏ ရေထွက်အရည်အသွေး စောင့်ကြည့်လေ့လာမှု ရလဒ်များ

စဉ်	ရေအရည်အသွေး အမျိုးအစား (parameters)	ယူနစ်	မြေပေါ်ရေနမူနာယူသည့် နေရာ-၁ (SW-1)	မြေပေါ်ရေနမူနာယူသည့် နေရာ-၅ (SW-5)	မြေပေါ်ရေနမူနာယူသည့် နေရာ-၆ (SW-6)	ရည်မှန်းတန်ဖိုး (ကိုယ်တိုင်စောင့်ကြည့်လေ့လာခြင်း အတွက် ရည့်အွန်းတန်ဖိုး)
၁	ရေအပူခံ့စ် (water temperature)	°C	J2	JJ	JG	၄၃၅
၂	ချဉ်ဖန်ကိုင်း (pH)	-	၉.၀	၇.၆	၆.၅	၆-၉
၃	ဆိုင်းကြအနယ် (suspended solid)	mg/L	၁၀၀	J၈	၁၄	၅၀
၄	ပျော်ဝင်အောက်စိုက် (Dissolved Oxygen)	mg/L	၁၀.၉၂	၆.၁၇	၅.၄၈	-
၅	မီးနည်းဖြိုးဖြော်ရန် အောက်စိုက် လိုအပ်ချက် (၅-ရက်) (BOD ₅)	mg/L	၈.၀၅	၃.၉၁	၃.၈၄	၂၀
၆	ဓာတ်နည်းဖြိုးဖြော်ရန် အောက်စိုက် လိုအပ်ချက် (COD _{Cr})	mg/L	၃၉.၂	၁၉.၂	၂၀.၂	၃၂၅
၇	ကိုလိုဖောင်းစုစုပေါင်း (Total Coliform)	MPN/100ml	J၄၀	၁၆၀၀	<၁.၈	၄၀၀
၈	နိုက်ထရိုဂျင်စုစုပေါင်း (Total Nitrogen)	mg/L	၄.၆	၁.၇	၁.၉	၈၀
၉	ဖော်စောရက်စုစုပေါင်း (Total Phosphorus)	mg/L	-	-	-	J
၁၀	အရောင် (Color)	TCU (True Color Unit)	၉.၄၁	၇.၄၆	၅.၁၃	၁၅၄
၁၁	အနဲ့ (Odor)	TON	၁	၁	၁	-



သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုနှင့်ဖြိုးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(တစ်နှစ် နှစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာမြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)

စဉ်	ရေအရည်အသွေး အချိုးအစား (parameters)	ယူနစ်	မြေပေါ်ရေနှစ်မှု နာယူသည့် နေရာ-၁ (SW-1)	မြေပေါ်ရေနှစ်မှု နာယူသည့် နေရာ-၅ (SW-5)	မြေပေါ်ရေနှစ်မှု နာယူသည့် နေရာ-၆ (SW-6)	ရည်မှန်းတန်ဖိုး (ကိုယ်တိုင်စောင့်ကြည့် လေ့လာမြင်း အတွက် ရည်အောင်းတန်ဖိုး)
		(Threshold Odor Number)				
၁၂	ဆီနှင့် အမဲဆီ (Oil and Grease)	mg/L	< ၃.၁	< ၃.၁	< ၃.၁	၁၀
၁၃	မြှေခါးဓာတ် (Mercury)	mg/L	≤ ၀.၀၀၂	≤ ၀.၀၀၂	≤ ၀.၀၀၂	၀.၀၀၅
၁၄	ဘွဲ့ (Zinc)	mg/L	၀.၀၃၄	၀.၀၀၆	၀.၀၀၆	၂
၁၅	အာဆီနှစ် (Arsenic)	mg/L	≤ ၀.၀၀၀	≤ ၀.၀၀၀	≤ ၀.၀၀၀	၀.၁
၁၆	ခရိုပိုယ် (Chromium)	mg/L	≤ ၀.၀၀၂	≤ ၀.၀၀၂	≤ ၀.၀၀၂	၀.၅
၁၇	ကမ်းဒိုပ်ယာ (Cadmium)	mg/L	≤ ၀.၀၀၂	≤ ၀.၀၀၂	≤ ၀.၀၀၂	၀.၀၃
၁၈	ဆယ်လိန်ယာ (Selenium)	mg/L	≤ ၀.၀၀၀	≤ ၀.၀၀၀	≤ ၀.၀၀၀	၀.၀၂
၁၉	ခဲ (Lead)	mg/L	≤ ၀.၀၀၂	≤ ၀.၀၀၂	≤ ၀.၀၀၂	၀.၁
၂၀	ကြေးနှံ (Copper)	mg/L	≤ ၀.၀၀၂	≤ ၀.၀၀၂	≤ ၀.၀၀၂	၀.၅
၂၁	ပေရိယာ (Barium)	mg/L	၀.၀၀၈	၀.၀၂၂	၀.၀၀၄	၁
၂၂	နှစ်ကုပ် (Nickel)	mg/L	≤ ၀.၀၀၂	≤ ၀.၀၀၂	≤ ၀.၀၀၂	၀.၂
၂၃	ဆိုင်ယာနှိမ် (Cyanide)	mg/L	< ၀.၀၀၂	< ၀.၀၀၂	< ၀.၀၀၂	၀.၁
၂၄	ဆိုင်ယာနှိမ်စုစုပေါင်း (Total Cyanide)	mg/L	၀.၀၀၉	၀.၀၀၃	၀.၀၀၅	၁
၂၅	လွတ်လပ်ကလိုဂုဏ် (Free Chlorine)	mg/L	< ၀.၁	< ၀.၁	၀.၁	၁
၂၆	ဆာလိုင် (Sulphide)	mg/L	၀.၁၅၁	၀.၀၄၄	၀.၀၀၆	၁
၂၇	ဖော်မယ်ဒီဟိုက် (Formaldehyde)	mg/L	၀.၀၂၅	၀.၀၂၇	၀.၀၀၉	၁
၂၈	ဖိနော (Phenols)	mg/L	၀.၀၀၈	၀.၀၀၇	< ၀.၀၀၂	၀.၅
၂၉	သံဓာတ် (Iron)	mg/L	၀.၂၄၆	၀.၈၀၂	၀.၂၀၄	၂၅
၃၀	ပျော်ဝင်အနုလုစုပေါင်း (Total Dissolved Solids)	mg/L	၃၄၀	၂၁၄	၄၄၄	၂၀၀၀
၃၁	ကြေးကျွန်းသောကလိုဂုဏ်ပေါ် င်း (Total Residual Chlorine)	mg/L	၀.၁	၀.၁	၀.၆	၀.၂
၃၂	ခရိုပိုယ် (Chromium Hexavalent)	mg/L	< ၀.၀၅	< ၀.၀၅	< ၀.၀၅	၀.၁
၃၃	အမြှုံးနီးယား (Ammonia)	mg/L	၀.၇၀	၀.၈၈	၇.၉၄	၁၀
၃၄	ဖလူအိုရိုက် (Fluoride)	mg/L	၁.၇၇၂	၁.၅၄၃	၂.၅၁၇	၂၀
၃၅	ရွှေ (Silver)	mg/L	≤ ၀.၀၀၂	≤ ၀.၀၀၂	≤ ၀.၀၀၂	၀.၅
၃၆	ဝမ်းကိုက်ရောဂါကိုဖြစ်စေသော ကိုလိုဖောင်း ဘက်တီးနီးယား (Escherichia Coli)	MPN/100ml (SW)	၇၉.၀	၁၇.၀	-	(၁၀၀၀)* (CFU/၁၀၀၀ml)
၃၇	စီးဆင်းနှုန်း (Flow Rate)	m³/s	၀.၁၁	၀.၀၉၉	၀.၀၁၁	-

မှတ်ချက်။ အနီရောင်ဖြင့်ဖော်ပြုထားသောတန်ဖိုးများသည်သတ်မှတ်ထားသည့်တန်ဖိုးများထက်ကျော်လွန်နေသည်ကိုဆိုလိုပါသည်။



မှတ်ချက်။ စွန့်ထဲတေသားစွန့်ထဲတေလိုက်သောချောင်း၏ အသုံးပြုမြေပါးမှာတည်၍ ရွေ့ပန်စိုင်ငြေး၊ ချီးရေစီးချိန်စွဲများ၊ (ပတ်ဝန်းကျင်စိုင်ရာနှင့်ဖြောန၊ စာဖြေရာ) ငါးပါးတို့ကိုရောဂါကိုဖြစ်စေသော ကိုလီဖော်သာက်တိုးယူသာ (E. coli)၏ ပည့်မှန်စာတို့အပြုံသတ်မှတ်ထားပါသည်။ သို့သေဆုံးလည်း ယာဉ်လက်ဘိုတွင် ကျွန်ုပ်တို့ ယုံကြည်စွာရေးမှုများ ပေါ်ပေါ်သော DOWA စေတဲ့ခန်းသည် စီအကိုပ်ယူတန်း၏ "Colony Forming Unit (CFU)" အား တိုင်းတာ၍မပေါ်။ ထိုအပြင် စာတို့ခန်းများ၏ ပညာရှင်မှုများ၏ အတွက်ကြော်ရှုသောက်စွဲများတွင်သာ စီအကိုပ်ယူတန်း၏ "Colony Forming Unit (CFU)" နည်းလည်းများကိုသာ အသုံးပြုသည်။ ထိုကြောင့်ခြေပါရန်မှာ နှင့် စွမ်းပိုင်ရေးမှုတွေ တိကျေသည့် ရလုပ်မှုများ ရရှိရန် အဓိကအန် "Most Probable Number (MPN)" ရလုပ်မှုများကို စီအကိုပ်ယူတန်းနှင့် တူညီသည်ဟုယူဆြေး။ အသုံးပြုပါမည်။ အဓိကအန် "Most Probable Number (MPN)" ရလုပ်မှုများကို စီအကိုပ်ယူတန်းနှင့် တူညီသည်ဟုယူဆြေး။ ရည်မှန်ပုံစံနှင့် ရိုင်းယူတို့သည်။ ရွေ့ပန်စိုင်ငြေး၊ ချီးရေ၊ ဧည့်ချိန်စွဲများ၊ (ပတ်ဝန်းကျင်စိုင်ရာနှင့်ဖြောန၊ စာဖြေရာ) ငါးပါးတို့ကိုရောဂါကိုဖြစ်စေသော ကိုလီဖော်သာက်တိုးယူသာ (E. coli) တန်း၏ ၁၀၀၀ CFU/၁၀၀ ml ထက်ကျော်လွှန်နေသည်မှာ ချီးရေအပြစ်သုံးရန် စသုင့်တော်ဟုယူဆပါသည်။

မူရင်း။ မြန်မာခိုအဲအင်တာနေရှင်နယ်လီမိတက်

ຈ.ເງ.ຈ ຖື້ນດັບຕົກເຮັດວຽກ ຖື້ນທີ່ເມືອງ ພະຍາຍາ ດັບຕົກ ຕົກສົ່ງ ທີ່ມີຄວາມ ດັບຕົກ ຕົກສົ່ງ ທີ່ມີຄວາມ

ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုရလဒ်များကို ယေား ၂၅-၂ တွင်ဖော်ပြထားပါသည်။ ရလဒ်များအား ပတ်ဝန်းကျင်ထိခိုက်မှု ဆန်းစစ်ခြင်းအစီအရင်ခံစာတွင် ပါဝင်သော ရေအရည်အသွေး၏ ရည်မှန်းတန်ဖိုးများနှင့် နှုန်းယဉ်ထားပါသည်။

ရည်မှန်းတန်ဖိုးနှင့်နှင့်ပြုလုပ်ရာတွင် ဆိုင်းကြေအနည်းများ၊ ကိုလိုဖောင်း စုစုပေါင်း နှင့် သံဓာတ်တို့မှာ
ရည်မှန်းတန်ဖိုးထက် ကျပ်လွန်နေကြောင်းတွေ့ရသည်။

ဆိုင်းကြွေအနည်းငါး ရလဒ်များအရ (မြေပေါ်ရေနမူနာယူသည့်နေရာ-၂ (SW-2) နှင့် မြေပေါ်ရေနမူနာယူသည့်နေရာ-၄ (SW-4)) တို့၏ ရလဒ်များသည် ရည်မှန်းတန်ဖိုးထက် ကျော်လွန်နေခြင်းမှာ (၁) သဘာဝအလျာက်ချောင်းအထက်ပိုင်းမှ စီးဆင်းလာခြင်းနှင့် သီလဝါအထူးစီးပွားရေးဇ် ပြင်ပရှိ ပြည်တွင်းစက်မှုဇုန်မှ စွန်ထုတ်လိုက်သော ရေများကြောင့်လည်းကောင်း၊ (၂)ချောင်းအောက်ဘက်ရှိ ရေများသည် ဒီဇရအတောက်အကျကြောင့် အထက်သို့ ပြန်လည်စီးဆင်းလာခြင်းကြောင့်လည်းကောင်း ဖြစ်နိုင်ပါသည်။

ကိုလိုဖောင်းစွမ်ပေါင်းရလဒ်အရ (မြေပြေဌရန်မူနာယူသည့်နေရာ-J (SW-2) နှင့် မြေပြေဌရန်မူနာယူသည့်နေရာ-D (SW-4)) တိုရှိ ရလဒ်များသည် ပည်မှန်းတန်ဖိုးထက် ကျော်လွန်နေခြင်းမှာ (၁)ချောင်းအထက်ပိုင်းတွင် တည်ရှိသော ဖွံ့ဖြိုးတိုးတက်မှုမရှိသေးသည့် ဇရီယာမှ တိရှိစွဲ့နှင့်များ၏ စွန့်ပစ်အညွစ်အကြေးများ နှင့် ပြည်တွင်းစက်မှုမြန်မှ စီးဆင်းလာသောရေများနှင့် သီလဝါအထူးစီးပွားရေးနှင့် ပြင်ပတွင်ရှိသော တရားမဝင်စွန့်ပစ်ရာနေရာများမှ လည်းကောင်း၊ (၂) ဒီရေသက်ရောက်မှုပြင့် ပတ်ဝန်းကျင်ရေးယာမှ ရေများ စီးဝင်လာခြင်းကြောင့်လည်းကောင်း ဖြစ်နိုင်ပါသည်။

သံဓာတ်ရုလ၏အနေဖြင့် (မြေပေါ်ရေနမူနာယဉ်သည့်နေရာ-၄ (SW-4)) တို့၏ ရလဒ်သည် ရည်မှန်းတန်ဖိုးထက် ကျော်လွန်နေကြောင်း တွေ့ရှုရပါသည်။ ဖြစ်နိုင်သောအကြောင်းအရာများမှာ သဘာဝ သံဓာတ် အရင်းအမြတ်၏ လွမ်းမိုးမှု ကြောင့် ဖြစ်နိုင်ပါသည် (သံဓာတ်သည်ရေစီးဆင်းမှုကြောင့် မြေဆီလွှာအတွင်းမှ ထွက်လာနိုင်ပါသည်)။ ဂျပန်နိုင်ငံ လူနေမှုပတ်ဝန်းကျင်စံနှုန်းတန်ဖိုးများတွင် (၁) ကျွန်းမာရေး (၂) လူနေမှုပတ်ဝန်းကျင်ဟူ၍ အမျိုးအစားနှစ်ခု သတ်မှတ်ထားပါသည်။ ကျွန်းမားရေးအမျိုးအစားတွင် သံဓာတ်အတွက် စံတန်ဖိုးသတ်မှတ်ထားခြင်းမတွေ့ရှုရပါ။ သို့သော် လူနေမှုပတ်ဝန်းကျင်အတွက်မှ ပျော်ဝင်နိုင်သောသံဓာတ် စံတန်ဖိုးအား ၁၀ မီလီကရမ်/လီတာ ဟူ၍သတ်မှတ်ထားသည်။ ဂျပန်နိုင်၏ လူနေမှုပတ်ဝန်းကျင်အတွက်



သီလဝါအထူးစီးပွားရေးဇာတ်အဖိုင်း(က)ရှိစက်မှုဇာန်ဖြုံဖြုံးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေလာမှုအဖိုင်ခံစာ
(တစ်နှစ် နှစ်ကြိုင်၊ စောင့်ကြည့်လေလာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခနှစ်)

သံဓာတ်စံတန်ဖိုးနှင့် နှိုင်းယူဉ်ရာတွင် မြေပေါ်ရေနမ်နာယူသည့်နေရာ-၄ (SW-4) ရှိ သံဓာတ်တန်ဖိုးသည် စံတန်ဖိုးအောက်နည်းပါးနောကြောင်း တွေ့ရှိရပါသည်။ ထိုကြောင့် လူနေမှုပတ်ဝန်းကျင်တွင် သီသာထင်ရှားသောထိခိုက်မှုမရှိကြောင်း သတ်မှတ်နိုင်ပါသည်။

ထေား J-၅-၂ စွန့်ထုတ်ရေထွက်ရှိသောနေရာများနှင့် စွန့်ထုတ်ရေရောက်ရှိနိုင်သည့်ချောင်း၏ အခြေအချက်အလက်များကို နှိုင်းယူဉ်ရန်အတွက် ရည်ညွှန်းစောင့်ကြည့်လေလာမှု ရေအရည်အသွေးရလဒ်များ

စဉ်	ရေအရည်အသွေးအဖိုး အစား (parameters)	ယူနစ်	မြေပေါ်ရေ နမ်နာယူသည့် နေရာ-၂ (SW-2)	မြေပေါ်ရေ နမ်နာယူသည့် နေရာ-၄ (SW- 4)	မြေအောက်ရေ နမ်နာယူသည့် နေရာ-၁ (GW-1)	ရည်မှန်းတန်ဖိုး (ကိုယ်တိုင်စောင့်ကြည့် လေလာခြင်းအတွက် ရည်ညွှန်းတန်ဖိုး)
၁	ရေအပူချိန် (water temperature)	°C	၃၉	၂၃	၂၅	≤ ၃၅
၂	ချုပ်ဖန်ကိန်း (pH)	-	၇.၂	၇.၂	၇.၈	၆ - ၈
၃	ဆိုင်းကြွားနှင့် (suspended solid)	mg/L	၇၈	၁၃၄	၆	၅၀
၄	ပျော်ဝင်အောက်စီဂျင် (Dissolved Oxygen)	mg/L	၂.၃၆	၄.၆၆	၇.၀၀	-
၅	မီဝန်းဖြင့်ဖြော်ရန် အောက်စီဂျင် လိုအပ်ချက် (၅- ရက်) (BOD ₍₅₎)	mg/L	၇၉၃	၃၄၇	၄၅၇	၂၀
၆	ဓာတုန်းဖြင့်ဖြော်ရန် အောက်စီဂျင် လိုအပ်ချက် (COD _(Cr))	mg/L	၃၀.၉	၁၉.၈	၁၅	၁၂၅
၇	ကိုလိုဖောင်းစုစုပေါင်း (Total Coliform)	MPN/ 100ml	၉၀၀၀	> ၁၆၀၀၀	၀၃.၀	၄၀၀
၈	နှုက်ထုပ္ပန်စုစုပေါင်း (Total Nitrogen)	mg/L	၇.၀	၆.၄	၉.၃	၈၀
၉	ဖော်စောင်ရောင်စုစုပေါင်း (Total Phosphorus)	mg/L	-	-	-	J
၁၀	အရောင် (Color)	TCU (True Color Unit)	၁၇.၀၆	၇.၈၆	၁.၅၂	၁၅၀
၁၁	အနဲ့ (Odor)	TON (Threshold Odor Number)	၁၁	၁၁	၁	-
၁၂	ဆီနှင့် အမဲဆီ (Oil and Grease)	mg/L	< ၃.၀	< ၃.၀	< ၃.၀	၁၀
၁၃	မြေဝါးဓတ် (Mercury)	mg/L	≤ ၀.၀၀၂	≤ ၀.၀၀၂	≤ ၀.၀၀၂	၀.၀၀၅
၁၄	ဘွဲ့ (Zinc)	mg/L	၀.၀၂၆	၀.၀၆၀	၀.၀၀၆	J
၁၅	အာဆီနှင့် (Arsenic)	mg/L	≤ ၀.၀၀၀	≤ ၀.၀၀၀	≤ ၀.၀၀၀	၀.၁
၁၆	ခရီးမြိုက် (Chromium)	mg/L	≤ ၀.၀၀၂	≤ ၀.၀၀၂	≤ ၀.၀၀၂	၀.၁

သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုဇုန်ဖြူးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအဖွဲ့ရင်ခံစာ
(တစ်နှစ် နှစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)

စဉ်	ရေအရည်အသွေးအချို့ အစား (parameters)	ယူနစ်	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၂ (SW-2)	မြေပေါ်ရေ နမူနာယူသည့် နေရာ-၄ (SW- 4)	မြေအောက်ရေ့နှု နမူနာယူသည့် နေရာ-၁ (GW-1)	ရည်မှန်းတန်ဖိုး (ကိုယ်တိုင်စောင့်ကြည့် လေ့လာခြင်းအတွက် ရည်ညွှန်းတန်ဖိုး)
၁၇	ကမ်းဒို့ယ် (Cadmium)	mg/L	≤ 0.001	≤ 0.001	≤ 0.001	0.02
၁၈	ဆယ်လီနီယ် (Selenium)	mg/L	≤ 0.000	≤ 0.000	≤ 0.000	0.0
၁၉	ခဲ့ (Lead)	mg/L	≤ 0.001	≤ 0.001	≤ 0.001	0.0
J၁	ကြွေးနီး (Copper)	mg/L	≤ 0.001	≤ 0.001	≤ 0.001	0.0
J၃	ပေါ်ယူယ် (Barium)	mg/L	0.03	0.03	0.03	0
J၅	နှစ်ကာယ် (Nickel)	mg/L	≤ 0.001	≤ 0.001	≤ 0.001	0.0
J၆	ဆိုင်ယာနိုင်စုစုပေါင်း (Total Cyanide)	mg/L	0.006	0.006	< 0.001	0
J၇	လွှတ်လပ်ကလိရင်း (Free Chlorine)	mg/L	0.0	< 0.0	< 0.0	0
J၈	ဆာလဖို့ (Sulphide)	mg/L	0.001	0.277	< 0.001	0
J၉	ဖော်မယ်ဒို့ပိုက် (Formaldehyde)	mg/L	0.006	0.007	0.006	0
J၁၀	ဖိနား (Phenols)	mg/L	0.001	0.001	< 0.001	0.0
J၁၁	အံစာတ် (Iron)	mg/L	0.002	0.002	0.002	0.0
၂၀	ပျော်ဝင်အနည်စုစုပေါင်း (Total Dissolved Solids)	mg/L	၁၀၆	၆၂	၁၃၃	၂၀၀
၂၁	ကြွင်းကျွန်းသာကလိရင်းစုစု ပေါင်း (Total Residual Chlorine)	mg/L	0.1	0.0	< 0.0	0.0
၂၂	ခရီ့မီယ် (Chromium Hexavalent)	mg/L	< 0.01	< 0.01	< 0.01	0.0
၂၃	အမိန့်ဗျား (Ammonia)	mg/L	0.00	0.06	0.06	0.0
၂၄	ဖလူအိုရိုက် (Fluoride)	mg/L	0.006	0.006	≤ 0.006	0.0
၂၅	ရွှေ (Silver)	mg/L	≤ 0.001	≤ 0.001	≤ 0.001	0.0
၂၆	ဝမ်းကိုက်ရောဂါကိုဖြစ်စေသော ကိုလီဖောင်းဘက်တိုးရီးယား (Escherichia Coli)	MPN/100ml*	-	-	-	(၁,၀၀၀)* (CFU/100ml)
		MPN/100ml** (GW)	-	-	< ၁.၈	(၁၀၀)** (MPN/100ml)
၂၇	စီးဆင်းနှုန်း (Flow Rate)	m ³ /s	-	0.02	-	-

မှတ်ချက်။ အနီးရောင်းဖြော်ဖြစ်သောတန်ဖိုးယူးသည်သတ်မှတ်ထားသည့်တန်ဖိုးယူးထက်ကျော်လွန်နေသည်။


*မှတ်ချက်။ စွမ်းလွှတ်ရော့မှုနှင့်လွှာလိုက်သာရော့မှုနှင့်၏ အသုံးပြုမှုပေါ်မှတ်လျှော့၍ ဂျပန်နိုင်ငံ၏ ချီးရော်ချိန်စုစုပေါင်း (DOWA) မှတ်ချွေခန်းသည် စီအကိုင်ယူတန်ဖိုး "Colony Forming Unit (CFU)" အား တိုးတက်ရှိမှုပါ။ ထိုအပြင် စာတို့ခွန်း ပညာရှင်များ၏ အတွက်ကြော်အရ သောက်သုံးရော့မှုများတွင်သာ စီအကိုင်ယူတန်ဖိုး "Colony Forming Unit (CFU)" နည်းလမ်းများကိုသာ အသုံးပြုသည်။ ထိုကြောင့်မြေပေါ်ရေနမူနာ့နှင့် စွမ်းပိုင်ရော့မှုများတွင် တိကျားသည့် ရလဒ်များ ရရှိရန် အမိပ်အန် "Most Probable Number (MPN)" ရလဒ်များကို အိုင်ပို့ယူတန်ဖိုးမှုနှင့် တူညီသည်ဟုယူဆပါသည်။

ဂျပန်နိုင်ငံ၏ ချီးရော်ရော်ချိန်စုစုပေါင်း (DOWA) မှတ်ချွေခန်းသုံးရော့မှုများ မသင့်တော်ဟုယူဆပါသည်။



သီလဝါအထူးစီးပွားရေးဦးစီးပွားရေးနှင့်အပိုင်း(က)ရှိုစက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(တစ်နှစ် နှစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)

**မှတ်ချက်။ မြေအောက်ရေစောင့်ကြည့်လေ့လာသာနေရာတွင် ရေအသုံးပြုမှုပေါ်မှတည်၍ မီယగ်နဲ့နိုင်ငံရှိ မြေအောက်ရေအရည်အသွေးဆိုင်ရာ အမျိုးသားနည်းပညာစည်းမျဉ်းသွေးပေါ် B1 (ဆည်မြောင်းရေ) (No. QCVN 08: 2008/BTNMT) ကို မြေအောက်ရေဂိုလ်တိုင်စောင့်ကြည့်လေ့လာခြင်းအတွက် ရည်မှန်းတန်ဖိုးအဖြစ်သတ်မှတ်ပါသည်။
မူရင်း။ မြန်မာနိုင်အင်တာနေရာင်နယ်လီမိတက်



အခန်း ၃ နိဂုံးချုပ် နှင့် အကြံပြုချက်များ

ဆိုင်းကြွာအနယ်များ နှင့် ကိုလိုဖောင်းစုစုပေါင်း ရလဒ်များသည် ဗဟိုစွန်းထုတ်ရေသနစင်စက်ရုံ၏ ထွက်ပေါက်
မြေပေါ်ရေနမူနာယူသည့်နေရာ-၆ (SW-6) မှရလဒ်သည် ရည်မှန်းထားသော တန်ဖိုးအတွင်းရှိကြောင်း
တွေ့ရှိရသည်။ ထိုကြောင့် စက်ရုံတစ်ရုံချင်းစီမှ ထွက်ရှိလာသော စွန်းထုတ်ရေများအား ပင်မစွန်းထုတ်ရေ
သန်စင်စက်ရုံမှ ကောင်းမွန်စွာ သန္တစ်ထားသည်ဟု ဆိုလိုနိုင်ပါသည်။ အခြားတစ်ဖက်တွင်လည်း စောင့်ကြည့်
လျေလာနေသော ရေတိန်းကန် မြေပေါ်ရေ နမူနာယူသည့်နေရာ-၁ (SW-1) မှ ဆိုင်းကြွာအနယ်ရလဒ်များသည်
ရည်မှန်းတန်ဖိုးထက် ကျော်လွန်နေသည့် အကြောင်းအရင်းမှာ ဇုန်အပိုင်း(က)ရှိ မြေလွှတ်များမှ မြေမျက်နှာပြင်
စီးဆင်းရေ များကြောင့် ဖြစ်နိုင်ပါသည်။

သီလဝါအထူးစီးပွားရေးနှင့် အပိုင်း(က)၏ အဓိကရေတွက်ပေါက်များဖြစ်သော မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅
(SW-5) တို့တွင် စုစုပေါင်းကိုလိုဖောင်း အပျိုးအစားမှာ ယခုစောင့်ကြည့်လျေလာသည် အချိန်တွင်
ရည်မှန်းတန်ဖိုးထက်များနေကြောင်း တွေ့ရှိရပါသည်။ ထိုအပြင် ရေထိန်းတူးမြောင်း
မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅ (SW-5) တွင် ဝမ်းကိုက်ရောက်ကို ဖြစ်စေသော
ကိုလိုဖောင်းသာက်တီးရီးယား(E.Coli) အတွက် ကိုယ်တိုင်စောင့်ကြည့်လျေလာမှုအရ ရလဒ်သည်
ရည်မှန်းတန်ဖိုးအောက် နည်းပါးကြောင်းတွေ့ရှိရပါသည်။ ထိုကြောင့် မြေပေါ်ရေနမူနာယူသည့်နေရာ-၅ (SW-5)
တွင် ကိုလိုဖောင်းစုစုပေါင်းမှာ ရည်မှန်းတန်ဖိုးထက် များနေသော်လည်း လူတို့၏ကျိုးမာရေးအပေါ်
သိသာထင်ရှားစွာ သက်ရောက်မှုမရှိဟု သတ်မှတ်နိုင်ပါသည်။

လွတ်လပ်ကလိုရင်း နှင့် ကြွင်းကျုန်းသောကလိုရင်းစုစုပေါင်း ရလဒ်အနေဖြင့် ဗဟိုစွန်းထုတ်ရေ သန်စင်စက်ရုံ၏
ထွက်ပေါက် မြေပေါ်ရေ နမူနာယူသည့်နေရာ-၆ (SW-6) မှရလဒ် သည် ရည်မှန်းတန်ဖိုးထက် ကျော်လွန်နေ
ကြောင်း တွေ့ရှိရသည်။ ရည်မှန်းထားသော တန်ဖိုးထက် ကျော်လွန်နေခြင်းမှာ စက်ရုံမှုမစွန်းထုတ်ခင်
စွန်းထုတ်ရေများတွင် ကလိုရင်းများကျုန်းရှိနေခြင်းကြောင့် ဖြစ်နိုင်သည်။ သို့သော်လည်း ဇုန်အပိုင်း(က)၏
နောက်ဆုံး စွန်းထုတ်ရာနေရာတဲ့ဖြစ်သော မြေပေါ်ရေနမူနာယူသည့် နေရာ-၁ (SW-1)၏
လွတ်လပ်ကလိုရင်းသည် ရည်မှန်းတန်ဖိုး(၁ မီလီဂရမ်/လီတာ) နှင့် ကြွင်းကျုန်းစုစုပေါင်းသည်
ရည်မှန်းတန်ဖိုး(၀.၂ မီလီဂရမ်/လီတာ) အောက် နည်းပါးနေကြောင်း တွေ့ရှိရပါသည်။ ထိုကြောင့် ရှိရှိထားသော
ရလဒ်များသည် လူ၏ကျိုးမာရေးနှင့် သက်ရှိပတ်ဝန်းကျင်တွင် သိသာထင်ရှားသော ထိခိုက်မှ မရှိနိုင်ကြောင်း
သတ်မှတ်နိုင်ပါသည်။

ရည်ညွှန်းစောင့်ကြည့်လျေလာသည့် မြေပေါ်ရေနမူနာယူသည့်နေရာများတွင် ဆိုင်းကြွာအနယ်များ၊
ကိုလိုဖောင်းစုစုပေါင်း နှင့် သံဓာတ် တို့၏ ရလဒ်များသည် ရည်မှန်းတန်ဖိုးထက် ကျော်လွန်နေကြောင်း
တွေ့ရှိရသည်။ ဖြစ်နိုင်ချေး အလားအလာရှိသည့်အကြောင်းအရင်းမှာ (မြေပေါ်ရေနမူနာယူသည့် နေရာ-၂)
နှင့် မြေပေါ်ရေနမူနာယူသည့် နေရာ-၄ (SW-4)) တို့၏ ဆိုင်းကြွာအနည်းဆုံးမှု ရလဒ်များသည် ရည်မှန်းတန်ဖိုးထက်
ကျော်လွန်နေခြင်းမှာ သဘာဝအလျောက် ချောင်းအထက်ပိုင်းမှ စီးဆင်းလာခြင်းနှင့် သီလဝါအထူးစီးပွားရေးနှင့်
ပြင်ပရှိ ပြည်တွင်းစက်မှုဇုန်မှ စွန်းထုတ်လိုက်သော ရေများကြောင့်လည်းကောင်း ဖြစ်နိုင်ပါသည်။ ကိုလိုဖောင်း
စုစုပေါင်းရလဒ်များအနေဖြင့် (မြေပေါ်ရေနမူနာယူသည့် နေရာ-၂) နှင့် မြေပေါ်ရေနမူနာယူသည့် နေရာ-၄



သီလဝါအထူးစီးပွားရေးဗုဏ်အပိုင်း(က)ရှိစက်မှုဇုန်ဖြီးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(တစ်နှစ် နှစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)

(SW-4) တွင် ရည်မှန်းတန်ဖိုးထက် ကျော်လွန်နေရခြင်းမှာ သဘာဝအလျောက် ရှိနေသော ဘက်တီးရီးယားများ
ကြောင့်ဖြစ်နိုင်ပါသည်။

သံဓာတ်ရလဒ်အနေဖြင့် (မြေပေါ်ရေနမှုနာယူသည့်နေရာ-၄ (SW-4)) တို့၏ ရလဒ်သည် ရည်မှန်းတန်ဖိုးထက်
ကျော်လွန်နေကြောင်း တွေ့ရှုရပါသည်။ ဖြစ်နိုင်သောအကြောင်းအရာများမှာ သဘာဝ သံဓာတ် အရင်းအမြစ်၏
လွမ်းမိုးမှု ကြောင့် ဖြစ်နိုင်ပါသည် (သံဓာတ်သည်ရေစီးဆင်းမှုကြောင့် မြေဆီလွှာအတွင်းမှ ထွက်လာနိုင်ပါသည်)။
ဂျပန်နိုင်ငံ၏ လူနေမှုပတ်ဝန်းကျင်အတွက် သံဓာတ်စံတန်ဖိုးနှင့် နှိုင်းယဉ်ရာတွင် မြေပေါ်ရေနမှုနာယူသည့် နေရာ-
၄ (SW-4) ရှိ သံဓာတ်တန်ဖိုးသည် စံတန်ဖိုးအောက်နည်းပါးနေကြောင်း တွေ့ရှုရပါသည်။ ထိုကြောင့်
လူနေမှုပတ်ဝန်းကျင်တွင် သိသာထင်ရှားသောထိခိုက်မှုမရှိကြောင်း သတ်မှတ်နိုင်ပါသည်။

အနာဂတ်တွင် သီလဝါအထူးစီးပွားရေးဗုဏ် အပိုင်း (က) ၅။ အမိကစ္စနှစ်ထုတ်ရေ ထွက်ရှိသောနေရာများမှ
ထွက်ရှိလာသော ရေအရည်အသွေးများဖြစ်သည့် ဆိုင်းကြအနုယ်များ၊ ကိုလိုဖောင်းစုစုပေါင်း၊ လွတ်လပ်ကလိုရင်း
နှင့် ကြွင်းကျွန်းသောကလိုရင်းစုစုပေါင်း တို့၏ သင့်တော်သော ရည်မှန်းအဆင့်ရှိနိုင်ရန်
အောက်ပါဆောက်ရွက်ချက်များကိုလုပ်ဆောင်သင့်ပါသည်။


-ဗဟိုစွန်ထုတ်ရေ သန္တစင်စက်ရုံကို ပုံမှန်ပြုပြင်ထိန်းသီမ်းခြင်း

-ကိုလိုဖောင်းဘက်တီးရီးယားများ၏ ကျွန်းမာရေးအပေါ်သက်ရောက်မှုကို သိရှိနိုင်ရန် ဝမ်းကိုက်ရောဂါကို
ဖြစ်စေသော ကိုလိုဖောင်းဘက်တီးရီးယား (E Coli) ကို ဆက်လက်စောင့်ကြည့်ရန်။

- ဆောက်လုပ်ရေးလုပ်ငန်းများမှရေများစီးဆင်းမှုအခြေအနေကိုစောင့်ကြည့်လေ့လာရန် နှင့်

- ဆောက်လုပ်ရေးလုပ်ငန်းများမှအတွက်ထွေသုံးစွန်ထုတ်ရေများ၏အခြေအနေကိုစောင့်ကြည့်လေ့လာရန်။

ဤတွင်စာတမ်းပြီးဆုံးပါသည်။



နောက်ဆက်တွဲ ၁ ရေနမူနာကောက်ယူသည့် မှတ်တမ်းဓာတ်ပုံများ




သီလဝါအထူးစီးပွားရေးဇုန်အဖိုင်း(က)ရှိုစက်မှုဇန်ဖွံ့ဖြိုးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေလာမှုအစီရင်ခံစာ
(တစ်နှစ် နှစ်ကြိမ်၊ စောင့်ကြည့်လေလာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)


သီလဝါအထူးစီးပွားရေးဇုန် အဖိုင်း (က) ရှို့စက်မှုအတွက်ရေနှစ်မှုနာကောက်ယူသည့်နေရာများ



မြေပေါ်ရေ နှစ်မှုနာကောက်ယူခြင်းနှင့်တိုင်းတာခြင်း



မြေပေါ်ရေ နှစ်မှုနာကောက်ယူခြင်းနှင့်တိုင်းတာခြင်း




မြေပေါ်ရေ နှစ်မှုနာကောက်ယူခြင်းနှင့်တိုင်းတာခြင်း

သိလဝါအတူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုဇုနစ်ဖြူးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(တစ်နှစ် နှစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)

စွန့်ထဲတ်ရေ့ထွက်ရှိသောနေရာများနှင့်စွန့်ထဲတ်ရေ့ရောက်ရှိနိုင်သည့်ချောင်း၏အခြေခံအချက်အလက်
များကို နှိမ်းယူ၍ရန်အတွက် ရည်ညွှန်းစောင့်ကြည့်လေ့လာသည့် နေရာများ



မြေပေါ်ရေ နမူနာယူသည့်နေရာ-J (SW-2) ဪ ရေနမူနာကောက်ယူခြင်းနှင့်တိုင်းတာခြင်း



မြေပေါ်ရေ နမူနာယူသည့်နေရာ-င (SW-4) ဪ ရေနမူနာကောက်ယူခြင်းနှင့်တိုင်းတာခြင်း



မြေအောက်ရေ နမူနာယူသည့်နေရာ-င (GW-1) ဪ ရေနမူနာကောက်ယူခြင်းနှင့်တိုင်းတာခြင်း



နောက်ဆက်တဲ့ ၂ ပေတ်ခွဲခန်းရလဒ်များ



သီလဝါအထူးစီပွားရေးဇုနစ်အဖိုင်း(က)ရှိစက်မှုဇုနစ်ဖြူးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(တစ်နှစ် နှစ်ကြမ်း၊ စောင့်ကြည့်လေ့လာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)

စွန်ထုတ်ရေတွက်ရှိသည့်နေရာများနှင့်ပဟိုစွန်ထုတ်ရေသနစင်စက်ရှိအတွက်



GOLDEN GOWA ECO-SYSTEM MYANMAR CO., LTD.
Plot No.E1 Thilawa SEZ Zone A, Yangon Region, Myanmar
Phone No. Fax No. (+95) 1 2304051

motivate our planet
Doc No. GEM-10-R004E/00
Page 1 of 1

Report No. : GEM-LAB-202112140

Revision No. : 1

Report Date : 28 December, 2021

Application No. : 0001-C001

Analysis Report

Client Name : Myanmar Koiil International LTD (MKI)
Address : No. 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar
Project Name : Environment Monitoring report for Zone A & B
Sample Description
Sample Name : MKI-SW-1 1214 Sampling Date : 14 December, 2021
Sample No. : W-2112073 Sampling By : Customer
Waste Profile No. : - Sample Received Date : 14 December, 2021

No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	100	-
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	8.05	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	39.2	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	240	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	4.6	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	9.41	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	390	-
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Zinc	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.034	0.002
12	Arsenic	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
13	Chromium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
14	Cadmium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
15	Selenium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
16	Lead	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
17	Copper	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
18	Barium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.018	0.002
19	Nickel	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
20	Silver	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
21	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.246	0.002
22	Cyanide	HACH 8027 (Pyridine -Pyrazalone Method)	mg/l	< 0.002	0.002
23	Total Cyanide	Distillation Process: APHA 4500-CN C. Total Cyanide after Distillation, Determine Cyanide Concentration Process: HACH 8027 (Pyridine -Pyrazalone Method)	mg/l	0.009	0.002
24	Ammonia	HACH Method 10205 (Silicate TNT Plus Method)	mg/l	0.70	0.02
25	Hexavalent Chromium (Cr6+)	ISO 11083:1994 (Determination of chromium(VI) Spectrometric method using 1,5-diphenylcarbazide)	mg/l	< 0.05	0.05
26	Fluoride	APHA 4110 B (Ion Chromatography with Chemical Suppression of Eluent Conductivity)	mg/l	1.772	0.014
27	Free Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	< 0.1	0.1
28	Total Residual Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	0.1	0.1
29	Sulphide	HACH 8131 (USEPA Methylene Blue Method)	mg/l	0.151	0.005
30	Formaldehyde	HACH 8110 (MBTH Method)	mg/l	0.025	0.003
31	Escherichia Coli	APHA 9221 F Escherichia Coli Procedure Using Fluorogenic Substrate	MPN/100ml	79.0	1.8
32	Phenols	USEPA Method 420.1 (Phenolics (Spectrophotometric, Manual 4AAP With Distillation))	mg/l	0.018	0.002

Remark : LOQ - Limit of Quantitation
APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By :

Ni Ni Aye Lwin
Assistant Manager



Approved By :

Htet Htet Yinn
Managing Director
Dec 28, 2021



သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုဇုန်ဖြုံးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေလာမှုအဖိုင်ခံစာ
(တစ်နှစ် နှစ်ပြိုမ်း စောင့်ကြည့်လေလာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)

DOWA

GOLDEN DOWA LCD-SYSTEM MYANMAR CO., LTD
Lot No E1 Thilawa SEZ Zone A, Yangon Region, Myanmar
Phone No. Fax No: (+95) 1 2309051


motivate our planet
Doc No: GEM-LB-R004R700
Page 1 of 1

Report No. : GEM-LAB-202112141

Revision No. : 1

Report Date : 28 December, 2021

Application No. : 0001-C001


Analysis Report

Client Name	: Myanmar Koei International LTD (MKI)		
Address	: No, 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar.		
Project Name	: Environment Monitoring report for Zone A & B		
Sample Description			
Sample Name	: MKI-SW-5-1214	Sampling Date :	14 December, 2021
Sample No.	: W-2112074	Sampling By :	Customer
Waste Profile No.	:	Sample Received Date :	14 December, 2021


No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	28	—
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	3.91	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	19.2	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	1600	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	1.7	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	7.46	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	214	—
10	Mercury	APIA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Zinc	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.016	0.002
12	Arsenic	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
13	Chromium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
14	Cadmium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
15	Selenium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
16	Lead	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
17	Copper	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
18	Barium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.022	0.002
19	Nickel	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
20	Silver	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
21	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.802	0.002
22	Cyanide	HACH 8027 (Pyridine -Pyrazalone Method)	mg/l	< 0.002	0.002
23	Total Cyanide	Distillation Process: APHA 4500-CN-C, Total Cyanide after Distillation, Determine Cyanide Concentration Process: HACH 8027 (Pyridine -Pyrazalone Method)	mg/l	0.003	0.002
24	Ammonia	HACH Method 10205 (Silicate-TNT Plus Method)	mg/l	0.18	0.02
25	Hexavalent Chromium (Cr6+)	ISO 11083:1994 (Determination of chromium(VI) Spectrometric method using 1,5-diphenylcarbazide)	mg/l	< 0.05	0.05
26	Fluoride	APHA 4110 B (Ion Chromatography with Chemical Suppression of Eluent Conductivity)	mg/l	1.543	0.014
27	Free Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	< 0.1	0.1
28	Total Residual Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	0.1	0.1
29	Sulphide	HACH 8131 (USEPA Methylene Blue Method)	mg/l	0.044	0.005
30	Formaldehyde	HACH 8110 (MBTH Method)	mg/l	0.027	0.003
31	Escherichia Coli	APHA 9221 F Escherichia Coli Procedure Using Fluorogenic Substrate	MPN/100ml	17.0	1.8
32	Phenols	USEPA Method 420.1 (Phenolics (Spectrophotometric, Manual 4AAP With Distillation))	mg/l	0.007	0.002


Remark : LOQ - Limit of Quantitation
APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By


Ni Ni Aye Lwin
Assistant Manager

Approved By :


Hideki Tomio
Managing Director



CC-J



သိလဝါအထူးစီးပွားရေးဇုန်အပိုင်း(က)ရှိစက်မှုဇုန်ဖြူးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေ့လာမှုအစီရင်ခံစာ
(တစ်နှစ် နှစ်ကြိမ်၊ စောင့်ကြည့်လေ့လာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)

DOWA

GOLDEN DOWA ECO-SYSTEM MYANMAR CO., LTD.
Lot No E1, Thilawa SEZ Zone A, Yangon Region, Myanmar
Phone No. Fax No: (+95) 1 2809051

motivate our planet
Doc No: GEM-LB-H0048/00
Page 1 of 1

Report No. : GEM-LAB-202112142
Revision No. : 1
Report Date : 28 December, 2021
Application No. : 0001-C001

Analysis Report


Client Name : Myanmar Koi International LTD (MKI)
Address : No, 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tarmwe Township, Yangon, Myanmar.
Project Name : Environment Monitoring report for Zone A & B
Sample Description
Sample Name : MKI-SW-6-1214 Sampling Date : 14 December, 2021
Sample No. : W-2112075 Sampling By : Customer
Waste Profile No. : - Sample Received Date : 14 December, 2021

No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	14	—
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	3.84	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	21.2	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100mL	< 1.8	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	8.9	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	5.13	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	444	—
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Zinc	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.016	0.002
12	Arsenic	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
13	Chromium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
14	Cadmium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
15	Selenium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
16	Lead	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
17	Copper	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
18	Barium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.004	0.002
19	Nickel	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
20	Silver	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
21	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.104	0.002
22	Cyanide	HACH 8027 (Pyridine-Pyrazalone Method)	mg/l	< 0.002	0.002
23	Total Cyanide	Distillation Process: APHA 4500-CN- C. Total Cyanide after Distillation, Determine Cyanide Concentration Process: HACH 8027 (Pyridine-Pyrazalone Method)	mg/l	0.005	0.002
24	Ammonia	HACH Method 10205 (Silicilate TNT Plus Method)	mg/l	7.94	0.02
25	Hexavalent Chromium (Cr6+)	ISO 11083:1994 (Determination of chromium(VI) Spectrometric method using 1,5-diphenylcarbazide)	mg/l	< 0.05	0.05
26	Fluoride	APHA 4110 B (Ion Chromatography with Chemical Suppression of Eluent Conductivity)	mg/l	3.517	0.014
27	Free Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	1.1	0.1
28	Total Residual Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	1.6	0.1
29	Sulphide	HACH 8131 (USEPA Methylene Blue Method)	mg/l	0.006	0.005
30	Formaldehyde	HACH 8110 (MBTH Method)	mg/l	0.019	0.003
31	Phenols	USEPA Method 420.1 (Phenolics (Spectrophotometric, Manual 4AAP with Distillation))	mg/l	< 0.002	0.002

Remark : LOQ - Limit of Quantitation
APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By :

Ni Ni Aye Lwin
Assistant Manager



Approved By :

Hideki Yomo
Managing Director



၃၂၂၂

သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုဇုန်ဖွံ့ဖြိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေလာမှုအစီရင်ခံစာ
(တစ်နှစ် နှစ်ကြိမ်၊ စောင့်ကြည့်လေလာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)

စွန်ထုတ်ရေထွက်ရှိသောနေရာများနှင့် စွန်ထုတ်ရေရောက်ရှိနှင့်သည့်ချောင်း၏ အခြေခံအချက်အလက်များကို နှိုင်းယဉ်ရန်အတွက် ရည်ညွှန်းစောင့်ကြည့်လေလာသည့် နေရာများ

DOWA

GOLDEN DOWA ECO-SYSTEM MYANMAR CO., LTD.
Lot No C1 Thilawa SEZ Zone A, Yangon Region, Myanmar
Phone No. Fax No.(+95) 1 2309051

Innovate our planet
Doc No: GEM-LB-R004E/00
Page 01 of 01

Report No. : GEM-LAB-202112143
Revision No. : 1
Report Date : 28 Decemeber, 2021
Application No. : 0001-C001

Analysis Report


Client Name	:	Myanmar Kothi International LTD (MKI)		
Address	:	No, 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar		
Project Name	:	Environment Monitoring report for Zone A & B		
Sample Description				
Sample Name	:	MKT-SW 2-1214	Sampling Date :	14 December, 2021
Sample No.	:	W-2112076	Sampling By :	Customer
Waste Profile No.	:	-	Sample Received Date :	14 December, 2021

No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	78	—
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	7.99	0.00
3	COD (Cr)	APHA 5220B (Close Reflux Colorimetric Method)	mg/l	30.9	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	92000	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	7.0	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	17.06	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	1026	—
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Zinc	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.026	0.002
12	Arsenic	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
13	Chromium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
14	Cadmium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
15	Selenium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
16	Lead	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
17	Copper	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
18	Barium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.062	0.002
19	Nickel	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
20	Silver	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
21	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	1.632	0.002
22	Cyanide	HACH 8027 (Pyridine -Pyrazalone Method)	mg/l	< 0.002	0.002
23	Total Cyanide	Distillation Process: APHA 4500-CN-C. Total Cyanide after Distillation, Determine Cyanide Concentration Process: HACH 8022 (Pyridine -Pyrazalone Method)	mg/l	0.006	0.002
24	Ammonia	HACH Method 10205 (Silicylate-TNT Plus Method)	mg/l	2.01	0.02
25	Hexavalent Chromium (Cr6+)	ISO 11083:1994 (Determination of chromium(VI) Spectrometric method using 1,5-diphenylcarbazide)	mg/l	< 0.05	0.05
26	Fluoride	APHA 4110 B (Ion Chromatography with Chemical Suppression of Eluent Conductivity)	mg/l	0.154	0.014
27	Free Chlorine	APHA 4500 CL G (DPP Colorimetric Method)	mg/l	0.1	0.1
28	Total Residual Chlorine	APHA 4500 CL G (DPP Colorimetric Method)	mg/l	0.2	0.1
29	Sulphide	HACH 8131 (USEPA Methylene Blue Method)	mg/l	0.068	0.005
30	Formaldehyde	HACH 8110 (MBTH Method)	mg/l	0.015	0.003
31	Phenols	USEPA Method 420.1 (Phenolics (Spectrophotometric, Manual 4AAP With Distillation))	mg/l	0.002	0.002

Remark : LOQ - Limit of Quantitation
APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By:

Ni Ni Aye Lwin
Assistant Manager



Approved By:

Hideki Yomo
28, Dec, 2021
Managing Director



CC-J-5

သိလဝါအထူးစီးပွားရေးဇုန်အပိုင်း(က)ရှိစက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လျေလာမှုအစီရင်ပါတာ
(တစ်နှစ် နှစ်ကြိမ်၊ စောင့်ကြည့်လျေလာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)

DOWA

GOLDEN DOWA ECO-SYSTEM MYANMAR CO., LTD.
Lot No E1, Thilawa SEZ Zone A, Yangon Region, Myanmar
Phone No. Fax No: +9511 2309051



motivate our planet
Doc No: GCM-L8-R004E/08
Page 1 of 1

Report No. : GEM-LAB-202112144
Revision No. : 1
Report Date : 28 December, 2021
Application No. : 0001-C001

Analysis Report

Client Name	: Myanmar Kobi International LTD (MKI)	
Address	: No, 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar.	
Project Name	: Environment Monitoring report for Zone A & B	
Sample Description		
Sample Name	: MKI-SW-4-1214	Sampling Date : 14 December, 2021
Sample No.	: W-2112077	Sampling By : Customer
Waste Profile No.	: -	Sample Received Date : 14 December, 2021

No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	194	-
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	3.47	0.00
3	COB (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	19.8	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100ml	>150000	1.8
5	Oil and Grease	APHA 5520B (Partition-Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	6.4	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	7.86	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	624	-
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Zinc	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.060	0.002
12	Arsenic	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
13	Chromium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
14	Cadmium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
15	Selenium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
16	Lead	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
17	Copper	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
18	Barium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.020	0.002
19	Nickel	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
20	Silver	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
21	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	6.884	0.002
22	Cyanide	HACH 8027 (Pyridine - Pyrazoline Method)	mg/l	0.002	0.002
23	Total Cyanide	Distillation Process: APHA 4500-CN C. Total Cyanide after Distillation, Determine Cyanide Concentration Process: HACH 8027 (Pyridine - Pyrazoline Method)	mg/l	0.015	0.002
24	Ammonia	HACH Method 10205 (Silicate TNT Plus Method)	mg/l	1.44	0.02
25	Hexavalent Chromium (Cr6+)	ISO 11083:1994 (Determination of chromium(VI) Spectrometric method using 1,5-diphenylcarbazide)	mg/l	< 0.05	0.05
26	Fluoride	APHA 4510 B (Ion Chromatography with Chemical Suppression of Eluent Conductivity)	mg/l	1.325	0.014
27	Free Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	< 0.1	0.1
28	Total Residual Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	0.1	0.1
29	Sulphide	HACH 8131 (USEPA Methylene Blue Method)	mg/l	0.377	0.005
30	Formaldehyde	HACH 8110 (MBTH Method)	mg/l	0.072	0.003
31	Phenols	USEPA Method 420.1 (Phenolics (Spectrophotometric, Manual 4AAP With Distillation))	mg/l	0.002	0.002

Remark : LOQ - Limit of Quantitation
APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By :

Ni Ni Aye Lwin
Assistant Manager



Approved By :

Hideki Yomo
Managing Director



သီလဝါအတွေးစီးပွားရေးစုနှင့်အပိုင်း(က)ရှိစက်မှုဖွန့်ဖြေးတိုးတက်မှုအတွက်ရေအရည်အသွေးစောင့်ကြည့်လေလာမှုအစီရင်ခံစာ
(တစ်နှစ် နှစ်ကြိမ် စောင့်ကြည့်လေလာခြင်း ဒီဇင်ဘာလ ၂၀၂၁ ခုနှစ်)

DOWA

GOLDEN DOWA ECO SYSTEM MYANMAR CO., LTD.
Lot No E1 Thilawa SEZ Zone A, Yangon Region, Myanmar
Phone No/Fax No: (+95) 1 2309051

motivate our planet
Doc. No.: GEM-B-R004E/00
Page 1 of 1


Report No. : GEM-LAB-202112145
Revision No. : 1
Report Date : 28 December, 2021
Application No. : 0001-C001


Analysis Report


Client Name	: Myanmar Koei International LTD (MKI)		
Address	: No. 36/A, 1st Floor, Grand Pho Sein Condominium, Pho Sein Road, Tamwe Township, Yangon, Myanmar.		
Project Name	: Environment Monitoring report for Zone A & B		
Sample Description			
Sample Name	: MKI-GW-1-1214	Sampling Date	: 14 December, 2021
Sample No.	: W-2112078	Sampling By	: Customer
Waste Profile No.		Sample Received Date	: 14 December, 2021

No.	Parameter	Method	Unit	Result	LOQ
1	SS	APHA 2540D (Dry at 103-105°C Method)	mg/l	6	—
2	BOD (5)	APHA 5210 B (5 Days BOD Test)	mg/l	4.57	0.00
3	COD (Cr)	APHA 5220D (Close Reflux Colorimetric Method)	mg/l	1.5	0.7
4	Total Coliform	APHA 9221B (Standard Total Coliform Fermentation Technique)	MPN/100mL	13.0	1.8
5	Oil and Grease	APHA 5520B (Partition Gravimetric Method)	mg/l	< 3.1	3.1
6	Total Nitrogen	HACH Method 10072 (TNT Persulfate Digestion Method)	mg/l	9.3	0.5
7	Color	APHA 2120C (Spectrophotometric Method)	TCU	1.52	0.00
8	Odor	APHA 2150 B (Threshold Odor Test)	TON	1	0
9	TDS	APHA 2540 C (Total Dissolved Solids Dried at 180°C Method)	mg/l	1330	—
10	Mercury	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
11	Zinc	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.006	0.002
12	Arsenic	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
13	Chromium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
14	Cadmium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
15	Selenium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.010	0.010
16	Lead	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
17	Copper	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
18	Barium	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.042	0.002
19	Nickel	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
20	Silver	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	≤ 0.002	0.002
21	Iron	APHA 3120 B (Inductively Coupled Plasma (ICP) Method)	mg/l	0.304	0.002
22	Cyanide	HACH 8027 (Pyridine - Pyrazalone Method)	mg/l	< 0.002	0.002
23	Total Cyanide	Distillation Process: APHA 4500-CN-C. Total Cyanide after Distillation, Determine Cyanide Concentration Process: HACH B027 (Pyridine - Pyrazalone Method)	mg/l	< 0.002	0.002
24	Ammonia	HACH Method 10205 (Silicate TNT Plus Method)	mg/l	1.94	0.02
25	Hexavalent Chromium (Cr6+)	ISO 11083:1994 (Determination of chromium(VI) Spectrometric method using 1,5-diphenylcarbazide)	mg/l	< 0.05	0.05
26	Fluoride	APHA 4110 B (Ion Chromatography with Chemical Suppression of Eluent Conductivity)	mg/l	≤ 0.014	0.014
27	Free Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	< 0.1	0.1
28	Total Residual Chlorine	APHA 4500 CL G (DPD Colorimetric Method)	mg/l	< 0.1	0.1
29	Sulphide	HACH 8131 (USEPA Methylene Blue Method)	mg/l	< 0.005	0.005
30	Formaldehyde	HACH 8110 (MBTH Method)	mg/l	0.005	0.003
31	Escherichia Coli	APHA 9221 F Escherichia Coli Procedure Using Fluorogenic Substrate	MPN/100mL	< 1.8	1.8
32	Phenols	USEPA Method 420.1 (Phenolics (Spectrophotometric, Manual 4AAP With Distillation))	mg/l	< 0.002	0.002

Remark : LOQ - Limit of Quantitation
APHA - American Public Health Association (APHA), the American Water Works Association (AWWA), and the Water Environment Federation (WEF), Standard Methods for the Examination of Water and Wastewater, 22nd edition

Analysed By :

Ni Ni Aye Lwin
Assistant Manager



Approved By :

Hideki Yamada
Managing Director

cc-j-6



သီလဝါအထူးစီးပွားရေးဇုန် အပိုင်း(က)ရှိ
စက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်ရေးအတွက်
လေထုအရည်အသွေးစောင့်ကြည့်လွှဲလာခြင်းအစီအရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ)

(တစ်နှစ် နှစ်ကြိမ်စောင့်ကြည့်လွှဲလာခြင်း)

၂၀၂၁ ခုနှစ်၊ စက်တင်ဘာလ^၁
မြန်မာနိုင် အင်တာနေရာင်နယ် လီမိတက်



မာတိကာ

အခန်း ၁ စောင့်ကြည့်လေ့လာသောအစီအစဉ်နှင့်အကျဉ်းချုပ်.....၁
၁.၁ ယော်ယျုဖော်ပြချက်၁
၁.၂ စောင့်ကြည့်လေ့လာသောအစီအစဉ်ဖော်ပြချက်များ၁
အခန်း ၂ လေထုအရည်အသွေးစောင့်ကြည့်လေ့လာခြင်း၂
၂.၁ စောင့်ကြည့်လေ့လာသည့်အမျိုးအစား၂
၂.၂ စောင့်ကြည့်လေ့လာသည့်တည်နေရာ၂
၂.၃ စောင့်ကြည့်လေ့လာသည့်ကာလ၃
၂.၄ စောင့်ကြည့်လေ့လာသည့်နည်းလမ်း၃
၂.၅ စောင့်ကြည့်လေ့လာမှုရလဒ်များ၄
အခန်း ၃ နိဂုံးချုပ် နှင့် အကြံပြချက်များ၅
နောက်ဆက်တဲ့-၁ ဘန္တရီပျိုမျှလေထုအရည်အသွေးတန်ဖိုး၉၁-၁

အယားများစာရင်း

အယား ၁.၂-၁ လေထုအရည်အသွေးစောင့်ကြည့်လေ့လာသောအစီအစဉ်.....၁
အယား ၂.၂-၁ လေထုအရည်အသွေးစောင့်ကြည့်လေ့လာမှုရလဒ် (နောက်ပျိုမျှ)၅

ပုံများစာရင်း

ပုံ၂.၂-၁ လေထုအရည်အသွေးစောင့်ကြည့်လေ့လာသည့်တည်နေရာ၂
ပုံ၂.၄-၁ လေထုအရည်အသွေးစောင့်ကြည့်လေ့လာခြင်းအခြေအနေ၄
ပုံ၂.၅-၁ လေထုအရည်အသွေးစောင့်ကြည့်လေ့လာသောတည်နေရာ နှင့် လေတိဂ်ခတ်ရာအရပ်အခြေအနေ၆

သီလဝါအထူးစီးပွားရေးဇုန်အပိုင်း(က)ရှိစက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်ရေးအတွက်လေထာণည်အသွေးစောင့်ကြည့်လျှော့ခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ခုနှစ်)

အခန်း ၁ စောင့်ကြည့်လျှော့သောအစီအစဉ်နှင့်အကျဉ်းချုပ်

၁.၁ ယေဘုယျဖော်ပြချက်

သီလဝါအထူးစီးပွားရေးဇုန်သည် ရန်ကုန်တိုင်းဒေသကြီး၏ တောင်ပိုင်းခရိုင်တွင်တည်ရှိပြီး ရန်ကုန်မြို့၏ အရွှေတောင်ဘက် ၂၃ ကိုလိုပါတာတွင် တည်ရှိပါသည်။ သီလဝါအထူးစီးပွားရေးဇုန်၏ အကောင်အထည်ဖော်ဆောင်သူအနေဖြင့် ဇုန်အပိုင်း(က)အတွင်းရှိ စက်မှုမြေနေရာအတွက် ခွင့်ပြချက်ရရှိထားသော ပတ်ဝန်းကျင်ထိခိုက်မှုဆန်းစစ်ခြင်း အစီရင်ခံစာနှင့် ပတ်ဝန်းကျင်ဆိုင်ရာစီမံခန့်ခွဲမှုအစီအစဉ်အတိုင်း ပုံမှန်စောင့်ကြည့်စစ်ဆေးခြင်းကို ဆောင်ရွက်ရန် မြန်မာ-ဂျပန် သီလဝါဖွံ့ဖြိုးရေးလီမိတက်တွင် တာဝန်ရှိပါသည်။ မြန်မာ-ဂျပန် သီလဝါဖွံ့ဖြိုးရေးလီမိတက်သည် ဇုန်အတွင်းနှင့် အနီးပတ်ဝန်းကျင်ရှိ သဘာဝပတ်ဝန်းကျင် အခြေအနေများကို သိရှိစေရန် သဘာဝပတ်ဝန်းကျင်နှင့်သက်ဆိုင်သော အချက်အလက်စောင့်ကြည့် လျှော့လှုပ်နည်းလွှာ ရေးဆွဲထားပြီး ထိုအစီအစဉ်များအရ အကောင်အထည်ဖော် ဆောင်ရွက်ခဲ့ပါသည်။

၁.၂ စောင့်ကြည့်လျှော့သောအစီအစဉ်ဖော်ပြချက်များ

သီလဝါအထူးစီးပွားရေးဇုန် အပိုင်း(က) စက်မှုဇုန်လုပ်ငန်းလည်ပတ်နေခြင်းကြောင့် စက်မှုဇုန်အတွင်းနှင့်အပြင်ရှိပါသည်။ ပတ်ဝန်းကျင်အခြေအနေအား အကဲဖြတ်နိုင်ရန်အတွက် အောက်ပါယေားတွင် ဖော်ပြထားသည့်အတိုင်း ၂၀၂၁ခုနှစ်၊ စက်တင်ဘာလ ၇ ရက်နေ့မှ စက်တင်ဘာလ ၁၄ ရက်နေ့အထိ လေထာণည်အသွေးအား စောင့်ကြည့် လျှော့သောသည်။

ယေား ၁.၂-၁ လေထာণည်အသွေးစောင့်ကြည့်လျှော့သောအစီအစဉ်

စောင့်ကြည့်လျှော့ရေးရှင်း	စောင့်ကြည့်လျှော့မှုအမျိုးအစား	တိုင်းတာသော အမျိုးအစားများ	တိုင်းတာသောနေရာအရောအတွက်	ဤချိန်	စောင့်ကြည့်လျှော့သောနည်းလမ်း
ရရှိ စက်တင်ဘာလ - ၁၄ရက် စက်တင်ဘာလ၊ ၂၀၂၁ခုနှစ်	လေထာণည်အသွေး	ကာဗွန်နိုးနောက်ဆိုဒ်(CO)၊ နိုက်ထရိုဂျင်ဒိုင်အောက်ဆိုဒ်(NO ₂)၊ စပေါင်းအမှုန်အများ (TSP)၊ အမှုန်အများ (PM ₁₀) နှင့် ဆာလဟာဒိုင်အောက်ဆိုဒ် (SO ₂)	၁	၇ ရက်	ပတ်ဝန်းကျင်လေအရည်အသွေးတိုင်းတာသည့်စက်ကိုရှိယာ (Haz-Scanner EPAS) ဖြင့် မြေပြင်တွင်ကွင်းဆင်းတိုင်းတာခြင်းမှုပ်နည်း။

မှုပ်နည်း။ မြန်မာနိုင်ငံအင်တာနေရာင်နယ်လီမိတက်



သီလဝါအထူးစီးပွားရေးဇုန်အပိုင်း(က)ရှိစက်မှုဇုန်ဖြူးတိုးတက်ရေးအတွက်လေထာရည်အသွေးစောင့်ကြည့်လေ့လာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ | စက်တင်ဘာလ ၂၀၂၁ခုနှစ်)

အခန်း J လေထာရည်အသွေးစောင့်ကြည့်လေ့လာခြင်း

J.၁ စောင့်ကြည့်လေ့လာသည့်အမျိုးအစား

လေထာရည်အသွေး စောင့်ကြည့်လေ့လာသော အမျိုးအစားများမှာ ကာမွန်မိန္ဒာက်ဆိုဒ် (CO)၊ နိုက်ထရိဂုင်ဒိုင်အောက်ဆိုဒ် (NO_2)၊ စပေါင်းအမှုန်အမွား (TSP)၊ အမှုန်အမွား (PM_{10}) နှင့် ဆာလယာဒိုင်အောက်ဆိုဒ် (SO_2) တို့ဖြစ်သည်။

J.၂ စောင့်ကြည့်လေ့လာသည့်တည်နေရာ

ပတ်ဝန်းကျင်လေထာရည်အသွေးတိုင်းတာသည့် စက်ကိရိယာဖြစ်သည့် "Haz-Scanner Environmental Perimeter Air Station (EPAS)" ကို သီလဝါအထူးစီးပွားရေးဇုန်အပိုင်း(က)၏ အရှေ့တောင်ဘက်၊ မြောက်လွှို့တွင် ၁၆°၄၀'၂၈.၀၇"၊ အရှေ့လောင်ဂျိတွင် ၉၆°၁၆'၃၄.၀၆"၊ ပဟိုစွန်းထုတ်ရောသနစံစက်ရုံ ဝန်းထဲတွင် တပ်ဆင်ထားပြီး သီလဝါအထူးစီးပွားရေးဇုန်အပိုင်း(က)ရှိစက်ရုံများ၊ မြောက်ဘက်တွင် ဒရိ-သီလဝါလမ်းနှင့် အရှေ့မြောက်ဘက်တို့တွင် မိုးကြိုးစွမ်းဘုန်းကြီးကျောင်းတို့ဖြင့် ဝန်းရုံထားသည်။ အမိကလေထားညားမှုကို ဖြစ်နိုင်သောစွန်းထုတ်ဓာတ်ဓာတ်ဒွေးများ၊ ထုတ်လွှာတ်ရာအရင်းအမြစ်များမှာ ဇုန်အပိုင်း(က)ရှိစက်ရုံများ၏ ဆောက်လုပ်ရေးလုပ်ငန်းစဉ်များမှ ပုန်များထွက်ရှိခြင်း၊ ပတ်ဝန်းကျင်ရှိစက်ရုံများမှ ဓာတ်ဒွေးများ ထွက်ရှိခြင်းများကြောင့် ဖြစ်နိုင်ပါသည်။ လေထာရည်အသွေး စောင့်ကြည့်လေ့လာသောနေရာကို ပုံJ.J-၁ တွင်ပြသထားပါသည်။



မူရင်း၊ ဂူဂောတ်

ပုံJ.J-၁ လေထာရည်အသွေးစောင့်ကြည့်လေ့လာသည့်တည်နေရာ

သီလဝအထူးစီးပွားရေးဇုန်အပိုင်း(က)ရှိစက်မှုစုနှင့်ဖြီးတိုးတက်ရေးအတွက်လေထာရည်အသွေးစောင့်ကြည့်လေ့လာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ ၂၀၂၁ခုနှစ်)

J.၃ စောင့်ကြည့်လေ့လာသည့်ကာလ

လေထာရည်အသွေးစောင့်ကြည့်လေ့လာမှုကို ၂၀၂၁ ခုနှစ်၊ စက်တင်ဘာလ ၇ ရက်နေ့မှ စက်တင်ဘာလ ၁၄ရက်နေ့အထိ (၇)ရက်ဆက်တိုက် ဆောင်ရွက်ခဲ့သည်။

J.၄ စောင့်ကြည့်လေ့လာသည့်နည်းလမ်း

ပတ်ဝန်းကျင်လေထာရည်အသွေး စံနမူနာရယူခြင်းနှင့် ဆန်းစစ်လေ့လာခြင်းများကို အမေရိကန်ပတ်ဝန်းကျင်ဆိုင်ရာ ထိန်းသိမ်းရေးအောက်ဆိုင် (U.S. EPA) ၏ အကြံပြုချက်များကို ကိုးကား၍ ကာဗွန်မို့နောက်ဆိုင် (CO)၊ နှိုက်ထရိုဂျင်ဒိုင်အောက်ဆိုင် (NO₂)၊ စုပေါင်းအမှုန်အမွား (TSP)၊ အမှုန်အမွား (PM₁₀) နှင့် ဆာလ္ဗာဒိုင်အောက်ဆိုင် (SO₂)တို့အား စောင့်ကြည့်လေ့လာမှုများ လုပ်ဆောင်ခဲ့သည်။
ပတ်ဝန်းကျင်လေထာရည်အသွေးကို စောင့်ကြည့်တိုင်းတာ၍ အချက်အလက်ရယူရန်အတွက် The Haz-Scanner Environmental Perimeter Air Station (EPAS)ကို အသုံးပြုခဲ့ပါသည်။ လေထာရည်အသွေး အချက်အလက်များကို တစ်မိနစ်တိုင်း အလိုအလျောက်တိုင်းတာသည့် လေအရည်အသွေးအမျိုးအစား၏ အချက်အလက်များ (ကာဗွန်မို့နောက်ဆိုင် (CO))၊ နှိုက်ထရိုဂျင်ဒိုင်အောက်ဆိုင် (NO₂)၊ စုပေါင်းအမှုန်အမွား (TSP)၊ အမှုန်အမွား (PM₁₀) နှင့် ဆာလ္ဗာဒိုင်အောက်ဆိုင် (SO₂)) ကို မှတ်တမ်းတင် သိမ်းဆည်းထားပါသည်။ လေထာရည်အသွေးတိုင်းတာသည့်စက် နှင့် တိုင်းတာမှုများပြုလုပ်ရာတွင် ကောင်းမွန်စွာ လည်ပတ်စေရန် ပုံမှန် ထိန်းသိမ်းမှုများကို ပြုလုပ်ထားပါသည်။ မြန်မာနိုင်ငံရှိ ခွဲခြမ်းစိတ်ဖြာမှုများကိုလုပ်ဆောင်သောစက်များ၏ လုပ်ဆောင်နိုင်မှု ကန်သတ်ချက်များအရ စုပေါင်းအမှုန်အမွား (TSP)၏ ရလဒ်များကို အမှုန်အမွား (PM₁₀) ၏ရလဒ်များမှ အခြေခံ၍ ခန့်မှန်းခြေတန်ဖိုးများအဖြစ် တွက်ထားပါသည်။ ထို့ကြောင့်စုပေါင်းအမှုန်အမွား (TSP) ရလဒ်များကို ခန့်မှန်းခြေ စုပေါင်းအမှုန်အမွား (TSP) တန်ဖိုးများမှ သုံးသပ်ထားပါသည်။ လေထာရည်အသွေး စောင့်ကြည့်လေ့လာသော အခြေအနေကို ပုံ J.၄-၁တွင် ပြသထားပါသည်။



သီလဝါအထူးစီးပွားရေးဗိုင်အပိုင်း(က)၏မြှစက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်ရေးအတွက်လေထာရည်အသွေးစောင့်ကြည့်လေ့လာခြင်းအစီရင်ခဲ့စာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ခုနှစ်)



မူရင်း။မြှစ်မာနိအခင်တာနေ့ရှင်နယ်လီမိတက်

ပုံ၂.၄-၁ လေထာရည်အသွေးစောင့်ကြည့်လေ့လာခြင်းအခြေအနေ

၂.၅ စောင့်ကြည့်လေ့လာမှုရလဒ်များ

ကာွုနှစ်မိုးနှစ်နှစ် (CO)၊ နှိမ်ကိုယ်ခိုင်အောက်ဆိုင် (NO₂)၊ စုပေါင်းအမှုနှစ်အမွား (TSP)၊ အမှုနှစ်အမွား (PM₁₀) နှင့် ဆာလာဖိုင်အောက်ဆိုင် (SO₂) တို့၏ လေထာရည်အသွေး စောင့်ကြည့်လေ့လာမှုရလဒ်များမှ နေ့စဉ် ပျမ်းမျှတန်ဖိုးများကို ပေါ်လေသည်။ သီလဝါအထူးစီးပွားရေးဇုန် ဖွံ့ဖြိုးတိုးတက်ရေးစီမံကိန်း အပိုင်း(က)၏ ပတ်ဝန်းကျင်ထိနိုက်မှုဆန်းစစ်ခြင်းအစီအရင်ခံစာတွင်ပါရှိသည့် ကာွုနှစ်မိုးနှစ်နှစ် (CO)၊ နှိမ်ကိုယ်ခိုင်အောက်ဆိုင် (NO₂)၊ စုပေါင်းအမှုနှစ်အမွား (TSP)၊ အမှုနှစ်အမွား (PM₁₀) နှင့် ဆာလာဖိုင်အောက်ဆိုင် (SO₂) တို့၏ ရည်မှန်းတန်ဖိုးနှင့် နှိမ်းယူဉ်ရာ၏ ကာွုနှစ်မိုးနှစ်နှစ် (CO)၊ နှိမ်ကိုယ်ခိုင်အောက်ဆိုင် (NO₂)၊ စုပေါင်းအမှုနှစ်အမွား (TSP)၊ အမှုနှစ်အမွား (PM₁₀) နှင့် ဆာလာဖိုင်အောက်ဆိုင် (SO₂) တို့၏ (ဂ)ရက်ပျမ်းမျှတန်ဖိုးသည် ရည်မှန်းတန်ဖိုးထက်လျော့နည်းသည်ကို တွေ့ရှိရသည်။

ခန်းမှန်းမြေ စုပေါင်းအမှုနှစ်အမွား(TSP)ကို တွက်ချက်ခြင်းနှင့် စပ်လျဉ်း၍ ထိုင်းနိုင်ငံ၏ ပတ်ဝန်းကျင် လေထာရည်အသွေး လမ်းညွှန်ချက်မှ အမှုနှစ်အမွား(PM₁₀) နှင့် စုပေါင်းအမှုနှစ်အမွား(TSP)တို့၏ ဆက်စပ်မှုတန်ဖိုးကို အောက်တွင် ဖော်ပြထားပါသည်။

$$220 \text{ } \mu\text{g} / \text{m}^3 \text{ (ထိုင်းနိုင်ငံ၏ TSP စံတန်ဖိုး) } / 190 \text{ } \mu\text{g} / \text{m}^3 \text{ (ထိုင်းနိုင်ငံ၏ အမှုနှစ်အမွား (PM10) စံတန်ဖိုး) } = 1.11 \\ (\text{ဆက်စပ်မှုတန်ဖိုး})$$

သိလဝါအထူးစီးပွားရေးဇုန်အပိုင်း(က)ရှိစက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်ရေးအတွက်လေထားရည်အသွေးစောင့်ကြည့်လေ့လာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ခုနှစ်)

ပေါ်သူးများ လေထားရည်အသွေးစောင့်ကြည့်လေ့လာမှုရလဒ် (နေ့စဉ်ပျမ်းများ)

နေ့	ကာဓာန်စိုးနောက် ဆိုင် (CO)	နိုက်ထရိဂျင်ဆိုင် အောက်ဆိုင် (NO ₂)	စုပေါင်း အမှုန်အမွှား (TSP)	အမှုန်အမွှား (PM ₁₀)	ဆာလဖုံး အောက်ဆိုင် (SO ₂)
mg/m ³	mg/m ³	mg/m ³	mg/m ³	mg/m ³	mg/m ³
၀၈~၀၉ စက်တင်ဘာလ၊ ၂၀၂၁ခုနှစ်	၀.၀၄၉	၀.၀၄၁	၀.၀၃၄	၀.၀၁၂	၀.၀၃၃
၀၈~၀၉ စက်တင်ဘာလ၊ ၂၀၂၁ခုနှစ်	၀.၀၄၆	၀.၀၃၈	၀.၀၅၂	၀.၀၁၉	၀.၀၆၇
၀၉~၁၀ စက်တင်ဘာလ၊ ၂၀၂၁ခုနှစ်	၀.၀၅၆	၀.၀၄၁	၀.၀၅၉	၀.၀၁၁	၀.၀၂၅
၁၀~၁၁ စက်တင်ဘာလ၊ ၂၀၂၁ခုနှစ်	၀.၀၃၈	၀.၀၅၉	၀.၀၂၆	၀.၀၀၉	၀.၀၁၃
၁၁~၁၂ စက်တင်ဘာလ၊ ၂၀၂၁ခုနှစ်	၀.၀၃၃	၀.၀၈၀	၀.၀၃၆	၀.၀၀၃	၀.၀၁၃
၁၂~၁၃ စက်တင်ဘာလ၊ ၂၀၂၁ခုနှစ်	၀.၀၄၄	၀.၀၆၆	၀.၀၅၇	၀.၀၂၁	၀.၀၀၉
၁၃~၁၄ စက်တင်ဘာလ၊ ၂၀၂၁ခုနှစ်	၀.၀၃၂	၀.၀၃၈	၀.၀၅၀	၀.၀၂၅	၀.၀၂၇
(ဂ)ရက် ပျမ်းမျှတန်ဖိုး	၀.၀၄၃	၀.၀၆၄	၀.၀၄၃	၀.၀၁၆	၀.၀၃၈
ရည်မှန်းတန်ဖိုး	၁၁.၄၅	၀.၁၁	< ၀.၃၃	< ၀.၁၂	၀.၁၁

မှတ်ချက်၊ CO, NO₂ နှင့် SO₂ တို့၏ ရည်မှန်းတန်ဖိုးများကို (ppm) ယူနစ်မှ (mg/m³) ယူနစ်သို့ ပြောင်းလဲထားပါသည်။ ပြောင်းလဲမှုညီမြှုပ်းမှာ အောက်ပါအတိုင်းဖြစ်ပါသည်။

(၁) (CO, mg/m³) = (CO, ppm) * (CO မော်လီကျူးမှုအလေးချိန် (၂၀)) / ၂၄.၄၅ (အပူချိန် ၂၂ ဒီဂရီစုစုတိတက်နှင့် ၁ atm အကြောင်း)

(၂) (NO₂, mg/m³) = (NO₂, ppm) * (NO₂ မော်လီကျူးမှုအလေးချိန် (၄၆)) / ၂၄.၄၅ (အပူချိန် ၂၂ ဒီဂရီစုစုတိတက်နှင့် ၁ atm အကြောင်း)


(၃) (SO₂, mg/m³) = (SO₂, ppm) * (SO₂ မော်လီကျူးမှုအလေးချိန် (၆၄)) / ၂၄.၄၅ (အပူချိန် ၂၂ ဒီဂရီစုစုတိတက်နှင့် ၁ atm အကြောင်း)

မူရင်း။ မြန်မာစိုးအောင်တာနေရာင်နယ်လိပ်တက်

လေထားရည်အသွေးစောင့်ကြည့်လေ့လာသည့် နေရာ-၁ (AQ-1)တွင် လေတိုက်ခတ်ရာအရပ်နှင့် လေတိုက်နှုန်းကို တိုင်းတာ့ပါသည်။ တိုင်းတာထားသော လေတိုက်ခတ်ရာအရပ်နှင့် လေတိုက်နှုန်းတို့၏ တစ်နာရီပျမ်းများ တန်ဖိုးများကို နောက်ဆက်တွဲ-၁ တွင်ဖော်ပြထားပါသည်။ လေထားရည်အသွေး စောင့်ကြည့်လေ့လာသော တည်နေရာ၏ အကြောင်းနှင့် လေတိုက်ခတ်ရာအရပ်တို့အား ပုံ၂၂-၁တွင် ပြထားပါသည်။



သီလဝအထူးစီးပွားရေးဦးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုဇန်ဖွံ့ဖြိုးတိုးတက်ရေးအတွက်လေထုအရည်အသွေးစောင့်ကြည့်လေလာခြင်းအစိရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ခုနှစ်)



မူရင်း။ ရှုံးအတ်

ပုံး၂-၁ လေထုအရည်အသွေးစောင့်ကြည့်လေလာသောတည်နေရာ နှင့် လေတိုက်ခတ်ရာအရပ်အခြေအနေ

မှတ်ချက်။ မြောက်(N) မြောက်-အရှုံးမြောက်(NNE) အရှုံးမြောက်(NE) အရှုံး-မြောက်(ENE) အရှုံး(E) အရှုံး-အရှုံးတောင်(ESE) အရှုံးတောင်(SE) တောင်-အရှုံးတောင်(SSE) တောင်(S) တောင်-အနောက်တောင်(SSW) အနောက်တောင်(SW) အနောက်-အနောက်တောင်(WSW) အနောက်(W) အနောက်-အနောက်မြောက်(WNW) အနောက်မြောက်(NW) မြောက်-အနောက်မြောက်(NNW)

သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုနှင့်ဖြိုးတက်ရေးအတွက်လေထာရည်အသွေးစောင့်ကြည့်လေလာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ခုနှစ်)

အခန်း ၃ နိဂုံးပျော် နှင့် အကြံပြုချက်များ


သီလဝါအထူးစီးပွားရေးဇုန် အပိုင်း(က)၏ လုပ်ငန်းလည်ပတ်နေစဉ်ကာလအတွင်း စက်မှုမြန်အတွင်းရှိ
ပတ်ဝန်းကျင်အခြေအနေအား သီရိနှင့်ရန်အတွက် ပုံမှန်စောင့်ကြည့်လေ့လာခြင်းကို လုပ်စောင်ရန်
လိုအပ်ပါသည်။ ပုံမှန်စုဆောင်းရရှိထားသော ပတ်ဝန်းကျင်ဆိုင်ရာအချက်အလက်များကို အပြော်၍ နောင်တွင်
ပတ်ဝန်းကျင်စီမံခိန့်ခွဲမှုအတွက် ဆိုးကျိုးလျော့ပါးသက်သာစေမည့် နည်းလမ်းများကို ပြန်လည်
သုံးသပ်သွားမည်ဖြစ်ပါသည်။



နောက်ဆက်တွဲ-၁ ၁နာရီပျမ်းမျှလေထုအရည်အသွေးတန်ဖိုး




သိလင်အထူးပိုးများရေးနှစ်အပိုင်း(က)ရှိစက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်ရေးအတွက်လေအရည်အသွေးစောင့်ကြည့်လေလာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ခုနှစ်)



သီလဝအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်ရေးအတွက်လေထာণည်အသွေးစောင့်ကြည့်လေ့လာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ခုနှစ်)


နေရက်	အချိန်	ကာမွန်မို့နောက်လိုင် (CO)	နိုက်ထရိုဂျင်နှင့်အောက်လိုင် (NO ₂)		စုပေါင်းအမှုနှုန်းအမွှား (TSP)		အမှုနှုန်းအမွှား (PM ₁₀)		ဆာလဖွံ့ဖြိုးအောက်လိုင် (SO ₂)		လေတိုက်နှုန်း		လေတိုက်ခတ်ရာအရှည်	
			mg/m ³	mg/m ³	mg/m ³	mg/m ³	mg/m ³	mg/m ³	mg/m ³	m/s	Deg.	အရပ်မျက်နှာ	အရပ်မျက်နှာ	
			သနာရီပျမ်းမျှ	သနာရီပျမ်းမျှ	သနာရီပျမ်းမျှ	သနာရီပျမ်းမျှ	သနာရီပျမ်းမျှ	သနာရီပျမ်းမျှ	သနာရီပျမ်းမျှ	သနာရီပျမ်းမျှ	သနာရီပျမ်းမျှ	သနာရီပျမ်းမျှ	သနာရီပျမ်းမျှ	
၁၀ရက် စက်တင်ဘာလ၊ ၂၀၂၁ ခုနှစ်	၁၁:၀၀ ~ ၁၁:၅၉	၀.၀၇၃	၀.၀၄၅	၀.၀၄၅	၀.၀၄၃	၀.၀၁၃	၀.၀၁၃	၀.၀၁၃	၀.၀၁၃	၈.၈၈	၁၄၄.၅၂	အရှေ့တောင်	အရှေ့တောင်	
၁၀ရက် စက်တင်ဘာလ၊ ၂၀၂၁ ခုနှစ်	၁၂:၀၀ ~ ၁၂:၅၉	၀.၀၇၅	၀.၀၄၃	၀.၀၆၄	၀.၀၂၃	၀.၀၁၃	၀.၀၁၃	၀.၀၁၃	၀.၀၁၃	၈.၈၈	၁၃၈.၃၀	အရှေ့တောင်	အရှေ့တောင်	
၁၀ရက် စက်တင်ဘာလ၊ ၂၀၂၁ ခုနှစ်	၁၃:၀၀ ~ ၁၃:၅၉	၀.၀၇၆	၀.၀၁၅	၀.၀၀၅	၀.၀၀၂	၀.၀၁၃	၀.၀၁၃	၀.၀၁၃	၀.၀၁၃	၈.၈၀	၁၄၄.၅၂	အရှေ့တောင်	အရှေ့တောင်	
၁၀ရက် စက်တင်ဘာလ၊ ၂၀၂၁ ခုနှစ်	၁၄:၀၀ ~ ၁၄:၅၉	၀.၀၇၇	၀.၀၄၅	၀.၀၄၅	၀.၀၄၃	၀.၀၁၅	၀.၀၁၅	၀.၀၁၅	၀.၀၁၅	၈.၈၈	၁၄၄.၅၂	အရှေ့တောင်	အရှေ့တောင်	
၁၀ရက် စက်တင်ဘာလ၊ ၂၀၂၁ ခုနှစ်	၁၅:၀၀ ~ ၁၅:၅၉	၀.၀၇၈	၀.၀၂၈	၀.၀၂၈	၀.၀၂၈	၀.၀၁၀	၀.၀၁၀	၀.၀၁၀	၀.၀၁၀	၈.၈၈	၁၄၀.၆၆	တောင်-အရှေ့တောင်	တောင်-အရှေ့တောင်	
၁၀ရက် စက်တင်ဘာလ၊ ၂၀၂၁ ခုနှစ်	၁၆:၀၀ ~ ၁၆:၅၉	၀.၀၇၉	၀.၀၂၆	၀.၀၆၄	၀.၀၁၄	၀.၀၁၄	၀.၀၁၄	၀.၀၁၄	၀.၀၁၄	၈.၈၈	၁၄၂.၂၀	တောင်-အရှေ့တောင်	တောင်-အရှေ့တောင်	
၁၀ရက် စက်တင်ဘာလ၊ ၂၀၂၁ ခုနှစ်	၁၇:၀၀ ~ ၁၇:၅၉	၀.၀၇၀	၀.၀၂၈	၀.၀၂၈	၀.၀၂၈	၀.၀၁၁	၀.၀၁၁	၀.၀၁၁	၀.၀၁၁	၈.၈၈	၁၄၂.၂၀	တောင်-အရှေ့တောင်	တောင်-အရှေ့တောင်	
၁၀ရက် စက်တင်ဘာလ၊ ၂၀၂၁ ခုနှစ်	၁၈:၀၀ ~ ၁၈:၅၉	၀.၀၇၁	၀.၀၂၈	၀.၀၂၈	၀.၀၂၈	၀.၀၁၁	၀.၀၁၁	၀.၀၁၁	၀.၀၁၁	၈.၈၈	၁၄၂.၂၀	တောင်-အရှေ့တောင်	တောင်-အရှေ့တောင်	
၁၀ရက် စက်တင်ဘာလ၊ ၂၀၂၁ ခုနှစ်	၁၉:၀၀ ~ ၁၉:၅၉	၀.၀၇၂	၀.၀၂၈	၀.၀၂၈	၀.၀၂၈	၀.၀၁၁	၀.၀၁၁	၀.၀၁၁	၀.၀၁၁	၈.၈၈	၁၄၂.၂၀	တောင်-အရှေ့တောင်	တောင်-အရှေ့တောင်	
၁၀ရက် စက်တင်ဘာလ၊ ၂၀၂၁ ခုနှစ်	၂၀:၀၀ ~ ၂၀:၅၉	၀.၀၇၃	၀.၀၂၈	၀.၀၂၈	၀.၀၂၈	၀.၀၁၁	၀.၀၁၁	၀.၀၁၁	၀.၀၁၁	၈.၈၈	၁၄၂.၂၀	တောင်-အရှေ့တောင်	တောင်-အရှေ့တောင်	
၁၀ရက် စက်တင်ဘာလ၊ ၂၀၂၁ ခုနှစ်	၂၁:၀၀ ~ ၂၁:၅၉	၀.၀၇၄	၀.၀၂၈	၀.၀၂၈	၀.၀၂၈	၀.၀၁၁	၀.၀၁၁	၀.၀၁၁	၀.၀၁၁	၈.၈၈	၁၄၄.၅၂	အရှေ့တောင်	အရှေ့တောင်	
	အများဆုံး	၀.၀၇၆	၀.၁၅၇	၀.၁၅၇	၀.၁၅၇	၀.၀၁၅	၀.၀၁၅	၀.၀၁၅	၀.၀၁၅	၈.၈၈	၁၄၄.၅၂			
	ပြုးမျှ	၀.၀၂၈	၀.၀၂၉	၀.၀၂၉	၀.၀၂၉	၀.၀၁၅	၀.၀၁၅	၀.၀၁၅	၀.၀၁၅	၈.၈၈	၁၄၀.၆၆			
	အနည်းဆုံး	၀.၀၂၄	၀.၀၂၄	၀.၀၂၄	၀.၀၂၄	၀.၀၁၀	၀.၀၁၀	၀.၀၁၀	၀.၀၁၀	၈.၈၈	၁၄၂.၂၀			

သီလဝါအထူးဦးပွားရေးနှစ်အပိုင်း(က)ရှုစက်မှုနှစ်ဖွံ့ဖြိုးတိုးတက်ရေးအတွက်လေထားရည်အသွေးစောင့်ကြည့်လေ့လာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ခုနှစ်)



သီလဝတိအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်ရေးအတွက်လေထာရည်အသွေးစောင့်ကြည့်လေလာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ခုနှစ်)

သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှုစက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်ရေးအတွက်လေထာကြည့်အသွေးစောင့်ကြည့်လေလာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ခုနှစ်)



သီလဝါအထူးစီးပွားရေးဇုန် အပိုင်း(က)ရှိ
စက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်ရေးအတွက်
ဆူညံသံ နှင့် တုန်ခါမှု စောင့်ကြည့်လေ့လာခြင်း အစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ)

(တစ်နှစ် နှစ်ကြိမ်စောင့်ကြည့်လေ့လာခြင်း)

၂၀၂၁ ခုနှစ်၊ စက်တင်ဘာလ^{၁၁}
မြန်မာနိုင် အင်တာနေရာင်နယ် လီမိတက်



မာတိကာ

အခန်း ၁	စောင့်ကြည့်လေ့လာသော အစီအစဉ်နှင့်အကျဉ်းချုပ်	၁
၁.၁	ယော်ယျာဖော်ပြချက်	၁
၁.၂	စောင့်ကြည့်လေ့လာသော အစီအစဉ်ဖော်ပြချက်များ	၁
အခန်း ၂	ဆူညံသံနှင့်တုန်ခါမှု စောင့်ကြည့်လေ့လာခြင်း	၂
၂.၁	စောင့်ကြည့်လေ့လာသည့် အမျိုးအစား	၂
၂.၂	စောင့်ကြည့်လေ့လာသည့် တည်နေရာ	၂
၂.၃	စောင့်ကြည့်လေ့လာသည့် နည်းလစ်း	၄
၂.၄	စောင့်ကြည့်လေ့လာမှု ရလဒ်များ	၆
အခန်း ၃	နိဂုံးချုပ်နှင့်အကြံပြချက်များ	၁၈

ဇယားများစာရင်း

ဇယား ၁-၁	ဆူညံသံနှင့်တုန်ခါမှုအဆင့် စောင့်ကြည့်လေ့လာသောအစီအစဉ်	၁
ဇယား ၂-၁	ဆူညံသံနှင့်တုန်ခါမှုအဆင့် စောင့်ကြည့်လေ့လာသောအမျိုးအစားများ	၂
ဇယား ၂-၂	(NV-1) ၏ဆူညံသံအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်များ (LA _{eq})	၆
ဇယား ၂-၂	(NV-2) ၏ဆူညံသံအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်များ (LA _{eq})	၆
ဇယား ၂-၃	(NV-3) ၏ဆူညံသံအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်များ (LA _{eq})	၇
ဇယား ၂-၄	(NV-1) ၏နာရီအလိုက်ဆူညံသံအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်များ (LA _{eq})	၇
ဇယား ၂-၅	(NV-2) ၏နာရီအလိုက်ဆူညံသံအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်များ (LA _{eq})	၈
ဇယား ၂-၆	(NV-3) ၏နာရီအလိုက်ဆူညံသံအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်များ (LA _{eq})	၉
ဇယား ၂-၇	(NV-1) ၏တုန်ခါမှုအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်များ (Lv ₁₀)	၁၂
ဇယား ၂-၈	(NV-2) ၏တုန်ခါမှုအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်များ (Lv ₁₀)	၁၂
ဇယား ၂-၉	(NV-3) ၏တုန်ခါမှုအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်များ (Lv ₁₀)	၁၃
ဇယား ၂-၁၀	(NV-1) ၏နာရီအလိုက်တုန်ခါမှုအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်များ (Lv ₁₀)	၁၃
ဇယား ၂-၁၁	(NV-2) ၏နာရီအလိုက်တုန်ခါမှုအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်များ (Lv ₁₀)	၁၄
ဇယား ၂-၁၂	(NV-3) ၏နာရီအလိုက်တုန်ခါမှုအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်များ (Lv ₁₀)	၁၅

ပုံများစာရင်း

ပုံ.၂-၁ ဆူညံသံနှင့်တုန်ခါမှူ စောင့်ကြည့်လေ့လာသည့်တည်နေရာများ.....	၃
ပုံ.၃-၁ ဆူညံသံနှင့်တုန်ခါမှူအဆင့် စောင့်ကြည့်လေ့လာမှုအခြေအနေ.....	၅
ပုံ.၄-၁ နေရာ-၁ (NV-1) ၏ဆူညံသံအဆင့်စောင့်ကြည့်လေ့လာမှုရလဒ်	၁၀
ပုံ.၄-၂ နေရာ-၂ (NV-2) ၏ဆူညံသံအဆင့်စောင့်ကြည့်လေ့လာမှုရလဒ်	၁၀
ပုံ.၄-၃ နေရာ-၃ (NV-3) ၏ဆူညံသံအဆင့်စောင့်ကြည့်လေ့လာမှုရလဒ်	၁၁
ပုံ.၅-၁ နေရာ-၁ (NV-1) ၏တုန်ခါမှူအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်	၁၆
ပုံ.၅-၂ နေရာ-၂ (NV-2) ၏တုန်ခါမှူအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်	၁၆
ပုံ.၅-၃ နေရာ-၃ (NV-3) ၏တုန်ခါမှူအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်	၁၇

(j)



သီလဝါအထူးစီးပွားရေးဗိန်အပိုင်း(က)ရှိစက်မှုဇာတ်ဖြူးပြီးတက်မှုအတွက်ဆူညံသံနှင့်တုန်ခါမှုစောင့်ကြည့်လေ့လာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ ခုနှစ်)

အခန်း ၁ စောင့်ကြည့်လေ့လာသော အစီအစဉ်နှင့်အကျဉ်းချုပ်

၁.၁ ယော့ယျဖော်ပြချက်

သီလဝါအထူးစီးပွားရေးဗိန်သည် ရန်ကုန်တိုင်းဒေသကြီး၏ တောင်ပိုင်းခရိုင်တွင်တည်ရှိပြီး ရန်ကုန်ဖြူးပြီး၏ အရွှေတောင်ဘက် ၂၃ ကိုလိမ့်တာတွင် တည်ရှိပါသည်။ သီလဝါအထူးစီးပွားရေးဗိန်၏ အကောင်အထည်ဖော်ဆောင်သူအနေဖြင့် ဗိန်အပိုင်း(က)အတွင်းရှိ စက်မှုမြေနေရာများအတွက် ခွင့်ပြုချက်ရရှိထားသော ပတ်ဝန်းကျင်ထိခိုက်မှုဆန်းစစ်ခြင်း အစီရင်ခံစာနှင့် ပတ်ဝန်းကျင်ဆိုင်ရာစီမံခန့်ခွဲမှုအစီအစဉ်အတိုင်း ပုံမှန်စောင့်ကြည့်စစ်ဆေးခြင်းကို ဆောင်ရွက်ရန် မြန်မာ-ဂျပန် သီလဝါဖွံ့ဖြိုးရေးလီမိတက်သည် ဗိန်အတွင်းနှင့် အနီးပတ်ဝန်းကျင်ရှိ သဘာဝပတ်ဝန်းကျင် အခြေအနေများကို သိရှိစေရန် သဘာဝပတ်ဝန်းကျင်နှင့်သက်ဆိုင်သော အချက်အလက် စောင့်ကြည့် လေ့လာမှုများကို ရေးဆွဲပြီး ထိုအစီအစဉ်များအရ အကောင်အထည်ဖော် ဆောင်ရွက်ခဲ့ပါသည်။

၁.၂ စောင့်ကြည့်လေ့လာသော အစီအစဉ်ဖော်ပြချက်များ

သီလဝါအထူးစီးပွားရေးဗိန် အပိုင်း(က) စက်မှုဇာတ်လုပ်ငန်းလည်ပတ်နေခြင်းကြောင့် စက်မှုဇာတ်အတွင်းနှင့်အပြင်ရှိ ပတ်ဝန်းကျင်အခြေအနေအား အကဲဖြတ်နိုင်ရန်အတွက် အောက်ပါယေးတွင် ဖော်ပြထားသည့်အတိုင်း ၂၀၂၁ ခုနှစ်၊ စက်တင်ဘာလ ၇ ရက်နေ့မှ စက်တင်ဘာလ ၉ ရက်နေ့အထိ ဆူညံသံနှင့်တုန်ခါမှုအဆင့်အား စောင့်ကြည့် လေ့လာခဲ့သည်။

ယေား၁.၂-၁ ဆူညံသံနှင့်တုန်ခါမှုအဆင့် စောင့်ကြည့်လေ့လာသောအစီအစဉ်

စောင့်ကြည့်လေ့လာရေးရက်စွဲ	စောင့်ကြည့်လေ့လာမှုအနီးအစား	တိုင်းတာသောအနီးအစားများ	တိုင်းတာသောနေရာအရေအတွက်	ကြောချိန်	စောင့်ကြည့်လေ့လာသောနည်းလမ်း
၂၀၂၁ ခုနှစ်၊ စက်တင်ဘာလ ၇ရက်နေ့	ဆူညံမှုအဆင့်	LA _{eq} (dB)	၁ (NV-1)	၈ နာရီ	Rion NL-42 အသေအဆင့်တိုင်းတာသည့်ကိရိယာဖြင့် မြေပြင်တွင်ကွင်းဆင်းတိုင်းတာခြင်း
၂၀၂၁ ခုနှစ်၊ စက်တင်ဘာလ ၉ရက်နေ့	ဆူညံမှုအဆင့်	LA _{eq} (dB)	၁ (NV-2)	၈ နာရီ	Rion NL-42 အသေအဆင့်တိုင်းတာသည့်ကိရိယာဖြင့် မြေပြင်တွင်ကွင်းဆင်းတိုင်းတာခြင်း
၂၀၂၁ ခုနှစ်၊ စက်တင်ဘာလ ၈ရက်နေ့	ဆူညံမှုအဆင့်	LA _{eq} (dB)	၁ (NV-3)	၈ နာရီ	Rion NL-42 အသေအဆင့်တိုင်းတာသည့်ကိရိယာဖြင့် မြေပြင်တွင်ကွင်းဆင်းတိုင်းတာခြင်း
၂၀၂၁ ခုနှစ်၊ စက်တင်ဘာလ ၇ရက်နေ့	တုန်ခါမှုအဆင့်	L _{v10} (dB)	၁ (NV-1)	၈ နာရီ	VM-53A တုန်ခါမှုအဆင့်တိုင်းတာသည့်ကိရိယာဖြင့် မြေပြင်တွင်ကွင်းဆင်းတိုင်းတာခြင်း
၂၀၂၁ ခုနှစ်၊ စက်တင်ဘာလ ၉ရက်နေ့	တုန်ခါမှုအဆင့်	L _{v10} (dB)	၁ (NV-2)	၈ နာရီ	VM-53A တုန်ခါမှုအဆင့်တိုင်းတာသည့်ကိရိယာဖြင့် မြေပြင်တွင်ကွင်းဆင်းတိုင်းတာခြင်း
၂၀၂၁ ခုနှစ်၊ စက်တင်ဘာလ ၈ရက်နေ့	တုန်ခါမှုအဆင့်	L _{v10} (dB)	၁ (NV-3)	၈ နာရီ	VM-53A တုန်ခါမှုအဆင့်တိုင်းတာသည့်ကိရိယာဖြင့် မြေပြင်တွင်ကွင်းဆင်းတိုင်းတာခြင်း

မှုရင်း၊ မြန်မာစိန္ဒာရေးနှင့်နယ်လီမိတက်

သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုဇုန်ဖွံ့ဖြိုးတက်မှုအတွက်ဆူညံသံနှင့်တုန်ခါမှုစောင့်ကြည့်လေ့လာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ ခုနှစ်)

အခန်း J ဆူညံသံနှင့်တုန်ခါမှု စောင့်ကြည့်လေ့လာခြင်း

J.C စောင့်ကြည့်လေ့လာသည့် အမျိုးအစား

ဆူညံသံနှင့်တုန်ခါမှုစောင့်ကြည့်လေ့လာသော အမျိုးအစားများအား ပေါ်ပြုထားပါသည်။

ပေါ်ပြုထားပါသည်။

စဉ်	စောင့်ကြည့်လေ့လာမှု	အမျိုးအစား
C	ဆူညံသံ	အသံကြိမ်နှင့် "အေ"နှင့် ညီမျှသော ကျယ်လောင်မှု (LAeq)
J	တုန်ခါမှု	တုန်ခါမှုအဆင့် (L _{v10})

မူရင်း။ မြန်မာနိအဲအင်တာနေရာင်နယ်လီမိတက်

J.J စောင့်ကြည့်လေ့လာသည့် တည်နေရာ


ဆူညံသံနှင့်တုန်ခါမှု စောင့်ကြည့်လေ့လာခဲ့သည့် တည်နေရာများကို ပေါ်ပြုထားပါသည်။ ပေါ်ပြုထားပါသည်။ ဆူညံသံနှင့်တုန်ခါမှု စောင့်ကြည့်လေ့လာခဲ့သည့် တည်နေရာများကို ပုံ J.J-၁ တွင် ပြသထားပါသည်။

ပေါ်ပြုထားပါသည်။

တိုင်းတာသောနေရာ	တည်နေရာများ	တိုင်းတာသောနေရာများ၏ တည်နေရာဖော်ပြချက်
နေရာ-C (NV-1)	မြောက်လတ္တိတွဒ် - ၁၆°၄၀'၁၁.၅၀"၊ အရှေ့လောင်ဂျိတွဒ် - ၉၆°၁၆' ၃၂.၀၀"	သီလဝါစီးပွားရေးစက်မှုဇုန်အပိုင်း(က)၏ အုပ်ချုပ်ရေးရုံး၊ အဆောက်အအုံ အရှေ့
နေရာ-J (NV-2)	မြောက်လတ္တိတွဒ် - ၁၆°၄၀'၅၂.၅၀"၊ အရှေ့လောင်ဂျိတွဒ် - ၉၆°၁၆' ၅၅.၅၀"	သီလဝါစီးပွားရေးစက်မှုဇုန်အပိုင်း(က)၏ အရှေ့အရပ်
နေရာ-၃ (NV-3)	မြောက်လတ္တိတွဒ် - ၁၆°၄၀'၄၆.၂၀"၊ အရှေ့လောင်ဂျိတွဒ် - ၉၆°၁၇' ၃၀.၁၀"	သီလဝါစီးပွားရေးစက်မှုဇုန်အပိုင်း(က)၏ အနောက်အရပ်၊ အလွမ်းဆွတ် ကျေးမှုရှိလူနေအိမ်ခြေများနှင့် အနီးဆုံးနေရာ

မူရင်း။ မြန်မာနိအဲအင်တာနေရာင်နယ်လီမိတက်





မူးကြော်မှု ဂုဏ်သွင်းအကို

ဗုံး J.J-၁ ဆူညံသံနှင့်တုန်ခါမှု စောင့်ကြည့်လေ့လာသည့်နေရာများ

ဆူညံသံနှင့်တုန်ခါမှု စောင့်ကြည့်လေ့လာသည့်နေရာ-၁ (NV-1)

စောင့်ကြည့်လေ့လာသည့် နေရာ-၁ (NV-1)သည် သီလဝါအထူးစီးပွားရေးဗိုလ်ချုပ်ရေးရုံးအဆောက်အအုံ အရှေ့နှင့် ဒရို-သီလဝါ လမ်းဘေးတွင်တည်ရှိပြီး၊ ဤလမ်းသည် နောက်နှင့်ညွှန်ပြုရှိထဲတွင် ဝန်တင်ယာ၏များ နှင့် ထပ်ကားများ အသွေးအလာများသော လမ်းဖြစ်ပါသည်။ ဤ စောင့်ကြည့် လေ့လာသည့် နေရာ၏ အဓိက ဆူညံသံနှင့်တုန်ခါမှု ဖြစ်နိုင်သော အရင်းအမြစ်များမှာ နောက်နှင့်ညွှန်ပြုရှိထဲတွင် အတွင်း ယာဉ်သွားလာမှုများ ကြောင့်ဖြစ်နိုင်ပါသည်။

ဆူညံသံနှင့်တုန်ခါမှု စောင့်ကြည့်လေ့လာသည့်နေရာ-၂ (NV-2)

စောင့်ကြည့်လေ့လာသည့် နေရာ-၂ (NV-2) သည် သီလဝါအထူးစီးပွားရေးဗိုလ်ချုပ် အပိုင်း(က)၏ အရှေ့ဘက် တွင်တည်ရှိပြီး၊ အနောက်ဘက်တွင် သီလဝါဆည်နှင့် အနောက်မြောက်ဘက်တွင်သီလဝါအထူးစီးပွားရေးဗိုလ်ချုပ် အပိုင်း(က) ရှိ ဆောက်လုပ်နေသော စက်ရုံများတည်ရှုပါသည်။ ဤစောင့်ကြည့် လေ့လာသည့်နေရာ၏ အဓိကဆူညံသံနှင့်တုန်ခါမှု ဖြစ်နိုင်သော အရင်းအမြစ်များမှာ ရှိနိုင်း(က)ရှိ လည်ပတ်နေသောလုပ်ငန်းများနှင့် ယာဉ်သွားလာမှုများ ကြောင့်ဖြစ်နိုင်ပါသည်။ စောင့်ကြည့်လေ့လာသည့် နေရာ-၂ (NV-2) ၏ အရှေ့ဘက်တွင် လမ်းတစ်လမ်းတည်ရှုနေပါသည်။

ဆူညံသံနှင့်တုန်ခါမှု စောင့်ကြည့်လေ့လာသည့်နေရာ-၃ (NV-3)

စောင့်ကြည့်လေ့လာသည့် နေရာ-၃ (NV-3) သည် သီလဝါအထူးစီးပွားရေးဇာတ်ခုပြုမှုအဖွဲ့မြို့တောင်းစာရင်း(က)၏အနောက်ဘက်တွင်တည်ရှိပြီး မြောက်ဘက်တွင် အလွမ်းဆွတ်ကျေးရွာရှိ လူနေအိမ်ခြေများနှင့် အနောက်မြောက်ဘက်တွင် အထည်ချုပ်စက်ရှိ၊ အရှေ့ဘက်တွင် သီလဝါအထူးစီးပွားရေးဇာတ်ခုပြုမှုအဖွဲ့မြို့တောင်းစာရင်း(က)၏ဆောက်လုပ်နေသော စက်ရုံများ အသီးသီး ဝန်းရုံနေပါသည်။ ဤစောင့်ကြည့် လေ့လာသည့်နေရာ၏ အမိုက်ဆူညံသံနှင့်တုန်ခါမှု ဖြစ်နိုင်သော အရင်းအမြစ်များမှာ ဇုန်အပိုင်း(က)ရှိ လည်ပတ်နေသောလုပ်ငန်းများနှင့် ဆောက်လုပ်ရေးလုပ်ငန်းများ ကြောင့်ဖြစ်နိုင်ပါသည်။ အခြား ဆူညံသံနှင့်တုန်ခါမှု ဖြစ်စောင့်သည့် အကြောင်းအရင်းများမှာ ယာဉ်သွားလာမှုများ နှင့် အလွမ်းဆွတ်ကျေးရွာရှိ နေထိုင်သူများ၏ နေစဉ်လုပ်ငန်းဆောင်တာများကြောင့် ဖြစ်နိုင်ပါသည်။ စောင့်ကြည့်လေ့လာသည့် နေရာ-၃ (NV-3) ၏ အရှေ့တောင်ဘက်တွင် လမ်းတစ်လမ်းတည်ရှုနေပါသည်။

J.၃ စောင့်ကြည့်လေ့လာသည့် နည်းလမ်း

ဆူညံသံအဆင့်အား “Rion NL-42 အသံအဆင့်တိုင်းတာသည့်ကိရိယာ” ဖြင့်တိုင်းတာပြီး ၁၀မိနစ်တိုင်းအလိုအလျောက်တိုင်းတာပြီး စက်အတွင်းရှိ မန်မိရှိက်ခံအတွင်း မှတ်သားထားပါသည်။ တုန်ခါမှုအဆင့်တိုင်းတာသည့် ကိရိယာ “Rion VM-53A” ဝင်ရှိသုံးခုပါဝင်သော တုန်ခါမှုအဆင့် သတ်မှတ်သည့် ကိရိယာအား မြေကြီးပေါ်တွင် ထားရှုပါသည်။ တုန်ခါမှု (L_v)အား နေရာ-၁ (NV-1)၊ နေရာ-၂ (NV-2)နှင့် နေရာ-၃ (NV-3)တို့၌ အလိုက်သုံး ပြောင်းလဲနိုင်သောအဆင့် (၁၀-၇၀) dB အတွင်းထားရှိပြီး ၁၀ မိနစ်တိုင်း အလိုအလျောက်တိုင်းတာပြီး စက်အတွင်းရှိ မန်မိရှိက်ခံအတွင်း မှတ်သားထားပါသည်။ စောင့်ကြည့်လေ့လာသော နေရာတစ်ခုစီတွင် ဆူညံသံနှင့်တုန်ခါမှု စောင့်ကြည့်လေ့လာမှုအား ၈ နာရီတိုင်းတာပါသည်။ နေရာ-၁ (NV-1)၊ နေရာ-၂ (NV-2)နှင့် နေရာ-၃ (NV-3) ရှိ ဆူညံသံနှင့်တုန်ခါမှုအဆင့် စောင့်ကြည့် လေ့လာသောအခြေအနေကို ပုံ J.၃-၁ တွင် ပြသထားပါသည်။



သီလဝါအထူးစီးပွားရေးဗိုလ်ချုပ်(က)ရှိစက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်မှုအတွက်ဆူညံသံနှင့်တုန်ခါမှုစောင့်ကြည့်လေ့လာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ ခုနှစ်)



မူရင်း။ မြန်မာနိအဲအင်တာနေဂျင်နယ်လိပ်တက်

ပုံ ၂.၃-၁ ဆူညံသံနှင့်တုန်ခါမှုအဆင့် စောင့်ကြည့်လေ့လာမှုအခြေအနေ

သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိမက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်မှုအတွက်ဆုည်သံပိုင်တုန်ခါမှုစောင့်ကြည့်လျေလာခြင်းအတိရှင်ခံစာ
(လုပ်ငန်းလည်ပပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ ခုနှစ်)

J.C ଟୋଣ୍ଡି କ୍ରିସ୍ତ ଲେଖାମ୍ବ ରଲାନ୍ତମ୍ବା:

ဆူသုသံစောင့်ကြည့်လျှော့လာမှုရလဒ်များ

ይሬ፡ J.C-1 ቁጥር-1 (NV-1) ንግድናውን የሚከተሉት በለምሳሌ ማረጋገጫዎች (LA_{eq})

ရက်စွဲ	ယူ၍အသွားအလာကြောင့်ဖြစ်ပေါ်သောဆူညံသံအဆင့် (LA _{eq} , dB)	
	နှေအခိုင် (မနက် ၆ နာရီ မှ ည ၁၀ နာရီ)	ညအခိုင် (ည ၁၀ နာရီ မှ မနက် ၆ နာရီ)
၇ စက်တင်ဘာ၊ ၂၀၂၁	၅၈	-
ရည်မှန်းတန်ဖိုး	၇၅	၇၀

යෙවා: |.c-| නොව- | (NV-2) ශ්‍රීලංකාවේ මුළුලාභයේ මූල්‍ය (LA_{eq})

ရက်စွဲ	စီးပွားရေးဆိုင်ရာနာများနှင့် စက်မှုဇုန်များ (L _{V10} , dB)			
	နေ့အချိန် (မနက် ၇ နာရီမှ ညနေ ၇ နာရီ)	ညနေခတ်အချိန် (ည ၇ နာရီမှ ည ၁၀ နာရီ)	ညအချိန် (ည ၁၀ နာရီမှ မနက် ၇ နာရီ)	
၉ စက်တင်ဘာ၊ ၂၀၂၁	၆၃	-	-	
ရည်မှန်းတန်ဖိုး	၇၀	၆၅	၆၀	

မှတ်ချက်၏ ရည်မှန်းတန်ဖိုးပျားကို သီလတ်အထူးတို့များရေးနှင့် ဖွံ့ဖြိုးတိုးတက်မှုစီမံကိန်း အပိုင်း(က) အတွက် လုပ်ငန်းလည်ပတ်နေစဉ် အဆင့်တွင်ရှုရမည့် အူညာငါးအဆင့် ရည်မှန်းတန်ဖိုးကို အသုံးပြုထားပါသည်။
မှတ်၏။ မြန်မာနိအားအင်တာနေဂရ်နယ်လီတော်



သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုအဖွဲ့မြို့တိုးတက်မှုအတွက်ဆူညံသံနှင့်တုန်ခါမှုစောင့်ကြည့်လေ့လာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ ခုနှစ်)

ပေါ်များ J.၄-၃ နေရာ-၃ (NV-3) အိုချူညံသံအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်များ (LA_{eq})

ရက်စွဲ	စီးပွားရေးခိုင်ရာနေရာများနှင့် စက်မှုအဖွဲ့မြို့တိုးတက်မှုရလဒ်များ (L _{A10} , dB)		
	နေ့အချိန် (မနက် ၇ နာရီမှ ည ၇ နာရီ)	ညနေ့ခေါင်းအချိန် (ည ၇ နာရီမှ ည ၁၀ နာရီ)	ညအချိန် (ည ၁၀ နာရီမှ မနက် ၇ နာရီ)
၈ စက်တင်ဘာ၊ ၂၀၂၁	၄၈	-	-
ရည်မှန်းတန်ဖိုး	၇၀	၆၅	၆၀

မှတ်ချက်။ ရည်မှန်းတန်ဖိုးများကို သီလဝါအထူးစီးပွားရေးအဖွဲ့မြို့တိုးတက်မှုစီမံခိန်း အပိုင်း(က) အတွက် လုပ်ငန်းလည်ပတ်နေစဉ် အဆင့်တွင်ရှိရမည့် အူညံသံအဆင့် ရည်မှန်းတန်ဖိုးကို အသုံးပြုထားပါသည်။

မူရင်း။ မြန်မာစိအဲအင်တာနေရာင်နယ်လိပ်စာ

ပေါ်များ J.၄-၄ နေရာ-၁ (NV-1) အိုနာရီအလိုက်ဆူညံသံအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်များ (LA_{eq})

ရက်စွဲ	အချိန်	(LA _{eq} , dB)	(LA _{eq} , dB) အချိန်အပိုင်းအခြား တစ်ခုစီအတွက်	(LA _{eq} , dB) ရည်မှန်းတန်ဖိုး
			ရက်စွဲ	
၈ စက်တင်ဘာ၊ ၂၀၂၁	၆:၀၀-၇:၀၀	-	၇၈	၇၅
	၇:၀၀-၈:၀၀	-		
	၈:၀၀-၉:၀၀	၇၈		
	၉:၀၀-၁၀:၀၀	၇၇		
	၁၀:၀၀-၁၁:၀၀	၇၈		
	၁၁:၀၀-၁၂:၀၀	၇၈		
	၁၂:၀၀-၁၃:၀၀	၇၈		
	၁၃:၀၀-၁၄:၀၀	၇၈		
	၁၄:၀၀-၁၅:၀၀	၇၈		
	၁၅:၀၀-၁၆:၀၀	၇၉		
	၁၆:၀၀-၁၇:၀၀	၇၈		
	၁၇:၀၀-၁၈:၀၀	၇၈		
	၁၈:၀၀-၁၉:၀၀	၇၈		
	၁၉:၀၀-၂၀:၀၀	၇၈		
	၂၀:၀၀-၂၁:၀၀	၇၈		
	၂၁:၀၀-၂၂:၀၀	၇၈		
	၂၂:၀၀-၂၃:၀၀	၇၈		
	၂၃:၀၀-၂၄:၀၀	၇၈		
	၂၄:၀၀-၂၅:၀၀	၇၈		
	၂၅:၀၀-၂၆:၀၀	၇၈		

မူရင်း။ မြန်မာစိအဲအင်တာနေရာင်နယ်လိပ်စာ

သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုဇုန်ဖြူးတိုးတက်မှုအတွက်ဆူညံသံနှင့်တုန်ခါမှုစောင့်ကြည့်လေ့လာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ ခုနှစ်)

ပေါ်မှုနှင့် အပိုင်း(NV-2)အော်ချိန်အလိုက်ဆူညံသံအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်များ (LA_{eq})

ရက်စွဲ	အချိန်	(LA _{eq} , dB)	(LA _{eq} , dB) အချိန်အပိုင်းအခြား တစ်ခုစီအတွက်	(LA _{eq} , dB) ရည်မှန်းတန်ဖိုး
၃ စက်တင်ဘာ လ ၂၀၂၁	၈:၀၀-၉:၀၀	-	၆၃	၇၀
	၉:၀၀-၉:၀၀	၆၄		
	၉:၀၀-၁၀:၀၀	၆၂		
	၁၀:၀၀-၁၁:၀၀	၆၃		
	၁၁:၀၀-၁၂:၀၀	၆၀		
	၁၂:၀၀-၁၃:၀၀	၆၀		
	၁၃:၀၀-၁၄:၀၀	၆၈		
	၁၄:၀၀-၁၅:၀၀	၆၂		
	၁၅:၀၀-၁၆:၀၀	၆၂		
	၁၆:၀၀-၁၇:၀၀	-		
	၁၇:၀၀-၁၈:၀၀	-		
	၁၈:၀၀-၁၉:၀၀	-		
	၁၉:၀၀-၂၀:၀၀	-		
	၂၀:၀၀-၂၁:၀၀	-		
	၂၁:၀၀-၂၂:၀၀	-		
၂၀၂၁	၂၂:၀၀-၂၃:၀၀	-	-	၆၅
	၂၃:၀၀-၂၄:၀၀	-		
	၂၄:၀၀-၂၅:၀၀	-		
	၂၅:၀၀-၂၆:၀၀	-		
	၂၆:၀၀-၂၇:၀၀	-		
	၂၇:၀၀-၂၈:၀၀	-		
	၂၈:၀၀-၂၉:၀၀	-		
	၂၉:၀၀-၂၁:၀၀	-		
	၂၁:၀၀-၂၂:၀၀	-		
	၂၂:၀၀-၂၃:၀၀	-		

မှုရင်း။ မြန်မာစိအောင်တာနေဂျင်နယ်လီမိတ်



သီလဝါအထူးစီးပွားရေးဇုနစ်အပိုင်း(က)ရှိစက်မှုဇုနစ်ဖွံ့ဖြိုးတိုးတက်မှုအတွက်ဆူညံသံနှင့်တုန်ခါမှုစောင့်ကြည့်လေ့လာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ ခုနှစ်)


ယော်: J.၄-၆ နေရာ-၃ (NV-3)၏နာရီအလိုက်ဆူညံသံအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်များ (LA_{eq})

ရက်စွဲ	အချိန်	(LA _{eq} , dB)	(LA _{eq} , dB) အချိန်အပိုင်းအခြား တစ်ခုစီအတွက်	(LA _{eq} , dB) ရည်မှန်းတန်ခိုး
၈ စက်တင်ဘာ လ ၂၀၂၁	၇:၀၀-၈:၀၀	-	၄၈	၇၀
	၈:၀၀-၉:၀၀	၄၈		
	၉:၀၀-၁၀:၀၀	၄၇		
	၁၀:၀၀-၁၁:၀၀	၄၆		
	၁၁:၀၀-၁၂:၀၀	၄၅		
	၁၂:၀၀-၁၃:၀၀	၄၄		
	၁၃:၀၀-၁၄:၀၀	၄၆		
	၁၄:၀၀-၁၅:၀၀	၅၀		
	၁၅:၀၀-၁၆:၀၀	၅၁		
	၁၆:၀၀-၁၇:၀၀	-		
	၁၇:၀၀-၁၈:၀၀	-		
	၁၈:၀၀-၁၉:၀၀	-		
	၁၉:၀၀-၂၀:၀၀	-		
	၂၀:၀၀-၂၁:၀၀	-		
	၂၁:၀၀-၂၂:၀၀	-		
၂၁ နာရီ	၂၂:၀၀-၂၃:၀၀	-	-	၆၅
	၂၃:၀၀-၂၄:၀၀	-		
	၂၄:၀၀-၂၅:၀၀	-		
	၂၅:၀၀-၂၆:၀၀	-		
	၂၆:၀၀-၂၇:၀၀	-		
	၂၇:၀၀-၂၈:၀၀	-		
	၂၈:၀၀-၂၉:၀၀	-		
	၂၉:၀၀-၂၁:၀၀	-		
	၂၁:၀၀-၂၂:၀၀	-		
	၂၂:၀၀-၂၃:၀၀	-		

မူရင်း၊ မြန်မာနိုင်အင်ဘာနေရာင်းယ်လီစာက်

သီလဝါအထူးစီးပွားရေးမှန်အပိုင်း(က)ရှိစက်မှုမှန်ဖွံ့ဖြိုးတိုးတက်မှုအတွက်ဆူညံသံနှင့်တုန်ခါမှုစောင့်ကြည့်လေ့လာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ ခုနှစ်)


နေရာ-C (NV-1) ရှိနာရီအလိုက် ဆူညံသံအဆင့် (LA_{eq})



မူရင်း၊ မြန်မာနိုင်ဒေသရှင်နယ်လီမိတ်

ပုံ J.၄-၁ နေရာ-C (NV-1) ၏ဆူညံသံအဆင့်စောင့်ကြည့်လေ့လာမှုရလဒ်


နေရာ-J (NV-2) ရှိနာရီအလိုက် ဆူညံသံအဆင့် (LA_{eq})



မူရင်း၊ မြန်မာနိုင်ဒေသရှင်နယ်လီမိတ်

ပုံ J.၄-၂ နေရာ-J (NV-2) ၏ဆူညံသံအဆင့်စောင့်ကြည့်လေ့လာမှုရလဒ်

သီလဝါအထူးစီးပွားရေးမှန်အပိုင်း(က)ရှိစက်မှုနှင့်ဖြီးတိုးတက်မှုအတွက်ဆူညံသံနှင့်တုန်ခါမှုစောင့်ကြည့်လေ့လာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ ခုနှစ်)



မူရင်း။ မြန်မာနိုင်အင်တာနေရာင်နယ်လီမိတက်

ပုံ J.၄-၃ နေရာ-၃ (NV-3) ၏ဆူညံသံအဆင့်စောင့်ကြည့်လေ့လာမှုရလဒ်

တုန်ခါမှုစောင့်ကြည့်လေ့လာမှု ရလဒ်များ

တုန်ခါမှုစောင့်ကြည့်လေ့လာမှုရလဒ်များအတွက် နေရာ-၁ (NV-1)၊ နေရာ-၂ (NV-2) နှင့် နေရာ-၃ (NV-3) တွင် နေအချိန် (မနက် ၇ နာရီ မှ ည ၇ နာရီ)၊ ညနေခင်းအချိန် (ည ၇ နာရီ မှ ည ၁၀ နာရီ) နှင့် ညအချိန် (ည ၁၀ နာရီ မှ မနက် ၇ နာရီ) ဟူ၍ အချိန်အပိုင်းအခြား ခွဲခြားသတ်မှတ်ထားပါသည်။ တုန်ခါမှု တိုင်းတာမှုအား သတ်မှတ်ထားသောနေရာတွင် ၂၄ နာရီကြာ တိုင်းတာမည့်အစား ဘေးအန္တရာယ်ကင်းရှင်းစေရန် နှင့် ဘေးကင်းလုပ်ချိန်အနေဖြင့် ၈ နာရီ (မနက် ၈ နာရီ မှ ညနေ ၄ နာရီ) ကြာ တိုင်းတာခဲ့ပါသည်။ တုန်ခါမှုစောင့်ကြည့်လေ့လာမှုရလဒ်များအား ယေား J.၄-၇၊ ယေား J.၄-၈ နှင့် ယေား J.၄-၉ တွင် အသီးသီး ဖော်ပြထားပါသည်။ နေရာ-၁ (NV-1)၊ နေရာ-၂ (NV-2)နှင့် နေရာ-၃ (NV-3)၏ တစ်နာရီတုန်ခါမှုအဆင့် (LAeq)၏ စောင့်ကြည့်လေ့လာမှုရလဒ်များကို ယေား J.၄-၁၀၊ ယေား J.၄-၁၁ နှင့် ယေား J.၄-၁၂ တွင် အကျဉ်းချုပ် ဖော်ပြထားပါသည်။ သီလဝါအထူးစီးပွားရေးဇုန် ဖွံ့ဖြိုးမှုစီမံခိုင်း အပိုင်း(က)၏ ပတ်ဝန်းကျင်ထိခိုက်မှ ဆန်းစစ်ခြင်းအစီအရင်ခံစာတွင်ပါရှိသော လုပ်ငန်းလည်ပတ်နေစဉ် အဆင့်တွင် ရည်မှန်းထားသော တုန်ခါမှုအဆင့်နှင့် နှိုင်းယှဉ်ရာ၌ ရလဒ်များသည် ရည်မှန်းတန်ဖိုးထက် လျှော့နည်းသည်ကို တွေ့ရှိရသည်။

ယေား J.၄-၇ နေရာ-၁ (NV-1) ၏ တုန်ခါမှုအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်များ (Lv₁₀)

ရက်စွဲ	ရုံးများ၊ စီးပွားရေးဆိုင်ရာနေရာများနှင့် စက်ရုံများ (Lv ₁₀ , dB)		
	နေအချိန် (မနက် ၇ နာရီ မှ ည ၇ နာရီ)	ညနေခင်းအချိန် (ည ၇ နာရီ မှ ည ၁၀ နာရီ)	ညအချိန် (ည ၁၀ နာရီ မှ မနက် ၇ နာရီ)
၇ စက်တင်ဘာ၊ ၂၀၂၁	၄၅	-	-
ရည်မှန်းတန်ဖိုး	၇၀	၆၅	၆၅

မှတ်ချက်။ ရည်မှန်းတန်ဖိုးများကို သီလဝါအထူးစီးပွားရေးဇုန် ဖွံ့ဖြိုးတိုးတက်မှုစီမံခိုင်း အပိုင်း(က)အတွက် လုပ်ငန်းလည်ပတ်နေစဉ် အဆင့်တွင်ရှိရသည့် တုန်ခါမှုအဆင့် ရည်မှန်းတန်ဖိုးကို အသုံးပြထားပါသည်။ မူရင်း။ မြန်မာစိုအောင်တာနေရာင်နယ်လိမ့်တက်

ယေား J.၄-၈ နေရာ-၂ (NV-2) ၏ တုန်ခါမှုအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်များ (Lv₁₀)

ရက်စွဲ	ရုံးများ၊ စီးပွားရေးဆိုင်ရာနေရာများနှင့် စက်ရုံများ (Lv ₁₀ , dB)		
	နေအချိန် (မနက် ၇ နာရီ မှ ည ၇ နာရီ)	ညနေခင်းအချိန် (ည ၇ နာရီ မှ ည ၁၀ နာရီ)	ညအချိန် (ည ၁၀ နာရီ မှ မနက် ၇ နာရီ)
၉ စက်တင်ဘာ၊ ၂၀၂၁	၃၆	-	-
ရည်မှန်းတန်ဖိုး	၇၀	၆၅	၆၅

မှတ်ချက်။ ရည်မှန်းတန်ဖိုးများတို့ သီလဝါအထူးစီးပွားရေးဇုန် ဖွံ့ဖြိုးတိုးတက်မှုစီမံခိုင်း အပိုင်း(က)အတွက် လုပ်ငန်းလည်ပတ်နေစဉ် အဆင့်တွင်ရှိရသည့် တုန်ခါမှုအဆင့် ရည်မှန်းတန်ဖိုးကို အသုံးပြထားပါသည်။ မူရင်း။ မြန်မာစိုအောင်တာနေရာင်နယ်လိမ့်တက်



သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုဇာတ်ဖွံ့ဖြိုးတိုးတက်မှုအတွက်ဆူညံသုန္တန်တုန်ခါမှုစောင့်ကြည့်လေ့လာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ ခုနှစ်)

ပေါ်သူး J.၄-၉ နေရာ-၃ (NV-3) ၅၇၈၁။ ၆၁၁၁။ ၂၀၂၁ ခုနှစ်ကြည့်လေ့လာမှုရလဒ်များ (L_{V10})

ရက်စွဲ	ရုံးများ၊ စီးပွားရေးခိုင်ရာနေရာများနှင့် စက်ရုံများ (L _{V10} , dB)		
	နှေ့ချိန် (မနက် ၇ နာရီ မှ ညနေ ၇ နာရီ)	ညနေချိန် (ည ၇ နာရီ မှ ညနေ ၁၀ နာရီ)	ညအချိန် (ည ၁၀ နာရီ မှ မနက် ၇ နာရီ)
၈ စက်တင်ဘာ၊ ၂၀၂၁	၂၇	-	-
ရည်မှန်းတန်ဖိုး	၇၀	၆၅	၆၅

မှတ်ချက်။ ရည်မှန်းတန်ဖိုးများကို သီလဝါအထူးစီးပွားရေးနှင့် ဖွံ့ဖြိုးတိုးတက်မှုစီမံကိန်း အပိုင်း(က)အတွက် လုပ်ငန်းလည်ပတ်နေစဉ် အဆင့်ဘွင်ရှိရမည့် တုန်ခြုံအဆင့် ရည်မှန်းတန်ဖိုးကို အသုံးပြုထားပါသည်။

မူရင်း။ မြန်မာစိုးအင်တာနေရာင်နယ်လီမိတက်

ပေါ်သူး J.၄-၁၀ နေရာ-၁ (NV-1) ၅၇၈၁။ ၆၁၁၁။ ၂၀၂၁ ခုနှစ်ကြည့်လေ့လာမှုရလဒ်များ (L_{V10})

ရက်စွဲ	အချိန်	(L _{V10} , dB)	(L _{V10} , dB) အချိန်အပိုင်းအခြား တစ်ဦစီအတွက်	(L _{V10} , dB) ရည်မှန်းတန်ဖိုး
၈ စက်တင်ဘာလ ၂၀၂၁	၇:၀၀-၈:၀၀	-	၂၇	၇၀
	၈:၀၀-၉:၀၀	၂၅		
	၉:၀၀-၁၀:၀၀	၂၅		
	၁၀:၀၀-၁၁:၀၀	၂၅		
	၁၁:၀၀-၁၂:၀၀	၂၆		
	၁၂:၀၀-၁၃:၀၀	၂၅		
	၁၃:၀၀-၁၄:၀၀	၂၆		
	၁၄:၀၀-၁၅:၀၀	၂၅		
	၁၅:၀၀-၁၆:၀၀	၂၅		
	၁၆:၀၀-၁၇:၀၀	-		
	၁၇:၀၀-၁၈:၀၀	-		၆၅
	၁၈:၀၀-၁၉:၀၀	-		
	၁၉:၀၀-၁၁:၀၀	-		
	၁၁:၀၀-၁၂:၀၀	-		
	၁၂:၀၀-၁၃:၀၀	-		
	၁၃:၀၀-၁၄:၀၀	-		
	၁၄:၀၀-၁၅:၀၀	-		
	၁၅:၀၀-၁၆:၀၀	-		
	၁၆:၀၀-၁၇:၀၀	-		
	၁၇:၀၀-၁၈:၀၀	-		

မူရင်း။ မြန်မာစိုးအင်တာနေရာင်နယ်လီမိတက်

သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်မှုအတွက်ဆုည်သံနှင့်တုန်ခါမှုစောင့်ကြည့်လေ့လာခြင်းအတိရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစွမ်းကာလ၊ စက်တင်ဘာလ ၂၀၂၁ ခုနှစ်)

ይዙዋ፡ J.ኅ-ቁ ቁጥር-ጀ (NV-2) ከኢትዮጵያልብንናትኩፌዴራልበሮች ወሰን ተወስኝነት ለመስጠት ይፈጸማል፡ (Lv₁₀)

မူရင်း။ မြန်မာခိုအဲအင်တာနေရင်နယ်လီမိတက်



သီလဝအထူးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုမြန်မြို့ပြီးတိုးတက်မှုအတွက်ဆုည်သံနှင့်တုန်ခါမှုစောင့်ကြည့်လျေလာခြင်းအဖြစ်ချုပ်
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ ခုနှစ်)


ይዙዋ፡ J.፭-၁၂ ቁጥር-၃ (NV-3) ከኩክር ስት ደንብ ተቻቷል፡ (Lv₁₀)

ရက်စွဲ	အချိန်	(L _{v10} , dB)	(L _{v10} , dB) အချိန်အပိုင်းအခြား တစ်ခုစီအတွက်	(L _{v10} , dB) ရည်မှန်းတန်ဖိုး
ဂ စက်တင်ဘာလ	၇:၀၀-၈:၀၀	-	၂၇	၇၀
	၈:၀၀-၉:၀၀	J၆		
	၉:၀၀-၁၀:၀၀	J၆		
	၁၀:၀၀-၁၁:၀၀	J၆		
	၁၁:၀၀-၁၂:၀၀	J၆		
	၁၂:၀၀-၁၃:၀၀	J၅		
	၁၃:၀၀-၁၄:၀၀	J၆		
	၁၄:၀၀-၁၅:၀၀	J၇		
	၁၅:၀၀-၁၆:၀၀	J၇		
	၁၆:၀၀-၁၇:၀၀	-		
	၁၇:၀၀-၁၈:၀၀	-		
	၁၈:၀၀-၁၉:၀၀	-		
	၁၉:၀၀-၂၀:၀၀	-		
	၂၀:၀၀-၂၁:၀၀	-		
	၂၁:၀၀-၂၂:၀၀	-		
J၂၂	၂၂:၀၀-၂၃:၀၀	-	၆၅	၆၅
	၂၃:၀၀-၂၄:၀၀	-		
	၂၄:၀၀-၂၅:၀၀	-		
	၂၅:၀၀-၂၆:၀၀	-		
	၂၆:၀၀-၂၇:၀၀	-		
	၂၇:၀၀-၂၈:၀၀	-		
	၂၈:၀၀-၂၉:၀၀	-		
	၂၉:၀၀-၁၀:၀၀	-		
	၁၀:၀၀-၁၁:၀၀	-		
	၁၁:၀၀-၁၂:၀၀	-		
	၁၂:၀၀-၁၃:၀၀	-		
	၁၃:၀၀-၁၄:၀၀	-		
	၁၄:၀၀-၁၅:၀၀	-		
	၁၅:၀၀-၁၆:၀၀	-		

မူရင်း။ မြန်မာနိအဲအင်တာနေရင်နယ်လီမိတက်

သီလဝါအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်မှုအတွက်ဆူညံသံနှင့်တုန်ခါမှုစောင့်ကြည့်လေ့လာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ ခုနှစ်)


နေရာ-၁ (NV-1) ရှိနာရီအလိုက် တုန်ခါမှုအဆင့် (Lv₁₀)



မူရင်း။ မြန်မာစိအဲအင်ဘာနေရာင်နယ်လီမိတက်

ပုံ J.၄-၄ နေရာ-၁ (NV-1) ၅၀၏တုန်ခါမှုအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်


နေရာ-၂ (NV-2) ရှိနာရီအလိုက် တုန်ခါမှုအဆင့် (Lv₁₀)



မူရင်း။ မြန်မာစိအဲအင်ဘာနေရာင်နယ်လီမိတက်

ပုံ J.၄-၅ နေရာ-၂ (NV-2) ၅၀၏တုန်ခါမှုအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်

သီလဝအထူးစီးပွားရေးနှင့်အပိုင်း(က)ရှိစက်မှုဇုန်ဖွံ့ဖြိုးတိုးတက်မှုအတွက် ဓမ္မညံ့သံနှင့်တုန်ခါမှုစောင့်ကြည့်လေ့လာခြင်းအခါးရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နောက်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ ခုနှစ်)



မူရင်း။ မြန်မာစိအဲအင်တာနေရာင်နယ်လိမ့်တက်


ပုံ J.၄-၆ နေရာ-၃ (NV-3) ၏တုန်ခါမှုအဆင့် စောင့်ကြည့်လေ့လာမှုရလဒ်

သီလဝါအတူးစီးပွားရေးဇုန်အပိုင်း(က)ရှိဖက်မှုနှင့်ဖြိုးတိုးတက်မှုအတွက်ဆူညံသံနှင့်တုန်ခါမှုစောင့်ကြည့်လေ့လာခြင်းအစီရင်ခံစာ
(လုပ်ငန်းလည်ပတ်နေစဉ်ကာလ၊ စက်တင်ဘာလ ၂၀၂၁ ခုနှစ်)

အခန်း ၃ နိဂုံးချုပ်နှင့်အကြံပြုချက်များ

သီလဝါအတူးစီးပွားရေးဇုန်ဖြိုးမှုစီမံကိန်း အပိုင်း(က)၏ ပတ်ဝန်းကျင်ထိခိုက်မှုဆန်းစစ်ခြင်းအစီအရင်ခံစာတွင် ပါရှိသည့် လုပ်ငန်း လည်ပတ်နေစဉ်ကာလအတွင်း သတ်မှတ်ထားသော ဆူညံသံနှင့် တုန်ခါမှုအဆင့်များနှင့် နှိမ်းယဉ်ရာ၌ နေရာ-၁ (NV-1)၊ နေရာ-၂ (NV-2) နှင့် နေရာ-၃ (NV-3) တို့၏ ရလဒ်များသည် ရည်မှန်းတက်လျော့နည်းနေသည်ကို တွေ့ရှိရသည်။

ဤပတ်ဝန်းကျင်စောင့်ကြည့်လေ့လာမှုအား ကောက်ချက်ချေရာတွင် စောင့်ကြည့်လေ့လာသောကာလအတွင်း သီလဝါအတူးစီးပွားရေးဇုန် အပိုင်း(က)အတွင်းရှိ စက်မှုမြေနေရာများမှ သေးပတ်ဝန်းကျင်အား သိသာထင်ရှားသော ဆူညံသံနှင့်တုန်ခါမှုဆိုင်ရာ သက်ရောက်မှုများ မရှိကြောင်းတွေ့ရှိရပါသည်။



သီလဝါအထူးစီးပွားရေးဇုန်အတွင်း မြေဆီလွှာညစ်ညမ်းမှုလေ့လာခြင်း
(သီလဝါအထူးစီးပွားရေးဇုန်အပိုင်း(က)

၂၀၁၃ ခုနှစ်၊ ဒီဇင်ဘာလ



Resource & Environment Myanmar Ltd. B-702/401 Delta Plaza Building,
Shwegondaing Rd., Bahan, Yangon. MYANMAR

Tel: (959) 7301 3448; Fax: (951) 552901

www.enviromyanmar.net



သီလဝါအထူးစီးပွားရေးဇုန်အတွင်း မြှုပ်နည်းလုပ်လာခြင်း
သီလဝါအထူးစီးပွားရေးဇုန်အပိုင်း(က)

ଲୁହାମୟ୍ୟକ୍ରିଂ: ରୟ୍ୟାଯ୍ସିକାରୀ

သီလဝါအထူးစီးပွားရေးဌာနအပိုင်း(က) ပတ်ဝန်းကျင်ထိခိုက်မှုဆန်းစစ်ခြင်းအစီရင်ခံ၏ ပတ်ဝန်းကျင်
စောင့်ကြပ်ကြည့်ရှုမှုအခန်းတွင် ထည့်သွင်းယော်ပြရန်အတွက် သီလဝါအထူးစီးပွားရေးဌာနအပိုင်း(က)အတွင်း
မြေဆီလွှာညစ်ညမ်းမှုလေ့လာခြင်းအား (၁)နှစ်လျှင် (၂)ကြိမ်လေ့လာရန်လိုအပ်ပါသည်။ မြေဆီလွှာ
ညစ်ညမ်းခြင်းသည် မြေသားပျက်စီးခြင်း၏တစ်စိတ်တစ်ပိုင်းဖြစ်ပြီး လူကြောင့်ဖြစ်သော
ခီဝောတုပစ္စည်းများ တည်ရှိမှုနှင့် သဘာဝမြေဆီလွှာတွင် အခြားပြောင်းလဲမှုများကြောင့်
မြေဆီလွှာညစ်ညမ်းခြင်းကိုဖြစ်ပေါ်စေပါသည်။

ယခုလေ့လာမှု၏ရည်ရွယ်ချက်မှာ မြေသားအတွင်း စာတုပစ္စည်းပါဝင်မှုပမာဏအား စောင့်ကြည့်ရနိုင် အကယ်၍ ပါဝင်မှုပမာဏသည် သတ်မှတ်ထားသောစံဆွဲနှင့်ထက်ပိုမိုလာပါက လျှော့ပါးစေရေးနည်းလမ်းများအားလုပ်ဆောင်ရန်ဖြစ်သည်။

လွှေလာမည့်အကြောင်းအရာ

မြေဆီလွှာည်စည်မှုခြင်းအတွက် စမ်းသပ်တိုင်းတာမည့်အချက်များအားဆုံးဖြတ်ရာတွင် ဂျပန်နှင့်အခြားနှင့်များ၏ မြေဆီလွှာလေ့လာသည့်အချက်များကို မြှုပြုမ်းထားပြီး၊ ယင်းအချက်များကို ထေား-ဘတ်ဖော်ပြထားပါသည်။

ଓয়াঃ-১ মেল্লিলুআৰ্ব্বাইয়োঃআত্মকলাত্মকাপৰ্য্যাকৰণ

စဉ်	စမ်းသပ်တိုင်းတာချက်	ယူနစ်	ဓာတ်		
			Japan	Thailand	Vietnam
၁	pH	-	-	-	-
၂	Mercury	ppm	15	610	-
၃	Arsenic	ppm	150	27	12
၄	Lead	ppm	150	750	300
၅	Cadmium	ppm	150	810	10
၆	Copper	ppm	125	-	100
၇	Zinc	ppm	150	-	300
၈	Chromium	ppm	250	640	-
၉	Fluoride	ppm	4000	-	-
၁၀	Boron	ppm	4000	-	-
၁၁	Selenium	ppm	150	10,000	-



အရင်းအမြစ်: Japan: Ministry of Environment, Government of Japan (2002), "Regulation for Implementing the Law on Soil Contamination Countermeasures"
 Thailand: Notification of National Environmental Board No.25, B.E. Thailand (2004), "other purpose" class
 Vietnam: QCVN 03:2008/BTNMT, Applied "industrial land", Vietnam.

လေ့လာသည့်နေရာများအကျဉ်းချုပ်

လေ့လာသည့်နေရာများသည် ရန်ကုန်တိုင်းဒေသကြီး၊ သန်လျင်မြို့နယ် သီလဝါအထူးစီးပွားရေးဇုန် အပိုင်း(က)အတွင်းတည်ရှိပါသည်။ မြေဆီလွှာညစ်ညမ်းမှုလေ့လာခြင်းအတွက် မြေသားနမူနာ ကောက်ယူသည့်နေရာ (၅)နေရာရှိပါသည်။



ပုံ-၁ မြေသားနမူနာများကောက်ယူသည့်တည်နေရာပြုပုံ

လေ့လာသည့်နေရာများအား အောက်ပါယေားတွင်ဖော်ပြထားပါသည်။ လေ့လာသည့်နေရာတစ်ခုချင်းစီ၏ အကြောင်းများကိုလည်းရှင်းလင်းဖော်ပြထားပါသည်။

အယား-၂ လေ့လာသည့်နေရာများအကျဉ်းချုပ်

နမူနာကောက်ယူသည့်နေရာ	ကိုယ့်ဖိန်	နမူနာကောက်ယူသည့်နေရာ၏ဖော်ပြချက်
S-1	16° 40' 13.49" N 96° 16' 29.89" E	သီလဝါအထူးစီးပွားရေးဇုန် စီမံခန့်ခွဲမှုကော်မတီ ရုံး၏ အရွှေ့မြောက်ဘက် မီတာ ၄၀အကွာနေရာ
S-2	16° 40' 10.74" N 96° 16' 22.01" E	သီလဝါအထူးစီးပွားရေးဇုန် ပင်မဝင်ပေါက်ဝအနီး ရေမြောင်း၏မြေသားဘောင်နေရာ
S-3	16° 40' 30.25" N 96° 16' 34.86" E	ဗဟိုရေဆိပ်သန့်စင်စက်ရုံမှ စီးဆင်းလာသော ရေမြောင်းအတွင်းနေရာ

S-4	$16^{\circ} 40' 24.29'' N$ $96^{\circ} 15' 49.55'' E$	ရေစစ်ကန်အနီးကွင်းပြင်နေရာ
S-5	$16^{\circ} 40' 32.36'' N$ $96^{\circ} 15' 49.81'' E$	ရေစစ်ကန်မှ စီးဆင်းလာသောရေမြောင်း အတွင်းနေရာ

S-1

S-1သည်သိလိုအထူးစီးပွားရေးဇွန်
စီမံခန့်ခွဲမှုကော်မတီရုံး၏ မီဘ အပိုင်း(က)၏ တောင်ဘက်ပိုင်းတွင်တည်ရှိပြီး
အမှိုက်ထားသို့ရာအဆောက်အအီးသေးနေရာမှ ကောက်ယူခဲ့ပါသည်။ မြေသားနမူနာအား
ထွက်ရှိလာသောရေဆိုးများသည် ရုပ်ဖို့ခဲ့ပါသည်။ အိမ်သုံးအမှိုက်များသန့်စင်ခြင်းကြောင့်
မြေသားအတွင်းသို့စိမ့်ဝင်သွားနိုင်ပါသည်။ အသေးစားမှုအလတ်စားရွယ်ကြီးစွေများ ပါဝင်သော
နီးညီရောင်နှင့်ဆန်သောချုံစွေးမြေဖြစ်ပါသည်။



ပုံ-J S-1နေရာတွင်မြေသားနမူနာကောက်ယူနေပုံ

S-2

S-2အား သိလိုအထူးစီးပွားရေးဇွန်အပိုင်း(က) ပင်မဝင်ပေါက်ဝအနီး ရေမြောင်း၏မြေသားလျှောစောက်
သောင်နေရာမှ ကောက်ယူခဲ့ပါသည်။ ငြင်းတည်နေရာသည် သိလိုအထူးစီးပွားရေးဇွန်ကားလမ်းမဘေးတွင်
တည်ရှိပြီး ယင်းမြေသားလျှောစောက်သောင်နေရာတွင် အပင်များစိုက်ပျိုးရုံဖြစ်ပါသည်။
မြေသားအခြေအနေမှာ အသေးစားမှုအလတ်စားရွယ်ကြီးစွေများပါဝင်သော နီးညီရောင်နှင့်ဆန်သော
ချုံစွေးမြေဖြစ်ပါသည်။





ပုံ-၃ S-2နေရာတွင်မြေသားနှမူနာကောက်ယူနေပုံ

S-3

S-3အားဗဟိုရေဆိုးသန့်စင်စက်ရုံမှ စီးဆင်းလာသောရေမြောင်းအတွင်းမှ ကောက်ယူခဲ့ပါသည်။ ငြင်းနေရာသည် ရေဆိုးစွန်းရေမြောင်းနှင့် ပင်မမိုးရေးဆင်းရေမြောင်းတို့ ဆုံးသည့်နေရာမှ ၅မီတာခန့်သာ ကွာဝေးပါသည်။ မြေသားအခြေအနေမှာ အသေးစားမှုအလတ်စားရွယ်ကြီးစွဲများပါဝင်သော ဝါညံ့ရောင်နှင့်ဆန်သော ချွဲ့စွဲ့မြေဖြစ်ပါသည်။



ပုံ-၄ S-3နေရာတွင်မြေသားနှမူနာကောက်ယူနေပုံ

S-4

S-4အားသီလဝါအထူးစီးပွားရေးဇွန်အပိုင်း(က)အတွင်း ရေစစ်ကန်အနီးကွင်းပြင်နေရာမှကောက်ယူခဲ့ပြီး ငြင်းနေရာသည် အကွက်နံပါတ်E-1မှ မီတာငွေအကွာတွင်တည်ရှိပါသည်။ ကွင်းပြင်နေရာသည် ၁၆,၅၀၀ စတုရန်းမီတာကျယ်ဝန်းပြီး အပိုင်း(က)၏ အဆင့်(၂)စီမံကိန်းများမှထွက်ရှိသော မြေသားများအား လာရောက်စွန့်ပစ်ထားခြင်းဖြစ်သည်။ မြေသားအခြေအနေမှာ အသေးစားမှုအလတ်စားရွယ်ကြီးစွဲများ ပါဝင်သော နှိပ်ပေါင်နှင့်ဆန်းဆန်သော ချွဲ့စွဲ့မြေဖြစ်ပါသည်။





ပုံ-၅ S-4နေရာတွင်မြေသားနမူနာကောက်ယူနေပုံ

S-5

S-5အားသီလဝါအထူးစီးပွားရေးဇုန်အပိုင်း(က)၏ ရေစစ်ကန်မှုစီးဆင်းလားသော ရေမြောင်းအတွင်းနေရာမှ ကောက်ယူခဲ့ပါသည်။ ငြင်းနေရာသည် ရေစစ်ကန်မှုမိတာဝေးကွာဝေးပါသည်။ မြေသားအခြေအနေမှာ အသေးစားရှုယ်ကြီးစွဲများပါဝင်သော ဂါဏ်ရောင်နှင့်ဆန်သော ရွှံ့စွဲများမြေဖြစ်ပါသည်။



ပုံ-၆ S-5နေရာတွင်မြေသားနမူနာကောက်ယူနေပုံ



လေလာသည်အခိုင်

မြေသားနှမူနာကောက်ယူခြင်းအား ၂၀၂၁ခုနှစ် ဒီဇင်ဘာလ(၂၂)ရက်နေ့တွင် ဆောင်ရွက်ခဲ့ပါသည်။

လေလာသည်နည်းစာစဉ်

မြေသားနှမူနာအား သဘာဝပါတ်ဝန်းကျင်လေလာမှုစံညွှန်းနှင့်ကိုက်ညီသော မြေတူးလွှန်အားအသုံးပြု၍ ကောက်ယူခဲ့ပါသည်။ မြေတူးလွှန်သည် စတီးဖြင့်ပြုလုပ်ထားသောဖြန့်ဖြစ်ပြီး၊ တစ်ဘက်တွင် ဆုန်ထက်သော အသွားပါရှိကာ အခြားတစ်ဘက်တွင် “T” ပုံလက်ကိုင်ပါရှိပါသည်။ ငါးမြွှန်သည်အချင်း ၃လက်မခန့်ရှိပါသည်။ မလိုအပ်သောရောတွေးစေမှုများမရရှိစေရန် မြေသားနှမူနာမကောက်ယူခဲ့ ၂၀၁၈တိမီတာခန့်ရှိပါသော အပေါ်ယု မြေသားများအား ဖယ်ရှားပစ်ပါသည်။ ယင်းနောက်မြေသားနှမူနာအားတူးဖော်ကောက်ယူကာ သန္တစင်သော ပလစ်စတစ်အိတ်အတွင်းသို့ထည့်သွင်းပါသည်။ မြေသားနှမူနာများအား ဓါတ်ပစ္စည်းများအသုံးပြု၍ ထိန်းသိမ်းသို့လောင်ခြင်းအား မလုပ်ဆောင်ရုံးလိုပါသည်။ မြေသားနှမူနာများအား အပူချိန် ၄၇ကရီစင်တိဂရီတိ အောက်ရှိပါသော ရေခဲဗူးနှင့် သို့လောင်သိမ်းဆည်းပါသည်။ ထိုအပြင် နှမူနာများအား အလားအလာရှိပါသော ပါတ်ပြုခြင်းများမဖြစ်စေရန် နေရာင်နှင့်တိုက်ရှိက်ထိတွေ့ခြင်းမရရှိအောင် ထားရှုပါသည်။

မြေသားနှမူနာကောက်ယူရာတွင် အသုံးပြုသောကိရိယာအား အောက်ပါပေါ်ယားတွင်ဖော်ပြထားပါသည်။

ပေါ်ယား-၃

မြေသားနှမူနာကောက်ယူရာတွင် အသုံးပြုသောကိရိယာ

စဉ်	ကိရိယာ	ထုတ်လုပ်သည့်နှင့်	မော်ဒယ်
၁	မြေတူးလွှန် (Soil Auger)	U.S.A	AMS

စမ်းသပ်တိုင်းတာမည့်အချက်တစ်ခုခြင်းစီ၏ ပါတ်ခွဲစမ်းသပ်ခြင်းဆိုင်ရာနည်းလမ်းများအား အောက်ပါ ပေါ်ယားတွင် ဖော်ပြထားပါသည်။

ပေါ်ယား-၄

မြေဆီလွှာအရည်အသွေးများ၏ ပါတ်ခွဲစမ်းသပ်မည်းလမ်းများ

စဉ်	စမ်းသပ်တိုင်းတာချက်	ပါတ်ခွဲစမ်းသပ်မည်းလမ်း
၁	pH	Atomic Absorption Spectrophotometer, Aqua-regia
၂	Mercury (Hg)	Atomic Absorption Spectrophotometer, Aqua-regia
၃	Arsenic (As)	Atomic Absorption Spectrophotometer, Aqua-regia
၄	Lead (Pb)	Atomic Absorption Spectrophotometer, Aqua-regia
၅	Cadmium (Cd)	Atomic Absorption Spectrophotometer, Aqua-regia
၆	Copper (Cu)	Atomic Absorption Spectrophotometer, Aqua-regia
၇	Zinc (Zn)	Atomic Absorption Spectrophotometer, Aqua-regia



၈	Chromium (VI)	Atomic Absorption Spectrophotometer, Aqua-regia
၉	Fluoride (F)	Atomic Absorption Spectrophotometer, Aqua-regia
၁၀	Boron (B)	Atomic Absorption Spectrophotometer, Aqua-regia
၁၁	Selenium (Se)	Atomic Absorption Spectrophotometer, Aqua-regia

ငလ္လာမူရလာခ်

မြန်မူနာများ စာတိခွဲစမ်းသပ်ခြင်းကို ထိုင်းနိုင်ငံ United Analyst and Engineering Consultant Co., Ltd.၏ ပါတ်ခွဲခန်းတွင် စမ်းသပ်တိုင်းတာခဲ့ပါသည်။ မြန်မူလွှာအရည်အသေးစမ်းသပ်ရလာခ်များအား အောက်ပါ ဧယားတွင် ဖော်ပြထားပါသည်။ ရလာဒ်အများစုမှာ အဆိုပြုခြံးစွမ်းတန်ဖိုးများနှင့်ကိုက်ညီမှုရှိသော်လည်း (S-1) ၁ S-4နှင့် S-5တို့၏ Arsenic ပါဝင်မှုများ ထိုင်းနိုင်ငံ နှင့် ပီယာက်နမ်နိုင်ငံ၏စွမ်းတန်ဖိုးထက် အနည်းငယ်များ နေသည်ကိုတွေ့ရှုပါသည်။

ဧယား-၅

မြန်မူလွှာအရည်အသေးရလာခ်များ

No.	Parameter	Unit	S-1	S-2	S-3	S-4	S-5	Standard		
								Japan	Thailand	Vietnam
1	pH	-	6	5.1	7.1	4.6	6.5	-	-	-
2	Mercury	Mg/kg	ND	ND	ND	ND	ND	15	610	-
3	Arsenic	Mg/kg	28.9	9.79	10.8	18.8	21.0	150	27	12
4	Lead	Mg/kg	24.2	11.8	14.2	21.9	18.8	150	750	300
5	Cadmium	Mg/kg	ND	ND	ND	ND	ND	150	810	10
6	Copper	Mg/kg	33.6	18.3	26.7	21.2	27.3	125	-	100
7	Zinc	Mg/kg	37.6	31.7	87.0	43.0	56.7	150	-	300
8	Chromium	Mg/kg	121	39.6	58.8	104	97.5	250	640	-
9	Fluoride	Mg/kg	2.86	1.10	2.67	ND	3.10	4000	-	-
10	Boron	Mg/kg	37.5	13.6	22.6	25.1	30.6	4000	-	-
11	Selenium	Mg/kg	0.811	0.159	ND	0.387	0.476	150	10,000	-



နောက်ဆက်တဲ့

မီတ်ခွဲခန်းရလား



ANALYSIS REPORT

PROJECT NAME : SOIL CONTAMINATION SURVEY IN THILAWA SEZ (ZONE A)
CUSTOMER NAME : RESOURCE AND ENVIRONMENT MYANMAR CO., LTD.
ADDRESS : B702 DELTA PLAZA, SHWEGONDAING ROAD, BAHAN, YANGON MYANMAR
CONTACT INFORMATION : TEL : +959 799855808 e-mail : toetoehlaing@rem-uaeconsultant.com
SAMPLING SOURCE : THILAWA
SAMPLE TYPE : SOIL
SAMPLING DATE : DECEMBER 22, 2021
SAMPLING TIME : 10:10 HOUR
SAMPLING METHOD : -
SAMPLING BY : CUSTOMER
ANALYZED BY : MISS JINTASUPA PLIANSRI

RECEIVED DATE : JANUARY 7, 2022
ANALYTICAL DATE : JANUARY 7-21, 2022
REPORT NO. : 2022-U005675
WORK NO. : 2022-000193
ANALYSIS NO. : T22AA311-0001

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			S-1 T22AA311-0001	
pH (1:1) ^b	-	ELECTROMETRIC METHOD (US EPA 2004: 9045D)	6.0 (25°C)	-
METALS				
ARSENIC (As) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1992: 7061A)	28.9	0.100
BORON (B) ^c	mg/kg	ACID DIGESTION AND INDUCTIVELY COUPLED PLASMA (ICP) METHOD (US EPA 1996: 3050B AND 2018: 6010D)	37.5	0.250
CADMIUM (Cd) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	ND	0.300
CHROMIUM (Cr) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	121	0.500
COPPER (Cu) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	33.6	0.300
LEAD (Pb) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	24.2	1.55
MERCURY (Hg) ^c	mg/kg	ACID DIGESTION AND COLD VAPOUR AAS METHOD (US EPA 2007: 7471B)	ND	0.100
SELENIUM (Se) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1994: 7742)	0.811	0.100
ZINC (Zn) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	37.6	0.350





United Analyst and Engineering Consultant Co., Ltd.

3 Soi Udomsuk 41, Sukhumvit Road, Bangchak, Phrakanong, Bangkok 10260

Tel. 0 2763 2828 Fax 0 2763 2800 www.uaeconsultant.com E-mail: uae@uaeconsultant.com



TESTING
No.0063

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT		DETECTION LIMIT
			S-1	T22AA311-0001	
TOTAL THRESHOLD LIMIT CONCENTRATION(TTLC)					
FLUORIDE ^c	mg/kg	ION SELECTIVE ELECTRODE METHOD (US EPA 1996: 9214)	2.86		0.80
SAMPLE CONDITION			BROWN SOIL		

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT STILL NOT ACCREDITED

ND : NON-DETECTABLE.

SAMPLE (S) ANALYSED ON AS RECEIVED BASIS. RESULT (S) REPORTED ON A DRY WEIGHT BASIS.

*United Analyst Engineering Consultant Co., Ltd is Sub-contractor of REM-UAE Laboratory and Consultant Co., Ltd



Bhuchonk P.

(MR BHUCHONK PANICHLERTUMPI)
LABORATORY SUPERVISOR

JANUARY 26, 2022

UNITED ANALYST AND ENGINEERING
CONSULTANT (THAILAND) CO., LTD.

United Analyst and Engineering Consultant Co., Ltd.

3 Soi Udomsuk 41, Sukhumvit Road, Bangchak, Phrakanong, Bangkok 10260

Tel: 0 2763 2828 Fax: 0 2763 2800 www.uaeconsultant.com E-mail: uae@uaeconsultant.com

TESTING
No.0063

ANALYSIS REPORT

PROJECT NAME : SOIL CONTAMINATION SURVEY IN THILAWA SEZ (ZONE A)
CUSTOMER NAME : RESOURCE AND ENVIRONMENT MYANMAR CO., LTD.
ADDRESS : B702 DELTA PLAZA, SHWEGONDAING ROAD, BAHAN, YANGON MYANMAR
CONTACT INFORMATION : TEL : +959 799855808 e-mail : toetoehlaing@rem-uaeconsultant.com
SAMPLING SOURCE : THILAWA
SAMPLE TYPE : SOIL
SAMPLING DATE : DECEMBER 22, 2021
SAMPLING TIME : 11:05 HOUR
SAMPLING METHOD : -
SAMPLING BY : CUSTOMER
ANALYZED BY : MISS JINTASUPA PLIANSRI

RECEIVED DATE : JANUARY 7, 2022
ANALYTICAL DATE : JANUARY 7-21, 2022
REPORT NO. : 2022-U005676
WORK NO. : 2022-000193
ANALYSIS NO. : T22AA311-0002

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			S-2 T22AA311-0002	
pH (1:1) ^b	-	ELECTROMETRIC METHOD (US EPA 2004: 9045D)	5.1 (25°C)	-
METALS				
ARSENIC (As) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1992: 7061A)	9.79	0.100
BORON (B) ^c	mg/kg	ACID DIGESTION AND INDUCTIVELY COUPLED PLASMA (ICP) METHOD (US EPA 1996: 3050B AND 2018: 6010D)	13.6	0.250
CADMIUM (Cd) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	ND	0.300
CHROMIUM (Cr) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	39.6	0.500
COPPER (Cu) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	18.3	0.300
LEAD (Pb) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	11.8	1.55
MERCURY (Hg) ^c	mg/kg	ACID DIGESTION AND COLD VAPOUR AAS METHOD (US EPA 2007: 7471B)	ND	0.100
SELENIUM (Se) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1994: 7742)	0.159	0.100
ZINC (Zn) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	31.7	0.350



- DO NOT COPY PARTIAL OF THIS ANALYSIS REPORT WITHOUT OFFICIAL APPROVAL .
- REPORTED ANALYSIS REFERS TO SUBMITTED SAMPLE ONLY.





United Analyst and Engineering Consultant Co., Ltd.

3 Soi Udomsuk 41, Sukhumvit Road, Bangchak, Phrakanong, Bangkok 10260

Tel 0 2763 2828 Fax 0 2763 2800 www.uaeconsultant.com E-mail: uae@uaeconsultant.com



TESTING
No.0063

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT		DETECTION LIMIT
			S-2	T22AA311-0002	
TOTAL THRESHOLD LIMIT CONCENTRATION(TLC)					
FLUORIDE ^c	mg/kg	ION SELECTIVE ELECTRODE METHOD (US EPA 1996: 9214)	1.10		0.80
SAMPLE CONDITION			BROWN SOIL		

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT STILL NOT ACCREDITED

ND : NON-DETECTABLE.

SAMPLE (S) ANALYSED ON AS RECEIVED BASIS. RESULT (S) REPORTED ON A DRY WEIGHT BASIS.


*United Analyst Engineering Consultant Co., Ltd is Sub-contractor of REM-UAE Laboratory and Consultant Co., Ltd



Bhuchonk

(MR BHUCHONK PANICHLERTUMPI)
LABORATORY SUPERVISOR

JANUARY 26, 2022



- DO NOT COPY PARTIAL OF THIS ANALYSIS REPORT WITHOUT OFFICIAL APPROVAL .
- REPORTED ANALYSIS REFERS TO SUBMITTED SAMPLE ONLY.

ANALYSIS REPORT

PROJECT NAME : SOIL CONTAMINATION SURVEY IN THILAWA SEZ (ZONE A)
CUSTOMER NAME : RESOURCE AND ENVIRONMENT MYANMAR CO., LTD.
ADDRESS : B702 DELTA PLAZA, SHWEGONDAING ROAD, BAHAN, YANGON MYANMAR
CONTACT INFORMATION : TEL : +959 799855808 e-mail : toetoehlaing@rem-uaeconsultant.com
SAMPLING SOURCE : THILAWA
SAMPLE TYPE : SOIL **RECEIVED DATE** : JANUARY 7, 2022
SAMPLING DATE : DECEMBER 22, 2021 **ANALYTICAL DATE** : JANUARY 7-21, 2022
SAMPLING TIME : 11:40 HOUR **REPORT NO.** : 2022-U005677
SAMPLING METHOD : - **WORK NO.** : 2022-000193
SAMPLING BY : CUSTOMER **ANALYSIS NO.** : T22AA311-0003
ANALYZED BY : MISS JINTASUPA PLIANSRI

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			S-3 T22AA311-0003	
pH (1:1) ^b	-	ELECTROMETRIC METHOD (US EPA 2004: 9045D)	7.1 (25°C)	-
METALS				
ARSENIC (As) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1992: 7061A)	10.8	0.100
BORON (B) ^c	mg/kg	ACID DIGESTION AND INDUCTIVELY COUPLED PLASMA (ICP) METHOD (US EPA 1996: 3050B AND 2018: 6010D)	22.6	0.250
CADMIUM (Cd) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	ND	0.300
CHROMIUM (Cr) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	58.8	0.500
COPPER (Cu) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	26.7	0.300
LEAD (Pb) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	14.2	1.55
MERCURY (Hg) ^c	mg/kg	ACID DIGESTION AND COLD VAPOUR AAS METHOD (US EPA 2007: 7471B)	ND	0.100
SELENIUM (Se) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1994: 7742)	ND	0.100
ZINC (Zn) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	87.0	0.350



• DO NOT COPY PARTIAL OF THIS ANALYSIS REPORT WITHOUT OFFICIAL APPROVAL .

• REPORTED ANALYSIS REFERS TO SUBMITTED SAMPLE ONLY.





United Analyst and Engineering Consultant Co., Ltd.

3 Soi Udomsuk 41, Sukhumvit Road, Bangchak, Phrakanong, Bangkok 10260

Tel. 0 2763 2828 Fax 0 2763 2800 www.uaeconsultant.com E-mail: uae@uaeconsultant.com



TESTING
No. 0063

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			S-3 T22AA311-0003	
TOTAL THRESHOLD LIMIT CONCENTRATION(TTLC)				
FLUORIDE ^c	mg/kg	ION SELECTIVE ELECTRODE METHOD (US EPA 1996: 9214)	2.67	0.80
SAMPLE CONDITION				
GRAY SOIL				

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT STILL NOT ACCREDITED

ND : NON-DETECTABLE.

SAMPLE(S) ANALYSED ON AS RECEIVED BASIS. RESULT(S) REPORTED ON A DRY WEIGHT BASIS.

*United Analyst Engineering Consultant Co., Ltd is Sub-contractor of REM-UAE Laboratory and Consultant Co., Ltd



Bhuchonk P.

(MR BHUCHONK PANICHLERTUMPI)
LABORATORY SUPERVISOR

JANUARY 26, 2022

- DO NOT COPY PARTIAL OF THIS ANALYSIS REPORT WITHOUT OFFICIAL APPROVAL .
- REPORTED ANALYSIS REFERS TO SUBMITTED SAMPLE ONLY.

ANALYSIS REPORT

PROJECT NAME : SOIL CONTAMINATION SURVEY IN THILAWA SEZ (ZONE A)
CUSTOMER NAME : RESOURCE AND ENVIRONMENT MYANMAR CO., LTD.
ADDRESS : B702 DELTA PLAZA, SHWEGONDAING ROAD, BAHAN, YANGON MYANMAR
CONTACT INFORMATION : TEL : +959 799855808 e-mail : toetoevlaing@rem-uaeconsultant.com
SAMPLING SOURCE : THILAWA
SAMPLE TYPE : SOIL **RECEIVED DATE** : JANUARY 7, 2022
SAMPLING DATE : DECEMBER 22, 2021 **ANALYTICAL DATE** : JANUARY 7-21, 2022
SAMPLING TIME : 12:00 HOUR **REPORT NO.** : 2022-U005678
SAMPLING METHOD : - **WORK NO.** : 2022-000193
SAMPLING BY : CUSTOMER **ANALYSIS NO.** : T22AA311-0004
ANALYZED BY : MISS JINTASUPA PLIANSRI

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			S-4 T22AA311-0004	
pH (1:1) ^b	-	ELECTROMETRIC METHOD (US EPA 2004: 9045D)	4.6 (25°C)	-
METALS				
ARSENIC (As) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1992: 7061A)	18.8	0.100
BORON (B) ^c	mg/kg	ACID DIGESTION AND INDUCTIVELY COUPLED PLASMA (ICP) METHOD (US EPA 1996: 3050B AND 2018: 6010D)	25.1	0.250
CADMIUM (Cd) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	ND	0.300
CHROMIUM (Cr) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	104	0.500
COPPER (Cu) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	21.2	0.300
LEAD (Pb) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	21.9	1.55
MERCURY (Hg) ^c	mg/kg	ACID DIGESTION AND COLD VAPOUR AAS METHOD (US EPA 2007: 7471B)	ND	0.100
SELENIUM (Se) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1994: 7742)	0.387	0.100
ZINC (Zn) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	43.0	0.350

- DO NOT COPY PARTIAL OF THIS ANALYSIS REPORT WITHOUT OFFICIAL APPROVAL .
- REPORTED ANALYSIS REFERS TO SUBMITTED SAMPLE ONLY.





United Analyst and Engineering Consultant Co., Ltd.

3 Soi Udomsuk 41, Sukhumvit Road, Bangchak, Phrakanong, Bangkok 10260

Tel. 0 2763 2828 Fax 0 2763 2800 www.uaeconsultant.com E-mail: uae@uaeconsultant.com



TESTING
No. 0063

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			S-4 T22AA311-0004	
TOTAL THRESHOLD LIMIT CONCENTRATION (TLC)				
FLUORIDE ^a	mg/kg	ION SELECTIVE ELECTRODE METHOD (US EPA 1996: 9214)	ND	0.80
SAMPLE CONDITION		BROWN SOIL		

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT STILL NOT ACCREDITED

ND : NON-DETECTABLE.

SAMPLE (S) ANALYSED ON AS RECEIVED BASIS. RESULT (S) REPORTED ON A DRY WEIGHT BASIS.

*United Analyst Engineering Consultant Co., Ltd is Sub-contractor of REM-UAE Laboratory and Consultant Co., Ltd



Bhuchonk *p.*

(MR. BHUCHONK PANICHLERTUMPI)
LABORATORY SUPERVISOR

JANUARY 26, 2022



- DO NOT COPY PARTIAL OF THIS ANALYSIS REPORT WITHOUT OFFICIAL APPROVAL .
- REPORTED ANALYSIS REFERS TO SUBMITTED SAMPLE ONLY.

ANALYSIS REPORT

PROJECT NAME : SOIL CONTAMINATION SURVEY IN THILAWA SEZ (ZONE A)
CUSTOMER NAME : RESOURCE AND ENVIRONMENT MYANMAR CO., LTD.
ADDRESS : B702 DELTA PLAZA, SHWEGONDAING ROAD, BAHAN, YANGON MYANMAR
CONTACT INFORMATION : TEL : +959 799855808 e-mail : toetoehlaing@rem-uaeconsultant.com
SAMPLING SOURCE : THILAWA
SAMPLE TYPE : SOTL **RECEIVED DATE** : JANUARY 7, 2022
SAMPLING DATE : DECEMBER 22, 2021 **ANALYTICAL DATE** : JANUARY 7-21, 2022
SAMPLING TIME : 12:20 HOUR **REPORT NO.** : 2022-U005679
SAMPLING METHOD : - **WORK NO.** : 2022-000193
SAMPLING BY : CUSTOMER **ANALYSIS NO.** : T22AA311-0005
ANALYZED BY : MISS JINTASUPA PLIANSRI

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT	DETECTION LIMIT
			S-5 T22AA311-0005	
pH (1:1) ^b	-	ELECTROMETRIC METHOD (US EPA 2004: 9045D)	6.5 (25°C)	-
METALS				
ARSENIC (As) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1992: 7061A)	210	0.100
BORON (B) ^c	mg/kg	ACID DIGESTION AND INDUCTIVELY COUPLED PLASMA (ICP) METHOD (US EPA 1996: 3050B AND 2018: 6010D)	30.6	0.250
CADMIUM (Cd) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	ND	0.300
CHROMIUM (Cr) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	97.5	0.500
COPPER (Cu) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	27.3	0.300
LEAD (Pb) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US FPA 1996: 3050B AND 2007: 7000B)	18.8	1.55
MERCURY (Hg) ^c	mg/kg	ACID DIGESTION AND COLD VAPOUR AAS METHOD (US EPA 2007: 7471B)	ND	0.100
SELENIUM (Se) ^c	mg/kg	ACID DIGESTION AND HYDRIDE GENERATION AAS METHOD (US EPA 1996: 3050B AND 1994: 7742)	0.476	0.100
ZINC (Zn) ^c	mg/kg	ACID DIGESTION AND DIRECT AIR ACETYLENE FLAME METHOD (US EPA 1996: 3050B AND 2007: 7000B)	56.7	0.350



- DO NOT COPY PARTIAL OF THIS ANALYSIS REPORT WITHOUT OFFICIAL APPROVAL .
- REPORTED ANALYSIS REFERS TO SUBMITTED SAMPLE ONLY.





United Analyst and Engineering Consultant Co., Ltd.

3 Soi Udomsuk 41, Sukhumvit Road, Bangchak, Phrakanong, Bangkok 10260

Tel. 0 2763 2828 Fax 0 2763 2800 www.uaeconsultant.com E-mail: uae@uaeconsultant.com



TESTING
No. 0063

PARAMETER	UNIT	METHOD OF ANALYSIS	RESULT		DETECTION LIMIT
			S-5	T22AA311-0005	
TOTAL THRESHOLD LIMIT CONCENTRATION(TLC)					
FLUORIDE ^c	mg/kg	ION SELECTIVE ELECTRODE METHOD (US EPA 1996: 9214)	3.10		0.80
SAMPLE CONDITION			BROWN SOIL		

^a : ISO/IEC 17025 ACCREDITED BY THAI INDUSTRIAL STANDARDS INSTITUTE (TISI)

^b : ISO/IEC 17025 ACCREDITED BY DEPARTMENT OF SCIENCE SERVICE (DSS)

^c : VERIFIED BY OWN LABORATORY QUALITY SYSTEM, BUT STILL NOT ACCREDITED

ND : NON-DETECTABLE.

SAMPLE (S) ANALYSED ON AS RECEIVED BASIS. RESULT (S) REPORTED ON A DRY WEIGHT BASIS.


*United Analyst Engineering Consultant Co., Ltd is Sub-contractor of REM-UAE Laboratory and Consultant Co., Ltd



Bhuchonk p.

(MR. BHUCHONK PANICHLERTUMPI)
LABORATORY SUPERVISOR

JANUARY 26, 2022



- DO NOT COPY PARTIAL OF THIS ANALYSIS REPORT WITHOUT OFFICIAL APPROVAL .
- REPORTED ANALYSIS REFERS TO SUBMITTED SAMPLE ONLY.

End of Document

